

Shadow DOM

A Formal Model of the Document Object Model *with Shadow Roots*

Achim D. Brucker* Michael Herzberg†

March 19, 2025

*Department of Computer Science, University of Exeter, Exeter, UK
a.brucker@exeter.ac.uk

† Department of Computer Science, The University of Sheffield, Sheffield, UK
msherzberg1@sheffield.ac.uk

Abstract

In this AFP entry, we extend our formalization of the core DOM (AFP entry Core_DOM) with *Shadow Roots*. Shadow roots are a recent proposal of the web community to support a component-based development approach for client-side web applications.

Shadow roots are a significant extension to the DOM standard and, as web standards are condemned to be backward compatible, such extensions often result in complex specification that may contain unwanted subtleties that can be detected by a formalization.

Our Isabelle/HOL formalization is, in the sense of object-orientation, an extension of our formalization of the core DOM and enjoys the same basic properties, i.e., it is 1. *extensible*, i.e., can be extended without the need of re-proving already proven properties and 2. *executable*, i.e., we can generate executable code from our specification. We exploit the executability to show that our formalization complies to the official standard of the W3C, respectively, the WHATWG.

Keywords: Document Object Model, DOM, Shadow Root, Web Component, Formal Semantics, Isabelle/HOL

Contents

1	Introduction	7
2	The Shadow DOM	9
2.1	The Shadow DOM Data Model (ShadowRootClass)	9
2.2	Shadow Root Monad (ShadowRootMonad)	15
2.3	The Shadow DOM (Shadow_DOM)	22
3	Test Suite	97
3.1	Shadow DOM Base Tests (Shadow_DOM_BaseTest)	97
3.2	Testing slots (slots)	102
3.3	Testing slots_fallback (slots_fallback)	118
3.4	Testing Document_adoptNode (Shadow_DOM_Document_adoptNode)	126
3.5	Testing Document_getElementById (Shadow_DOM_Document_getElementById)	127
3.6	Testing Node_insertBefore (Shadow_DOM_Node_insertBefore)	131
3.7	Testing Node_removeChild (Shadow_DOM_Node_removeChild)	133
3.8	Shadow DOM Tests (Shadow_DOM_Tests)	135

1 Introduction

In a world in which more and more applications are offered as services on the internet, web browsers start to take on a similarly central role in our daily IT infrastructure as operating systems. Thus, web browsers should be developed as rigidly and formally as operating systems. While formal methods are a well-established technique in the development of operating systems (see, e.g., Klein [13] for an overview of formal verification of operating systems), there are few proposals for improving the development of web browsers using formal approaches [1, 10, 12, 14].

In [3], we formalized the core of the Document Object Model (DOM) in Isabelle/HOL. The DOM [15, 16] is *the* central data structure of all modern web browsers. In this work, we extend the formalization presented in [3] with support for *shadow trees*. Shadow trees are a recent addition to the DOM standard [16] that promise support for web components. As we will see, this promise is not fully achieved and, for example, the DOM standard itself does not formally define what a component should be. In this work, we focus on a standard compliant representation of the DOM with shadow trees. As [3], our formalization has the following properties:

- It provides a *consistency guarantee*. Since all definitions in our formal semantics are conservative and all rules are derived, the logical consistency of the DOM node-tree is reduced to the consistency of HOL.
- It serves as a *technical basis for a proof system*. Based on the derived rules and specific setup of proof tactics over node-trees, our formalization provides a generic proof environment for the verification of programs manipulating node-trees.
- It is *executable*, which allows to validate its compliance to the standard by evaluating the compliance test suite on the formal model and
- It is *extensible* in the sense of [2, 8], i.e., properties proven over the core DOM do not need to be re-proven for object-oriented extensions such as the HTML document model.

In this AFP entry, we limit ourselves to the faithful formalization of the DOM. As the DOM standard does not formally define web components, we address the question of formally defining web components and discussing their safety properties elsewhere [5, 6].

The rest of this document is automatically generated from the formalization in Isabelle/HOL, i.e., all content is checked by Isabelle (we refer readers interested in a more high-level presentation and additional explanations to [6, 11]). The structure follows the theory dependencies (see Figure 1.1): first, we formalize the DOM with Shadow Roots (chapter 2) and then formalize the relevant compliance test cases in chapter 3.




Figure 1.1: The Dependency Graph of the Isabelle Theories.

2 The Shadow DOM

In this chapter, we introduce the formalization of the core DOM *with Shadow Roots*, i.e., the most important algorithms for querying or modifying the Shadow DOM, as defined in the standard.

2.1 The Shadow DOM Data Model (ShadowRootClass)

```
theory ShadowRootClass
imports
  Core_DOM.ShadowRootPointer
  Core_DOM.DocumentClass
begin

2.1.1 ShadowRoot

datatype shadow_root_mode = Open | Closed
record ('node_ptr, 'element_ptr, 'character_data_ptr) RShadowRoot = RObject +
  nothing :: unit
  mode :: shadow_root_mode
  child_nodes :: "('node_ptr, 'element_ptr, 'character_data_ptr) node_ptr list"
type_synonym ('node_ptr, 'element_ptr, 'character_data_ptr, 'ShadowRoot) ShadowRoot
  = "('node_ptr, 'element_ptr, 'character_data_ptr, 'ShadowRoot option) RShadowRoot_scheme"
register_default_tvars "('node_ptr, 'element_ptr, 'character_data_ptr, 'ShadowRoot) ShadowRoot"
type_synonym ('node_ptr, 'element_ptr, 'character_data_ptr, 'shadow_root_ptr, 'Object, 'Node,
  'Element, 'CharacterData, 'Document,
  'ShadowRoot) Object
  = "('node_ptr, 'element_ptr, 'character_data_ptr, 'shadow_root_ptr, ('node_ptr, 'element_ptr,
  'character_data_ptr, 'ShadowRoot option)
    RShadowRoot_ext + 'Object, 'Node, 'Element, 'CharacterData, 'Document) Object"
register_default_tvars "('node_ptr, 'element_ptr, 'character_data_ptr, 'shadow_root_ptr, 'Object,
  'Node, 'Element, 'CharacterData,
  'Document, 'ShadowRoot) Object"

type_synonym ('object_ptr, 'node_ptr, 'element_ptr, 'character_data_ptr, 'document_ptr,
  'shadow_root_ptr, 'Object, 'Node,
  'Element, 'CharacterData, 'Document, 'ShadowRoot) heap
  = "('object_ptr, 'node_ptr, 'element_ptr, 'character_data_ptr, 'document_ptr, 'shadow_root_ptr,
  ('node_ptr, 'element_ptr,
  'character_data_ptr, 'ShadowRoot option) RShadowRoot_ext + 'Object, 'Node, 'Element,
  'CharacterData, 'Document) heap"
register_default_tvars "('object_ptr, 'node_ptr, 'element_ptr, 'character_data_ptr, 'document_ptr,
  'shadow_root_ptr, 'Object,
  'Node, 'Element, 'CharacterData, 'Document, 'ShadowRoot) heap"
type_synonym "heap_final" = "(unit, unit, unit, unit, unit, unit, unit, unit, unit) heap"

definition shadow_root_ptr_kinds :: "(_ heap ⇒ _) shadow_root_ptr fset"
  where
    "shadow_root_ptr_kinds heap =
the |`| (cast |`| (ffilter is_shadow_root_ptr_kind (object_ptr_kinds heap)))"

lemma shadow_root_ptr_kinds_simp [simp]:
  "shadow_root_ptr_kinds (Heap (fmupd (cast shadow_root_ptr) shadow_root (the_heap h))) =
{|shadow_root_ptr|} |`| shadow_root_ptr_kinds h"
  ⟨proof⟩
```

```

definition shadow_root_ptrs :: "(_ heap ⇒ (_ shadow_root_ptr fset"
  where
    "shadow_root_ptrs heap = ffilter is_shadow_root_ptr (shadow_root_ptr_kinds heap)"

definition castObject2ShadowRoot :: "(_ Object ⇒ (_ ShadowRoot option"
  where
    "castObject2ShadowRoot obj = (case RObject.more obj of
      Inr (Inl shadow_root)) ⇒ Some (RObject.extend (RObject.truncate obj) shadow_root)
    | _ ⇒ None)"
adhoc_overloading cast ≡ castObject2ShadowRoot

definition castShadowRoot2Object :: "(_ ShadowRoot ⇒ (_ Object"
  where
    "castShadowRoot2Object shadow_root =
(RObject.extend (RObject.truncate shadow_root) (Inr (Inr (Inl (RObject.more shadow_root))))))"
adhoc_overloading cast ≡ castShadowRoot2Object

definition is_shadow_root_kind :: "(_ Object ⇒ bool"
  where
    "is_shadow_root_kind ptr ↔ castObject2ShadowRoot ptr ≠ None"

lemma shadow_root_ptr_kinds_heap_upd [simp]:
  "shadow_root_ptr_kinds (Heap (fmupd (cast shadow_root_ptr) shadow_root (the_heap h))) =
{shadow_root_ptr} ∪ shadow_root_ptr_kinds h"
  ⟨proof⟩

lemma shadow_root_ptr_kinds_commutes [simp]:
  "cast shadow_root_ptr ∉ object_ptr_kinds h ↔ shadow_root_ptr ∉ shadow_root_ptr_kinds h"
  ⟨proof⟩

definition getShadowRoot :: "(_ shadow_root_ptr ⇒ (_ heap ⇒ (_ ShadowRoot option"
  where
    "getShadowRoot shadow_root_ptr h = Option.bind (get (cast shadow_root_ptr) h) cast"
adhoc_overloading get ≡ getShadowRoot

locale l_type_wf_defShadowRoot
begin
definition a_type_wf :: "(_ heap ⇒ bool"
  where
    "a_type_wf h = (DocumentClass.type_wf h ∧ (∀ shadow_root_ptr ∈ fset (shadow_root_ptr_kinds h).
      getShadowRoot shadow_root_ptr h ≠ None))"
end
global_interpretation l_type_wf_defShadowRoot defines type_wf = a_type_wf ⟨proof⟩
lemmas type_wf_defs = a_type_wf_def

locale l_type_wfShadowRoot = l_type_wf type_wf for type_wf :: "(_ heap ⇒ bool)" +
assumes type_wfShadowRoot: "type_wf h ⇒ ShadowRootClass.type_wf h"

sublocale l_type_wfShadowRoot ⊆ l_type_wfDocument
  ⟨proof⟩

lemma type_wf_implies_previous: "type_wf h ⇒ DocumentClass.type_wf h"
  ⟨proof⟩

locale l_getShadowRoot_lemmas = l_type_wfShadowRoot
begin
sublocale l_getDocument_lemmas ⟨proof⟩
lemma getShadowRoot_type_wf:
  assumes "type_wf h"
  shows "shadow_root_ptr ∉ shadow_root_ptr_kinds h ↔ getShadowRoot shadow_root_ptr h ≠ None"
  ⟨proof⟩
end

```

```

global_interpretation l_getShadowRoot_lemmas type_wf ⟨proof⟩

definition putShadowRoot :: "(_ shadow_root_ptr ⇒ _) ShadowRoot ⇒ (_ heap ⇒ _) heap"
  where
    "putShadowRoot shadow_root_ptr shadow_root = put (cast shadow_root_ptr) (cast shadow_root)"
adhoc_overloading put ≡ putShadowRoot

lemma putShadowRoot_ptr_in_heap:
  assumes "putShadowRoot shadow_root_ptr shadow_root h = h'"
  shows "shadow_root_ptr ∈ shadow_root_ptr_kinds h'"
⟨proof⟩

lemma putShadowRoot_put_ptrs:
  assumes "putShadowRoot shadow_root_ptr shadow_root h = h'"
  shows "object_ptr_kinds h' = object_ptr_kinds h ∪ {cast shadow_root_ptr}"
⟨proof⟩

lemma castShadowRoot2Object_inject [simp]: "castShadowRoot2Object x = castShadowRoot2Object y ⟷ x = y"
⟨proof⟩

lemma castObject2ShadowRoot_none [simp]:
  "castObject2ShadowRoot obj = None ⟷ ¬ (∃ shadow_root. castShadowRoot2Object shadow_root = obj)"
⟨proof⟩

lemma castObject2ShadowRoot_some [simp]:
  "castObject2ShadowRoot obj = Some shadow_root ⟷ cast shadow_root = obj"
⟨proof⟩

lemma castObject2ShadowRoot_inv [simp]: "castObject2ShadowRoot (castShadowRoot2Object shadow_root) = Some shadow_root"
⟨proof⟩

lemma cast_shadow_root_not_node [simp]:
  "castShadowRoot2Object shadow_root ≠ castNode2Object node"
  "castNode2Object node ≠ castShadowRoot2Object shadow_root"
⟨proof⟩

lemma get_shadow_root_ptr_simp1 [simp]:
  "getShadowRoot shadow_root_ptr (putShadowRoot shadow_root_ptr shadow_root h) = Some shadow_root"
⟨proof⟩

lemma get_shadow_root_ptr_simp2 [simp]:
  "shadow_root_ptr ≠ shadow_root_ptr"
  ⟹ "getShadowRoot shadow_root_ptr (putShadowRoot shadow_root_ptr' shadow_root h) =
  getShadowRoot shadow_root_ptr h"
⟨proof⟩

lemma get_shadow_root_ptr_simp3 [simp]:
  "getElement element_ptr (putShadowRoot shadow_root_ptr f h) = getElement element_ptr h"
⟨proof⟩

lemma get_shadow_root_ptr_simp4 [simp]:
  "getShadowRoot shadow_root_ptr (putElement element_ptr f h) = getShadowRoot shadow_root_ptr h"
⟨proof⟩

lemma get_shadow_root_ptr_simp5 [simp]:
  "getCharacterData character_data_ptr (putShadowRoot shadow_root_ptr f h) = getCharacterData character_data_ptr h"
⟨proof⟩

lemma get_shadow_root_ptr_simp6 [simp]:
  "getShadowRoot shadow_root_ptr (putCharacterData character_data_ptr f h) = getShadowRoot shadow_root_ptr h"
⟨proof⟩

```

```

lemma get_shadow_root_ptr_simp7 [simp]:
  "getDocument document_ptr (putShadowRoot shadow_root_ptr f h) = getDocument document_ptr h"
  ⟨proof⟩
lemma get_shadow_root_ptr_simp8 [simp]:
  "getShadowRoot shadow_root_ptr (putDocument document_ptr f h) = getShadowRoot shadow_root_ptr h"
  ⟨proof⟩

lemma newElement_getShadowRoot [simp]:
  assumes "newElement h = (new_element_ptr, h')"
  shows "getShadowRoot ptr h = getShadowRoot ptr h'"
  ⟨proof⟩

lemma newCharacterData_getShadowRoot [simp]:
  assumes "newCharacterData h = (new_character_data_ptr, h')"
  shows "getShadowRoot ptr h = getShadowRoot ptr h'"
  ⟨proof⟩

lemma newDocument_getShadowRoot [simp]:
  assumes "newDocument h = (new_document_ptr, h')"
  shows "getShadowRoot ptr h = getShadowRoot ptr h'"
  ⟨proof⟩

abbreviation "create_shadow_root_obj mode_arg child_nodes_arg"
  ≡ ( RObject.nothing = (), RShadowRoot.nothing = (), mode = mode_arg,
    RShadowRoot.child_nodes = child_nodes_arg, ... = None )

definition newShadowRoot :: "(_ heap ⇒ ((_) shadow_root_ptr × (_ heap))"
  where
    "newShadowRoot h = (let new_shadow_root_ptr =
      shadow_root_ptr.Ref (Suc (fMax (shadow_root_ptr.the_ref `|` shadow_root_ptrs h))) in
      (new_shadow_root_ptr, put new_shadow_root_ptr (create_shadow_root_obj Open []) h))"

lemma newShadowRoot_ptr_in_heap:
  assumes "newShadowRoot h = (new_shadow_root_ptr, h')"
  shows "new_shadow_root_ptr ∈ shadow_root_ptr_kinds h'"
  ⟨proof⟩

lemma new_shadow_root_ptr_new:
  "shadow_root_ptr.Ref (Suc (finsert 0 (shadow_root_ptr.the_ref `|` shadow_root_ptrs h))) ∉ shadow_root_ptrs h"
  ⟨proof⟩

lemma newShadowRoot_ptr_not_in_heap:
  assumes "newShadowRoot h = (new_shadow_root_ptr, h')"
  shows "new_shadow_root_ptr ∉ shadow_root_ptr_kinds h"
  ⟨proof⟩

lemma newShadowRoot_new_ptr:
  assumes "newShadowRoot h = (new_shadow_root_ptr, h')"
  shows "object_ptr_kinds h' = object_ptr_kinds h ∪ {cast new_shadow_root_ptr}"
  ⟨proof⟩

lemma newShadowRoot_is_shadow_root_ptr:
  assumes "newShadowRoot h = (new_shadow_root_ptr, h')"
  shows "is_shadow_root_ptr new_shadow_root_ptr"
  ⟨proof⟩

lemma newShadowRoot_getObject [simp]:
  assumes "newShadowRoot h = (new_shadow_root_ptr, h')"
  assumes "ptr ≠ cast new_shadow_root_ptr"
  shows "getObject ptr h = getObject ptr h'"

```

(proof)

```

lemma newShadowRoot_getNode [simp]:
assumes "newShadowRoot h = (new_shadow_root_ptr, h')"
shows "getNode ptr h = getNode ptr h'"
(proof)

lemma newShadowRoot_getElement [simp]:
assumes "newShadowRoot h = (new_shadow_root_ptr, h')"
shows "getElement ptr h = getElement ptr h'"
(proof)

lemma newShadowRoot_getCharacterData [simp]:
assumes "newShadowRoot h = (new_shadow_root_ptr, h')"
shows "getCharacterData ptr h = getCharacterData ptr h'"
(proof)

lemma newShadowRoot_getDocument [simp]:
assumes "newShadowRoot h = (new_shadow_root_ptr, h')"
shows "getDocument ptr h = getDocument ptr h'"
(proof)

lemma newShadowRoot_getShadowRoot [simp]:
assumes "newShadowRoot h = (new_shadow_root_ptr, h')"
assumes "ptr ≠ new_shadow_root_ptr"
shows "getShadowRoot ptr h = getShadowRoot ptr h'"
(proof)

```

```

locale l_known_ptrShadowRoot
begin
definition a_known_ptr :: "(_) object_ptr ⇒ bool"
  where
    "a_known_ptr ptr = (known_ptr ptr ∨ is_shadow_root_ptr ptr)"

lemma known_ptr_not_shadow_root_ptr: "a_known_ptr ptr ⇒ ¬is_shadow_root_ptr ptr ⇒ known_ptr ptr"
(proof)
lemma known_ptr_new_shadow_root_ptr: "a_known_ptr ptr ⇒ ¬known_ptr ptr ⇒ is_shadow_root_ptr ptr"
(proof)

end
global_interpretation l_known_ptrShadowRoot defines known_ptr = a_known_ptr (proof)
lemmas known_ptr_defs = a_known_ptr_def

locale l_known_ptrsShadowRoot = l_known_ptr known_ptr for known_ptr :: "(_) object_ptr ⇒ bool"
begin
definition a_known_ptrs :: "(_) heap ⇒ bool"
  where
    "a_known_ptrs h = (∀ptr ∈ fset (object_ptr_kinds h). known_ptr ptr)"

lemma known_ptrs_known_ptr: "a_known_ptrs h ⇒ ptr ∉ object_ptr_kinds h ⇒ known_ptr ptr"
(proof)

lemma known_ptrs_preserved:
  "object_ptr_kinds h = object_ptr_kinds h' ⇒ a_known_ptrs h = a_known_ptrs h''"
(proof)
lemma known_ptrs_subset:
  "object_ptr_kinds h' ⊂ object_ptr_kinds h ⇒ a_known_ptrs h ⇒ a_known_ptrs h''"
(proof)
lemma known_ptrs_new_ptr:
  "object_ptr_kinds h' = object_ptr_kinds h ∪ {new_ptr} ⇒ known_ptr new_ptr ⇒
  a_known_ptrs h ⇒ a_known_ptrs h''"
(proof)

```

```

end
global_interpretation l_known_ptrsShadowRoot known_ptr defines known_ptrs = a_known_ptrs ⟨proof⟩
lemmas known_ptrs_defs = a_known_ptrs_def

lemma known_ptrs_is_l_known_ptrs [instances]: "l_known_ptrs known_ptr known_ptrs"
  ⟨proof⟩

lemma shadow_root_get_put_1 [simp]:
  "getShadowRoot shadow_root_ptr (putShadowRoot shadow_root_ptr shadow_root h) = Some shadow_root"
  ⟨proof⟩
lemma shadow_root_different_get_put [simp]:
  "shadow_root_ptr ≠ shadow_root_ptr' ⟹
  getShadowRoot shadow_root_ptr (putShadowRoot shadow_root_ptr' shadow_root h) = getShadowRoot shadow_root_ptr
  h"
  ⟨proof⟩

lemma shadow_root_get_put_2 [simp]:
  "getElement element_ptr (putShadowRoot shadow_root_ptr f h) = getElement element_ptr h"
  ⟨proof⟩
lemma shadow_root_get_put_3 [simp]:
  "getShadowRoot element_ptr (putElement shadow_root_ptr f h) = getShadowRoot element_ptr h"
  ⟨proof⟩
lemma shadow_root_get_put_4 [simp]:
  "getCharacterData character_data_ptr (putShadowRoot shadow_root_ptr f h) = getCharacterData character_data_ptr
  h"
  ⟨proof⟩
lemma shadow_root_get_put_5 [simp]:
  "getShadowRoot character_data_ptr (putCharacterData shadow_root_ptr f h) = getShadowRoot character_data_ptr
  h"
  ⟨proof⟩
lemma shadow_root_get_put_6 [simp]:
  "getDocument document_ptr (putShadowRoot shadow_root_ptr f h) = getDocument document_ptr h"
  ⟨proof⟩
lemma shadow_root_get_put_7 [simp]:
  "getShadowRoot document_ptr (putDocument shadow_root_ptr f h) = getShadowRoot document_ptr h"
  ⟨proof⟩

lemma known_ptrs_implies: "DocumentClass.known_ptrs h ⟹ ShadowRootClass.known_ptrs h"
  ⟨proof⟩

definition deleteShadowRoot :: "(_ shadow_root_ptr ⇒ (_ heap ⇒ (_ heap option)) where
  "deleteShadowRoot shadow_root_ptr = deleteObject (cast shadow_root_ptr)""

lemma deleteShadowRoot_pointer_removed:
  assumes "deleteShadowRoot ptr h = Some h'"
  shows "ptr ∉ shadow_root_ptr_kinds h'"
  ⟨proof⟩

lemma deleteShadowRoot_pointer_ptr_in_heap:
  assumes "deleteShadowRoot ptr h = Some h'"
  shows "ptr ∈ shadow_root_ptr_kinds h"
  ⟨proof⟩

lemma deleteShadowRoot_ok:
  assumes "ptr ∉ shadow_root_ptr_kinds h"
  shows "deleteShadowRoot ptr h ≠ None"
  ⟨proof⟩

lemma shadow_root_delete_get_1 [simp]:
  "deleteShadowRoot shadow_root_ptr h = Some h' ⟹ getShadowRoot shadow_root_ptr h' = None"
  ⟨proof⟩

```

```

lemma shadow_root_different_delete_get [simp]:
  "shadow_root_ptr ≠ shadow_root_ptr' ⇒ deleteShadowRoot shadow_root_ptr' h = Some h' ⇒
  getShadowRoot shadow_root_ptr h' = getShadowRoot shadow_root_ptr h"
  ⟨proof⟩

lemma shadow_root_delete_get_2 [simp]:
  "deleteShadowRoot shadow_root_ptr h = Some h' ⇒ object_ptr ≠ cast shadow_root_ptr ⇒
  getObject object_ptr h' = getObject object_ptr h"
  ⟨proof⟩

lemma shadow_root_delete_get_3 [simp]:
  "deleteShadowRoot shadow_root_ptr h = Some h' ⇒ getNode node_ptr h' = getNode node_ptr h"
  ⟨proof⟩

lemma shadow_root_delete_get_4 [simp]:
  "deleteShadowRoot shadow_root_ptr h = Some h' ⇒ getElement element_ptr h' = getElement element_ptr h"
  ⟨proof⟩

lemma shadow_root_delete_get_5 [simp]:
  "deleteShadowRoot shadow_root_ptr h = Some h' ⇒
  getCharacterData character_data_ptr h' = getCharacterData character_data_ptr h"
  ⟨proof⟩

lemma shadow_root_delete_get_6 [simp]:
  "deleteShadowRoot shadow_root_ptr h = Some h' ⇒ getDocument document_ptr h' = getDocument document_ptr h"
  ⟨proof⟩

lemma shadow_root_delete_get_7 [simp]:
  "deleteShadowRoot shadow_root_ptr h = Some h' ⇒ shadow_root_ptr' ≠ shadow_root_ptr ⇒
  getShadowRoot shadow_root_ptr' h' = getShadowRoot shadow_root_ptr' h"
  ⟨proof⟩
end

```

2.2 Shadow Root Monad (ShadowRootMonad)

```

theory ShadowRootMonad
imports
  "Core_DOM.DocumentMonad"
  "../classes/ShadowRootClass"
begin

type_synonym ('object_ptr, 'node_ptr, 'element_ptr, 'character_data_ptr, 'document_ptr,
  'shadow_root_ptr, 'Object, 'Node, 'Element, 'CharacterData, 'Document, 'ShadowRoot, 'result) dom_prog
  = "((_) heap, exception, 'result) prog"
register_default_tvars "('object_ptr, 'node_ptr, 'element_ptr, 'character_data_ptr, 'document_ptr,
  'shadow_root_ptr, 'Object, 'Node, 'Element, 'CharacterData, 'Document, 'ShadowRoot, 'result) dom_prog"

global_interpretation l_ptr_kinds_M shadow_root_ptr_kinds defines shadow_root_ptr_kinds_M = a_ptr_kinds_M
⟨proof⟩
lemmas shadow_root_ptr_kinds_M_defs = a_ptr_kinds_M_def

lemma shadow_root_ptr_kinds_M_eq:
  assumes "/h ⊢ object_ptr_kinds_M/r = /h' ⊢ object_ptr_kinds_M/r"
  shows "/h ⊢ shadow_root_ptr_kinds_M/r = /h' ⊢ shadow_root_ptr_kinds_M/r"
  ⟨proof⟩

global_interpretation l_dummy defines get_M_ShadowRoot = "l_get_M.a_get_M getShadowRoot" ⟨proof⟩
lemma get_M_is_l_get_M: "l_get_M getShadowRoot type_wf shadow_root_ptr_kinds"
  ⟨proof⟩
lemmas get_M_defs = get_M_ShadowRoot_def[unfolded l_get_M.a_get_M_def[OF get_M_is_l_get_M]]
```

```

adhoc_overloading get_M ==> get_MShadowRoot

locale l_get_MShadowRoot_lemmas = l_type_wfShadowRoot
begin
sublocale l_get_MCharacterData_lemmas {proof}

interpretation l_get_M getShadowRoot type_wf shadow_root_ptr_kinds
  {proof}
lemmas get_MShadowRoot_ok = get_M_ok[folded get_MShadowRoot_def]
lemmas get_MShadowRoot_ptr_in_heap = get_M_ptr_in_heap[folded get_MShadowRoot_def]
end

global_interpretation l_get_MShadowRoot_lemmas type_wf {proof}

global_interpretation l_put_M type_wf shadow_root_ptr_kinds getShadowRoot putShadowRoot rewrites
  "a_get_M = get_MShadowRoot" defines put_MShadowRoot = a_put_M
  {proof}

lemmas put_M_defs = a_put_M_def
adhoc_overloading put_M ==> put_MShadowRoot

locale l_put_MShadowRoot_lemmas = l_type_wfShadowRoot
begin
sublocale l_put_MCharacterData_lemmas {proof}

interpretation l_put_M type_wf shadow_root_ptr_kinds getShadowRoot putShadowRoot
  {proof}
lemmas put_MShadowRoot_ok = put_M_ok[folded put_MShadowRoot_def]
end

global_interpretation l_put_MShadowRoot_lemmas type_wf {proof}

lemma shadow_root_put_get [simp]: "h ⊢ put_MShadowRoot shadow_root_ptr setter v →_h h"
  ==> (λx. getter (setter (λ_. v) x) = v)
  ==> h' ⊢ get_MShadowRoot shadow_root_ptr getter →_r v"
  {proof}
lemma get_M_Mshadow_root_preserved1 [simp]:
  "shadow_root_ptr ≠ shadow_root_ptr"
  ==> h ⊢ put_MShadowRoot shadow_root_ptr setter v →_h h'
  ==> preserved (get_MShadowRoot shadow_root_ptr' getter) h h'"
  {proof}
lemma shadow_root_put_get_preserved [simp]:
  "h ⊢ put_MShadowRoot shadow_root_ptr setter v →_h h"
  ==> (λx. getter (setter (λ_. v) x) = getter x)
  ==> preserved (get_MShadowRoot shadow_root_ptr' getter) h h'"
  {proof}
lemma get_M_Mshadow_root_preserved2 [simp]:
  "h ⊢ put_MShadowRoot shadow_root_ptr setter v →_h h' ==> preserved (get_MNode node_ptr getter) h h''"
  {proof}
lemma get_M_Mshadow_root_preserved3 [simp]:
  "cast shadow_root_ptr ≠ object_ptr"
  ==> h ⊢ put_MShadowRoot shadow_root_ptr setter v →_h h'
  ==> preserved (get_MObject object_ptr getter) h h'"
  {proof}
lemma get_M_Mshadow_root_preserved4 [simp]:
  "h ⊢ put_MShadowRoot shadow_root_ptr setter v →_h h'
  ==> (λx. getter (cast (setter (λ_. v) x)) = getter (cast x))

```

```

 $\implies \text{preserved } (\text{get\_MObject object\_ptr getter}) h h'$ 
⟨proof⟩

lemma get_M_Mshadow_root_preserved5 [simp]:
  "cast shadow_root_ptr ≠ object_ptr"
 $\implies h \vdash \text{put\_MObject object\_ptr setter } v \rightarrow_h h'$ 
 $\implies \text{preserved } (\text{get\_MShadowRoot shadow\_root\_ptr getter}) h h'$ 
⟨proof⟩

lemma get_M_Mshadow_root_preserved6 [simp]:
  "h \vdash \text{put\_MShadowRoot shadow\_root\_ptr setter } v \rightarrow_h h' \implies \text{preserved } (\text{get\_MElement element\_ptr getter}) h h'"
⟨proof⟩

lemma get_M_Mshadow_root_preserved7 [simp]:
  "h \vdash \text{put\_MElement element\_ptr setter } v \rightarrow_h h' \implies \text{preserved } (\text{get\_MShadowRoot shadow\_root\_ptr getter}) h h'"
⟨proof⟩

lemma get_M_Mshadow_root_preserved8 [simp]:
  "h \vdash \text{put\_MShadowRoot shadow\_root\_ptr setter } v \rightarrow_h h'
 $\implies \text{preserved } (\text{get\_MCharacterData character\_data\_ptr getter}) h h'$ 
⟨proof⟩

lemma get_M_Mshadow_root_preserved9 [simp]:
  "h \vdash \text{put\_MCharacterData character\_data\_ptr setter } v \rightarrow_h h'
 $\implies \text{preserved } (\text{get\_MShadowRoot shadow\_root\_ptr getter}) h h'$ 
⟨proof⟩

lemma get_M_Mshadow_root_preserved10 [simp]:
  " $(\lambda x. \text{getter } (\text{cast } (\text{setter } (\lambda_. v) x)) = \text{getter } (\text{cast } x))$ "
 $\implies h \vdash \text{put\_MShadowRoot shadow\_root\_ptr setter } v \rightarrow_h h' \implies \text{preserved } (\text{get\_MObject object\_ptr getter}) h h'$ 
⟨proof⟩

lemma new_element_get_MShadowRoot:
  "h \vdash \text{new\_element} \rightarrow_h h' \implies \text{preserved } (\text{get\_MShadowRoot ptr getter}) h h'"
⟨proof⟩

lemma new_character_data_get_MShadowRoot:
  "h \vdash \text{new\_character\_data} \rightarrow_h h' \implies \text{preserved } (\text{get\_MShadowRoot ptr getter}) h h'"
⟨proof⟩

lemma new_document_get_MShadowRoot:
  "h \vdash \text{new\_document} \rightarrow_h h' \implies \text{preserved } (\text{get\_MShadowRoot ptr getter}) h h'"
⟨proof⟩

definition deleteShadowRoot_M :: "(_ shadow_root_ptr ⇒ (_, unit) dom_prog" where
  "deleteShadowRoot_M shadow_root_ptr = do {
    h ← get_heap;
    (case deleteShadowRoot shadow_root_ptr h of
      Some h ⇒ return heap h |
      None ⇒ error HierarchyRequestError)
  }"
adhoc_overloading delete_M ≡ deleteShadowRoot_M

lemma deleteShadowRoot_M_ok [simp]:
  assumes "shadow_root_ptr ∉ shadow_root_ptr_kinds h"
  shows "h ⊢ ok (deleteShadowRoot_M shadow_root_ptr)"
⟨proof⟩

lemma deleteShadowRoot_M_ptr_in_heap:
  assumes "h ⊢ deleteShadowRoot_M shadow_root_ptr →_h h'"
  shows "shadow_root_ptr ∉ shadow_root_ptr_kinds h"
⟨proof⟩

```

```

lemma delete_ShadowRoot_M_ptr_not_in_heap:
  assumes "h ⊢ delete_ShadowRoot_M shadow_root_ptr →_h h'"
  shows "shadow_root_ptr ∉ shadow_root_ptr_kinds h'"
  ⟨proof⟩

lemma delete_shadow_root_pointers:
  assumes "h ⊢ delete_ShadowRoot_M shadow_root_ptr →_h h'"
  shows "object_ptr_kinds h = object_ptr_kinds h' ∪ {cast shadow_root_ptr}"
  ⟨proof⟩

lemma delete_shadow_root_get_MObject: "h ⊢ delete_ShadowRoot_M shadow_root_ptr →_h h' ⇒
ptr ≠ cast shadow_root_ptr ⇒ preserved (get_MObject ptr getter) h h'"
  ⟨proof⟩
lemma delete_shadow_root_get_MNode: "h ⊢ delete_ShadowRoot_M shadow_root_ptr →_h h' ⇒
preserved (get_MNode ptr getter) h h'"
  ⟨proof⟩
lemma delete_shadow_root_get_MElement: "h ⊢ delete_ShadowRoot_M shadow_root_ptr →_h h' ⇒
preserved (get_MElement ptr getter) h h'"
  ⟨proof⟩
lemma delete_shadow_root_get_MCharacterData: "h ⊢ delete_ShadowRoot_M shadow_root_ptr →_h h' ⇒
preserved (get_MCharacterData ptr getter) h h'"
  ⟨proof⟩
lemma delete_shadow_root_get_MDocument: "h ⊢ delete_ShadowRoot_M shadow_root_ptr →_h h' ⇒
preserved (get_MDocument ptr getter) h h'"
  ⟨proof⟩
lemma delete_shadow_root_get_MShadowRoot: "h ⊢ delete_ShadowRoot_M shadow_root_ptr →_h h' ⇒
shadow_root_ptr ≠ shadow_root_ptr' ⇒ preserved (get_MShadowRoot shadow_root_ptr' getter) h h'"
  ⟨proof⟩

lemma shadow_root_put_get_1 [simp]: "shadow_root_ptr ≠ shadow_root_ptr' ⇒
h ⊢ put_MShadowRoot shadow_root_ptr setter v →_h h' ⇒
preserved (get_MShadowRoot shadow_root_ptr' getter) h h'"
  ⟨proof⟩
lemma shadow_root_put_get_2 [simp]: "(λx. getter (setter (λ_. v) x)) = getter x ⇒
h ⊢ put_MShadowRoot shadow_root_ptr setter v →_h h' ⇒
preserved (get_MShadowRoot shadow_root_ptr' getter) h h'"
  ⟨proof⟩
lemma shadow_root_put_get_3 [simp]: "h ⊢ put_MShadowRoot shadow_root_ptr setter v →_h h' ⇒
preserved (get_MElement element_ptr getter) h h'"
  ⟨proof⟩
lemma shadow_root_put_get_4 [simp]: "h ⊢ put_MElement element_ptr setter v →_h h' ⇒
preserved (get_MShadowRoot shadow_root_ptr getter) h h'"
  ⟨proof⟩
lemma shadow_root_put_get_5 [simp]: "h ⊢ put_MShadowRoot shadow_root_ptr setter v →_h h' ⇒
preserved (get_MCharacterData character_data_ptr getter) h h'"
  ⟨proof⟩
lemma shadow_root_put_get_6 [simp]: "h ⊢ put_MCharacterData character_data_ptr setter v →_h h' ⇒
preserved (get_MShadowRoot shadow_root_ptr getter) h h'"
  ⟨proof⟩
lemma shadow_root_put_get_7 [simp]: "h ⊢ put_MShadowRoot shadow_root_ptr setter v →_h h' ⇒
preserved (get_MDocument document_ptr getter) h h'"
  ⟨proof⟩
lemma shadow_root_put_get_8 [simp]: "h ⊢ put_MDocument document_ptr setter v →_h h' ⇒
preserved (get_MShadowRoot shadow_root_ptr getter) h h'"
  ⟨proof⟩
lemma shadow_root_put_get_9 [simp]: "(λx. getter (cast (setter (λ_. v) x))) = getter (cast x) ⇒
h ⊢ put_MShadowRoot shadow_root_ptr setter v →_h h' ⇒ preserved (get_MObject object_ptr getter) h h'"
  ⟨proof⟩

```

2.2.1 new_M

```
definition new_ShadowRoot_M :: "(_ , _) shadow_root_ptr) dom_prog"
```

where

```
"newShadowRoot_M = do {
    h ← get_heap;
    (new_ptr, h') ← return (newShadowRoot h);
    return_heap h';
    return new_ptr
}"
```

lemma newShadowRoot_M_ok [simp]:

```
"h ⊢ ok newShadowRoot_M"
⟨proof⟩
```

lemma newShadowRoot_M_ptr_in_heap:

```
assumes "h ⊢ newShadowRoot_M →_h h'"
and "h ⊢ newShadowRoot_M →_r new_shadow_root_ptr"
shows "new_shadow_root_ptr ∈ shadow_root_ptr_kinds h"
⟨proof⟩
```

lemma newShadowRoot_M_ptr_not_in_heap:

```
assumes "h ⊢ newShadowRoot_M →_h h'"
and "h ⊢ newShadowRoot_M →_r new_shadow_root_ptr"
shows "new_shadow_root_ptr ∉ shadow_root_ptr_kinds h"
⟨proof⟩
```

lemma newShadowRoot_M_new_ptr:

```
assumes "h ⊢ newShadowRoot_M →_h h'"
and "h ⊢ newShadowRoot_M →_r new_shadow_root_ptr"
shows "object_ptr_kinds h' = object_ptr_kinds h ∪ {cast new_shadow_root_ptr}"
⟨proof⟩
```

lemma newShadowRoot_M_is_shadow_root_ptr:

```
assumes "h ⊢ newShadowRoot_M →_r new_shadow_root_ptr"
shows "is_shadow_root_ptr new_shadow_root_ptr"
⟨proof⟩
```

lemma new_shadow_root_mode:

```
assumes "h ⊢ newShadowRoot_M →_h h'"
assumes "h ⊢ newShadowRoot_M →_r new_shadow_root_ptr"
shows "h' ⊢ get_M new_shadow_root_ptr mode →_r Open"
⟨proof⟩
```

lemma new_shadow_root_children:

```
assumes "h ⊢ newShadowRoot_M →_h h'"
assumes "h ⊢ newShadowRoot_M →_r new_shadow_root_ptr"
shows "h' ⊢ get_M new_shadow_root_ptr child_nodes →_r []"
⟨proof⟩
```

lemma new_shadow_root_get_MObject:

```
"h ⊢ newShadowRoot_M →_h h' ⇒ h ⊢ newShadowRoot_M →_r new_shadow_root_ptr
⇒ ptr ≠ cast new_shadow_root_ptr ⇒ preserved (get_MObject ptr getter) h h'"
⟨proof⟩
```

lemma new_shadow_root_get_MNode:

```
"h ⊢ newShadowRoot_M →_h h' ⇒ h ⊢ newShadowRoot_M →_r new_shadow_root_ptr
⇒ preserved (get_MNode ptr getter) h h'"
⟨proof⟩
```

lemma new_shadow_root_get_MElement:

```
"h ⊢ newShadowRoot_M →_h h' ⇒ h ⊢ newShadowRoot_M →_r new_shadow_root_ptr
⇒ preserved (get_MElement ptr getter) h h'"
⟨proof⟩
```

lemma new_shadow_root_get_MCharacterData:

```
"h ⊢ newShadowRoot_M →_h h' ⇒ h ⊢ newShadowRoot_M →_r new_shadow_root_ptr
⇒ preserved (get_MCharacterData ptr getter) h h'"
⟨proof⟩
```

```

lemma new_shadow_root_get_MDocument:
  "h ⊢ newShadowRoot_M →_h h"
  ⟹ h ⊢ newShadowRoot_M →_r new_shadow_root_ptr
  ⟹ preserved (get_MDocument ptr getter) h h"
  ⟨proof⟩
lemma new_shadow_root_get_MShadowRoot:
  "h ⊢ newShadowRoot_M →_h h"
  ⟹ h ⊢ newShadowRoot_M →_r new_shadow_root_ptr ⟹ ptr ≠ new_shadow_root_ptr
  ⟹ preserved (get_MShadowRoot ptr getter) h h"
  ⟨proof⟩

```

2.2.2 modified heaps

```

lemma shadow_root_get_put_1 [simp]: "getShadowRoot shadow_root_ptr (putObject ptr obj h) = (if ptr = cast
shadow_root_ptr
then cast obj else get shadow_root_ptr h)"
  ⟨proof⟩

lemma shadow_root_ptr_kinds_new[simp]: "shadow_root_ptr_kinds (putObject ptr obj h) = shadow_root_ptr_kinds
h ∪ /
(if is_shadow_root_ptr_kind ptr then {|the (cast ptr)|} else {})"
  ⟨proof⟩

lemma type_wf_put_I:
  assumes "type_wf h"
  assumes "DocumentClass.type_wf (putObject ptr obj h)"
  assumes "is_shadow_root_ptr_kind ptr ⟹ is_shadow_root_kind obj"
  shows "type_wf (putObject ptr obj h)"
  ⟨proof⟩

lemma type_wf_put_ptr_not_in_heap_E:
  assumes "type_wf (putObject ptr obj h)"
  assumes "ptr ∉ object_ptr_kinds h"
  shows "type_wf h"
  ⟨proof⟩

lemma type_wf_put_ptr_in_heap_E:
  assumes "type_wf (putObject ptr obj h)"
  assumes "ptr ∈ object_ptr_kinds h"
  assumes "DocumentClass.type_wf h"
  assumes "is_shadow_root_ptr_kind ptr ⟹ is_shadow_root_kind (the (get ptr h))"
  shows "type_wf h"
  ⟨proof⟩

```

2.2.3 type_wf

```

lemma new_element_type_wf_preserved [simp]:
  assumes "h ⊢ new_element →_h h"
  shows "type_wf h = type_wf h"
  ⟨proof⟩

lemma put_MElement_tag_name_type_wf_preserved [simp]:
  assumes "h ⊢ put_M_element_ptr tag_name_update v →_h h"
  shows "type_wf h = type_wf h"
  ⟨proof⟩

lemma put_MElement_child_nodes_type_wf_preserved [simp]:
  assumes "h ⊢ put_M_element_ptr RElement.child_nodes_update v →_h h"
  shows "type_wf h = type_wf h"
  ⟨proof⟩

lemma put_MElement_attrs_type_wf_preserved [simp]:
  assumes "h ⊢ put_M_element_ptr attrs_update v →_h h"
  shows "type_wf h = type_wf h"
  ⟨proof⟩

```

```

lemma put_MElement_shadow_root_opt_type_wf_preserved [simp]:
  assumes "h ⊢ put_M element_ptr shadow_root_opt_update v →_h h'"
  shows "type_wf h = type_wf h'"
  ⟨proof⟩

lemma new_character_data_type_wf_preserved [simp]:
  assumes "h ⊢ new_character_data →_h h'"
  shows "type_wf h = type_wf h'"
  ⟨proof⟩

lemma put_MCharacterData_val_type_wf_preserved [simp]:
  assumes "h ⊢ put_M character_data_ptr val_update v →_h h'"
  shows "type_wf h = type_wf h'"
  ⟨proof⟩

lemma new_document_type_wf_preserved [simp]:
  assumes "h ⊢ new_document →_h h'"
  shows "type_wf h = type_wf h'"
  ⟨proof⟩

lemma put_MDocument_doctype_type_wf_preserved [simp]:
  assumes "h ⊢ put_M document_ptr doctype_update v →_h h'"
  shows "type_wf h = type_wf h'"
  ⟨proof⟩

lemma put_MDocument_document_element_type_wf_preserved [simp]:
  assumes "h ⊢ put_M document_ptr document_element_update v →_h h'"
  shows "type_wf h = type_wf h'"
  ⟨proof⟩

lemma put_MDocument_disconnected_nodes_type_wf_preserved [simp]:
  assumes "h ⊢ put_M document_ptr disconnected_nodes_update v →_h h'"
  shows "type_wf h = type_wf h'"
  ⟨proof⟩

lemma put_MShadowRoot_mode_type_wf_preserved [simp]:
  "h ⊢ put_M shadow_root_ptr mode_update v →_h h' ⇒ type_wf h = type_wf h'"
  ⟨proof⟩

lemma put_MShadowRoot_child_nodes_type_wf_preserved [simp]:
  "h ⊢ put_M shadow_root_ptr RShadowRoot.child_nodes_update v →_h h' ⇒ type_wf h = type_wf h'"
  ⟨proof⟩

lemma shadow_root_ptr_kinds_small:
  assumes "¬ object_ptr. preserved (get_MObject object_ptr RObject.nothing) h h'"
  shows "shadow_root_ptr_kinds h = shadow_root_ptr_kinds h'"
  ⟨proof⟩

lemma shadow_root_ptr_kinds_preserved:
  assumes "writes SW setter h h'"
  assumes "h ⊢ setter →_h h'"
  assumes "¬ h h'. ∀ w ∈ SW. h ⊢ w →_h h' →
    (∀ object_ptr. preserved (get_MObject object_ptr RObject.nothing) h h')"
  shows "shadow_root_ptr_kinds h = shadow_root_ptr_kinds h'"
  ⟨proof⟩

lemma new_shadow_root_known_ptr:
  assumes "h ⊢ newShadowRoot_M →_r new_shadow_root_ptr"
  shows "known_ptr (cast new_shadow_root_ptr)"
  ⟨proof⟩

lemma new_shadow_root_type_wf_preserved [simp]: "h ⊢ newShadowRoot_M →_h h' ⇒ type_wf h = type_wf h'"
  ⟨proof⟩

```

```

locale l_new_shadow_root = l_type_wf +
assumes new_shadow_root_types_preserved: "h ⊢ newShadowRoot_M →_h h' ⟹ type_wf h = type_wf h'"

lemma new_shadow_root_is_l_new_shadow_root [instances]: "l_new_shadow_root type_wf"
⟨proof⟩

lemma type_wf_preserved_small:
assumes "¬ object_ptr. preserved (get_MObject object_ptr RObject.nothing) h h'"
assumes "¬ node_ptr. preserved (get_MNode node_ptr RNode.nothing) h h'"
assumes "¬ element_ptr. preserved (get_MElement element_ptr REElement.nothing) h h'"
assumes "¬ character_data_ptr. preserved (get_MCharacterData character_data_ptr RCharacterData.nothing) h h"
assumes "¬ document_ptr. preserved (get_MDocument document_ptr RDocument.nothing) h h'"
assumes "¬ shadow_root_ptr. preserved (get_MShadowRoot shadow_root_ptr RShadowRoot.nothing) h h'"
shows "type_wf h = type_wf h"
⟨proof⟩

lemma new_element_is_l_new_element [instances]:
"l_new_element type_wf"
⟨proof⟩

lemma new_character_data_is_l_new_character_data [instances]:
"l_new_character_data type_wf"
⟨proof⟩

lemma new_document_is_l_new_document [instances]:
"l_new_document type_wf"
⟨proof⟩

lemma type_wf_preserved:
assumes "writes SW setter h h'"
assumes "h ⊢ setter →_h h'"
assumes "¬ h h' w. w ∈ SW ⟹ h ⊢ w →_h h' ⟹
∀ object_ptr. preserved (get_MObject object_ptr RObject.nothing) h h'"
assumes "¬ h h' w. w ∈ SW ⟹ h ⊢ w →_h h' ⟹
∀ node_ptr. preserved (get_MNode node_ptr RNode.nothing) h h'"
assumes "¬ h h' w. w ∈ SW ⟹ h ⊢ w →_h h' ⟹
∀ element_ptr. preserved (get_MElement element_ptr REElement.nothing) h h'"
assumes "¬ h h' w. w ∈ SW ⟹ h ⊢ w →_h h' ⟹
∀ character_data_ptr. preserved (get_MCharacterData character_data_ptr RCharacterData.nothing) h h'"
assumes "¬ h h' w. w ∈ SW ⟹ h ⊢ w →_h h' ⟹
∀ document_ptr. preserved (get_MDocument document_ptr RDocument.nothing) h h'"
assumes "¬ h h' w. w ∈ SW ⟹ h ⊢ w →_h h' ⟹
∀ shadow_root_ptr. preserved (get_MShadowRoot shadow_root_ptr RShadowRoot.nothing) h h'"
shows "type_wf h = type_wf h"
⟨proof⟩

lemma type_wf_drop: "type_wf h ⟹ type_wf (Heap (fmdrop_ptr (the_heap h)))"
⟨proof⟩

lemma delete_shadow_root_type_wf_preserved [simp]:
assumes "h ⊢ deleteShadowRoot_M shadow_root_ptr →_h h'"
assumes "type_wf h"
shows "type_wf h"
⟨proof⟩
end

```

2.3 The Shadow DOM (Shadow_DOM)

```

theory Shadow_DOM
imports
"monads/ShadowRootMonad"

```

```

Core_DOM.Core_DOM
begin

abbreviation "safe_shadow_root_element_types ≡ {''article'', ''aside'', ''blockquote'', ''body'',
  ''div'', ''footer'', ''h1'', ''h2'', ''h3'', ''h4'', ''h5'', ''h6'', ''header'', ''main'',
  ''nav'', ''p'', ''section'', ''span''}"

```

2.3.1 Function Definitions

get_child_nodes

```

locale l_get_child_nodesShadow_DOM_defs =
  CD: l_get_child_nodesCore_DOM_defs
begin
definition get_child_nodesshadow_root_ptr :: "(_ shadow_root_ptr ⇒ unit
  ⇒ (_, (_ node_ptr list) dom_prog)" where
  "get_child_nodesshadow_root_ptr shadow_root_ptr _ = get_M shadow_root_ptr RShadowRoot.child_nodes"

definition a_get_child_nodes_tups :: "((_) object_ptr ⇒ bool) × ((_) object_ptr ⇒ unit
  ⇒ (_, (_ node_ptr list) dom_prog)) list" where
  "a_get_child_nodes_tups ≡ [(is_shadow_root_ptrobject_ptr, get_child_nodesshadow_root_ptr ∘ the ∘ cast)]"

definition a_get_child_nodes :: "(_ object_ptr ⇒ (_ node_ptr list) dom_prog" where
  "a_get_child_nodes ptr = invoke (CD.a_get_child_nodes_tups @ a_get_child_nodes_tups) ptr ()"

definition a_get_child_nodes_locs :: "(_ object_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set" where
  "a_get_child_nodes_locs ptr ≡
    (if is_shadow_root_ptr_kind ptr
     then {preserved (get_M (the (cast ptr)) RShadowRoot.child_nodes)} else {}) ∪
    CD.a_get_child_nodes_locs ptr"

definition first_child :: "(_ object_ptr ⇒ (_ node_ptr option) dom_prog"
  where
  "first_child ptr = do {
    children ← a_get_child_nodes ptr;
    return (case children of [] ⇒ None | child#_ ⇒ Some child)}"
end

global_interpretation l_get_child_nodesShadow_DOM_defs defines
  get_child_nodes = l_get_child_nodesShadow_DOM_defs.a_get_child_nodes and
  get_child_nodes_locs = l_get_child_nodesShadow_DOM_defs.a_get_child_nodes_locs
  ⟨proof⟩

locale l_get_child_nodesShadow_DOM =
  l_type_wf type_wf +
  l_known_ptr known_ptr +
  l_get_child_nodesShadow_DOM_defs +
  l_get_child_nodes_defs get_child_nodes get_child_nodes_locs +
  CD: l_get_child_nodesCore_DOM type_wfCore_DOM known_ptrCore_DOM get_child_nodesCore_DOM
  get_child_nodes_locsCore_DOM
  for type_wf :: "(_ heap ⇒ bool"
    and known_ptr :: "(_ object_ptr ⇒ bool"
    and type_wfCore_DOM :: "(_ heap ⇒ bool"
    and known_ptrCore_DOM :: "(_ object_ptr ⇒ bool"
    and get_child_nodes :: "(_ object_ptr ⇒ (_ node_ptr list) dom_prog"
    and get_child_nodes_locs :: "(_ object_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
    and get_child_nodesCore_DOM :: "(_ object_ptr ⇒ (_ node_ptr list) dom_prog"
    and get_child_nodes_locsCore_DOM :: "(_ object_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set" +
  assumes known_ptr_impl: "known_ptr = ShadowRootClass.known_ptr"
  assumes type_wf_impl: "type_wf = ShadowRootClass.type_wf"
  assumes get_child_nodes_impl: "get_child_nodes = a_get_child_nodes"
  assumes get_child_nodes_locs_impl: "get_child_nodes_locs = a_get_child_nodes_locs"
begin

```

```

lemmas get_child_nodes_def = get_child_nodesImpl[unfolded a_get_child_nodes_def get_child_nodes_def]
lemmas get_child_nodes_locs_def = get_child_nodes_locsImpl[unfolded a_get_child_nodes_locs_def
    get_child_nodes_locs_def, folded CD.get_child_nodes_locsImpl]

lemma get_child_nodes_ok:
    assumes "known_ptr ptr"
    assumes "type_wf h"
    assumes "ptr ∉ object_ptr_kinds h"
    shows "h ⊢ ok (get_child_nodes ptr)"
    ⟨proof⟩

lemma get_child_nodes_ptr_in_heap:
    assumes "h ⊢ get_child_nodes ptr →r children"
    shows "ptr ∉ object_ptr_kinds h"
    ⟨proof⟩

lemma get_child_nodes_pure [simp]:
    "pure (get_child_nodes ptr) h"
    ⟨proof⟩

lemma get_child_nodes_reads: "reads (get_child_nodes_locs ptr) (get_child_nodes ptr) h h'"
    ⟨proof⟩
end

interpretation i_get_child_nodes?: l_get_child_nodesShadow_DOM type_wf known_ptr DocumentClass.type_wf
    DocumentClass.known_ptr get_child_nodes get_child_nodes_locs Core_DOM_Functions.get_child_nodes
    Core_DOM_Functions.get_child_nodes_locs
    ⟨proof⟩
declare l_get_child_nodesShadow_DOM_axioms [instances]

lemma get_child_nodes_is_l_get_child_nodes [instances]: "l_get_child_nodes type_wf known_ptr
    get_child_nodes get_child_nodes_locs"
    ⟨proof⟩

new_document locale l_new_document_get_child_nodesShadow_DOM =
    CD: l_new_document_get_child_nodesCore_DOM type_wfCore_DOM known_ptrCore_DOM get_child_nodesCore_DOM
    get_child_nodes_locsCore_DOM
    + l_get_child_nodesShadow_DOM type_wf known_ptr type_wfCore_DOM known_ptrCore_DOM get_child_nodes
    get_child_nodes_locs get_child_nodesCore_DOM get_child_nodes_locsCore_DOM
    for type_wf :: "(_ heap ⇒ bool"
        and known_ptr :: "(_ object_ptr ⇒ bool"
        and get_child_nodes :: "(_ object_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
        and get_child_nodes_locs :: "(_ object_ptr ⇒ ((_) heap ⇒ bool) set"
        and type_wfCore_DOM :: "(_ heap ⇒ bool"
        and known_ptrCore_DOM :: "(_ object_ptr ⇒ bool"
        and get_child_nodesCore_DOM :: "(_ object_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
        and get_child_nodes_locsCore_DOM :: "(_ object_ptr ⇒ ((_) heap ⇒ bool) set"
begin
lemma get_child_nodes_new_document:
    "ptr' ≠ cast new_document_ptr ==> h ⊢ new_document →r new_document_ptr
    ==> h ⊢ new_document →h h' ==> r ∈ get_child_nodes_locs ptr' ==> r h h'"
    ⟨proof⟩

lemma new_document_no_child_nodes:
    "h ⊢ new_document →r new_document_ptr ==> h ⊢ new_document →h h'
    ==> h ⊢ get_child_nodes (cast new_document_ptr) →r []"
    ⟨proof⟩
end
interpretation i_new_document_get_child_nodes?:
    l_new_document_get_child_nodesShadow_DOM type_wf known_ptr get_child_nodes get_child_nodes_locs
    DocumentClass.type_wf DocumentClass.known_ptr Core_DOM_Functions.get_child_nodes
    Core_DOM_Functions.get_child_nodes_locs
    ⟨proof⟩

```

```

declare l_new_document_get_child_nodesCore_DOM_axioms[instances]

lemma new_document_get_child_nodes_is_l_new_document_get_child_nodes [instances]:
  "l_new_document_get_child_nodes type_wf known_ptr get_child_nodes get_child_nodes_locs"
  ⟨proof⟩

new_shadow_root locale l_new_shadow_root_get_child_nodesShadow_DOM =
  l_get_child_nodesShadow_DOM type_wf known_ptr type_wfCore_DOM known_ptrCore_DOM get_child_nodes
  get_child_nodes_locs get_child_nodesCore_DOM get_child_nodes_locsCore_DOM
  for type_wf :: "(_ heap ⇒ bool"
    and known_ptr :: "(_ object_ptr ⇒ bool"
    and get_child_nodes :: "(_ object_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
    and get_child_nodes_locs :: "(_ object_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
    and type_wfCore_DOM :: "(_ heap ⇒ bool"
    and known_ptrCore_DOM :: "(_ object_ptr ⇒ bool"
    and get_child_nodesCore_DOM :: "(_ object_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
    and get_child_nodes_locsCore_DOM :: "(_ object_ptr ⇒ ((_) heap ⇒ bool) set"
begin
lemma get_child_nodes_new_shadow_root:
  "ptr' ≠ cast new_shadow_root_ptr ⇒ h ⊢ newShadowRoot_M →_r new_shadow_root_ptr
   ⇒ h ⊢ newShadowRoot_M →_h h' ⇒ r ∈ get_child_nodes_locs ptr' ⇒ r h h'"
  ⟨proof⟩

lemma new_shadow_root_no_child_nodes:
  "h ⊢ newShadowRoot_M →_r new_shadow_root_ptr ⇒ h ⊢ newShadowRoot_M →_h h'
   ⇒ h' ⊢ get_child_nodes (cast new_shadow_root_ptr) →_r []"
  ⟨proof⟩
end
interpretation i_new_shadow_root_get_child_nodes?:
  l_new_shadow_root_get_child_nodesShadow_DOM type_wf known_ptr get_child_nodes get_child_nodes_locs
  DocumentClass.type_wf DocumentClass.known_ptr Core_DOM_Functions.get_child_nodes
  Core_DOM_Functions.get_child_nodes_locs
  ⟨proof⟩
declare l_new_shadow_root_get_child_nodesShadow_DOM_def[instances]

locale l_new_shadow_root_get_child_nodes = l_get_child_nodes +
  assumes get_child_nodes_new_shadow_root:
    "ptr' ≠ cast new_shadow_root_ptr ⇒ h ⊢ newShadowRoot_M →_r new_shadow_root_ptr
     ⇒ h ⊢ newShadowRoot_M →_h h' ⇒ r ∈ get_child_nodes_locs ptr' ⇒ r h h'"
  assumes new_shadow_root_no_child_nodes:
    "h ⊢ newShadowRoot_M →_r new_shadow_root_ptr ⇒ h ⊢ newShadowRoot_M →_h h'
     ⇒ h' ⊢ get_child_nodes (cast new_shadow_root_ptr) →_r []"

lemma new_shadow_root_get_child_nodes_is_l_new_shadow_root_get_child_nodes [instances]:
  "l_new_shadow_root_get_child_nodes type_wf known_ptr get_child_nodes get_child_nodes_locs"
  ⟨proof⟩

new_element locale l_new_element_get_child_nodesShadow_DOM =
  l_get_child_nodesShadow_DOM +
  l_new_element_get_child_nodesCore_DOM type_wfCore_DOM known_ptrCore_DOM get_child_nodesCore_DOM
  get_child_nodes_locsCore_DOM
begin
lemma get_child_nodes_new_element:
  "ptr' ≠ cast new_element_ptr ⇒ h ⊢ new_element →_r new_element_ptr ⇒ h ⊢ new_element →_h h'
   ⇒ r ∈ get_child_nodes_locs ptr' ⇒ r h h'"
  ⟨proof⟩

lemma new_element_no_child_nodes:
  "h ⊢ new_element →_r new_element_ptr ⇒ h ⊢ new_element →_h h'
   ⇒ h' ⊢ get_child_nodes (cast new_element_ptr) →_r []"
  ⟨proof⟩
end

```

```

interpretation i_new_element_get_child_nodes?:
  l_new_element_get_child_nodesShadow_DOM type_wf known_ptr DocumentClass.type_wf
  DocumentClass.known_ptr get_child_nodes get_child_nodes_locs Core_DOM_Functions.get_child_nodes
  Core_DOM_Functions.get_child_nodes_locs
  ⟨proof⟩
declare l_new_element_get_child_nodesShadow_DOM_axioms[instances]

lemma new_element_get_child_nodes_is_l_new_element_get_child_nodes [instances]:
  "l_new_element_get_child_nodes type_wf known_ptr get_child_nodes get_child_nodes_locs"
  ⟨proof⟩

delete_shadow_root

locale l_delete_shadow_root_get_child_nodesShadow_DOM =
  l_get_child_nodesShadow_DOM
begin
  lemma get_child_nodes_delete_shadow_root:
    "ptr' ≠ cast shadow_root_ptr ==> h ⊢ deleteShadowRoot_M shadow_root_ptr →h h' ==>
     r ∈ get_child_nodes_locs ptr' ==> r h h'"
    ⟨proof⟩
  end

  locale l_delete_shadow_root_get_child_nodes = l_get_child_nodes_defs +
    assumes get_child_nodes_delete_shadow_root:
    "ptr' ≠ cast shadow_root_ptr ==> h ⊢ deleteShadowRoot_M shadow_root_ptr →h h' ==>
     r ∈ get_child_nodes_locs ptr' ==> r h h'"

interpretation l_delete_shadow_root_get_child_nodesShadow_DOM type_wf known_ptr DocumentClass.type_wf
  DocumentClass.known_ptr get_child_nodes get_child_nodes_locs Core_DOM_Functions.get_child_nodes
  Core_DOM_Functions.get_child_nodes_locs
  ⟨proof⟩

lemma l_delete_shadow_root_get_child_nodes_get_child_nodes_locs [instances]: "l_delete_shadow_root_get_child_nodes
get_child_nodes_locs"
  ⟨proof⟩

set_child_nodes

locale l_set_child_nodesShadow_DOM_defs =
  CD: l_set_child_nodesCore_DOM_defs
begin
  definition set_child_nodesshadow_root_ptr :: "(_ shadow_root_ptr ⇒ _) node_ptr list
  ⇒ (_, unit) dom_prog" where
    "set_child_nodesshadow_root_ptr shadow_root_ptr = putM shadow_root_ptr RShadowRoot.child_nodes_update"

  definition a_set_child_nodes_tups :: "((_) object_ptr ⇒ bool) × ((_) object_ptr ⇒ _) node_ptr list
  ⇒ (_, unit) dom_prog" where
    "a_set_child_nodes_tups ≡ [(is_shadow_root_ptrobject_ptr, set_child_nodesshadow_root_ptr ∘ the ∘ cast)]"

  definition a_set_child_nodes :: "(_) object_ptr ⇒ (_) node_ptr list ⇒ (_, unit) dom_prog" where
    "a_set_child_nodes ptr children = invoke (CD.a_set_child_nodes_tups @ a_set_child_nodes_tups)
    ptr children"

  definition a_set_child_nodes_locs :: "(_) object_ptr ⇒ (_, unit) dom_prog set"
  where
    "a_set_child_nodes_locs ptr ≡
     (if is_shadow_root_ptr_kind ptr
      then all_args (putM (the (cast ptr)) RShadowRoot.child_nodes_update)
      else {}) ∪ CD.a_set_child_nodes_locs ptr"
  end

  global_interpretation l_set_child_nodesShadow_DOM_defs defines
    set_child_nodes = l_set_child_nodesShadow_DOM_defs.a_set_child_nodes and

```

```

set_child_nodes_locs = l_set_child_nodesShadow_DOM_defs.a_set_child_nodes_locs
⟨proof⟩

locale l_set_child_nodesShadow_DOM =
l_type_wf type_wf +
l_known_ptr known_ptr +
l_set_child_nodesShadow_DOM_defs +
l_set_child_nodes_defs set_child_nodes set_child_nodes_locs +
CD: l_set_child_nodesCore_DOM type_wfCore_DOM known_ptrCore_DOM set_child_nodesCore_DOM
set_child_nodes_locsCore_DOM
for type_wf :: "(_ heap ⇒ bool"
  and known_ptr :: "(_ object_ptr ⇒ bool"
  and type_wfCore_DOM :: "(_ heap ⇒ bool"
  and known_ptrCore_DOM :: "(_ object_ptr ⇒ bool"
  and set_child_nodes :: "(_ object_ptr ⇒ (_ node_ptr list ⇒ (_, unit) dom_prog"
  and set_child_nodes_locs :: "(_ object_ptr ⇒ (_ node_ptr list ⇒ (_, unit) dom_prog set"
  and set_child_nodesCore_DOM :: "(_ object_ptr ⇒ (_ node_ptr list ⇒ (_, unit) dom_prog"
  and set_child_nodes_locsCore_DOM :: "(_ object_ptr ⇒ (_ node_ptr list ⇒ (_, unit) dom_prog set" +
assumes known_ptr_impl: "known_ptr = ShadowRootClass.known_ptr"
assumes type_wf_impl: "type_wf = ShadowRootClass.type_wf"
assumes set_child_nodes_impl: "set_child_nodes = a_set_child_nodes"
assumes set_child_nodes_locs_impl: "set_child_nodes_locs = a_set_child_nodes_locs"
begin
lemmas set_child_nodes_def = set_child_nodes_impl[unfolded a_set_child_nodes_def set_child_nodes_def]
lemmas set_child_nodes_locs_def = set_child_nodes_locs_impl[unfolded a_set_child_nodes_locs_def
  set_child_nodes_locs_def, folded CD.set_child_nodes_locsImpl]

lemma set_child_nodes_writes: "writes (set_child_nodes_locs ptr) (set_child_nodes ptr children) h h"
⟨proof⟩

lemma set_child_nodes_pointers_preserved:
  assumes "w ∈ set_child_nodes_locs object_ptr"
  assumes "h ⊢ w →_h h'"
  shows "object_ptr_kinds h = object_ptr_kinds h'"
⟨proof⟩

lemma set_child_nodes_types_preserved:
  assumes "w ∈ set_child_nodes_locs object_ptr"
  assumes "h ⊢ w →_h h'"
  shows "type_wf h = type_wf h"
⟨proof⟩
end

interpretation
i_set_child_nodes?: l_set_child_nodesShadow_DOM type_wf known_ptr DocumentClass.type_wf
DocumentClass.known_ptr set_child_nodes set_child_nodes_locs Core_DOM_Functions.set_child_nodes
Core_DOM_Functions.set_child_nodes_locs
⟨proof⟩
declare l_set_child_nodesShadow_DOM_axioms[instances]

lemma set_child_nodes_is_l_set_child_nodes [instances]: "l_set_child_nodes type_wf set_child_nodes
  set_child_nodes_locs"
⟨proof⟩

get_child_nodes locale l_set_child_nodes_get_child_nodesShadow_DOM =
l_get_child_nodesShadow_DOM
type_wf known_ptr type_wfCore_DOM known_ptrCore_DOM get_child_nodes get_child_nodes_locs
get_child_nodesCore_DOM get_child_nodes_locsCore_DOM
+ l_set_child_nodesShadow_DOM
type_wf known_ptr type_wfCore_DOM known_ptrCore_DOM set_child_nodes set_child_nodes_locs
set_child_nodesCore_DOM set_child_nodes_locsCore_DOM
+ CD: l_set_child_nodes_get_child_nodesCore_DOM
type_wfCore_DOM known_ptrCore_DOM get_child_nodesCore_DOM get_child_nodes_locsCore_DOM

```

```

set_child_nodesCore_DOM set_child_nodes_locsCore_DOM
for type_wf :: "(_ heap ⇒ bool"
  and known_ptr :: "(_ object_ptr ⇒ bool"
  and type_wfCore_DOM :: "(_ heap ⇒ bool"
  and known_ptrCore_DOM :: "(_ object_ptr ⇒ bool"
  and get_child_nodes :: "(_ object_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
  and get_child_nodes_locs :: "(_ object_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
  and get_child_nodesCore_DOM :: "(_ object_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
  and get_child_nodes_locsCore_DOM :: "(_ object_ptr ⇒ ((_) heap ⇒ bool) set"
  and set_child_nodes :: "(_ object_ptr ⇒ (_ node_ptr list ⇒ ((_) heap, exception, unit) prog"
  and set_child_nodes_locs :: "(_ object_ptr ⇒ ((_) heap, exception, unit) prog set"
  and set_child_nodesCore_DOM :: "(_ object_ptr ⇒ (_ node_ptr list ⇒ ((_) heap, exception, unit) prog"
  and set_child_nodes_locsCore_DOM :: "(_ object_ptr ⇒ ((_) heap, exception, unit) prog set"
begin

lemma set_child_nodes_get_child_nodes:
  assumes "known_ptr ptr"
  assumes "type_wf h"
  assumes "h ⊢ set_child_nodes ptr children →h h'"
  shows "h' ⊢ get_child_nodes ptr →r children"
  ⟨proof⟩

lemma set_child_nodes_get_child_nodes_different_pointers:
  assumes "ptr ≠ ptr'"
  assumes "w ∈ set_child_nodes_locs ptr"
  assumes "h ⊢ w →h h'"
  assumes "r ∈ get_child_nodes_locs ptr"
  shows "r h h'"
  ⟨proof⟩

end

interpretation
  i_set_child_nodes_get_child_nodes?: l_set_child_nodes_get_child_nodesShadow_DOM type_wf known_ptr
  DocumentClass.type_wf DocumentClass.known_ptr get_child_nodes get_child_nodes_locs
  Core_DOM_Functions.get_child_nodes Core_DOM_Functions.get_child_nodes_locs set_child_nodes
  set_child_nodes_locs Core_DOM_Functions.set_child_nodes Core_DOM_Functions.set_child_nodes_locs
  ⟨proof⟩
declare l_set_child_nodes_get_child_nodesShadow_DOM_axioms[instances]

lemma set_child_nodes_get_child_nodes_is_l_set_child_nodes_get_child_nodes [instances]:
  "l_set_child_nodes_get_child_nodes type_wf known_ptr get_child_nodes get_child_nodes_locs
   set_child_nodes set_child_nodes_locs"
  ⟨proof⟩

set_tag_type

locale l_set_tag_nameShadow_DOM =
  CD: l_set_tag_nameCore_DOM type_wfCore_DOM set_tag_name set_tag_name_locs +
  l_type_wf type_wf
  for type_wf :: "(_ heap ⇒ bool"
    and type_wfCore_DOM :: "(_ heap ⇒ bool"
    and set_tag_name :: "(_ element_ptr ⇒ tag_name ⇒ (_, unit) dom_prog"
    and set_tag_name_locs :: "(_ element_ptr ⇒ (_, unit) dom_prog set" +
  assumes type_wf_impl: "type_wf = ShadowRootClass.type_wf"
begin
lemmas set_tag_name_def = CD.set_tag_nameImpl[unfolded CD.a_set_tag_name_def set_tag_name_def]
lemmas set_tag_name_locs_def = CD.set_tag_name_locsImpl[unfolded CD.a_set_tag_name_locs_def
  set_tag_name_locs_def]

lemma set_tag_name_ok:
  "type_wf h ⇒ element_ptr ∉ element_ptr_kinds h ⇒ h ⊢ ok (set_tag_name element_ptr tag)"

```

```

⟨proof⟩

lemma set_tag_name_writes:
  "writes (set_tag_name_locs element_ptr) (set_tag_name element_ptr tag) h h''"
  ⟨proof⟩

lemma set_tag_name_pointers_preserved:
  assumes "w ∈ set_tag_name_locs element_ptr"
  assumes "h ⊢ w →h h''"
  shows "object_ptr_kinds h = object_ptr_kinds h''"
  ⟨proof⟩

lemma set_tag_name_typepreserved:
  assumes "w ∈ set_tag_name_locs element_ptr"
  assumes "h ⊢ w →h h''"
  shows "type_wf h = type_wf h''"
  ⟨proof⟩
end

interpretation i_set_tag_name?: l_set_tag_nameShadow_DOM type_wf DocumentClass.type_wf set_tag_name
  set_tag_name_locs
  ⟨proof⟩
declare l_set_tag_nameShadow_DOM_axioms [instances]

lemma set_tag_name_is_l_set_tag_name [instances]:
  "l_set_tag_name type_wf set_tag_name set_tag_name_locs"
  ⟨proof⟩

get_child_nodes locale l_set_tag_name_get_child_nodesShadow_DOM =
  l_set_tag_nameShadow_DOM +
  l_get_child_nodesShadow_DOM +
  CD: l_set_tag_name_get_child_nodesCore_DOM type_wfCore_DOM set_tag_name set_tag_name_locs
    known_ptrCore_DOM get_child_nodesCore_DOM get_child_nodes_locsCore_DOM
begin
  lemma set_tag_name_get_child_nodes:
    "∀ w ∈ set_tag_name_locs ptr. (h ⊢ w →h h' → (∀ r ∈ get_child_nodes_locs ptr'. r h h'))"
    ⟨proof⟩
end

interpretation
  i_set_tag_name_get_child_nodes?: l_set_tag_name_get_child_nodesShadow_DOM type_wf
  DocumentClass.type_wf set_tag_name set_tag_name_locs known_ptr DocumentClass.known_ptr
  get_child_nodes get_child_nodes_locs Core_DOM_Functions.get_child_nodes
  Core_DOM_Functions.get_child_nodes_locs
  ⟨proof⟩
declare l_set_tag_name_get_child_nodesShadow_DOM_axioms [instances]

lemma set_tag_name_get_child_nodes_is_l_set_tag_name_get_child_nodes [instances]:
  "l_set_tag_name_get_child_nodes type_wf set_tag_name set_tag_name_locs known_ptr get_child_nodes
    get_child_nodes_locs"
  ⟨proof⟩

get_shadow_root
locale l_get_shadow_rootShadow_DOM_defs
begin
definition a_get_shadow_root :: "(_ element_ptr ⇒ (_, _) shadow_root_ptr option) dom_prog"
  where
    "a_get_shadow_root element_ptr = get_M element_ptr shadow_root_opt"

definition a_get_shadow_root_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set)"
  where
    "a_get_shadow_root_locs element_ptr ≡ {preserved (get_M element_ptr shadow_root_opt)}"

```

```

end

global_interpretation l_get_shadow_rootShadow_DOM_defs
  defines get_shadow_root = a_get_shadow_root
  and get_shadow_root_locs = a_get_shadow_root_locs
  ⟨proof⟩

locale l_get_shadow_root_defs =
  fixes get_shadow_root :: "(_ element_ptr ⇒ (_ _ shadow_root_ptr option) dom_prog"
  fixes get_shadow_root_locs :: "(_ element_ptr ⇒ (_ heap ⇒ (_ heap ⇒ bool) set"

locale l_get_shadow_rootShadow_DOM =
  l_get_shadow_rootShadow_DOM_defs +
  l_get_shadow_root_defs get_shadow_root get_shadow_root_locs +
  l_type_wf type_wf
  for type_wf :: "(_ heap ⇒ bool"
    and get_shadow_root :: "(_ element_ptr ⇒ ((_) heap, exception, (_ shadow_root_ptr option) prog"
      and get_shadow_root_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set" +
  assumes type_wfImpl: "type_wf = ShadowRootClass.type_wf"
  assumes get_shadow_rootImpl: "get_shadow_root = a_get_shadow_root"
  assumes get_shadow_root_locsImpl: "get_shadow_root_locs = a_get_shadow_root_locs"
begin
lemmas get_shadow_root_def = get_shadow_rootImpl[unfolded get_shadow_root_def a_get_shadow_root_def]
lemmas get_shadow_root_locs_def = get_shadow_root_locsImpl[unfolded get_shadow_root_locs_def
  a_get_shadow_root_locs_def]

lemma get_shadow_root_ok:
  "type_wf h ⇒ element_ptr /∈ element_ptr_kinds h ⇒ h ⊢ ok (get_shadow_root element_ptr)"
  ⟨proof⟩

lemma get_shadow_root_pure [simp]: "pure (get_shadow_root element_ptr) h"
  ⟨proof⟩

lemma get_shadow_root_ptr_in_heap:
  assumes "h ⊢ get_shadow_root element_ptr →r children"
  shows "element_ptr /∈ element_ptr_kinds h"
  ⟨proof⟩

lemma get_shadow_root_reads:
  "reads (get_shadow_root_locs element_ptr) (get_shadow_root element_ptr) h h'"
  ⟨proof⟩
end

interpretation i_get_shadow_root?: l_get_shadow_rootShadow_DOM type_wf get_shadow_root
  get_shadow_root_locs
  ⟨proof⟩
declare l_get_shadow_rootShadow_DOM_axioms [instances]

locale l_get_shadow_root = l_type_wf + l_get_shadow_root_defs +
  assumes get_shadow_root_reads:
    "reads (get_shadow_root_locs element_ptr) (get_shadow_root element_ptr) h h'"
  assumes get_shadow_root_ok:
    "type_wf h ⇒ element_ptr /∈ element_ptr_kinds h ⇒ h ⊢ ok (get_shadow_root element_ptr)"
  assumes get_shadow_root_ptr_in_heap:
    "h ⊢ ok (get_shadow_root element_ptr) ⇒ element_ptr /∈ element_ptr_kinds h"
  assumes get_shadow_root_pure [simp]:
    "pure (get_shadow_root element_ptr) h"

lemma get_shadow_root_is_l_get_shadow_root [instances]:
  "l_get_shadow_root type_wf get_shadow_root get_shadow_root_locs"
  ⟨proof⟩

set_disconnected_nodes locale l_set_disconnected_nodes_get_shadow_rootShadow_DOM =

```

```

l_set_disconnected_nodesCore_DOM type_wfCore_DOM set_disconnected_nodes set_disconnected_nodes_locs
+
l_get_shadow_rootShadow_DOM type_wf get_shadow_root get_shadow_root_locs
for type_wf :: "(_ heap ⇒ bool"
  and type_wfCore_DOM :: "(_ heap ⇒ bool"
  and set_disconnected_nodes
    :: "(_ document_ptr ⇒ (_ node_ptr list ⇒ ((_) heap, exception, unit) prog"
    and set_disconnected_nodes_locs :: "(_ document_ptr ⇒ ((_) heap, exception, unit) prog set"
    and get_shadow_root :: "(_ element_ptr ⇒ ((_) heap, exception, (_ shadow_root_ptr option) prog"
    and get_shadow_root_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ bool) set"
begin
lemma set_disconnected_nodes_get_shadow_root:
  "∀ w ∈ set_disconnected_nodes_locs ptr. (h ⊢ w →h h' → (forall r ∈ get_shadow_root_locs ptr'. r h h'))"
  ⟨proof⟩
end

locale l_set_disconnected_nodes_get_shadow_root =
l_set_disconnected_nodes_defs +
l_get_shadow_root_defs +
assumes set_disconnected_nodes_get_shadow_root:
  "∀ w ∈ set_disconnected_nodes_locs ptr. (h ⊢ w →h h' → (forall r ∈ get_shadow_root_locs ptr'. r h h'))"

interpretation
i_set_disconnected_nodes_get_shadow_root?: l_set_disconnected_nodes_get_shadow_rootShadow_DOM
type_wf DocumentClass.type_wf set_disconnected_nodes set_disconnected_nodes_locs get_shadow_root
get_shadow_root_locs
⟨proof⟩
declare l_set_disconnected_nodes_get_shadow_rootShadow_DOM_axioms[instances]

lemma set_disconnected_nodes_get_shadow_root_is_l_set_disconnected_nodes_get_shadow_root [instances]:
  "l_set_disconnected_nodes_get_shadow_root set_disconnected_nodes_locs get_shadow_root_locs"
  ⟨proof⟩

set_tag_type locale l_set_tag_name_get_shadow_rootCore_DOM =
l_set_tag_nameShadow_DOM +
l_get_shadow_rootShadow_DOM
begin
lemma set_tag_name_get_shadow_root:
  "∀ w ∈ set_tag_name_locs ptr. (h ⊢ w →h h' → (forall r ∈ get_shadow_root_locs ptr'. r h h'))"
  ⟨proof⟩
end

locale l_set_tag_name_get_shadow_root = l_set_tag_name + l_get_shadow_root +
assumes set_tag_name_get_shadow_root:
  "∀ w ∈ set_tag_name_locs ptr. (h ⊢ w →h h' → (forall r ∈ get_shadow_root_locs ptr'. r h h'))"

interpretation
i_set_tag_name_get_shadow_root?: l_set_tag_name_get_shadow_rootCore_DOM type_wf DocumentClass.type_wf
set_tag_name set_tag_name_locs
get_shadow_root get_shadow_root_locs
⟨proof⟩
declare l_set_tag_name_get_shadow_rootCore_DOM_axioms[instances]

lemma set_tag_name_get_shadow_root_is_l_set_tag_name_get_shadow_root [instances]:
  "l_set_tag_name_get_shadow_root type_wf set_tag_name set_tag_name_locs get_shadow_root
  get_shadow_root_locs"
  ⟨proof⟩

set_child_nodes locale l_set_child_nodes_get_shadow_rootShadow_DOM =
l_set_child_nodesShadow_DOM type_wf known_ptr type_wfCore_DOM known_ptrCore_DOM set_child_nodes
set_child_nodes_locs set_child_nodesCore_DOM set_child_nodes_locsCore_DOM +
l_get_shadow_rootShadow_DOM type_wf get_shadow_root get_shadow_root_locs
for type_wf :: "(_ heap ⇒ bool"

```

```

and known_ptr :: "(_ object_ptr ⇒ bool"
and type_wfCore_DOM :: "(_ heap ⇒ bool"
and known_ptrCore_DOM :: "(_ object_ptr ⇒ bool"
and set_child_nodes :: "(_ object_ptr ⇒ (_ node_ptr list ⇒ ((_) heap, exception, unit) prog"
and set_child_nodes_locs :: "(_ object_ptr ⇒ ((_) heap, exception, unit) prog set"
and set_child_nodesCore_DOM :: "(_ object_ptr ⇒ (_ node_ptr list ⇒ ((_) heap, exception, unit)
prog"
and set_child_nodes_locsCore_DOM :: "(_ object_ptr ⇒ ((_) heap, exception, unit) prog set"
and get_shadow_root :: "(_ element_ptr ⇒ ((_) heap, exception, (_ shadow_root_ptr option) prog"
and get_shadow_root_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ bool) set"
begin
lemma set_child_nodes_get_shadow_root: "∀ w ∈ set_child_nodes_locs ptr. (h ⊢ w →_h h' →
(∀ r ∈ get_shadow_root_locs ptr'. r h h'))"
⟨proof⟩
end

locale l_set_child_nodes_get_shadow_root = l_set_child_nodes_defs + l_get_shadow_root_defs +
assumes set_child_nodes_get_shadow_root:
"∀ w ∈ set_child_nodes_locs ptr. (h ⊢ w →_h h' → (∀ r ∈ get_shadow_root_locs ptr'. r h h'))"

interpretation
i_set_child_nodes_get_shadow_root?: l_set_child_nodes_get_shadow_rootShadow_DOM type_wf known_ptr
DocumentClass.type_wf DocumentClass.known_ptr set_child_nodes set_child_nodes_locs
Core_DOM_Functions.set_child_nodes Core_DOM_Functions.set_child_nodes_locs get_shadow_root
get_shadow_root_locs
⟨proof⟩
declare l_set_child_nodes_get_shadow_rootShadow_DOM_axioms[instances]

lemma set_child_nodes_get_shadow_root_is_l_set_child_nodes_get_shadow_root [instances]:
"l_set_child_nodes_get_shadow_root set_child_nodes_locs get_shadow_root_locs"
⟨proof⟩

delete_shadow_root locale l_delete_shadow_root_get_shadow_rootShadow_DOM =
l_get_shadow_rootShadow_DOM
begin
lemma get_shadow_root_delete_shadow_root: "h ⊢ deleteShadowRoot_M shadow_root_ptr →_h h'
⇒ r ∈ get_shadow_root_locs ptr' ⇒ r h h'"
⟨proof⟩
end

locale l_delete_shadow_root_get_shadow_root = l_get_shadow_root_defs +
assumes get_shadow_root_delete_shadow_root: "h ⊢ deleteShadowRoot_M shadow_root_ptr →_h h'
⇒ r ∈ get_shadow_root_locs ptr' ⇒ r h h'"
interpretation l_delete_shadow_root_get_shadow_rootShadow_DOM type_wf get_shadow_root
get_shadow_root_locs
⟨proof⟩

lemma l_delete_shadow_root_get_shadow_root_get_shadow_root_locs [instances]: "l_delete_shadow_root_get_shadow_root
get_shadow_root_locs"
⟨proof⟩

new_character_data locale l_new_character_data_get_shadow_rootShadow_DOM =
l_get_shadow_rootShadow_DOM type_wf get_shadow_root get_shadow_root_locs
for type_wf :: "(_ heap ⇒ bool"
and get_shadow_root :: "(_ element_ptr ⇒ ((_) heap, exception, (_ shadow_root_ptr option) prog"
and get_shadow_root_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ bool) set"
begin
lemma get_shadow_root_new_character_data:
"h ⊢ new_character_data →_r new_character_data_ptr ⇒ h ⊢ new_character_data →_h h'
⇒ r ∈ get_shadow_root_locs ptr' ⇒ r h h'"
⟨proof⟩
end

```

```

locale l_new_character_data_get_shadow_root = l_new_character_data + l_get_shadow_root +
assumes get_shadow_root_new_character_data:
  "h ⊢ new_character_data →r new_character_data_ptr
   ⇒ h ⊢ new_character_data →h h' ⇒ r ∈ get_shadow_root_locs ptr' ⇒ r h h''"

interpretation i_new_character_data_get_shadow_root?:
  l_new_character_data_get_shadow_rootShadow_DOM type_wf get_shadow_root get_shadow_root_locs
  ⟨proof⟩
declare l_new_character_data_get_shadow_rootShadow_DOM_axioms [instances]

lemma new_character_data_get_shadow_root_is_l_new_character_data_get_shadow_root [instances]:
  "l_new_character_data_get_shadow_root type_wf get_shadow_root get_shadow_root_locs"
  ⟨proof⟩

new_document locale l_new_document_get_shadow_rootShadow_DOM =
  l_get_shadow_rootShadow_DOM type_wf get_shadow_root get_shadow_root_locs
  for type_wf :: "(_) heap ⇒ bool"
    and get_shadow_root :: "(_) element_ptr ⇒ ((_) heap, exception, (_) shadow_root_ptr option) prog"
    and get_shadow_root_locs :: "(_) element_ptr ⇒ ((_) heap ⇒ (_)) heap ⇒ bool) set"
begin
lemma get_shadow_root_new_document:
  "h ⊢ new_document →r new_document_ptr ⇒ h ⊢ new_document →h h'
   ⇒ r ∈ get_shadow_root_locs ptr' ⇒ r h h''"
  ⟨proof⟩
end

locale l_new_document_get_shadow_root = l_new_document + l_get_shadow_root +
assumes get_shadow_root_new_document:
  "h ⊢ new_document →r new_document_ptr
   ⇒ h ⊢ new_document →h h' ⇒ r ∈ get_shadow_root_locs ptr' ⇒ r h h''"

interpretation i_new_document_get_shadow_root?:
  l_new_document_get_shadow_rootShadow_DOM type_wf get_shadow_root get_shadow_root_locs
  ⟨proof⟩
declare l_new_document_get_shadow_rootShadow_DOM_axioms [instances]

lemma new_document_get_shadow_root_is_l_new_document_get_shadow_root [instances]:
  "l_new_document_get_shadow_root type_wf get_shadow_root get_shadow_root_locs"
  ⟨proof⟩

new_element locale l_new_element_get_shadow_rootShadow_DOM =
  l_get_shadow_rootShadow_DOM type_wf get_shadow_root get_shadow_root_locs
  for type_wf :: "(_) heap ⇒ bool"
    and get_shadow_root :: "(_) element_ptr ⇒ ((_) heap, exception, (_) shadow_root_ptr option) prog"
    and get_shadow_root_locs :: "(_) element_ptr ⇒ ((_) heap ⇒ (_)) heap ⇒ bool) set"
begin
lemma get_shadow_root_new_element:
  "ptr' ≠ new_element_ptr ⇒ h ⊢ new_element →r new_element_ptr ⇒ h ⊢ new_element →h h'
   ⇒ r ∈ get_shadow_root_locs ptr' ⇒ r h h''"
  ⟨proof⟩

lemma new_element_no_shadow_root:
  "h ⊢ new_element →r new_element_ptr ⇒ h ⊢ new_element →h h'
   ⇒ h' ⊢ get_shadow_root new_element_ptr →r None"
  ⟨proof⟩
end

locale l_new_element_get_shadow_root = l_new_element + l_get_shadow_root +
assumes get_shadow_root_new_element:
  "ptr' ≠ new_element_ptr ⇒ h ⊢ new_element →r new_element_ptr
   ⇒ h ⊢ new_element →h h' ⇒ r ∈ get_shadow_root_locs ptr' ⇒ r h h''"

```

```

assumes new_element_no_shadow_root:
  "h ⊢ new_element →r new_element_ptr ⟹ h ⊢ new_element →h h' 
   ⟹ h' ⊢ get_shadow_root new_element_ptr →r None"

```

interpretation i_new_element_get_shadow_root?:

```

l_new_element_get_shadow_rootShadow_DOM type_wf get_shadow_root get_shadow_root_locs
⟨proof⟩
declare l_new_element_get_shadow_rootShadow_DOM_axioms [instances]

```

lemma new_element_get_shadow_root_is_l_new_element_get_shadow_root [instances]:

```

"l_new_element_get_shadow_root type_wf get_shadow_root get_shadow_root_locs"
⟨proof⟩

```

new_shadow_root locale l_new_shadow_root_get_shadow_root_{Shadow_DOM} =
 l_get_shadow_root_{Shadow_DOM} type_wf get_shadow_root get_shadow_root_locs
 for type_wf :: "(_) heap ⇒ bool"
 and get_shadow_root :: "(_) element_ptr ⇒ ((_) heap, exception, (_) shadow_root_ptr option) prog"
 and get_shadow_root_locs :: "(_) element_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
begin
 lemma get_shadow_root_new_shadow_root:
 "h ⊢ newShadowRoot_M →_r new_shadow_root_ptr ⟹ h ⊢ newShadowRoot_M →_h h'
 ⟹ r ∈ get_shadow_root_locs ptr' ⟹ r h h'"
 ⟨proof⟩
end

locale l_new_shadow_root_get_shadow_root = l_get_shadow_root +
 assumes get_shadow_root_new_shadow_root:
 "h ⊢ newShadowRoot_M →_r new_shadow_root_ptr
 ⟹ h ⊢ newShadowRoot_M →_h h' ⟹ r ∈ get_shadow_root_locs ptr' ⟹ r h h'"

interpretation i_new_shadow_root_get_shadow_root?:

```

l_new_shadow_root_get_shadow_rootShadow_DOM type_wf get_shadow_root get_shadow_root_locs
⟨proof⟩
declare l_new_shadow_root_get_shadow_rootShadow_DOM_axioms [instances]

```

lemma new_shadow_root_get_shadow_root_is_l_new_shadow_root_get_shadow_root [instances]:

```

"l_new_shadow_root_get_shadow_root type_wf get_shadow_root get_shadow_root_locs"
⟨proof⟩

```

set_shadow_root

```

locale l_set_shadow_rootShadow_DOM_defs
begin
  definition a_set_shadow_root :: "(_) element_ptr ⇒ (_ shadow_root_ptr option ⇒ (_, unit) dom_prog"
    where
      "a_set_shadow_root element_ptr = put_M element_ptr shadow_root_opt_update"
  definition a_set_shadow_root_locs :: "(_) element_ptr ⇒ ((_, unit) dom_prog) set"
    where
      "a_set_shadow_root_locs element_ptr ≡ all_args (put_M element_ptr shadow_root_opt_update)"
end

global_interpretation l_set_shadow_rootShadow_DOM_defs
  defines set_shadow_root = a_set_shadow_root
  and set_shadow_root_locs = a_set_shadow_root_locs
  ⟨proof⟩

locale l_set_shadow_root_defs =
  fixes set_shadow_root :: "(_) element_ptr ⇒ (_ shadow_root_ptr option ⇒ (_, unit) dom_prog"
  fixes set_shadow_root_locs :: "(_) element_ptr ⇒ (_, unit) dom_prog set"

```

```

locale l_set_shadow_root_Shadow_DOM =
l_type_wf type_wf +
l_set_shadow_root_defs set_shadow_root set_shadow_root_locs +
l_set_shadow_root_Shadow_DOM_defs
for type_wf :: "(_ heap ⇒ bool"
  and set_shadow_root :: "(_ element_ptr ⇒ (_ shadow_root_ptr option ⇒ (_, unit) dom_prog"
    and set_shadow_root_locs :: "(_ element_ptr ⇒ (_ unit) dom_prog set" +
assumes type_wfImpl: "type_wf = ShadowRootClass.type_wf"
assumes set_shadow_rootImpl: "set_shadow_root = a_set_shadow_root"
assumes set_shadow_root_locsImpl: "set_shadow_root_locs = a_set_shadow_root_locs"
begin
lemmas set_shadow_root_def = set_shadow_rootImpl[unfolded set_shadow_root_def
a_set_shadow_root_def]
lemmas set_shadow_root_locs_def = set_shadow_root_locsImpl[unfolded set_shadow_root_locs_def
a_set_shadow_root_locs_def]

lemma set_shadow_root_ok: "type_wf h ⇒ element_ptr /∈ element_ptr_kinds h ⇒
h ⊢ ok (set_shadow_root element_ptr tag)"
⟨proof⟩

lemma set_shadow_root_ptr_in_heap:
"h ⊢ ok (set_shadow_root element_ptr shadow_root) ⇒ element_ptr /∈ element_ptr_kinds h"
⟨proof⟩

lemma set_shadow_root_writes:
"writes (set_shadow_root_locs element_ptr) (set_shadow_root element_ptr tag) h h'"
⟨proof⟩

lemma set_shadow_root_pointers_preserved:
assumes "w ∈ set_shadow_root_locs element_ptr"
assumes "h ⊢ w →_h h'"
shows "object_ptr_kinds h = object_ptr_kinds h'"
⟨proof⟩

lemma set_shadow_root_types_preserved:
assumes "w ∈ set_shadow_root_locs element_ptr"
assumes "h ⊢ w →_h h'"
shows "type_wf h = type_wf h"
⟨proof⟩
end

interpretation i_set_shadow_root?: l_set_shadow_root_Shadow_DOM type_wf set_shadow_root
set_shadow_root_locs
⟨proof⟩
declare l_set_shadow_root_Shadow_DOM_axioms [instances]

locale l_set_shadow_root = l_type_wf + l_set_shadow_root_defs +
assumes set_shadow_root_writes:
"writes (set_shadow_root_locs element_ptr) (set_shadow_root element_ptr disc_nodes) h h'"
assumes set_shadow_root_ok:
"type_wf h ⇒ element_ptr /∈ element_ptr_kinds h ⇒
h ⊢ ok (set_shadow_root element_ptr shadow_root)"
assumes set_shadow_root_ptr_in_heap:
"h ⊢ ok (set_shadow_root element_ptr shadow_root) ⇒ element_ptr /∈ element_ptr_kinds h"
assumes set_shadow_root_pointers_preserved:
"w ∈ set_shadow_root_locs element_ptr ⇒ h ⊢ w →_h h' ⇒
object_ptr_kinds h = object_ptr_kinds h'"
assumes set_shadow_root_types_preserved:
"w ∈ set_shadow_root_locs element_ptr ⇒ h ⊢ w →_h h' ⇒ type_wf h = type_wf h"

lemma set_shadow_root_is_l_set_shadow_root [instances]:
"l_set_shadow_root type_wf set_shadow_root set_shadow_root_locs"
⟨proof⟩

```

```

get_shadow_root locale l_set_shadow_root_get_shadow_rootShadow_DOM =
  l_set_shadow_rootShadow_DOM +
  l_get_shadow_rootShadow_DOM
begin
lemma set_shadow_root_get_shadow_root:
  "type_wf h ==> h ⊢ set_shadow_root ptr shadow_root_ptr_opt →h h' ==>
   h' ⊢ get_shadow_root ptr →r shadow_root_ptr_opt"
  ⟨proof⟩

lemma set_shadow_root_get_shadow_root_different_pointers: "ptr ≠ ptr' ==>
  ∀ w ∈ set_shadow_root_locs ptr. (h ⊢ w →h h' ==> (∀ r ∈ get_shadow_root_locs ptr'. r h h'))"
  ⟨proof⟩
end

interpretation i_set_shadow_root_get_shadow_root?: l_set_shadow_root_get_shadow_rootShadow_DOM type_wf
  set_shadow_root set_shadow_root_locs get_shadow_root get_shadow_root_locs
  ⟨proof⟩
declare l_set_shadow_root_get_shadow_rootShadow_DOM_axioms[instances]

locale l_set_shadow_root_get_shadow_root =
  l_type_wf +
  l_set_shadow_root_defs +
  l_get_shadow_root_defs +
  assumes set_shadow_root_get_shadow_root:
    "type_wf h ==> h ⊢ set_shadow_root ptr shadow_root_ptr_opt →h h' ==>
     h' ⊢ get_shadow_root ptr →r shadow_root_ptr_opt"
  assumes set_shadow_root_get_shadow_root_different_pointers:
    "ptr ≠ ptr' ==> w ∈ set_shadow_root_locs ptr ==> h ⊢ w →h h' ==>
     r ∈ get_shadow_root_locs ptr' ==> r h h'"

lemma set_shadow_root_get_shadow_root_is_l_set_shadow_root_get_shadow_root [instances]:
  "l_set_shadow_root_get_shadow_root type_wf set_shadow_root set_shadow_root_locs get_shadow_root
  get_shadow_root_locs"
  ⟨proof⟩

set_mode

locale l_set_modeShadow_DOM_defs
begin
definition a_set_mode :: "(_ shadow_root_ptr ⇒ shadow_root_mode ⇒ (_, unit) dom_prog"
  where
    "a_set_mode shadow_root_ptr = put_M shadow_root_ptr mode_update"

definition a_set_mode_locs :: "(_ shadow_root_ptr ⇒ ((_, unit) dom_prog) set"
  where
    "a_set_mode_locs shadow_root_ptr ≡ all_args (put_M shadow_root_ptr mode_update)"
end

global_interpretation l_set_modeShadow_DOM_defs
  defines set_mode = a_set_mode
  and set_mode_locs = a_set_mode_locs
  ⟨proof⟩

locale l_set_mode_defs =
  fixes set_mode :: "(_ shadow_root_ptr ⇒ shadow_root_mode ⇒ (_, unit) dom_prog"
  fixes set_mode_locs :: "(_ shadow_root_ptr ⇒ (_, unit) dom_prog set"

locale l_set_modeShadow_DOM =
  l_type_wf type_wf +
  l_set_mode_defs set_mode set_mode_locs +
  l_set_modeShadow_DOM_defs
  for type_wf :: "(_ heap ⇒ bool"

```

```

and set_mode :: "(_ shadow_root_ptr ⇒ shadow_root_mode ⇒ (_, unit) dom_prog"
and set_mode_locs :: "(_ shadow_root_ptr ⇒ (_, unit) dom_prog set" +
assumes type_wfImpl: "type_wf = ShadowRootClass.type_wf"
assumes setModeImpl: "set_mode = a_set_mode"
assumes setModeLocsImpl: "set_mode_locs = a_set_mode_locs"
begin
lemmas set_mode_def = set_modeImpl[unfolded set_mode_def a_set_mode_def]
lemmas set_mode_locs_def = setModeLocsImpl[unfolded set_mode_locs_def a_set_mode_locs_def]

lemma set_mode_ok:
"type_wf h ⇒ shadow_root_ptr /∈ shadow_root_ptr_kinds h ⇒
h ⊢ ok (set_mode shadow_root_ptr shadow_root_mode)"
⟨proof⟩

lemma set_mode_ptr_in_heap:
"h ⊢ ok (set_mode shadow_root_ptr shadow_root_mode) ⇒
shadow_root_ptr /∈ shadow_root_ptr_kinds h"
⟨proof⟩

lemma set_mode_writes:
"writes (set_mode_locs shadow_root_ptr) (set_mode shadow_root_ptr shadow_root_mode) h h'"
⟨proof⟩

lemma set_mode_pointers_preserved:
assumes "w ∈ set_mode_locs element_ptr"
assumes "h ⊢ w →h h'"
shows "object_ptr_kinds h = object_ptr_kinds h'"
⟨proof⟩

lemma set_mode_types_preserved:
assumes "w ∈ set_mode_locs element_ptr"
assumes "h ⊢ w →h h'"
shows "type_wf h = type_wf h'"
⟨proof⟩
end

interpretation i_set_mode?: l_set_modeShadow_DOM type_wf set_mode set_mode_locs
⟨proof⟩
declare l_set_modeShadow_DOM_axioms [instances]

locale l_set_mode = l_type_wf +l_set_mode_defs +
assumes set_mode_writes:
"writes (set_mode_locs shadow_root_ptr) (set_mode shadow_root_ptr shadow_root_mode) h h'"
assumes set_mode_ok:
"type_wf h ⇒ shadow_root_ptr /∈ shadow_root_ptr_kinds h ⇒
h ⊢ ok (set_mode shadow_root_ptr shadow_root_mode)"
assumes set_mode_ptr_in_heap:
"h ⊢ ok (set_mode shadow_root_ptr shadow_root_mode) ⇒
shadow_root_ptr /∈ shadow_root_ptr_kinds h"
assumes set_mode_pointers_preserved:
"w ∈ set_mode_locs shadow_root_ptr ⇒
h ⊢ w →h h' ⇒ object_ptr_kinds h = object_ptr_kinds h'"
assumes set_mode_types_preserved:
"w ∈ set_mode_locs shadow_root_ptr ⇒ h ⊢ w →h h' ⇒ type_wf h = type_wf h"

lemma set_mode_is_l_set_mode [instances]: "l_set_mode type_wf set_mode set_mode_locs"
⟨proof⟩

get_child_nodes locale l_set_shadow_root_get_child_nodesShadow_DOM =
l_get_child_nodesShadow_DOM +
l_set_shadow_rootShadow_DOM
begin
lemma set_shadow_root_get_child_nodes:

```

```

"∀w ∈ set_shadow_root_locs ptr. (h ⊢ w →h h' → (∀r ∈ get_child_nodes_locs ptr'. r h h'))"
⟨proof⟩
end

interpretation i_set_shadow_root_get_child_nodes?: l_set_shadow_root_get_child_nodesShadow_DOM type_wf
known_ptr DocumentClass.type_wf DocumentClass.known_ptr get_child_nodes get_child_nodes_locs
Core_DOM_Functions.get_child_nodes Core_DOM_Functions.get_child_nodes_locs set_shadow_root
set_shadow_root_locs
⟨proof⟩
declare l_set_shadow_root_get_child_nodesShadow_DOM_axioms[instances]

locale l_set_shadow_root_get_child_nodes = l_set_shadow_root + l_get_child_nodes +
assumes set_shadow_root_get_child_nodes:
"∀w ∈ set_shadow_root_locs ptr. (h ⊢ w →h h' → (∀r ∈ get_child_nodes_locs ptr'. r h h'))"

lemma set_shadow_root_get_child_nodes_is_l_set_shadow_root_get_child_nodes [instances]:
"l_set_shadow_root_get_child_nodes type_wf set_shadow_root set_shadow_root_locs known_ptr
get_child_nodes get_child_nodes_locs"
⟨proof⟩

get_shadow_root locale l_set_mode_get_shadow_rootShadow_DOM =
l_set_modeShadow_DOM +
l_get_shadow_rootShadow_DOM
begin
lemma set_mode_get_shadow_root:
"∀w ∈ set_mode_locs ptr. (h ⊢ w →h h' → (∀r ∈ get_shadow_root_locs ptr'. r h h'))"
⟨proof⟩
end

interpretation
i_set_mode_get_shadow_root?: l_set_mode_get_shadow_rootShadow_DOM type_wf
set_mode set_mode_locs get_shadow_root
get_shadow_root_locs
⟨proof⟩
declare l_set_mode_get_shadow_rootShadow_DOM_axioms[instances]

locale l_set_mode_get_shadow_root = l_set_mode + l_get_shadow_root +
assumes set_mode_get_shadow_root:
"∀w ∈ set_mode_locs ptr. (h ⊢ w →h h' → (∀r ∈ get_shadow_root_locs ptr'. r h h'))"

lemma set_mode_get_shadow_root_is_l_set_mode_get_shadow_root [instances]:
"l_set_mode_get_shadow_root type_wf set_mode set_mode_locs get_shadow_root
get_shadow_root_locs"
⟨proof⟩

get_child_nodes locale l_set_mode_get_child_nodesShadow_DOM =
l_set_modeShadow_DOM +
l_get_child_nodesShadow_DOM
begin
lemma set_mode_get_child_nodes:
"∀w ∈ set_mode_locs ptr. (h ⊢ w →h h' → (∀r ∈ get_child_nodes_locs ptr'. r h h'))"
⟨proof⟩
end

interpretation i_set_mode_get_child_nodes?: l_set_mode_get_child_nodesShadow_DOM type_wf set_mode
set_mode_locs known_ptr DocumentClass.type_wf DocumentClass.known_ptr get_child_nodes
get_child_nodes_locs Core_DOM_Functions.get_child_nodes Core_DOM_Functions.get_child_nodes_locs
⟨proof⟩
declare l_set_mode_get_child_nodesShadow_DOM_axioms[instances]

locale l_set_mode_get_child_nodes = l_set_mode + l_get_child_nodes +
assumes set_mode_get_child_nodes:
"∀w ∈ set_mode_locs ptr. (h ⊢ w →h h' → (∀r ∈ get_child_nodes_locs ptr'. r h h'))"

```

```

lemma set_mode_get_child_nodes_is_l_set_mode_get_child_nodes [instances]:
  "l_set_mode_get_child_nodes type_wf set_mode set_mode_locs known_ptr get_child_nodes
   get_child_nodes_locs"
  ⟨proof⟩

get_host

locale l_get_host_Shadow_DOM_defs =
  l_get_shadow_root_defs get_shadow_root get_shadow_root_locs
  for get_shadow_root
    :: "(::linorder) element_ptr ⇒ ((_) heap, exception, (_)
      shadow_root_ptr option) prog"
    and get_shadow_root_locs :: "(_)
      element_ptr ⇒ ((_) heap ⇒ (_)
      heap ⇒ bool) set"
begin
definition a_get_host :: "(_)
      shadow_root_ptr ⇒ (, (_)
      element_ptr) dom_prog" where
  "a_get_host shadow_root_ptr = do {
    host_ptrs ← element_ptr_kinds_M ≈ filter_M (λelement_ptr. do {
      shadow_root_opt ← get_shadow_root element_ptr;
      return (shadow_root_opt = Some shadow_root_ptr)
    });
    (case host_ptrs of host_ptr#[] ⇒ return host_ptr | _ ⇒ error HierarchyRequestError)
  }"
definition "a_get_host_locs ≡ (⋃ element_ptr. (get_shadow_root_locs element_ptr)) ∪
  (⋃ ptr. {preserved (get_MObject ptr RObject.nothing)})"
end

global_interpretation l_get_host_Shadow_DOM_defs get_shadow_root get_shadow_root_locs
  defines get_host = "a_get_host"
  and get_host_locs = "a_get_host_locs"
  ⟨proof⟩

locale l_get_host_defs =
  fixes get_host :: "(_)
      shadow_root_ptr ⇒ (, (_)
      element_ptr) dom_prog"
  fixes get_host_locs :: "((_) heap ⇒ (_)
      heap ⇒ bool) set"

locale l_get_host_Shadow_DOM =
  l_get_host_Shadow_DOM_defs +
  l_get_host_defs +
  l_get_shadow_root +
  assumes get_hostImpl: "get_host = a_get_host"
  assumes get_host_locsImpl: "get_host_locs = a_get_host_locs"
begin
lemmas get_host_def = get_hostImpl[unfolded a_get_host_def]
lemmas get_host_locs_def = get_host_locsImpl[unfolded a_get_host_locs_def]

lemma get_host_pure [simp]: "pure (get_host element_ptr) h"
  ⟨proof⟩

lemma get_host_reads: "reads get_host_locs (get_host element_ptr) h h'"
  ⟨proof⟩
end

locale l_get_host = l_get_host_defs +
  assumes get_host_pure [simp]: "pure (get_host element_ptr) h"
  assumes get_host_reads: "reads get_host_locs (get_host node_ptr) h h'"

interpretation i_get_host?: l_get_host_Shadow_DOM get_shadow_root get_shadow_root_locs get_host
  get_host_locs type_wf
  ⟨proof⟩
declare l_get_host_Shadow_DOM_axioms [instances]

```

```

lemma get_host_is_l_get_host [instances]: "l_get_host get_host get_host_locs"
  ⟨proof⟩

get_mode

locale l_get_mode_Shadow_DOM_defs
begin
definition a_get_mode :: "(_ shadow_root_ptr ⇒ (_, shadow_root_mode) dom_prog"
  where
    "a_get_mode shadow_root_ptr = get_M shadow_root_ptr mode"

definition a_get_mode_locs :: "(_ shadow_root_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
  where
    "a_get_mode_locs shadow_root_ptr ≡ {preserved (get_M shadow_root_ptr mode)}"
end

global_interpretation l_get_mode_Shadow_DOM_defs
  defines get_mode = a_get_mode
  and get_mode_locs = a_get_mode_locs
  ⟨proof⟩

locale l_get_mode_defs =
  fixes get_mode :: "(_ shadow_root_ptr ⇒ (_, shadow_root_mode) dom_prog"
  fixes get_mode_locs :: "(_ shadow_root_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"

locale l_get_mode_Shadow_DOM =
  l_get_mode_Shadow_DOM_defs +
  l_get_mode_defs get_mode get_mode_locs +
  l_type_wf type_wf
  for get_mode :: "(_ shadow_root_ptr ⇒ ((_) heap, exception, shadow_root_mode) prog"
    and get_mode_locs :: "(_ shadow_root_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
    and type_wf :: "(_ heap ⇒ bool" +
      assumes type_wfImpl: "type_wf = ShadowRootClass.type_wf"
      assumes get_modeImpl: "get_mode = a_get_mode"
      assumes get_mode_locsImpl: "get_mode_locs = a_get_mode_locs"
begin
lemmas get_mode_def = get_modeImpl[unfolded get_mode_def a_get_mode_def]
lemmas get_mode_locs_def = get_mode_locsImpl[unfolded get_mode_locs_def a_get_mode_locs_def]

lemma get_mode_ok: "type_wf h ⇒ shadow_root_ptr ∉ shadow_root_ptr_kinds h ⇒
  h ⊢ ok (get_mode shadow_root_ptr)"
  ⟨proof⟩

lemma get_mode_pure [simp]: "pure (get_mode element_ptr) h"
  ⟨proof⟩

lemma get_mode_ptr_in_heap:
  assumes "h ⊢ get_mode shadow_root_ptr →r children"
  shows "shadow_root_ptr ∉ shadow_root_ptr_kinds h"
  ⟨proof⟩

lemma get_mode_reads: "reads (get_mode_locs element_ptr) (get_mode element_ptr) h h'"
  ⟨proof⟩
end

interpretation i_get_mode?: l_get_mode_Shadow_DOM get_mode get_mode_locs type_wf
  ⟨proof⟩
declare l_get_mode_Shadow_DOM_axioms [instances]

locale l_get_mode = l_type_wf + l_get_mode_defs +
  assumes get_mode_reads: "reads (get_mode_locs shadow_root_ptr) (get_mode shadow_root_ptr) h h'"
  assumes get_mode_ok:
    "type_wf h ⇒ shadow_root_ptr ∉ shadow_root_ptr_kinds h ⇒ h ⊢ ok (get_mode shadow_root_ptr)"

```

```

assumes get_mode_ptr_in_heap:
  "h ⊢ ok (get_mode shadow_root_ptr) ==> shadow_root_ptr ∈ shadow_root_ptr_kinds h"
assumes get_mode_pure [simp]: "pure (get_mode shadow_root_ptr) h"

lemma get_mode_is_l_get_mode [instances]: "l_get_mode type_wf get_mode get_mode_locs"
  ⟨proof⟩

get_shadow_root_safe

locale l_get_shadow_root_safe_Shadow_DOM_defs =
  l_get_shadow_root_defs get_shadow_root get_shadow_root_locs +
  l_get_mode_defs get_mode get_mode_locs
  for get_shadow_root :: "(_ element_ptr ⇒ (_, (_ shadow_root_ptr option) dom_prog"
    and get_shadow_root_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
    and get_mode :: "(_ shadow_root_ptr ⇒ (_, shadow_root_mode) dom_prog"
    and get_mode_locs :: "(_ shadow_root_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
begin
definition a_get_shadow_root_safe :: "(_ element_ptr ⇒ (_, (_ shadow_root_ptr option) dom_prog"
  where
    "a_get_shadow_root_safe element_ptr = do {
      shadow_root_ptr_opt ← get_shadow_root element_ptr;
      (case shadow_root_ptr_opt of
        Some shadow_root_ptr ⇒ do {
          mode ← get_mode shadow_root_ptr;
          (if mode = Open then
            return (Some shadow_root_ptr)
          else
            return None
          )
        } | None ⇒ return None
      )
    }"
  }

definition a_get_shadow_root_safe_locs
  :: "(_ element_ptr ⇒ (_ shadow_root_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set) set" where
  "a_get_shadow_root_safe_locs element_ptr shadow_root_ptr ≡
    (get_shadow_root_locs element_ptr) ∪ (get_mode_locs shadow_root_ptr)"
end

global_interpretation l_get_shadow_root_safe_Shadow_DOM_defs get_shadow_root get_shadow_root_locs
  get_mode get_mode_locs
  defines get_shadow_root_safe = a_get_shadow_root_safe
  and get_shadow_root_locs = a_get_shadow_root_locs
  ⟨proof⟩

locale l_get_shadow_root_safe_defs =
  fixes get_shadow_root_safe :: "(_ element_ptr ⇒ (_, (_ shadow_root_ptr option) dom_prog"
  fixes get_shadow_root_locs :: "(_ element_ptr ⇒ (_ shadow_root_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set)"

locale l_get_shadow_root_safe_Shadow_DOM =
  l_get_shadow_root_safe_Shadow_DOM_defs get_shadow_root get_shadow_root_locs get_mode get_mode_locs +
  l_get_shadow_root_safe_defs get_shadow_root_safe get_shadow_root_locs +
  l_get_shadow_root_type_wf get_shadow_root get_shadow_root_locs +
  l_get_mode_type_wf get_mode get_mode_locs +
  l_type_wf_type_wf
  for type_wf :: "(_ heap ⇒ bool"
    and get_shadow_root_safe :: "(_ element_ptr ⇒ ((_) heap, exception, (_ shadow_root_ptr option) prog"
    and get_shadow_root_locs :: "(_ element_ptr ⇒ (_ shadow_root_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
    and get_shadow_root :: "(_ element_ptr ⇒ (_, (_ shadow_root_ptr option) dom_prog"
    and get_shadow_root_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
    and get_mode :: "(_ shadow_root_ptr ⇒ (_, shadow_root_mode) dom_prog"

```

```

and get_mode_locs :: "(_ shadow_root_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set)" +
assumes type_wfImpl: "type_wf = ShadowRootClass.type_wf"
assumes get_shadow_root_safeImpl: "get_shadow_root_safe = a_get_shadow_root_safe"
assumes get_shadow_root_locsImpl: "get_shadow_root_locs = a_get_shadow_root_locs"
begin
lemmas get_shadow_root_safe_def =
  get_shadow_root_locsImpl[unfolded get_shadow_root_locs_def a_get_shadow_root_locs_def]
lemmas get_shadow_root_locs_def =
  get_shadow_root_locsImpl[unfolded get_shadow_root_locs_def a_get_shadow_root_locs_def]

lemma get_shadow_root_safe_pure [simp]: "pure (get_shadow_root_safe element_ptr) h"
  ⟨proof⟩
end

interpretation i_get_shadow_root_safe?: l_get_shadow_root_safeShadow_DOM type_wf get_shadow_root_safe
  get_shadow_root_locs get_shadow_root get_shadow_root_locs get_mode get_mode_locs
  ⟨proof⟩
declare l_get_shadow_root_safeShadow_DOM_axioms [instances]

locale l_get_shadow_root_safe = l_get_shadow_root_safe_defs +
  assumes get_shadow_root_safe_pure [simp]: "pure (get_shadow_root_safe element_ptr) h"

lemma get_shadow_root_safe_is_l_get_shadow_root_safe [instances]:
  "l_get_shadow_root_safe get_shadow_root_safe"
  ⟨proof⟩

set_disconnected_nodes

locale l_set_disconnected_nodesShadow_DOM =
  CD: l_set_disconnected_nodesCore_DOM type_wfCore_DOM set_disconnected_nodes set_disconnected_nodes_locs
+
  l_type_wf type_wf
  for type_wf :: "(_ heap ⇒ bool"
    and type_wfCore_DOM :: "(_ heap ⇒ bool"
    and set_disconnected_nodes :: "
      "(_ document_ptr ⇒ (_ node_ptr list ⇒ ((_) heap, exception, unit) prog"
      and set_disconnected_nodes_locs :: "(_ document_ptr ⇒ ((_) heap, exception, unit) prog set" +
        assumes type_wfImpl: "type_wf = ShadowRootClass.type_wf"
begin
lemma set_disconnected_nodes_ok:
  "type_wf h ⇒ document_ptr ∉ document_ptr_kinds h ⇒
   h ⊢ ok (set_disconnected_nodes document_ptr node_ptrs)"
  ⟨proof⟩

lemma set_disconnected_nodes_typess_preserved:
  assumes "w ∈ set_disconnected_nodes_locs object_ptr"
  assumes "h ⊢ w →_h h'"
  shows "type_wf h = type_wf h'"
  ⟨proof⟩
end

interpretation i_set_disconnected_nodes?: l_set_disconnected_nodesShadow_DOM type_wf
  DocumentClass.type_wf set_disconnected_nodes set_disconnected_nodes_locs
  ⟨proof⟩
declare l_set_disconnected_nodesShadow_DOM_axioms [instances]

lemma set_disconnected_nodes_is_l_set_disconnected_nodes [instances]:
  "l_set_disconnected_nodes type_wf set_disconnected_nodes set_disconnected_nodes_locs"
  ⟨proof⟩

get_child_nodes locale l_set_disconnected_nodes_get_child_nodesShadow_DOM =
  l_set_disconnected_nodesCore_DOM type_wfCore_DOM set_disconnected_nodes set_disconnected_nodes_locs
+

```

```

l_get_child_nodesShadow_DOM type_wf known_ptr type_wfCore_DOM known_ptrCore_DOM get_child_nodes
get_child_nodes_locs get_child_nodesCore_DOM get_child_nodes_locsCore_DOM
for type_wf :: "(_ heap ⇒ bool"
  and set_disconnected_nodes :: "(_ document_ptr ⇒ (_ node_ptr list ⇒ ((_) heap, exception, unit) prog"
  and set_disconnected_nodes_locs :: "(_ document_ptr ⇒ ((_) heap, exception, unit) prog set"
  and known_ptr :: "(_ object_ptr ⇒ bool"
  and type_wfCore_DOM :: "(_ heap ⇒ bool"
  and known_ptrCore_DOM :: "(_ object_ptr ⇒ bool"
  and get_child_nodes :: "(_ object_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
  and get_child_nodes_locs :: "(_ object_ptr ⇒ ((_) heap ⇒ bool) set"
  and get_child_nodesCore_DOM :: "(_ object_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
  and get_child_nodes_locsCore_DOM :: "(_ object_ptr ⇒ ((_) heap ⇒ bool) set"
begin

lemma set_disconnected_nodes_get_child_nodes:
  "∀ w ∈ set_disconnected_nodes_locs ptr. (h ⊢ w →h h' → (forall r ∈ get_child_nodes_locs ptr'. r h h'))"
  ⟨proof⟩
end

interpretation i_set_disconnected_nodes_get_child_nodes?:
  l_set_disconnected_nodes_get_child_nodesShadow_DOM type_wf set_disconnected_nodes
  set_disconnected_nodes_locs known_ptr DocumentClass.type_wf DocumentClass.known_ptr get_child_nodes
  get_child_nodes_locs Core_DOM_Functions.get_child_nodes Core_DOM_Functions.get_child_nodes_locs
  ⟨proof⟩
declare l_set_disconnected_nodes_get_child_nodesShadow_DOM_axioms[instances]

lemma set_disconnected_nodes_get_child_nodes_is_l_set_disconnected_nodes_get_child_nodes [instances]:
  "l_set_disconnected_nodes_get_child_nodes set_disconnected_nodes_locs get_child_nodes_locs"
  ⟨proof⟩

get_host locale l_set_disconnected_nodes_get_hostShadow_DOM =
  l_set_disconnected_nodesShadow_DOM +
  l_get_shadow_rootShadow_DOM +
  l_get_hostShadow_DOM
begin
lemma set_disconnected_nodes_get_host:
  "∀ w ∈ set_disconnected_nodes_locs ptr. (h ⊢ w →h h' → (forall r ∈ get_host_locs. r h h'))"
  ⟨proof⟩
end

interpretation i_set_disconnected_nodes_get_host?: l_set_disconnected_nodes_get_hostShadow_DOM type_wf
  DocumentClass.type_wf set_disconnected_nodes set_disconnected_nodes_locs get_shadow_root
  get_shadow_root_locs get_host get_host_locs
  ⟨proof⟩
declare l_set_disconnected_nodes_get_hostShadow_DOM_axioms [instances]

locale l_set_disconnected_nodes_get_host = l_set_disconnected_nodes_defs + l_get_host_defs +
  assumes set_disconnected_nodes_get_host:
    "∀ w ∈ set_disconnected_nodes_locs ptr. (h ⊢ w →h h' → (forall r ∈ get_host_locs. r h h'))"

lemma set_disconnected_nodes_get_host_is_l_set_disconnected_nodes_get_host [instances]:
  "l_set_disconnected_nodes_get_host set_disconnected_nodes_locs get_host_locs"
  ⟨proof⟩

get_tag_name
locale l_get_tag_nameShadow_DOM =
  CD: l_get_tag_nameCore_DOM type_wfCore_DOM get_tag_name get_tag_name_locs +
  l_type_wf type_wf
  for type_wf :: "(_ heap ⇒ bool"
    and type_wfCore_DOM :: "(_ heap ⇒ bool"
    and get_tag_name :: "(_ element_ptr ⇒ (_, tag_name) dom_prog"

```

```

and get_tag_name_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set)" +
assumes type_wfImpl: "type_wf = ShadowRootClass.type_wf"
begin

lemma get_tag_name_ok:
  "type_wf h ⇒ element_ptr ∉ element_ptr_kinds h ⇒ h ⊢ ok (get_tag_name element_ptr)"
  ⟨proof⟩
end

interpretation i_get_tag_name?: l_get_tag_nameShadow_DOM type_wf DocumentClass.type_wf get_tag_name
  get_tag_name_locs
  ⟨proof⟩
declare l_get_tag_nameShadow_DOM_axioms [instances]

lemma get_tag_name_is_l_get_tag_name [instances]: "l_get_tag_name type_wf get_tag_name
  get_tag_name_locs"
  ⟨proof⟩

set_disconnected_nodes locale l_set_disconnected_nodes_get_tag_nameShadow_DOM =
  l_set_disconnected_nodesShadow_DOM +
  l_get_tag_nameShadow_DOM
begin
lemma set_disconnected_nodes_get_tag_name:
  "∀ w ∈ set_disconnected_nodes_locs ptr. (h ⊢ w →_h h' → (∀ r ∈ get_tag_name_locs ptr'. r h h'))"
  ⟨proof⟩
end

interpretation i_set_disconnected_nodes_get_tag_name?: l_set_disconnected_nodes_get_tag_nameShadow_DOM
  type_wf DocumentClass.type_wf set_disconnected_nodes set_disconnected_nodes_locs get_tag_name
  get_tag_name_locs
  ⟨proof⟩
declare l_set_disconnected_nodes_get_tag_nameShadow_DOM_axioms [instances]

lemma set_disconnected_nodes_get_tag_name_is_l_set_disconnected_nodes_get_tag_name [instances]:
  "l_set_disconnected_nodes_get_tag_name type_wf set_disconnected_nodes set_disconnected_nodes_locs
  get_tag_name get_tag_name_locs"
  ⟨proof⟩

set_child_nodes locale l_set_child_nodes_get_tag_nameShadow_DOM =
  l_set_child_nodesShadow_DOM +
  l_get_tag_nameShadow_DOM
begin
lemma set_child_nodes_get_tag_name:
  "∀ w ∈ set_child_nodes_locs ptr. (h ⊢ w →_h h' → (∀ r ∈ get_tag_name_locs ptr'. r h h'))"
  ⟨proof⟩
end

interpretation i_set_child_nodes_get_tag_name?: l_set_child_nodes_get_tag_nameShadow_DOM type_wf
  known_ptr DocumentClass.type_wf DocumentClass.known_ptr set_child_nodes set_child_nodes_locs
  Core_DOM_Functions.set_child_nodes Core_DOM_Functions.set_child_nodes_locs get_tag_name
  get_tag_name_locs
  ⟨proof⟩
declare l_set_child_nodes_get_tag_nameShadow_DOM_axioms [instances]

lemma set_child_nodes_get_tag_name_is_l_set_child_nodes_get_tag_name [instances]:
  "l_set_child_nodes_get_tag_name type_wf set_child_nodes set_child_nodes_locs get_tag_name
  get_tag_name_locs"
  ⟨proof⟩

delete_shadow_root locale l_delete_shadow_root_get_tag_nameShadow_DOM =
  l_get_tag_nameShadow_DOM
begin

```

```

lemma get_tag_name_delete_shadow_root: " $h \vdash \text{delete}_{\text{ShadowRoot\_M}} \text{shadow\_root\_ptr} \rightarrow_h h'$ 
 $\implies r \in \text{get\_tag\_name\_locs} \text{ptr}' \implies r h h''$ "
⟨proof⟩
end

locale l_delete_shadow_root_get_tag_name = l_get_tag_name_defs +
assumes get_tag_name_delete_shadow_root: " $h \vdash \text{delete}_{\text{ShadowRoot\_M}} \text{shadow\_root\_ptr} \rightarrow_h h'$ 
 $\implies r \in \text{get\_tag\_name\_locs} \text{ptr}' \implies r h h''$ "
interpretation l_delete_shadow_root_get_tag_name_Shadow_DOM type_wf DocumentClass.type_wf get_tag_name
get_tag_name_locs
⟨proof⟩

lemma l_delete_shadow_root_get_tag_name_get_tag_name_locs [instances]: "l_delete_shadow_root_get_tag_name
get_tag_name_locs"
⟨proof⟩

set_shadow_root locale l_set_shadow_root_get_tag_name_Shadow_DOM =
l_set_shadow_root_Shadow_DOM +
l_get_tag_name_Shadow_DOM
begin
lemma set_shadow_root_get_tag_name:
" $\forall w \in \text{set\_shadow\_root\_locs} \text{ptr}. (h \vdash w \rightarrow_h h' \longrightarrow (\forall r \in \text{get\_tag\_name\_locs} \text{ptr}'. r h h'))$ "
⟨proof⟩
end

interpretation i_set_shadow_root_get_tag_name?: l_set_shadow_root_get_tag_name_Shadow_DOM type_wf
set_shadow_root set_shadow_root_locs DocumentClass.type_wf get_tag_name get_tag_name_locs
⟨proof⟩
declare l_set_shadow_root_get_tag_name_Shadow_DOM_axioms[instances]

locale l_set_shadow_root_get_tag_name = l_set_shadow_root_defs + l_get_tag_name_defs +
assumes set_shadow_root_get_tag_name:
" $\forall w \in \text{set\_shadow\_root\_locs} \text{ptr}. (h \vdash w \rightarrow_h h' \longrightarrow (\forall r \in \text{get\_tag\_name\_locs} \text{ptr}'. r h h'))$ "

lemma set_shadow_root_get_tag_name_is_l_set_shadow_root_get_tag_name [instances]:
"l_set_shadow_root_get_tag_name set_shadow_root_locs get_tag_name_locs"
⟨proof⟩

new_element locale l_new_element_get_tag_name_Shadow_DOM =
l_get_tag_name_Shadow_DOM type_wf type_wf_Core_DOM get_tag_name get_tag_name_locs
for type_wf :: "(_ heap ⇒ bool"
and type_wf_Core_DOM :: "(_ heap ⇒ bool"
and get_tag_name :: "(_ element_ptr ⇒ (_, tag_name) dom_prog"
and get_tag_name_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
begin
lemma get_tag_name_new_element:
"ptr' ≠ new_element_ptr ⇒ h ⊢ new_element →_r new_element_ptr ⇒ h ⊢ new_element →_h h'
 $\implies r \in \text{get\_tag\_name\_locs} \text{ptr}' \implies r h h''$ "
⟨proof⟩

lemma new_element_empty_tag_name:
" $h \vdash \text{new\_element} \rightarrow_r \text{new\_element\_ptr} \implies h \vdash \text{new\_element} \rightarrow_h h'$ 
 $\implies h' \vdash \text{get\_tag\_name} \text{new\_element\_ptr} \rightarrow_r \text{'}, , , '$ "
⟨proof⟩
end

locale l_new_element_get_tag_name = l_new_element + l_get_tag_name +
assumes get_tag_name_new_element:
"ptr' ≠ new_element_ptr ⇒ h ⊢ new_element →_r new_element_ptr
 $\implies h \vdash \text{new\_element} \rightarrow_h h' \implies r \in \text{get\_tag\_name\_locs} \text{ptr}' \implies r h h''$ "
assumes new_element_empty_tag_name:
" $h \vdash \text{new\_element} \rightarrow_r \text{new\_element\_ptr} \implies h \vdash \text{new\_element} \rightarrow_h h'$ 
 $\implies h' \vdash \text{get\_tag\_name} \text{new\_element\_ptr} \rightarrow_r \text{'}, , , '$ "

```

```

interpretation i_new_element_get_tag_name?:
  l_new_element_get_tag_nameShadow_DOM type_wf DocumentClass.type_wf get_tag_name get_tag_name_locs
  ⟨proof⟩
declare l_new_element_get_tag_nameShadow_DOM_axioms [instances]

lemma new_element_get_tag_name_is_l_new_element_get_tag_name [instances]:
  "l_new_element_get_tag_name type_wf get_tag_name get_tag_name_locs"
  ⟨proof⟩

get_shadow_root locale l_set_mode_get_tag_nameShadow_DOM =
  l_set_modeShadow_DOM +
  l_get_tag_nameShadow_DOM
begin
lemma set_mode_get_tag_name:
  " $\forall w \in \text{set\_mode\_locs} \text{ ptr}. (h \vdash w \rightarrow_h h' \longrightarrow (\forall r \in \text{get\_tag\_name\_locs} \text{ ptr}'. r h h'))$ "
  ⟨proof⟩
end

interpretation
  i_set_mode_get_tag_name?: l_set_mode_get_tag_nameShadow_DOM type_wf
  set_mode set_mode_locs DocumentClass.type_wf get_tag_name
  get_tag_name_locs
  ⟨proof⟩
declare l_set_mode_get_tag_nameShadow_DOM_axioms [instances]

locale l_set_mode_get_tag_name = l_set_mode + l_get_tag_name +
assumes set_mode_get_tag_name:
  " $\forall w \in \text{set\_mode\_locs} \text{ ptr}. (h \vdash w \rightarrow_h h' \longrightarrow (\forall r \in \text{get\_tag\_name\_locs} \text{ ptr}'. r h h'))$ ""

lemma set_mode_get_tag_name_is_l_set_mode_get_tag_name [instances]:
  "l_set_mode_get_tag_name type_wf set_mode set_mode_locs get_tag_name
   get_tag_name_locs"
  ⟨proof⟩

new_document locale l_new_document_get_tag_nameShadow_DOM =
  l_get_tag_nameShadow_DOM type_wf type_wfCore_DOM get_tag_name get_tag_name_locs
  for type_wf :: "(_ heap ⇒ bool"
    and type_wfCore_DOM :: "(_ heap ⇒ bool"
    and get_tag_name :: "(_ element_ptr ⇒ ((_) heap, exception, tag_name) prog"
    and get_tag_name_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
begin
lemma get_tag_name_new_document:
  " $h \vdash \text{new\_document} \rightarrow_r \text{new\_document\_ptr} \implies h \vdash \text{new\_document} \rightarrow_h h'$ 
    $\implies r \in \text{get\_tag\_name\_locs} \text{ ptr}' \implies r h h'$ "
  ⟨proof⟩
end

locale l_new_document_get_tag_name = l_get_tag_name_defs +
assumes get_tag_name_new_document:
  " $h \vdash \text{new\_document} \rightarrow_r \text{new\_document\_ptr} \implies h \vdash \text{new\_document} \rightarrow_h h'$ 
    $\implies r \in \text{get\_tag\_name\_locs} \text{ ptr}' \implies r h h'$ ""

interpretation i_new_document_get_tag_name?:
  l_new_document_get_tag_nameShadow_DOM type_wf DocumentClass.type_wf get_tag_name
  get_tag_name_locs
  ⟨proof⟩
declare l_new_document_get_tag_nameShadow_DOM_def [instances]

lemma new_document_get_tag_name_is_l_new_document_get_tag_name [instances]:
  "l_new_document_get_tag_name get_tag_name_locs"
  ⟨proof⟩

```

```

new_shadow_root locale l_new_shadow_root_get_tag_nameShadow_DOM =
  l_get_tag_nameShadow_DOM
begin
  lemma get_tag_name_new_shadow_root:
    " $h \vdash \text{newShadowRoot}_M \rightarrow_r \text{new_shadow_root_ptr} \implies h \vdash \text{newShadowRoot}_M \rightarrow_h h'$ 
      $\implies r \in \text{get\_tag\_name\_locs} \text{ptr}' \implies r \ h \ h'$ "
     $\langle \text{proof} \rangle$ 
end

locale l_new_shadow_root_get_tag_name = l_get_tag_name +
  assumes get_tag_name_new_shadow_root:
    " $h \vdash \text{newShadowRoot}_M \rightarrow_r \text{new_shadow_root_ptr}$ 
      $\implies h \vdash \text{newShadowRoot}_M \rightarrow_h h' \implies r \in \text{get\_tag\_name\_locs} \text{ptr}' \implies r \ h \ h'$ ""

interpretation i_new_shadow_root_get_tag_name?:
  l_new_shadow_root_get_tag_nameShadow_DOM type_wf DocumentClass.type_wf get_tag_name get_tag_name_locs
   $\langle \text{proof} \rangle$ 
declare l_new_shadow_root_get_tag_nameShadow_DOM_axioms [instances]

lemma new_shadow_root_get_tag_name_is_l_new_shadow_root_get_tag_name [instances]:
  "l_new_shadow_root_get_tag_name type_wf get_tag_name get_tag_name_locs"
   $\langle \text{proof} \rangle$ 

new_character_data locale l_new_character_data_get_tag_nameShadow_DOM =
  l_get_tag_nameShadow_DOM type_wf type_wfCore_DOM get_tag_name get_tag_name_locs
  for type_wf :: "(_ heap  $\Rightarrow$  bool"
    and type_wfCore_DOM :: "(_ heap  $\Rightarrow$  bool"
    and get_tag_name :: "(_ element_ptr  $\Rightarrow$  (_ heap, exception, tag_name) prog"
    and get_tag_name_locs :: "(_ element_ptr  $\Rightarrow$  (_ heap  $\Rightarrow$  (_ heap  $\Rightarrow$  bool) set"
begin
  lemma get_tag_name_new_character_data:
    " $h \vdash \text{new_character_data} \rightarrow_r \text{new_character_data_ptr} \implies h \vdash \text{new_character_data} \rightarrow_h h'$ 
      $\implies r \in \text{get\_tag\_name\_locs} \text{ptr}' \implies r \ h \ h'$ "
     $\langle \text{proof} \rangle$ 
end

locale l_new_character_data_get_tag_name = l_get_tag_name_defs +
  assumes get_tag_name_new_character_data:
    " $h \vdash \text{new_character_data} \rightarrow_r \text{new_character_data_ptr} \implies h \vdash \text{new_character_data} \rightarrow_h h'$ 
      $\implies r \in \text{get\_tag\_name\_locs} \text{ptr}' \implies r \ h \ h'$ ""

interpretation i_new_character_data_get_tag_name?:
  l_new_character_data_get_tag_nameShadow_DOM type_wf DocumentClass.type_wf get_tag_name
  get_tag_name_locs
   $\langle \text{proof} \rangle$ 
declare l_new_character_data_get_tag_nameShadow_DOM_def [instances]

lemma new_character_data_get_tag_name_is_l_new_character_data_get_tag_name [instances]:
  "l_new_character_data_get_tag_name get_tag_name_locs"
   $\langle \text{proof} \rangle$ 

get_tag_type locale l_set_tag_name_get_tag_nameShadow_DOM = l_get_tag_nameShadow_DOM
  + l_set_tag_nameShadow_DOM
begin
  lemma set_tag_name_get_tag_name:
    assumes " $h \vdash \text{CD.a\_set\_tag\_name element\_ptr tag} \rightarrow_h h'$ "
    shows " $h' \vdash \text{CD.a\_get\_tag\_name element\_ptr} \rightarrow_r \text{tag}$ "
     $\langle \text{proof} \rangle$ 

  lemma set_tag_name_get_tag_name_different_pointers:
    assumes "ptr  $\neq$  ptr'"
    assumes "w  $\in$  CD.a_set_tag_name_locs ptr"
    assumes " $h \vdash w \rightarrow_h h'$ "

```

```

assumes "r ∈ CD.a_get_tag_name_locs ptr"
shows "r h h"
⟨proof⟩
end

interpretation i_set_tag_name_get_tag_name?:
  l_set_tag_name_get_tag_nameShadow_DOM type_wf DocumentClass.type_wf get_tag_name
  get_tag_name_locs set_tag_name set_tag_name_locs
  ⟨proof⟩
declare l_set_tag_name_get_tag_nameShadow_DOM_axioms[instances]

lemma set_tag_name_get_tag_name_is_l_set_tag_name_get_tag_name [instances]:
  "l_set_tag_name_get_tag_name type_wf get_tag_name get_tag_name_locs
   set_tag_name set_tag_name_locs"
  ⟨proof⟩

attach_shadow_root

locale l_attach_shadow_rootShadow_DOM_defs =
  l_set_shadow_root_defs set_shadow_root set_shadow_root_locs +
  l_set_mode_defs set_mode set_mode_locs +
  l_get_tag_name_defs get_tag_name get_tag_name_locs +
  l_get_shadow_root_defs get_shadow_root get_shadow_root_locs
for set_shadow_root :: "
  "(_) element_ptr ⇒ ( _) shadow_root_ptr option ⇒ ((_) heap, exception, unit) prog"
  and set_shadow_root_locs :: "(_) element_ptr ⇒ ((_) heap, exception, unit) prog set"
  and set_mode :: "(_) shadow_root_ptr ⇒ shadow_root_mode ⇒ ((_) heap, exception, unit) prog"
  and set_mode_locs :: "(_) shadow_root_ptr ⇒ ((_) heap, exception, unit) prog set"
  and get_tag_name :: "(_) element_ptr ⇒ (_, char list) dom_prog"
  and get_tag_name_locs :: "(_) element_ptr ⇒ ((_) heap ⇒ ( _ ) heap ⇒ bool) set"
  and get_shadow_root :: "(_) element_ptr ⇒ ((_) heap, exception, ( _ ) shadow_root_ptr option) prog"
  and get_shadow_root_locs :: "(_) element_ptr ⇒ ((_) heap ⇒ ( _ ) heap ⇒ bool) set"
begin
definition a_attach_shadow_root :: "
  "(_) element_ptr ⇒ shadow_root_mode ⇒ (_, ( _ ) shadow_root_ptr) dom_prog"
  where
    "a_attach_shadow_root element_ptr shadow_root_mode = do {
      tag ← get_tag_name element_ptr;
      (if tag ∉ safe_shadow_root_element_types then error NotSupportedError else return ());
      prev_shadow_root ← get_shadow_root element_ptr;
      (if prev_shadow_root ≠ None then error NotSupportedError else return ());
      new_shadow_root_ptr ← newShadowRoot_M;
      set_mode new_shadow_root_ptr shadow_root_mode;
      set_shadow_root element_ptr (Some new_shadow_root_ptr);
      return new_shadow_root_ptr
    }"
  end

locale l_attach_shadow_root_defs =
  fixes attach_shadow_root :: "
    "(_) element_ptr ⇒ shadow_root_mode ⇒ (_, ( _ ) shadow_root_ptr) dom_prog"

global_interpretation l_attach_shadow_rootShadow_DOM_defs set_shadow_root set_shadow_root_locs
  set_mode set_mode_locs get_tag_name get_tag_name_locs get_shadow_root get_shadow_root_locs
  defines attach_shadow_root = a_attach_shadow_root
  ⟨proof⟩

locale l_attach_shadow_rootShadow_DOM =
  l_attach_shadow_rootShadow_DOM_defs set_shadow_root set_shadow_root_locs set_mode set_mode_locs
  get_tag_name get_tag_name_locs get_shadow_root get_shadow_root_locs +
  l_attach_shadow_root_defs attach_shadow_root +
  l_set_shadow_rootShadow_DOM type_wf set_shadow_root set_shadow_root_locs +
  l_set_mode type_wf set_mode set_mode_locs +

```

```

l_get_tag_name type_wf get_tag_name get_tag_name_locs +
l_get_shadow_root type_wf get_shadow_root get_shadow_root_locs +
l_known_ptr known_ptr
for known_ptr :: "(_ object_ptr ⇒ bool"
  and set_shadow_root :: "
    "(_ element_ptr ⇒ (_ shadow_root_ptr option ⇒ ((_) heap, exception, unit) prog"
    and set_shadow_root_locs :: "(_ element_ptr ⇒ ((_) heap, exception, unit) prog set"
    and set_mode :: "(_ shadow_root_ptr ⇒ shadow_root_mode ⇒ ((_) heap, exception, unit) prog"
    and set_mode_locs :: "(_ shadow_root_ptr ⇒ ((_) heap, exception, unit) prog set"
    and attach_shadow_root :: "
      "(_ element_ptr ⇒ shadow_root_mode ⇒ ((_) heap, exception, (_ shadow_root_ptr) prog"
      and type_wf :: "(_ heap ⇒ bool"
      and get_tag_name :: "(_ element_ptr ⇒ (_, char list) dom_prog"
      and get_tag_name_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
      and get_shadow_root :: "(_ element_ptr ⇒ ((_) heap, exception, (_ shadow_root_ptr option) prog"
      and get_shadow_root_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set" +
assumes known_ptr_impl: "known_ptr = a_known_ptr"
assumes attach_shadow_root_impl: "attach_shadow_root = a_attach_shadow_root"
begin
lemmas attach_shadow_root_def = a_attach_shadow_root_def [folded attach_shadow_rootImpl]

lemma attach_shadow_root_element_ptr_in_heap:
  assumes "h ⊢ ok (attach_shadow_root element_ptr shadow_root_mode)"
  shows "element_ptr ∉ element_ptr_kinds h"
  ⟨proof⟩

lemma create_shadow_root_known_ptr:
  assumes "h ⊢ attach_shadow_root element_ptr shadow_root_mode →, new_shadow_root_ptr"
  shows "known_ptr (castshadow_root_ptr2object_ptr new_shadow_root_ptr)"
  ⟨proof⟩
end

locale l_attach_shadow_root = l_attach_shadow_root_defs

interpretation
  i_attach_shadow_root?: l_attach_shadow_rootShadow_DOM known_ptr set_shadow_root set_shadow_root_locs
  set_mode set_mode_locs attach_shadow_root type_wf get_tag_name get_tag_name_locs get_shadow_root
  get_shadow_root_locs
  ⟨proof⟩
declare l_attach_shadow_rootShadow_DOM_axioms [instances]

get_parent
global_interpretation l_get_parentCore_DOM_defs get_child_nodes get_child_nodes_locs
  defines get_parent = "l_get_parentCore_DOM_defs.a_get_parent get_child_nodes"
  and get_parent_locs = "l_get_parentCore_DOM_defs.a_get_parent_locs get_child_nodes_locs"
  ⟨proof⟩

interpretation i_get_parent?: l_get_parentCore_DOM known_ptr type_wf get_child_nodes
  get_child_nodes_locs known_ptrs get_parent get_parent_locs
  ⟨proof⟩
declare l_get_parentCore_DOM_axioms [instances]

lemma get_parent_is_l_get_parent [instances]: "l_get_parent type_wf known_ptr known_ptrs get_parent
  get_parent_locs get_child_nodes get_child_nodes_locs"
  ⟨proof⟩

set_disconnected_nodes locale l_set_disconnected_nodes_get_parentShadow_DOM =
  l_set_disconnected_nodes_get_child_nodes
  + l_set_disconnected_nodesShadow_DOM
  + l_get_parentCore_DOM
begin
lemma set_disconnected_nodes_get_parent [simp]:

```

```

"∀ w ∈ set_disconnected_nodes_locs ptr. (h ⊢ w →h h' → (forall r ∈ get_parent_locs. r h h'))"
⟨proof⟩
end
interpretation i_set_disconnected_nodes_get_parent?: l_set_disconnected_nodes_get_parentShadow_DOM
set_disconnected_nodes set_disconnected_nodes_locs get_child_nodes get_child_nodes_locs type_wf
DocumentClass.type_wf known_ptr known_ptrs get_parent get_parent_locs
⟨proof⟩
declare l_set_disconnected_nodes_get_parentCore_DOM_axioms[instances]

lemma set_disconnected_nodes_get_parent_is_l_set_disconnected_nodes_get_parent [instances]:
"l_set_disconnected_nodes_get_parent set_disconnected_nodes_locs get_parent_locs"
⟨proof⟩

get_root_node

global_interpretation l_get_root_nodeCore_DOM_defs get_parent get_parent_locs
defines get_root_node = "l_get_root_nodeCore_DOM_defs.a_get_root_node get_parent"
and get_root_node_locs = "l_get_root_nodeCore_DOM_defs.a_get_root_node_locs get_parent_locs"
and get_ancestors = "l_get_root_nodeCore_DOM_defs.a_get_ancestors get_parent"
and get_ancestors_locs = "l_get_root_nodeCore_DOM_defs.a_get_ancestors_locs get_parent_locs"
⟨proof⟩
declare a_get_ancestors.simps [code]

interpretation i_get_root_node?: l_get_root_nodeCore_DOM type_wf known_ptr known_ptrs get_parent
get_parent_locs get_child_nodes get_child_nodes_locs get_ancestors get_ancestors_locs
get_root_node get_root_node_locs
⟨proof⟩
declare l_get_root_nodeCore_DOM_axioms[instances]

lemma get_ancestors_is_l_get_ancestors [instances]: "l_get_ancestors get_ancestors"
⟨proof⟩

lemma get_root_node_is_l_get_root_node [instances]: "l_get_root_node get_root_node get_parent"
⟨proof⟩

get_root_node_si

locale l_get_root_node_siShadow_DOM_defs =
l_get_parent_defs get_parent get_parent_locs +
l_get_host_defs get_host get_host_locs
for get_parent :: "(_) node_ptr ⇒ ((_) heap, exception, (_::linorder) object_ptr option) prog"
and get_parent_locs :: "((_) heap ⇒ (_ heap ⇒ bool) set"
and get_host :: "(_ shadow_root_ptr ⇒ ((_) heap, exception, (_ element_ptr) prog"
and get_host_locs :: "((_) heap ⇒ (_ heap ⇒ bool) set"
begin
partial_function (dom_prog) a_get_ancestors_si ::_
"(_::linorder) object_ptr ⇒ ( _, (_ object_ptr list) dom_prog"
where
  "a_get_ancestors_si ptr = do {
    check_in_heap ptr;
    ancestors ← (case castobject_ptr2node_ptr ptr of
      Some node_ptr ⇒ do {
        parent_ptr_opt ← get_parent node_ptr;
        (case parent_ptr_opt of
          Some parent_ptr ⇒ a_get_ancestors_si parent_ptr
          | None ⇒ return [])
      }
      | None ⇒ (case cast ptr of
        Some shadow_root_ptr ⇒ do {
          host ← get_host shadow_root_ptr;
          a_get_ancestors_si (cast host)
        }
        | None ⇒ return []));
    }
  "

```

```

    return (ptr # ancestors)
}"

definition "a_get_ancestors_si_locs = get_parent_locs ∪ get_host_locs"

definition a_get_root_node_si :: "(_ object_ptr ⇒ (_ object_ptr) dom_prog"
  where
    "a_get_root_node_si ptr = do {
      ancestors ← a_get_ancestors_si ptr;
      return (last ancestors)
    }"
definition "a_get_root_node_si_locs = a_get_ancestors_si_locs"
end

locale l_get_ancestors_si_defs =
  fixes get_ancestors_si :: "(_::linorder) object_ptr ⇒ (_ object_ptr list) dom_prog"
  fixes get_ancestors_si_locs :: "(_ heap ⇒ (_ heap ⇒ bool) set)"

locale l_get_root_node_si_defs =
  fixes get_root_node_si :: "(_ object_ptr ⇒ (_ object_ptr) dom_prog"
  fixes get_root_node_si_locs :: "(_ heap ⇒ (_ heap ⇒ bool) set)"

locale l_get_root_node_si_Shadow_DOM =
  l_get_parent +
  l_get_host +
  l_get_root_node_si_Shadow_DOM_defs +
  l_get_ancestors_si_defs +
  l_get_root_node_si_defs +
  assumes get_ancestors_siImpl: "get_ancestors_si = a_get_ancestors_si"
  assumes get_ancestors_si_locsImpl: "get_ancestors_si_locs = a_get_ancestors_si_locs"
  assumes get_root_node_siImpl: "get_root_node_si = a_get_root_node_si"
  assumes get_root_node_si_locsImpl: "get_root_node_si_locs = a_get_root_node_si_locs"
begin
lemmas get_ancestors_si_def = a_get_ancestors_si.simps[folded get_ancestors_siImpl]
lemmas get_ancestors_si_locs_def = a_get_ancestors_si_locs_def[folded get_ancestors_si_locsImpl]
lemmas get_root_node_si_def =
  a_get_root_node_si_def[folded get_root_node_siImpl get_ancestors_siImpl]
lemmas get_root_node_si_locs_def =
  a_get_root_node_si_locs_def[folded get_root_node_si_locsImpl get_ancestors_si_locsImpl]

lemma get_ancestors_si_pure [simp]:
  "pure (get_ancestors_si ptr) h"
  ⟨proof⟩

lemma get_root_node_si_pure [simp]: "pure (get_root_node_si ptr) h"
  ⟨proof⟩

lemma get_ancestors_si_ptr_in_heap:
  assumes "h ⊢ ok (get_ancestors_si ptr)"
  shows "ptr ∈ object_ptr_kinds h"
  ⟨proof⟩

lemma get_ancestors_si_ptr:
  assumes "h ⊢ get_ancestors_si ptr →_r ancestors"
  shows "ptr ∈ set ancestors"
  ⟨proof⟩

lemma get_ancestors_si_never_empty:
  assumes "h ⊢ get_ancestors_si child →_r ancestors"
  shows "ancestors ≠ []"

```

$\langle proof \rangle$

```

lemma get_root_node_si_no_parent:
  "h ⊢ get_parent node_ptr →r None ⟹ h ⊢ get_root_node_si (cast node_ptr) →r cast node_ptr"
  ⟨proof⟩

lemma get_root_node_si_root_not_shadow_root:
  assumes "h ⊢ get_root_node_si ptr →r root"
  shows "¬ is_shadow_root_ptrobject_ptr root"
  ⟨proof⟩
end

global_interpretation l_get_root_node_si_Shadow_DOM_defs get_parent get_parent_locs get_host get_host_locs
  defines get_root_node_si = a_get_root_node_si
    and get_root_node_si_locs = a_get_root_node_si_locs
    and get_ancestors_si = a_get_ancestors_si
    and get_ancestors_si_locs = a_get_ancestors_si_locs
  ⟨proof⟩
declare a_get_ancestors_si.simps [code]

interpretation i_get_root_node_si?: l_get_root_node_si_Shadow_DOM type_wf known_ptr known_ptrs
  get_parent get_parent_locs get_child_nodes get_child_nodes_locs get_host get_host_locs
  get_ancestors_si get_ancestors_si_locs get_root_node_si get_root_node_si_locs
  ⟨proof⟩
declare l_get_root_node_si_Shadow_DOM_axioms[instances]

lemma get_ancestors_si_is_l_get_ancestors [instances]: "l_get_ancestors get_ancestors_si"
  ⟨proof⟩

lemma get_root_node_si_is_l_get_root_node [instances]: "l_get_root_node get_root_node_si get_parent"
  ⟨proof⟩

set_disconnected_nodes locale l_set_disconnected_nodes_get_ancestors_si_Core_DOM =
  l_set_disconnected_nodes_get_parent
  + l_get_root_node_si_Shadow_DOM
  + l_set_disconnected_nodes_Shadow_DOM
  + l_set_disconnected_nodes_get_host
begin
lemma set_disconnected_nodes_get_ancestors_si:
  "∀ w ∈ set_disconnected_nodes_locs ptr. (h ⊢ w →h h' ⟹ (∀ r ∈ get_ancestors_si_locs. r h h'))"
  ⟨proof⟩
end

locale l_set_disconnected_nodes_get_ancestors_si =
  l_set_disconnected_nodes_defs +
  l_get_ancestors_si_defs +
  assumes set_disconnected_nodes_get_ancestors_si:
    "∀ w ∈ set_disconnected_nodes_locs ptr. (h ⊢ w →h h' ⟹ (∀ r ∈ get_ancestors_si_locs. r h h'))"

interpretation i_set_disconnected_nodes_get_ancestors_si?:
  l_set_disconnected_nodes_get_ancestors_si_Core_DOM set_disconnected_nodes set_disconnected_nodes_locs
  get_parent get_parent_locs type_wf known_ptr known_ptrs get_child_nodes get_child_nodes_locs
  get_host get_host_locs get_ancestors_si get_ancestors_si_locs get_root_node_si
  get_root_node_si_locs DocumentClass.type_wf
  ⟨proof⟩
declare l_set_disconnected_nodes_get_ancestors_si_Core_DOM_axioms[instances]

lemma set_disconnected_nodes_get_ancestors_si_is_l_set_disconnected_nodes_get_ancestors_si [instances]:
  "l_set_disconnected_nodes_get_ancestors_si set_disconnected_nodes_locs get_ancestors_si_locs"
  ⟨proof⟩

```

get_attribute

```
lemma get_attribute_is_l_get_attribute [instances]:
  "l_get_attribute type_wf get_attribute get_attribute_locs"
  ⟨proof⟩
```

to_tree_order

```
global_interpretation l_to_tree_orderCore_DOM_defs get_child_nodes get_child_nodes_locs defines
  to_tree_order = "l_to_tree_orderCore_DOM_defs.a_to_tree_order get_child_nodes" ⟨proof⟩
declare a_to_tree_order.simps [code]
```

```
interpretation i_to_tree_order?: l_to_tree_orderCore_DOM ShadowRootClass.known_ptr
  ShadowRootClass.type_wf Shadow_DOM.get_child_nodes Shadow_DOM.get_child_nodes_locs to_tree_order
  ⟨proof⟩
declare l_to_tree_orderCore_DOM_axioms [instances]
```

to_tree_order_si

```
locale l_to_tree_order_siCore_DOM_defs =
  l_get_child_nodes_defs get_child_nodes get_child_nodes_locs +
  l_get_shadow_root_defs get_shadow_root get_shadow_root_locs
  for get_child_nodes :: "(_ : linorder) object_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
    and get_child_nodes_locs :: "(_ object_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
    and get_shadow_root :: "(_ element_ptr ⇒ ((_) heap, exception, (_ shadow_root_ptr option) prog"
    and get_shadow_root_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
begin
partial_function (dom_prog) a_to_tree_order_si :: "(_ object_ptr ⇒ (, (_ object_ptr list) dom_prog"
  where
    "a_to_tree_order_si ptr = (do {
      children ← get_child_nodes ptr;
      shadow_root_part ← (case cast ptr of
        Some element_ptr ⇒ do {
          shadow_root_opt ← get_shadow_root element_ptr;
          (case shadow_root_opt of
            Some shadow_root_ptr ⇒ return [cast shadow_root_ptr]
            | None ⇒ return [])
        }
      )
      None ⇒ return []);
      treeorders ← map_M a_to_tree_order_si ((map (cast) children) @ shadow_root_part);
      return (ptr # concat treeorders)
    })"
end
```

```
locale l_to_tree_order_si_defs =
  fixes to_tree_order_si :: "(_ object_ptr ⇒ (, (_ object_ptr list) dom_prog"
```

```
global_interpretation l_to_tree_order_siCore_DOM_defs get_child_nodes get_child_nodes_locs
  get_shadow_root get_shadow_root_locs
  defines to_tree_order_si = "a_to_tree_order_si" ⟨proof⟩
declare a_to_tree_order_si.simps [code]
```

```
locale l_to_tree_order_siShadow_DOM =
  l_to_tree_order_si_defs +
  l_to_tree_order_siCore_DOM_defs +
  l_get_child_nodes +
  l_get_shadow_root +
  assumes to_tree_order_si_impl: "to_tree_order_si = a_to_tree_order_si"
```

```
begin
lemmas to_tree_order_si_def = a_to_tree_order_si.simps[folded to_tree_order_si_impl]
```

```
lemma to_tree_order_si_pure [simp]: "pure (to_tree_order_si ptr) h"
  ⟨proof⟩
```

```
end
```

```

interpretation i_to_tree_order_si?: l_to_tree_order_siShadow_DOM to_tree_order_si get_child_nodes
  get_child_nodes_locs get_shadow_root get_shadow_root_locs type_wf known_ptr
  ⟨proof⟩
declare l_to_tree_order_siShadow_DOM_axioms [instances]

first_in_tree_order

global_interpretation l_first_in_tree_orderCore_DOM_defs to_tree_order defines
  first_in_tree_order = "l_first_in_tree_orderCore_DOM_defs.a_first_in_tree_order to_tree_order" ⟨proof⟩

interpretation i_first_in_tree_order?: l_first_in_tree_orderCore_DOM to_tree_order first_in_tree_order
  ⟨proof⟩
declare l_first_in_tree_orderCore_DOM_axioms [instances]

lemma to_tree_order_is_l_to_tree_order [instances]: "l_to_tree_order to_tree_order"
  ⟨proof⟩

first_in_tree_order

global_interpretation l_dummy defines
  first_in_tree_order_si = "l_first_in_tree_orderCore_DOM_defs.a_first_in_tree_order to_tree_order_si"
  ⟨proof⟩

get_element_by

global_interpretation l_get_element_byCore_DOM_defs to_tree_order first_in_tree_order get_attribute
  get_attribute_locs
  defines
    get_element_by_id =
      "l_get_element_byCore_DOM_defs.a_get_element_by_id first_in_tree_order get_attribute" and
    get_elements_by_class_name =
      "l_get_element_byCore_DOM_defs.a_get_elements_by_class_name to_tree_order get_attribute" and
    get_elements_by_tag_name =
      "l_get_element_byCore_DOM_defs.a_get_elements_by_tag_name to_tree_order" ⟨proof⟩

interpretation i_get_element_by?: l_get_element_byCore_DOM to_tree_order first_in_tree_order
  get_attribute get_attribute_locs get_element_by_id get_elements_by_class_name
  get_elements_by_tag_name type_wf
  ⟨proof⟩
declare l_get_element_byCore_DOM_axioms [instances]

lemma get_element_by_is_l_get_element_by [instances]:
  "l_get_element_by get_element_by_id get_elements_by_tag_name to_tree_order"
  ⟨proof⟩

get_element_by_si

global_interpretation l_dummy defines
  get_element_by_id_si =
    "l_get_element_byCore_DOM_defs.a_get_element_by_id first_in_tree_order_si get_attribute" and
  get_elements_by_class_name_si =
    "l_get_element_byCore_DOM_defs.a_get_elements_by_class_name to_tree_order_si get_attribute" and
  get_elements_by_tag_name_si =
    "l_get_element_byCore_DOM_defs.a_get_elements_by_tag_name to_tree_order_si" ⟨proof⟩

find_slot

locale l_find_slotShadow_DOM_defs =
  l_get_parent_defs get_parent get_parent_locs +
  l_get_shadow_root_defs get_shadow_root get_shadow_root_locs +
```

```

l_get_mode_defs get_mode get_mode_locs +
l_get_attribute_defs get_attribute get_attribute_locs +
l_get_tag_name_defs get_tag_name get_tag_name_locs +
l_first_in_tree_order_defs first_in_tree_order
for get_parent :: "(_ node_ptr ⇒ ((_) heap, exception, (_::linorder) object_ptr option) prog"
  and get_parent_locs :: "(_ heap ⇒ (_ heap ⇒ bool) set"
  and get_shadow_root :: "(_ element_ptr ⇒ ((_) heap, exception, (_ shadow_root_ptr option) prog"
  and get_shadow_root_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ bool) set"
  and get_mode :: "(_ shadow_root_ptr ⇒ ((_) heap, exception, shadow_root_mode) prog"
  and get_mode_locs :: "(_ shadow_root_ptr ⇒ ((_) heap ⇒ bool) set"
  and get_attribute :: "(_ element_ptr ⇒ char list ⇒ ((_) heap, exception, char list option) prog"
  and get_attribute_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ bool) set"
  and get_tag_name :: "(_ element_ptr ⇒ ((_) heap, exception, char list) prog"
  and get_tag_name_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ bool) set"
  and first_in_tree_order :: "
    (_ object_ptr ⇒ ((_) object_ptr ⇒ ((_) heap, exception, (_ element_ptr option) prog) ⇒
      ((_) heap, exception, (_ element_ptr option) prog"
begin
definition a_find_slot :: "bool ⇒ (_ node_ptr ⇒ (_, (_ element_ptr option) dom_prog"
  where
    "a_find_slot open_flag slotable = do {
      parent_opt ← get_parent slotable;
      (case parent_opt of
        Some parent ⇒
          if is_element_ptr_kind parent
          then do {
            shadow_root_ptr_opt ← get_shadow_root (the (cast parent));
            (case shadow_root_ptr_opt of
              Some shadow_root_ptr ⇒ do {
                shadow_root_mode ← get_mode shadow_root_ptr;
                if open_flag ∧ shadow_root_mode ≠ Open
                then return None
                else first_in_tree_order (cast shadow_root_ptr) (λptr. if is_element_ptr_kind ptr
                  then do {
                    tag ← get_tag_name (the (cast ptr));
                    name_attr ← get_attribute (the (cast ptr)) ''name'';
                    slotable_name_attr ← (if is_element_ptr_kind slotable
                      then get_attribute (the (cast slotable)) ''slot''
                      else return None);
                    (if (tag = ''slot'' ∧ (name_attr = slotable_name_attr ∨
                      (name_attr = None ∧ slotable_name_attr = Some ''')) ∨
                      (name_attr = Some '','' ∧ slotable_name_attr = None))
                      then return (Some (the (cast ptr)))
                      else return None)
                    else return None)
                  | None ⇒ return None)
                else return None
              }
            )
          )
        | _ ⇒ return None
      )
    "
definition a_assigned_slot :: "(_ node_ptr ⇒ (_, (_ element_ptr option) dom_prog"
  where
    "a_assigned_slot = a_find_slot True"
end

global_interpretation l_find_slotShadow_DOM_defs get_parent get_parent_locs get_shadow_root
  get_shadow_root_locs get_mode get_mode_locs get_attribute get_attribute_locs get_tag_name
  get_tag_name_locs first_in_tree_order
  defines find_slot = a_find_slot
    and assigned_slot = a_assigned_slot
  ⟨proof⟩

locale l_find_slot_defs =
  fixes find_slot :: "bool ⇒ (_ node_ptr ⇒ (_, (_ element_ptr option) dom_prog"

```

```

and assigned_slot :: "(_ node_ptr ⇒ _, (_ element_ptr option) dom_prog"

locale l_find_slot_Shadow_DOM =
l_find_slot_Shadow_DOM_defs +
l_find_slot_defs +
l_get_parent +
l_get_shadow_root +
l_get_mode +
l_get_attribute +
l_get_tag_name +
l_to_tree_order +
l_first_in_tree_orderCore_DOM +
assumes find_slot_impl: "find_slot = a_find_slot"
assumes assigned_slot_impl: "assigned_slot = a_assigned_slot"
begin
lemmas find_slot_def = find_slotImpl[unfolded a_find_slot_def]
lemmas assigned_slot_def = assigned_slotImpl[unfolded a_assigned_slot_def]

lemma find_slot_ptr_in_heap:
assumes "h ⊢ find_slot open_flag slotable →r slot_opt"
shows "slotable ∈ node_ptr_kinds h"
⟨proof⟩

lemma find_slot_slot_in_heap:
assumes "h ⊢ find_slot open_flag slotable →r Some slot"
shows "slot ∈ element_ptr_kinds h"
⟨proof⟩

lemma find_slot_pure [simp]: "pure (find_slot open_flag slotable) h"
⟨proof⟩
end

interpretation i_find_slot?: l_find_slot_Shadow_DOM get_parent get_parent_locs get_shadow_root
get_shadow_root_locs get_mode get_mode_locs get_attribute get_attribute_locs get_tag_name
get_tag_name_locs first_in_tree_order find_slot assigned_slot type_wf known_ptr known_ptrs
get_child_nodes get_child_nodes_locs to_tree_order
⟨proof⟩
declare l_find_slot_Shadow_DOM_axioms [instances]

locale l_find_slot = l_find_slot_defs +
assumes find_slot_ptr_in_heap:
"h ⊢ find_slot open_flag slotable →r slot_opt ⇒ slotable ∈ node_ptr_kinds h"
assumes find_slot_slot_in_heap:
"h ⊢ find_slot open_flag slotable →r Some slot ⇒ slot ∈ element_ptr_kinds h"
assumes find_slot_pure [simp]:
"pure (find_slot open_flag slotable) h"

lemma find_slot_is_l_find_slot [instances]: "l_find_slot find_slot"
⟨proof⟩

get_disconnected_nodes

locale l_get_disconnected_nodes_Shadow_DOM =
CD: l_get_disconnected_nodesCore_DOM type_wfCore_DOM get_disconnected_nodes
get_disconnected_nodes_locs +
l_type_wf type_wf
for type_wf :: "(_ heap ⇒ bool"
  and type_wfCore_DOM :: "(_ heap ⇒ bool"
  and get_disconnected_nodes :: "(_ document_ptr ⇒ _, (_ node_ptr list) dom_prog"
  and get_disconnected_nodes_locs :: "(_ document_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set" +
assumes type_wfImpl: "type_wf = ShadowRootClass.type_wf"
begin

```

```

lemma get_disconnected_nodes_ok:
  "type_wf h ==> document_ptr /∈/ document_ptr_kinds h ==>
   h ⊢ ok (get_disconnected_nodes document_ptr)"
  ⟨proof⟩
end

interpretation i_get_disconnected_nodes?: l_get_disconnected_nodesShadow_DOM type_wf
  DocumentClass.type_wf get_disconnected_nodes get_disconnected_nodes_locs
  ⟨proof⟩
declare l_get_disconnected_nodesShadow_DOM_axioms [instances]

lemma get_disconnected_nodes_is_l_get_disconnected_nodes [instances]:
  "l_get_disconnected_nodes type_wf get_disconnected_nodes get_disconnected_nodes_locs"
  ⟨proof⟩

set_child_nodes locale l_set_child_nodes_get_disconnected_nodesShadow_DOM =
  l_set_child_nodesShadow_DOM +
  l_get_disconnected_nodesShadow_DOM
begin
lemma set_child_nodes_get_disconnected_nodes:
  "∀ w ∈ set_child_nodes_locs ptr. (h ⊢ w →h h' —> (∀ r ∈ get_disconnected_nodes_locs ptr'. r h h'))"
  ⟨proof⟩
end

interpretation
  i_set_child_nodes_get_disconnected_nodes?: l_set_child_nodes_get_disconnected_nodesShadow_DOM type_wf
  known_ptr DocumentClass.type_wf DocumentClass.known_ptr set_child_nodes set_child_nodes_locs
  Core_DOM_Functions.set_child_nodes Core_DOM_Functions.set_child_nodes_locs
  get_disconnected_nodes get_disconnected_nodes_locs
  ⟨proof⟩
declare l_set_child_nodes_get_disconnected_nodesShadow_DOM_axioms [instances]

lemma set_child_nodes_get_disconnected_nodes_is_l_set_child_nodes_get_disconnected_nodes [instances]:
  "l_set_child_nodes_get_disconnected_nodes type_wf set_child_nodes set_child_nodes_locs
   get_disconnected_nodes get_disconnected_nodes_locs"
  ⟨proof⟩

set_disconnected_nodes lemma set_disconnected_nodes_get_disconnected_nodes_l_set_disconnected_nodes_get_discon-
[instances]:
  "l_set_disconnected_nodes_get_disconnected_nodes ShadowRootClass.type_wf get_disconnected_nodes
   get_disconnected_nodes_locs set_disconnected_nodes set_disconnected_nodes_locs"
  ⟨proof⟩

delete_shadow_root locale l_delete_shadow_root_get_disconnected_nodesShadow_DOM =
  l_get_disconnected_nodesShadow_DOM
begin
lemma get_disconnected_nodes_delete_shadow_root: "h ⊢ deleteShadowRoot_M shadow_root_ptr →h h'
  ==> r ∈ get_disconnected_nodes_locs ptr' ==> r h h'"
  ⟨proof⟩
end

locale l_delete_shadow_root_get_disconnected_nodes = l_get_disconnected_nodes_defs +
  assumes get_disconnected_nodes_delete_shadow_root: "h ⊢ deleteShadowRoot_M shadow_root_ptr →h h'
  ==> r ∈ get_disconnected_nodes_locs ptr' ==> r h h"
interpretation l_delete_shadow_root_get_disconnected_nodesShadow_DOM type_wf DocumentClass.type_wf
  get_disconnected_nodes get_disconnected_nodes_locs
  ⟨proof⟩

lemma l_delete_shadow_root_get_disconnected_nodes_get_disconnected_nodes_locs [instances]: "l_delete_shadow_root_
get_disconnected_nodes_locs"
  ⟨proof⟩

```

```

set_shadow_root locale l_set_shadow_root_get_disconnected_nodesShadow_DOM =
  l_set_shadow_rootShadow_DOM +
  l_get_disconnected_nodesShadow_DOM
begin
lemma set_shadow_root_get_disconnected_nodes:
  " $\forall w \in \text{set\_shadow\_root\_locs} \text{ptr}. (h \vdash w \rightarrow_h h' \longrightarrow (\forall r \in \text{get\_disconnected\_nodes\_locs} \text{ptr}'. r \text{ } h \text{ } h'))$ ""
  ⟨proof⟩
end

interpretation i_set_shadow_root_get_disconnected_nodes?:
  l_set_shadow_root_get_disconnected_nodesShadow_DOM type_wf set_shadow_root set_shadow_root_locs
  DocumentClass.type_wf get_disconnected_nodes get_disconnected_nodes_locs
  ⟨proof⟩
declare l_set_shadow_root_get_disconnected_nodesShadow_DOM_axioms[instances]

locale l_set_shadow_root_get_disconnected_nodes =
  l_set_shadow_root_defs +
  l_get_disconnected_nodes_defs +
assumes set_shadow_root_get_disconnected_nodes:
  " $\forall w \in \text{set\_shadow\_root\_locs} \text{ptr}. (h \vdash w \rightarrow_h h' \longrightarrow (\forall r \in \text{get\_disconnected\_nodes\_locs} \text{ptr}'. r \text{ } h \text{ } h'))$ ""

lemma set_shadow_root_get_disconnected_nodes_is_l_set_shadow_root_get_disconnected_nodes [instances]:
  "l_set_shadow_root_get_disconnected_nodes set_shadow_root_locs get_disconnected_nodes_locs"
  ⟨proof⟩

set_mode locale l_set_mode_get_disconnected_nodesShadow_DOM =
  l_set_modeShadow_DOM +
  l_get_disconnected_nodesShadow_DOM
begin
lemma set_mode_get_disconnected_nodes:
  " $\forall w \in \text{set\_mode\_locs} \text{ptr}. (h \vdash w \rightarrow_h h' \longrightarrow (\forall r \in \text{get\_disconnected\_nodes\_locs} \text{ptr}'. r \text{ } h \text{ } h'))$ ""
  ⟨proof⟩
end

interpretation i_set_mode_get_disconnected_nodes?: l_set_mode_get_disconnected_nodesShadow_DOM type_wf
  set_mode set_mode_locs DocumentClass.type_wf get_disconnected_nodes get_disconnected_nodes_locs
  ⟨proof⟩
declare l_set_mode_get_disconnected_nodesShadow_DOM_axioms[instances]

locale l_set_mode_get_disconnected_nodes = l_set_mode + l_get_disconnected_nodes +
assumes set_mode_get_disconnected_nodes:
  " $\forall w \in \text{set\_mode\_locs} \text{ptr}. (h \vdash w \rightarrow_h h' \longrightarrow (\forall r \in \text{get\_disconnected\_nodes\_locs} \text{ptr}'. r \text{ } h \text{ } h'))$ ""

lemma set_mode_get_disconnected_nodes_is_l_set_mode_get_disconnected_nodes [instances]:
  "l_set_mode_get_disconnected_nodes type_wf set_mode set_mode_locs get_disconnected_nodes
   get_disconnected_nodes_locs"
  ⟨proof⟩

new_shadow_root locale l_new_shadow_root_get_disconnected_nodesShadow_DOM =
  l_get_disconnected_nodesShadow_DOM type_wf type_wfCore_DOM get_disconnected_nodes
  get_disconnected_nodes_locs
  for type_wf :: "(_ heap ⇒ bool"
    and type_wfCore_DOM :: "(_ heap ⇒ bool"
    and get_disconnected_nodes :: "(_ document_ptr ⇒ (_ , (_ node_ptr list) dom_prog"
    and get_disconnected_nodes_locs :: "(_ document_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
begin
lemma get_disconnected_nodes_new_shadow_root:
  " $h \vdash \text{newShadowRoot\_M} \rightarrow_r \text{new\_shadow\_root\_ptr} \implies h \vdash \text{newShadowRoot\_M} \rightarrow_h h'$ 
   $\implies r \in \text{get\_disconnected\_nodes\_locs} \text{ptr}' \implies r \text{ } h \text{ } h'$ ""
  ⟨proof⟩
end

interpretation i_new_shadow_root_get_disconnected_nodes?:

```

```

l_new_shadow_root_get_disconnected_nodesShadow_DOM type_wf DocumentClass.type_wf
get_disconnected_nodes get_disconnected_nodes_locs
⟨proof⟩
declare l_new_shadow_root_get_disconnected_nodesShadow_DOM_axioms[instances]

locale l_new_shadow_root_get_disconnected_nodes = l_get_disconnected_nodes_defs +
assumes get_disconnected_nodes_new_shadow_root:
  "h ⊢ newShadowRoot_M →r new_shadow_root_ptr ⟹ h ⊢ newShadowRoot_M →h h'
  ⟹ r ∈ get_disconnected_nodes_locs ptr' ⟹ r h h''"

lemma new_shadow_root_get_disconnected_nodes_is_l_new_shadow_root_get_disconnected_nodes [instances]:
  "l_new_shadow_root_get_disconnected_nodes get_disconnected_nodes_locs"
⟨proof⟩

remove_shadow_root

locale l_remove_shadow_rootShadow_DOM_defs =
l_get_child_nodes_defs get_child_nodes get_child_nodes_locs +
l_get_shadow_root_defs get_shadow_root get_shadow_root_locs +
l_set_shadow_root_defs set_shadow_root set_shadow_root_locs +
l_get_disconnected_nodes_defs get_disconnected_nodes get_disconnected_nodes_locs
for get_child_nodes :: "(_ object_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
  and get_child_nodes_locs :: "(_ object_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
  and get_shadow_root :: "(_ element_ptr ⇒ ((_) heap, exception, (_ shadow_root_ptr option) prog"
  and get_shadow_root_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
  and set_shadow_root :: "
    "(_ element_ptr ⇒ (_ shadow_root_ptr option ⇒ ((_) heap, exception, unit) prog"
    and set_shadow_root_locs :: "(_ element_ptr ⇒ ((_) heap, exception, unit) prog set"
    and get_disconnected_nodes :: "(_ document_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
    and get_disconnected_nodes_locs :: "(_ document_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
begin

definition a_remove_shadow_root :: "(_ element_ptr ⇒ (, unit) dom_prog" where
  "a_remove_shadow_root element_ptr = do {
    shadow_root_ptr_opt ← get_shadow_root element_ptr;
    (case shadow_root_ptr_opt of
      Some shadow_root_ptr ⇒ do {
        children ← get_child_nodes (cast shadow_root_ptr);
        (if children = []
        then do {
          set_shadow_root element_ptr None;
          delete_M shadow_root_ptr
        } else do {
          error HierarchyRequestError
        })
      } /
    None ⇒ error HierarchyRequestError)
  }"
}

definition a_remove_shadow_root_locs :: "
  "(_ element_ptr ⇒ (_ shadow_root_ptr ⇒ ((_, unit) dom_prog) set"
  where
    "a_remove_shadow_root_locs element_ptr shadow_root_ptr ≡
      set_shadow_root_locs element_ptr ∪ {delete_M shadow_root_ptr}"
end

global_interpretation l_remove_shadow_rootShadow_DOM_defs get_child_nodes get_child_nodes_locs
  get_shadow_root get_shadow_root_locs set_shadow_root set_shadow_root_locs get_disconnected_nodes
  get_disconnected_nodes_locs
defines remove_shadow_root = "a_remove_shadow_root"
  and remove_shadow_root_locs = a_remove_shadow_root_locs
⟨proof⟩

```

```

locale l_remove_shadow_root_defs =
fixes remove_shadow_root :: "(_ element_ptr ⇒ (_, unit) dom_prog"
fixes remove_shadow_root_locs :: "
  (_ element_ptr ⇒ (_ shadow_root_ptr ⇒ ((_, unit) dom_prog) set"

```

```

locale l_remove_shadow_root_Shadow_DOM =
l_remove_shadow_root_Shadow_DOM_defs +
l_remove_shadow_root_defs +
l_get_shadow_root_Shadow_DOM +
l_set_shadow_root_Shadow_DOM +
l_get_child_nodes +
l_get_disconnected_nodes type_wf get_disconnected_nodes get_disconnected_nodes_locs +
assumes remove_shadow_rootImpl: "remove_shadow_root = a_remove_shadow_root"
assumes remove_shadow_root_locsImpl: "remove_shadow_root_locs = a_remove_shadow_root_locs"
begin
lemmas remove_shadow_root_def =
remove_shadow_rootImpl[unfolded remove_shadow_root_def a_remove_shadow_root_def]
lemmas remove_shadow_root_locs_def =
remove_shadow_root_locsImpl[unfolded remove_shadow_root_locs_def a_remove_shadow_root_locs_def]
```

```

lemma remove_shadow_root_writes:
  "writes (remove_shadow_root_locs element_ptr (the |h ⊢ get_shadow_root element_ptr|,))
    (remove_shadow_root element_ptr) h h'"
  ⟨proof⟩
end
```

```

interpretation i_remove_shadow_root?: l_remove_shadow_root_Shadow_DOM get_child_nodes
get_child_nodes_locs get_shadow_root get_shadow_root_locs set_shadow_root set_shadow_root_locs
get_disconnected_nodes get_disconnected_nodes_locs remove_shadow_root remove_shadow_root_locs
type_wf known_ptr
⟨proof⟩
declare l_remove_shadow_root_Shadow_DOM_axioms [instances]
```

```

get_child_nodes locale l_remove_shadow_root_get_child_nodes_Shadow_DOM =
l_get_child_nodes_Shadow_DOM +
l_remove_shadow_root_Shadow_DOM
begin
```

```

lemma remove_shadow_root_get_child_nodes_different_pointers:
  assumes "ptr ≠ cast shadow_root_ptr"
  assumes "w ∈ remove_shadow_root_locs element_ptr shadow_root_ptr"
  assumes "h ⊢ w →_h h'"
  assumes "r ∈ get_child_nodes_locs ptr"
  shows "r h h'"
  ⟨proof⟩
end
```

```

locale l_remove_shadow_root_get_child_nodes = l_get_child_nodes_defs + l_remove_shadow_root_defs +
assumes remove_shadow_root_get_child_nodes_different_pointers:
  "ptr ≠ cast shadow_root_ptr ⇒ w ∈ remove_shadow_root_locs element_ptr shadow_root_ptr ⇒
    h ⊢ w →_h h' ⇒ r ∈ get_child_nodes_locs ptr ⇒ r h h'"
```

```

interpretation i_remove_shadow_root_get_child_nodes?: l_remove_shadow_root_get_child_nodes_Shadow_DOM
type_wf known_ptr DocumentClass.type_wf DocumentClass.known_ptr get_child_nodes
get_child_nodes_locs Core_DOM_Functions.get_child_nodes Core_DOM_Functions.get_child_nodes_locs
get_shadow_root get_shadow_root_locs set_shadow_root set_shadow_root_locs get_disconnected_nodes
get_disconnected_nodes_locs remove_shadow_root remove_shadow_root_locs
⟨proof⟩
declare l_remove_shadow_root_get_child_nodes_Shadow_DOM_axioms [instances]
```

```

lemma remove_shadow_root_get_child_nodes_is_l_remove_shadow_root_get_child_nodes [instances]:
  "l_remove_shadow_root_get_child_nodes get_child_nodes_locs remove_shadow_root_locs"
```

$\langle proof \rangle$

```

get_tag_name locale l_remove_shadow_root_get_tag_nameShadow_DOM =
  l_get_tag_nameShadow_DOM +
  l_remove_shadow_rootShadow_DOM
begin

lemma remove_shadow_root_get_tag_name:
  assumes "w ∈ remove_shadow_root_locs element_ptr shadow_root_ptr"
  assumes "h ⊢ w →h h'"
  assumes "r ∈ get_tag_name_locs ptr"
  shows "r h h'"
  ⟨proof⟩
end

locale l_remove_shadow_root_get_tag_name = l_get_tag_name_defs + l_remove_shadow_root_defs +
assumes remove_shadow_root_get_tag_name:
  "w ∈ remove_shadow_root_locs element_ptr shadow_root_ptr ⇒ h ⊢ w →h h' ⇒
  r ∈ get_tag_name_locs ptr ⇒ r h h'"

interpretation i_remove_shadow_root_get_tag_name?: l_remove_shadow_root_get_tag_nameShadow_DOM type_wf
  DocumentClass.type_wf get_tag_name get_tag_name_locs get_child_nodes get_child_nodes_locs
  get_shadow_root get_shadow_root_locs set_shadow_root set_shadow_root_locs get_disconnected_nodes
  get_disconnected_nodes_locs remove_shadow_root remove_shadow_root_locs known_ptr
  ⟨proof⟩
declare l_remove_shadow_root_get_tag_nameShadow_DOM_axioms[instances]

lemma remove_shadow_root_get_tag_name_is_l_remove_shadow_root_get_tag_name [instances]:
  "l_remove_shadow_root_get_tag_name get_tag_name_locs remove_shadow_root_locs"
  ⟨proof⟩

get_owner_document

locale l_get_owner_documentShadow_DOM_defs =
  l_get_host_defs get_host get_host_locs +
  CD: l_get_owner_documentCore_DOM_defs get_root_node get_root_node_locs get_disconnected_nodes
  get_disconnected_nodes_locs
  for get_root_node :: "(_::linorder) object_ptr ⇒ ((_) heap, exception, (_ object_ptr) prog"
    and get_root_node_locs :: "((_) heap ⇒ (_ heap ⇒ bool) set"
    and get_disconnected_nodes :: "(_ document_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
    and get_disconnected_nodes_locs :: "(_ document_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
    and get_host :: "(_ shadow_root_ptr ⇒ ((_) heap, exception, (_ element_ptr) prog"
    and get_host_locs :: "((_) heap ⇒ (_ heap ⇒ bool) set"
begin
definition a_get_owner_documentshadow_root_ptr :: 
  "(_ shadow_root_ptr ⇒ unit ⇒ (, (_ document_ptr) dom_prog)"
  where
    "a_get_owner_documentshadow_root_ptr shadow_root_ptr _ = do {
      host ← get_host shadow_root_ptr;
      CD.a_get_owner_documentnode_ptr (cast host) ()
    }"
definition a_get_owner_document_tups :: "(((_) object_ptr ⇒ bool) × ((_) object_ptr ⇒ unit
  ⇒ (, (_ document_ptr) dom_prog)) list"
  where
    "a_get_owner_document_tups = [(is_shadow_root_ptr, a_get_owner_documentshadow_root_ptr ∘ the ∘ cast)]"
definition a_get_owner_document :: "(_::linorder) object_ptr ⇒ (, (_ document_ptr) dom_prog"
  where
    "a_get_owner_document ptr = invoke (CD.a_get_owner_document_tups @ a_get_owner_document_tups) ptr ()"
end

global_interpretation l_get_owner_documentShadow_DOM_defs get_root_node_si get_root_node_si_locs

```

```

get_disconnected_nodes get_disconnected_nodes_locs get_host get_host_locs
defines get_owner_document_tups = a_get_owner_document_tups
  and get_owner_document = a_get_owner_document
  and get_owner_documentshadow_root_ptr = a_get_owner_documentshadow_root_ptr
  and get_owner_document_tupsCore_DOM =
    "l_get_owner_documentCore_DOM_defs.a_get_owner_document_tups
      get_root_node_si get_disconnected_nodes"
  and get_owner_documentnode_ptr =
    "l_get_owner_documentCore_DOM_defs.a_get_owner_documentnode_ptr
      get_root_node_si get_disconnected_nodes"
⟨proof⟩

locale l_get_owner_documentShadow_DOM =
l_known_ptr known_ptr +
l_get_owner_documentShadow_DOM_defs get_root_node_si get_root_node_si_locs get_disconnected_nodes
get_disconnected_nodes_locs get_host get_host_locs +
l_get_owner_document_defs get_owner_document +
l_get_host get_host get_host_locs +
CD: l_get_owner_documentCore_DOM
get_parent get_parent_locs known_ptrCore_DOM type_wf get_disconnected_nodes
get_disconnected_nodes_locs get_root_node_si get_root_node_si_locs get_owner_documentCore_DOM
for known_ptr :: "(_::linorder) object_ptr ⇒ bool"
  and known_ptrCore_DOM :: "(_::linorder) object_ptr ⇒ bool"
  and get_parent :: "(_ node_ptr ⇒ ((_) heap, exception, (_ object_ptr option) prog"
  and get_parent_locs :: "((_) heap ⇒ (_ heap ⇒ bool) set"
  and type_wf :: "(_ heap ⇒ bool"
  and get_disconnected_nodes :: "(_ document_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
  and get_disconnected_nodes_locs :: "(_ document_ptr ⇒ ((_) heap ⇒ bool) set"
  and get_root_node_si :: "(_ object_ptr ⇒ ((_) heap, exception, (_ object_ptr) prog"
  and get_root_node_si_locs :: "((_) heap ⇒ (_ heap ⇒ bool) set"
  and get_owner_documentCore_DOM :: "(_ object_ptr ⇒ ((_) heap, exception, (_ document_ptr) prog"
  and get_host :: "(_ shadow_root_ptr ⇒ ((_) heap, exception, (_ element_ptr) prog"
  and get_host_locs :: "((_) heap ⇒ (_ heap ⇒ bool) set"
  and get_owner_document :: "(_ object_ptr ⇒ ((_) heap, exception, (_ document_ptr) prog" +
assumes known_ptr_impl: "known_ptr = a_known_ptr"
assumes get_owner_document_impl: "get_owner_document = a_get_owner_document"
begin
lemmas known_ptr_def = known_ptr_impl[unfolded a_known_ptr_def]
lemmas get_owner_document_def = a_get_owner_document_def[folded get_owner_document_impl]

lemma get_owner_document_pure [simp]:
  "pure (get_owner_document ptr) h"
⟨proof⟩

lemma get_owner_document_ptr_in_heap:
  assumes "h ⊢ ok (get_owner_document ptr)"
  shows "ptr /∈ object_ptr_kinds h"
⟨proof⟩

end

interpretation i_get_owner_document?: l_get_owner_documentShadow_DOM known_ptr DocumentClass.known_ptr
  get_parent get_parent_locs type_wf get_disconnected_nodes get_disconnected_nodes_locs
  get_root_node_si get_root_node_si_locs CD.a_get_owner_document get_host get_host_locs
  get_owner_document
⟨proof⟩
declare l_get_owner_documentShadow_DOM_axioms [instances]

lemma get_owner_document_is_l_get_owner_document [instances]:
  "l_get_owner_document get_owner_document"
⟨proof⟩

```

remove_child

```
global_interpretation l_remove_childCore_DOM_defs get_child_nodes get_child_nodes_locs set_child_nodes
set_child_nodes_locs get_parent get_parent_locs get_owner_document get_disconnected_nodes
get_disconnected_nodes_locs set_disconnected_nodes set_disconnected_nodes_locs
defines remove = "l_remove_childCore_DOM_defs.a_remove get_child_nodes set_child_nodes get_parent
get_owner_document get_disconnected_nodes set_disconnected_nodes"
and remove_child = "l_remove_childCore_DOM_defs.a_remove_child get_child_nodes set_child_nodes
get_owner_document get_disconnected_nodes set_disconnected_nodes"
and remove_child_locs = "l_remove_childCore_DOM_defs.a_remove_child_locs set_child_nodes_locs
set_disconnected_nodes_locs"
⟨proof⟩
```

interpretation i_remove_child?: l_remove_childCore_DOM Shadow_DOM.get_child_nodes
Shadow_DOM.get_child_nodes_locs Shadow_DOM.set_child_nodes Shadow_DOM.set_child_nodes_locs
Shadow_DOM.get_parent Shadow_DOM.get_parent_locs Shadow_DOM.get_owner_document
get_disconnected_nodes get_disconnected_nodes_locs set_disconnected_nodes
set_disconnected_nodes_locs remove_child remove_child_locs remove ShadowRootClass.type_wf
ShadowRootClass.known_ptr ShadowRootClass.known_ptrs
⟨proof⟩

declare l_remove_childCore_DOM_axioms [instances]

get_disconnected_document

```
locale l_get_disconnected_documentCore_DOM_defs =
l_get_disconnected_nodes_defs get_disconnected_nodes get_disconnected_nodes_locs
for get_disconnected_nodes :: "
  (::_linorder) document_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
  and get_disconnected_nodes_locs :: "(_ document_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
begin
definition a_get_disconnected_document :: "(_ node_ptr ⇒ (, (_ document_ptr) dom_prog"
where
  "a_get_disconnected_document node_ptr = do {
    check_in_heap (cast node_ptr);
    ptrs ← document_ptr_kinds_M;
    candidates ← filter_M (λdocument_ptr. do {
      disconnected_nodes ← get_disconnected_nodes document_ptr;
      return (node_ptr ∈ set disconnected_nodes)
    }) ptrs;
    (case candidates of
      Cons document_ptr [] ⇒ return document_ptr |
      _ ⇒ error HierarchyRequestError
    )
  }"
definition "a_get_disconnected_document_locs =
  (U document_ptr. get_disconnected_nodes_locs document_ptr) ∪
  (U ptr. {preserved (get_MObject_ptr RObject.nothing)})"
end

locale l_get_disconnected_document_defs =
fixes get_disconnected_document :: "(_ node_ptr ⇒ (, (_::linorder) document_ptr) dom_prog"
fixes get_disconnected_document_locs :: "((_) heap ⇒ (_ heap ⇒ bool) set"

locale l_get_disconnected_documentCore_DOM =
l_get_disconnected_documentCore_DOM_defs +
l_get_disconnected_document_defs +
l_get_disconnected_nodes +
assumes get_disconnected_document_impl:
  "get_disconnected_document = a_get_disconnected_document"
assumes get_disconnected_document_locs_impl:
  "get_disconnected_document_locs = a_get_disconnected_document_locs"
begin
lemmas get_disconnected_document_def =
```

```

get_disconnected_documentImpl[unfolded a_get_disconnected_document_def]
lemmas get_disconnected_document_locs_def =
  get_disconnected_document_locsImpl[unfolded a_get_disconnected_document_locs_def]

lemma get_disconnected_document_pure [simp]: "pure (get_disconnected_document ptr) h"
  ⟨proof⟩

lemma get_disconnected_document_ptr_in_heap [simp]:
  "h ⊢ ok (get_disconnected_document node_ptr) ⟹ node_ptr ∉ node_ptr_kinds h"
  ⟨proof⟩

lemma get_disconnected_document_disconnected_document_in_heap:
  assumes "h ⊢ get_disconnected_document child_node →r disconnected_document"
  shows "disconnected_document ∉ document_ptr_kinds h"
  ⟨proof⟩

lemma get_disconnected_document_reads:
  "reads get_disconnected_document_locs (get_disconnected_document node_ptr) h h'"
  ⟨proof⟩

end

locale l_get_disconnected_document = l_get_disconnected_document_defs +
  assumes get_disconnected_document_reads:
    "reads get_disconnected_document_locs (get_disconnected_document node_ptr) h h'"
  assumes get_disconnected_document_ptr_in_heap:
    "h ⊢ ok (get_disconnected_document node_ptr) ⟹ node_ptr ∉ node_ptr_kinds h"
  assumes get_disconnected_document_pure [simp]:
    "pure (get_disconnected_document node_ptr) h"
  assumes get_disconnected_document_disconnected_document_in_heap:
    "h ⊢ get_disconnected_document child_node →r disconnected_document ⟹
     disconnected_document ∉ document_ptr_kinds h"

global_interpretation l_get_disconnected_documentCore_DOM_defs get_disconnected_nodes
  get_disconnected_nodes_locs defines
  get_disconnected_document = a_get_disconnected_document and
  get_disconnected_document_locs = a_get_disconnected_document_locs ⟨proof⟩

interpretation i_get_disconnected_document?: l_get_disconnected_documentCore_DOM
  get_disconnected_nodes get_disconnected_nodes_locs get_disconnected_document
  get_disconnected_document_locs type_wf
  ⟨proof⟩
declare l_get_disconnected_documentCore_DOM_axioms [instances]

lemma get_disconnected_document_is_l_get_disconnected_document [instances]:
  "l_get_disconnected_document get_disconnected_document get_disconnected_document_locs"
  ⟨proof⟩

get_disconnected_nodes locale l_set_tag_name_get_disconnected_nodesShadow_DOM =
  l_set_tag_nameShadow_DOM +
  l_get_disconnected_nodesShadow_DOM
begin
lemma set_tag_name_get_disconnected_nodes:
  "∀w ∈ set_tag_name_locs ptr. (h ⊢ w →h h' → (∀r ∈ get_disconnected_nodes_locs ptr'. r h h'))"
  ⟨proof⟩
end

interpretation
  i_set_tag_name_get_disconnected_nodes?: l_set_tag_name_get_disconnected_nodesShadow_DOM type_wf
  DocumentClass.type_wf set_tag_name set_tag_name_locs get_disconnected_nodes
  get_disconnected_nodes_locs
  ⟨proof⟩

```

```

declare l_set_tag_name_get_disconnected_nodesCore_DOM_axioms[instances]

lemma set_tag_name_get_disconnected_nodes_is_l_set_tag_name_get_disconnected_nodes [instances]:
  "l_set_tag_name_get_disconnected_nodes type_wf set_tag_name set_tag_name_locs
   get_disconnected_nodes get_disconnected_nodes_locs"
  ⟨proof⟩

adopt_node

global_interpretation l_adopt_nodeCore_DOM_defs get_owner_document get_parent get_parent_locs
  remove_child remove_child_locs get_disconnected_nodes get_disconnected_nodes_locs
  set_disconnected_nodes set_disconnected_nodes_locs
  defines adopt_node = a_adopt_node
    and adopt_node_locs = a_adopt_node_locs
  ⟨proof⟩
interpretation i_adopt_node?: l_adopt_nodeCore_DOM get_owner_document get_parent get_parent_locs
  remove_child remove_child_locs get_disconnected_nodes get_disconnected_nodes_locs
  set_disconnected_nodes set_disconnected_nodes_locs adopt_node adopt_node_locs known_ptr type_wf
  get_child_nodes get_child_nodes_locs known_ptrs set_child_nodes set_child_nodes_locs remove
  ⟨proof⟩
declare l_adopt_nodeCore_DOM_axioms[instances]

lemma adopt_node_is_l_adopt_node [instances]: "l_adopt_node type_wf known_ptr known_ptrs get_parent
  adopt_node adopt_node_locs get_child_nodes get_owner_document"
  ⟨proof⟩

get_shadow_root locale l_adopt_node_get_shadow_rootShadow_DOM =
  l_set_child_nodes_get_shadow_rootShadow_DOM +
  l_set_disconnected_nodes_get_shadow_rootShadow_DOM +
  l_adopt_nodeCore_DOM
begin
lemma adopt_node_get_shadow_root:
  " $\forall w \in \text{adopt\_node\_locs} \text{ parent } \text{owner\_document} \text{ document\_ptr}.$ 
    $(h \vdash w \rightarrow_h h' \longrightarrow (\forall r \in \text{get\_shadow\_root\_locs} \text{ ptr'. } r \ h \ h'))$ "
  ⟨proof⟩
end

locale l_adopt_node_get_shadow_root = l_adopt_node_defs + l_get_shadow_root_defs +
assumes adopt_node_get_shadow_root:
  " $\forall w \in \text{adopt\_node\_locs} \text{ parent } \text{owner\_document} \text{ document\_ptr}.$ 
    $(h \vdash w \rightarrow_h h' \longrightarrow (\forall r \in \text{get\_shadow\_root\_locs} \text{ ptr'. } r \ h \ h'))$ ""

interpretation i_adopt_node_get_shadow_root?: l_adopt_node_get_shadow_rootShadow_DOM type_wf known_ptr
  DocumentClass.type_wf DocumentClass.known_ptr set_child_nodes set_child_nodes_locs
  Core_DOM_Functions.set_child_nodes Core_DOM_Functions.set_child_nodes_locs get_shadow_root
  get_shadow_root_locs set_disconnected_nodes set_disconnected_nodes_locs get_owner_document
  get_parent get_parent_locs remove_child remove_child_locs get_disconnected_nodes
  get_disconnected_nodes_locs adopt_node adopt_node_locs get_child_nodes get_child_nodes_locs
  known_ptrs remove
  ⟨proof⟩
declare l_adopt_node_get_shadow_rootShadow_DOM_axioms[instances]

lemma adopt_node_get_shadow_root_is_l_adopt_node_get_shadow_root [instances]:
  "l_adopt_node_get_shadow_root adopt_node_locs get_shadow_root_locs"
  ⟨proof⟩

insert_before

global_interpretation l_insert_beforeCore_DOM_defs get_parent get_parent_locs get_child_nodes
  get_child_nodes_locs set_child_nodes set_child_nodes_locs get_ancestors_si get_ancestors_si_locs
  adopt_node adopt_node_locs set_disconnected_nodes set_disconnected_nodes_locs
  get_disconnected_nodes get_disconnected_nodes_locs get_owner_document
  defines

```

```

next_sibling = a_next_sibling and
insert_node = a_insert_node and
ensure_pre_insertion_validity = a_ensure_pre_insertion_validity and
insert_before = a_insert_before and
insert_before_locs = a_insert_before_locs
⟨proof⟩
global_interpretation l_append_childCore_DOM_defs insert_before
  defines append_child = "l_append_childCore_DOM_defs.a_append_child insert_before"
  ⟨proof⟩

interpretation i_insert_before?: l_insert_beforeCore_DOM get_parent get_parent_locs get_child_nodes
  get_child_nodes_locs set_child_nodes set_child_nodes_locs get_ancestors_si get_ancestors_si_locs
  adopt_node adopt_node_locs set_disconnected_nodes set_disconnected_nodes_locs get_disconnected_nodes
  get_disconnected_nodes_locs get_owner_document insert_before insert_before_locs append_child type_wf
  known_ptr known_ptrs
  ⟨proof⟩
declare l_insert_beforeCore_DOM_axioms [instances]

interpretation i_append_child?: l_append_childCore_DOM append_child insert_before insert_before_locs
  ⟨proof⟩
declare l_append_childCore_DOM_axioms[instances]

get_assigned_nodes

fun map_filter_M2 :: "('x ⇒ ('heap, 'e, 'y option) prog) ⇒ 'x list
  ⇒ ('heap, 'e, 'y list) prog"
where
  "map_filter_M2 f [] = return []" |
  "map_filter_M2 f (x # xs) = do {
    res ← f x;
    remainder ← map_filter_M2 f xs;
    return ((case res of Some r ⇒ [r] | None ⇒ []) @ remainder)
  }"
lemma map_filter_M2_pure [simp]:
  assumes "¬(x ∈ set xs) ⇒ pure (f x) h"
  shows "pure (map_filter_M2 f xs) h"
  ⟨proof⟩

lemma map_filter_pure_no_monad:
  assumes "¬(x ∈ set xs) ⇒ pure (f x) h"
  assumes "h ⊢ map_filter_M2 f xs →r ys"
  shows
    "ys = map the (filter (λx. x ≠ None) (map (λx. |h ⊢ f x|r) xs))" and
    "¬(x ∈ set xs) ⇒ h ⊢ ok (f x)"
  ⟨proof⟩

lemma map_filter_pure_foo:
  assumes "¬(x ∈ set xs) ⇒ pure (f x) h"
  assumes "h ⊢ map_filter_M2 f xs →r ys"
  assumes "y ∈ set ys"
  obtains x where "h ⊢ f x →r Some y" and "x ∈ set xs"
  ⟨proof⟩

lemma map_filter_M2_in_result:
  assumes "h ⊢ map_filter_M2 P xs →r ys"
  assumes "a ∈ set xs"
  assumes "¬(x ∈ set xs) ⇒ pure (P x) h"
  assumes "h ⊢ P a →r Some b"
  shows "b ∈ set ys"
  ⟨proof⟩

```

```

locale l_assigned_nodes_Shadow_DOM_defs =
l_get_tag_name_defs get_tag_name get_tag_name_locs +
l_get_root_node_defs get_root_node get_root_node_locs +
l_get_host_defs get_host get_host_locs +
l_get_child_nodes_defs get_child_nodes get_child_nodes_locs +
l_find_slot_defs find_slot assigned_slot +
l_remove_defs remove +
l_insert_before_defs insert_before insert_before_locs +
l_append_child_defs append_child +
l_remove_shadow_root_defs remove_shadow_root remove_shadow_root_locs
for get_child_nodes :: "(_::linorder) object_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
    and get_child_nodes_locs :: "(_ object_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
    and get_tag_name :: "(_ element_ptr ⇒ ((_) heap, exception, char list) prog"
    and get_tag_name_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
    and get_root_node :: "(_ object_ptr ⇒ ((_) heap, exception, (_ object_ptr) prog"
    and get_root_node_locs :: "((_) heap ⇒ (_ heap ⇒ bool) set"
    and get_host :: "(_ shadow_root_ptr ⇒ ((_) heap, exception, (_ element_ptr) prog"
    and get_host_locs :: "((_) heap ⇒ (_ heap ⇒ bool) set"
    and find_slot :: "bool ⇒ (_ node_ptr ⇒ ((_) heap, exception, (_ element_ptr option) prog"
    and assigned_slot :: "(_ node_ptr ⇒ ((_) heap, exception, (_ element_ptr option) prog"
    and remove :: "(_ node_ptr ⇒ ((_) heap, exception, unit) prog"
    and insert_before :: :
        "(_ object_ptr ⇒ (_ node_ptr ⇒ (_ node_ptr option ⇒ ((_) heap, exception, unit) prog"
    and insert_before_locs :: "(_ object_ptr ⇒ (_ object_ptr option ⇒ (_ document_ptr ⇒
        (_ document_ptr ⇒ (_, unit) dom_prog set"
    and append_child :: "(_ object_ptr ⇒ (_ node_ptr ⇒ ((_) heap, exception, unit) prog"
    and remove_shadow_root :: "(_ element_ptr ⇒ ((_) heap, exception, unit) prog"
    and remove_shadow_root_locs :: "(_ element_ptr ⇒ (_ shadow_root_ptr ⇒
        ((_) heap, exception, unit) prog set"
begin
definition a_assigned_nodes :: "(_ element_ptr ⇒ (_, (_ node_ptr list) dom_prog"
where
    "a_assigned_nodes slot = do {
        tag ← get_tag_name slot;
        (if tag ≠ 'slot'
            then error HierarchyRequestError
            else return ());
        root ← get_root_node (cast slot);
        if is_shadow_root_ptr_kind root
            then do {
                host ← get_host (the (cast root));
                children ← get_child_nodes (cast host);
                filter_M (λslotable. do {
                    found_slot ← find_slot False slotable;
                    return (found_slot = Some slot)}) children}
            else return []}"
partial_function (dom_prog) a_assigned_nodes_flatten :: "
    "(_ element_ptr ⇒ (_, (_ node_ptr list) dom_prog"
where
    "a_assigned_nodes_flatten slot = do {
        tag ← get_tag_name slot;
        (if tag ≠ 'slot'
            then error HierarchyRequestError
            else return ());
        root ← get_root_node (cast slot);
        (if is_shadow_root_ptr_kind root
            then do {
                slotables ← a_assigned_nodes slot;
                slotables_or_child_nodes ← (if slotables = []
                    then do {
                        get_child_nodes (cast slot)
                    } else do {

```

```

        return slotables
    });
    list_of_lists ← map_M (λnode_ptr. do {
        (case cast node_ptr of
            Some element_ptr ⇒ do {
                tag ← get_tag_name element_ptr;
                (if tag = 'slot',
                    then do {
                        root ← get_root_node (cast element_ptr);
                        (if is_shadow_root_ptr_kind root
                            then do {
                                a_assigned_nodes_flatten element_ptr
                            } else do {
                                return [node_ptr]
                            })
                        } else do {
                            return [node_ptr]
                        })
                    }
                )
            | None ⇒ return [node_ptr])
        }) slotables_or_child_nodes;
    return (concat list_of_lists)
} else return []
}"
```

definition a_flatten_dom :: "(_ , unit) dom_prog" where

```

"a\_flatten\_dom = do {
    tups ← element_ptr_kinds_M ≈ map_filter_M2 (λelement_ptr. do {
        tag ← get_tag_name element_ptr;
        assigned_nodes ← a_assigned_nodes element_ptr;
        (if tag = 'slot' ∧ assigned_nodes ≠ []
            then return (Some (element_ptr, assigned_nodes))
            else return None));
    forall_M (λ(slot, assigned_nodes). do {
        get_child_nodes (cast slot) ≈ forall_M remove;
        forall_M (append_child (cast slot)) assigned_nodes
    }) tups;
    shadow_root_ptr_kinds_M ≈ forall_M (λshadow_root_ptr. do {
        host ← get_host shadow_root_ptr;
        get_child_nodes (cast host) ≈ forall_M remove;
        get_child_nodes (cast shadow_root_ptr) ≈ forall_M (append_child (cast host));
        remove_shadow_root host
    });
    return ()
}"
```

end

global_interpretation l_assigned_nodes_Shadow_DOM_defs get_child_nodes get_child_nodes_locs

```

get_tag_name get_tag_name_locs get_root_node get_root_node_locs get_host get_host_locs find_slot
assigned_slot remove insert_before insert_before_locs append_child remove_shadow_root
remove_shadow_root_locs
```

defines assigned_nodes = a_assigned_nodes

```

and assigned_nodes_flatten = a_assigned_nodes_flatten
and flatten_dom = a_flatten_dom
```

(proof)

declare a_assigned_nodes_flatten.simps [code]

locale l_assigned_nodes_defs =

```

fixes assigned_nodes :: "(_ ) element_ptr ⇒ (_ , (_ ) node_ptr list) dom_prog"
fixes assigned_nodes_flatten :: "(_ ) element_ptr ⇒ (_ , (_ ) node_ptr list) dom_prog"
fixes flatten_dom :: "(_ , unit) dom_prog"
```

```

locale l_assigned_nodes_Shadow_DOM =
l_assigned_nodes_defs
assigned_nodes assigned_nodes_flatten flatten_dom
+ l_assigned_nodes_Shadow_DOM_defs
get_child_nodes get_child_nodes_locs get_tag_name get_tag_name_locs get_root_node
get_root_node_locs get_host get_host_locs find_slot assigned_slot remove insert_before
insert_before_locs append_child remove_shadow_root remove_shadow_root_locs
+ l_get_shadow_root
type_wf get_shadow_root get_shadow_root_locs
+ l_set_shadow_root
type_wf set_shadow_root set_shadow_root_locs
+ l_remove
+ l_insert_before
insert_before insert_before_locs
+ l_find_slot
find_slot assigned_slot
+ l_get_tag_name
type_wf get_tag_name get_tag_name_locs
+ l_get_root_node
get_root_node get_root_node_locs get_parent get_parent_locs
+ l_get_host
get_host get_host_locs
+ l_get_child_nodes
type_wf known_ptr get_child_nodes get_child_nodes_locs
+ l_to_tree_order
to_tree_order
for known_ptr :: "(_::linorder) object_ptr => bool"
and assigned_nodes :: "(_ element_ptr => ((_) heap, exception, (_ node_ptr list) prog"
and assigned_nodes_flatten :: "(_ element_ptr => ((_) heap, exception, (_ node_ptr list) prog"
and flatten_dom :: "((_) heap, exception, unit) prog"
and get_child_nodes :: "(_ object_ptr => ((_) heap, exception, (_ node_ptr list) prog"
and get_child_nodes_locs :: "(_ object_ptr => ((_) heap => bool) set"
and get_tag_name :: "(_ element_ptr => ((_) heap, exception, char list) prog"
and get_tag_name_locs :: "(_ element_ptr => ((_) heap => bool) set"
and get_root_node :: "(_ object_ptr => ((_) heap, exception, (_ object_ptr) prog"
and get_root_node_locs :: "((_) heap => (_ heap => bool) set"
and get_host :: "(_ shadow_root_ptr => ((_) heap, exception, (_ element_ptr) prog"
and get_host_locs :: "((_) heap => (_ heap => bool) set"
and find_slot :: "bool => (_ node_ptr => ((_) heap, exception, (_ element_ptr option) prog"
and assigned_slot :: "(_ node_ptr => ((_) heap, exception, (_ element_ptr option) prog"
and remove :: "(_ node_ptr => ((_) heap, exception, unit) prog"
and insert_before :::
"(_ object_ptr => (_ node_ptr option => ((_) heap, exception, unit) prog"
and insert_before_locs :: "(_ object_ptr => (_ object_ptr option => (_ document_ptr =>
(_ document_ptr => (_, unit) dom_prog set"
and append_child :: "(_ object_ptr => (_ node_ptr => ((_) heap, exception, unit) prog"
and remove_shadow_root :: "(_ element_ptr => ((_) heap, exception, unit) prog"
and remove_shadow_root_locs :: "(_ element_ptr => (_ shadow_root_ptr =>
((_) heap, exception, unit) prog set"
and type_wf :: "(_ heap => bool"
and get_shadow_root :::
"(_ element_ptr => ((_) heap, exception, (_ shadow_root_ptr option) prog"
and get_shadow_root_locs :: "(_ element_ptr => ((_) heap => (_ heap => bool) set"
and set_shadow_root :::
"(_ element_ptr => (_ shadow_root_ptr option => ((_) heap, exception, unit) prog"
and set_shadow_root_locs :: "(_ element_ptr => ((_) heap, exception, unit) prog set"
and get_parent :: "(_ node_ptr => ((_) heap, exception, (_ object_ptr option) prog"
and get_parent_locs :: "((_) heap => (_ heap => bool) set"
and to_tree_order :: "(_ object_ptr => ((_) heap, exception, (_ object_ptr list) prog" +
assumes assigned_nodes_impl: "assigned_nodes = a_assigned_nodes"
assumes flatten_dom_impl: "flatten_dom = a_flatten_dom"
begin
lemmas assigned_nodes_def = assigned_nodesImpl[unfolded a_assigned_nodes_def]

```

```

lemmas flatten_dom_def = flatten_domImpl[unfolded a_flatten_dom_def, folded assigned_nodesImpl]

lemma assigned_nodes_pure [simp]: "pure (assigned_nodes slot) h"
  ⟨proof⟩

lemma assigned_nodes_ptr_in_heap:
  assumes "h ⊢ ok (assigned_nodes slot)"
  shows "slot ∉ element_ptr_kinds h"
  ⟨proof⟩

lemma assigned_nodes_slot_is_slot:
  assumes "h ⊢ ok (assigned_nodes slot)"
  shows "h ⊢ get_tag_name slot →r ''slot''"
  ⟨proof⟩

lemma assigned_nodes_different_ptr:
  assumes "h ⊢ assigned_nodes slot →r nodes"
  assumes "h ⊢ assigned_nodes slot' →r nodes'"
  assumes "slot ≠ slot'"
  shows "set nodes ∩ set nodes' = {}"
  ⟨proof⟩
end

interpretation i_assigned_nodes?: l_assigned_nodesShadow_DOM known_ptr assigned_nodes
  assigned_nodes_flatten flatten dom get_child_nodes get_child_nodes_locs get_tag_name
  get_tag_name_locs get_root_node get_root_node_locs get_host get_host_locs find_slot
  assigned_slot remove insert_before insert_before_locs append_child remove_shadow_root
  remove_shadow_root_locs type_wf get_shadow_root get_shadow_root_locs set_shadow_root
  set_shadow_root_locs get_parent get_parent_locs to_tree_order
  ⟨proof⟩
declare l_assigned_nodesShadow_DOM_axioms [instances]

locale l_assigned_nodes = l_assigned_nodes_defs +
  assumes assigned_nodes_pure [simp]: "pure (assigned_nodes slot) h"
  assumes assigned_nodes_ptr_in_heap:
    "h ⊢ ok (assigned_nodes slot) ⟹ slot ∉ element_ptr_kinds h"
  assumes assigned_nodes_slot_is_slot:
    "h ⊢ ok (assigned_nodes slot) ⟹ h ⊢ get_tag_name slot →r ''slot''"
  assumes assigned_nodes_different_ptr:
    "h ⊢ assigned_nodes slot →r nodes ⟹ h ⊢ assigned_nodes slot' →r nodes' ⟹
     slot ≠ slot' ⟹ set nodes ∩ set nodes' = {}"

lemma assigned_nodes_is_l_assigned_nodes [instances]: "l_assigned_nodes assigned_nodes"
  ⟨proof⟩

set_val

locale l_set_valShadow_DOM =
  CD: l_set_valCore_DOM type_wfCore_DOM set_val set_val_locs +
  l_type_wf type_wf
  for type_wf :: "(_ heap ⇒ bool"
    and type_wfCore_DOM :: "(_ heap ⇒ bool"
      and set_val :: "(_ character_data_ptr ⇒ char list ⇒ (_, unit) dom_prog"
        and set_val_locs :: "(_ character_data_ptr ⇒ (_, unit) dom_prog set" +
  assumes type_wfImpl: "type_wf = ShadowRootClass.type_wf"
begin

lemma set_val_ok:
  "type_wf h ⟹ character_data_ptr ∉ character_data_ptr_kinds h ⟹
   h ⊢ ok (set_val character_data_ptr tag)"
  ⟨proof⟩

lemma set_val_writes:

```

```

>writes (set_val_locs character_data_ptr) (set_val character_data_ptr tag) h h'"

<proof>

lemma set_val_pointers_preserved:
  assumes "w ∈ set_val_locs character_data_ptr"
  assumes "h ⊢ w →h h'"
  shows "object_ptr_kinds h = object_ptr_kinds h'"
  <proof>
end

lemma set_val_typess_preserved:
  assumes "w ∈ set_val_locs character_data_ptr"
  assumes "h ⊢ w →h h'"
  shows "type_wf h = type_wf h'"
  <proof>
interpretation
  i_set_val?: l_set_valShadow_DOM type_wf DocumentClass.type_wf set_val set_val_locs
  <proof>
declare l_set_valShadow_DOM_axioms[instances]

lemma set_val_is_l_set_val [instances]: "l_set_val type_wf set_val set_val_locs"
  <proof>

get_shadow_root locale l_set_val_get_shadow_rootShadow_DOM =
  l_set_valShadow_DOM +
  l_get_shadow_rootShadow_DOM
begin
lemma set_val_get_shadow_root:
  "∀ w ∈ set_val_locs ptr. (h ⊢ w →h h' → ( ∀ r ∈ get_shadow_root_locs ptr'. r h h'))"
  <proof>
end

locale l_set_val_get_shadow_root = l_set_val + l_get_shadow_root +
  assumes set_val_get_shadow_root:
    "∀ w ∈ set_val_locs ptr. (h ⊢ w →h h' → ( ∀ r ∈ get_shadow_root_locs ptr'. r h h'))"

interpretation
  i_set_val_get_shadow_root?: l_set_val_get_shadow_rootShadow_DOM type_wf DocumentClass.type_wf
  set_val set_val_locs
  get_shadow_root get_shadow_root_locs
  <proof>
declare l_set_val_get_shadow_rootShadow_DOM_axioms[instances]

lemma set_val_get_shadow_root_is_l_set_val_get_shadow_root [instances]:
  "l_set_val_get_shadow_root type_wf set_val set_val_locs get_shadow_root
   get_shadow_root_locs"
  <proof>

get_tag_type locale l_set_val_get_tag_nameShadow_DOM =
  l_set_valShadow_DOM +
  l_get_tag_nameShadow_DOM
begin
lemma set_val_get_tag_name:
  "∀ w ∈ set_val_locs ptr. (h ⊢ w →h h' → ( ∀ r ∈ get_tag_name_locs ptr'. r h h'))"
  <proof>
end

locale l_set_val_get_tag_name = l_set_val + l_get_tag_name +
  assumes set_val_get_tag_name:
    "∀ w ∈ set_val_locs ptr. (h ⊢ w →h h' → ( ∀ r ∈ get_tag_name_locs ptr'. r h h'))"

interpretation

```

```

i_set_val_get_tag_name?: l_set_val_get_tag_nameShadow_DOM type_wf DocumentClass.type_wf set_val
set_val_locs get_tag_name get_tag_name_locs
⟨proof⟩
declare l_set_val_get_tag_nameShadow_DOM_axioms [instances]

lemma set_val_get_tag_name_is_l_set_val_get_tag_name [instances]:
  "l_set_val_get_tag_name type_wf set_val set_val_locs get_tag_name get_tag_name_locs"
⟨proof⟩

create_character_data

locale l_create_character_dataShadow_DOM =
  CD: l_create_character_dataCore_DOM ----- type_wfCore_DOM _ known_ptrCore_DOM +
  l_known_ptr known_ptr
  for known_ptr :: "(_ object_ptr ⇒ bool"
    and type_wfCore_DOM :: "(_ heap ⇒ bool"
    and known_ptrCore_DOM :: "(_ object_ptr ⇒ bool" +
  assumes known_ptr_impl: "known_ptr = a_known_ptr"
begin

lemma create_character_data_document_in_heap:
  assumes "h ⊢ ok (create_character_data document_ptr text)"
  shows "document_ptr /∈ document_ptr_kinds h"
⟨proof⟩

lemma create_character_data_known_ptr:
  assumes "h ⊢ create_character_data document_ptr text →r new_character_data_ptr"
  shows "known_ptr (cast new_character_data_ptr)"
⟨proof⟩
end

locale l_create_character_data = l_create_character_data_defs

interpretation i_create_character_data?: l_create_character_dataShadow_DOM get_disconnected_nodes
  get_disconnected_nodes_locs set_disconnected_nodes set_disconnected_nodes_locs set_val set_val_locs
  create_character_data known_ptr DocumentClass.type_wf DocumentClass.known_ptr
⟨proof⟩
declare l_create_character_dataCore_DOM_axioms [instances]

```

create_element

```

locale l_create_elementShadow_DOM =
  CD: l_create_elementCore_DOM get_disconnected_nodes get_disconnected_nodes_locs set_disconnected_nodes
  set_disconnected_nodes_locs set_tag_name set_tag_name_locs type_wfCore_DOM create_element
  known_ptrCore_DOM +
  l_known_ptr known_ptr
  for get_disconnected_nodes :: "(_ document_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
    and get_disconnected_nodes_locs :: "(_ document_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
    and set_disconnected_nodes :: "(_ document_ptr ⇒ (_ heap, exception, unit) prog"
    and set_disconnected_nodes_locs :: "(_ document_ptr ⇒ ((_) heap, exception, unit) prog set"
    and set_tag_name :: "(_ element_ptr ⇒ char list ⇒ ((_) heap, exception, unit) prog"
    and set_tag_name_locs :: "(_ element_ptr ⇒ ((_) heap, exception, unit) prog set"
    and type_wf :: "(_ heap ⇒ bool"
    and create_element :: "(_ document_ptr ⇒ char list ⇒ ((_) heap, exception, (_ element_ptr) prog"
    and known_ptr :: "(_ object_ptr ⇒ bool"
    and type_wfCore_DOM :: "(_ heap ⇒ bool"
    and known_ptrCore_DOM :: "(_ object_ptr ⇒ bool" +
  assumes known_ptr_impl: "known_ptr = a_known_ptr"
begin
lemmas create_element_def = CD.create_element_def

```

```

lemma create_element_document_in_heap:
  assumes "h ⊢ ok (create_element document_ptr tag)"
  shows "document_ptr ∉ document_ptr_kinds h"
  ⟨proof⟩

lemma create_element_known_ptr:
  assumes "h ⊢ create_element document_ptr tag →r new_element_ptr"
  shows "known_ptr (cast new_element_ptr)"
  ⟨proof⟩
end

interpretation i_create_element?: l_create_elementShadow_DOM get_disconnected_nodes
  get_disconnected_nodes_locs set_disconnected_nodes set_disconnected_nodes_locs set_tag_name
  set_tag_name_locs type_wf create_element known_ptr DocumentClass.type_wf DocumentClass.known_ptr
  ⟨proof⟩
declare l_create_elementShadow_DOM_axioms[instances]

```

2.3.2 A wellformed heap (Core DOM)

wellformed_heap

```

locale l_heap_is_wellformedShadow_DOM_defs =
CD: l_heap_is_wellformedCore_DOM_defs get_child_nodes get_child_nodes_locs get_disconnected_nodes
get_disconnected_nodes_locs +
l_get_shadow_root_defs get_shadow_root get_shadow_root_locs +
l_get_tag_name_defs get_tag_name get_tag_name_locs
for get_child_nodes :: "(_::linorder) object_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
  and get_child_nodes_locs :: "(_ object_ptr ⇒ ((_) heap ⇒ bool) set"
  and get_disconnected_nodes :: "(_ document_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
  and get_disconnected_nodes_locs :: "(_ document_ptr ⇒ ((_) heap ⇒ bool) set"
  and get_shadow_root :: "(_ element_ptr ⇒ ((_) heap, exception, (_ shadow_root_ptr option) prog"
  and get_shadow_root_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ bool) set"
  and get_tag_name :: "(_ element_ptr ⇒ ((_) heap, exception, char list) prog"
  and get_tag_name_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ bool) set"
begin
definition a_host_shadow_root_rel :: "(_ heap ⇒ ((_) object_ptr × (_ object_ptr) set"
  where
    "a_host_shadow_root_rel h = (λ(x, y). (cast x, cast y)) ` {(host, shadow_root).
      host ∉ element_ptr_kinds h ∧ |h ⊢ get_shadow_root host|_r = Some shadow_root}"
    "a_host_shadow_root_rel_code [code]: "a_host_shadow_root_rel h = set (concat (map
      (λhost. (case |h ⊢ get_shadow_root host|_r of
        Some shadow_root ⇒ [(cast host, cast shadow_root)] |
        None ⇒ []))
      (sorted_list_of_fset (element_ptr_kinds h))))"
  )"
  ⟨proof⟩

definition a_all_ptrs_in_heap :: "(_ heap ⇒ bool" where
  "a_all_ptrs_in_heap h = ((∀host shadow_root_ptr.
    (h ⊢ get_shadow_root host →r Some shadow_root_ptr) →
    shadow_root_ptr ∉ shadow_root_ptr_kinds h))"

definition a_distinct_lists :: "(_ heap ⇒ bool"
  where
    "a_distinct_lists h = distinct (concat (
      map (λelement_ptr. (case |h ⊢ get_shadow_root element_ptr|_r of
        Some shadow_root_ptr ⇒ [shadow_root_ptr] | None ⇒ [])))
      |h ⊢ element_ptr_kinds_M|_r
    ))"

definition a_shadow_root_valid :: "(_ heap ⇒ bool" where

```

```

"a\_shadow\_root\_valid h = \( \$\forall shadow\\_root\\_ptr \in fset \(shadow\\_root\\_ptr\\_kinds h\).\$ 
 \$\exists host \in fset\(element\\_ptr\\_kinds h\).\$ 
 \$\| h \vdash get\\_tag\\_name host |\_r \in safe\\_shadow\\_root\\_element\\_types \wedge\$ 
 \$\| h \vdash get\\_shadow\\_root host |\_r = Some shadow\\_root\\_ptr\)"\$ 

definition a_heap_is_wellformed :: "(_ heap) bool"
  where
    "a_heap_is_wellformed h  $\longleftrightarrow$  CD.a_heap_is_wellformed h  $\wedge$ 
     acyclic (CD.a_parent_child_rel h  $\cup$  a_host_shadow_root_rel h)  $\wedge$ 
     a_all_ptrs_in_heap h  $\wedge$ 
     a_distinct_lists h  $\wedge$ 
     a_shadow_root_valid h"
end

global_interpretation l_heap_is_wellformedShadow_DOM_defs get_child_nodes get_child_nodes_locs
get_disconnected_nodes get_disconnected_nodes_locs get_shadow_root get_shadow_root_locs
get_tag_name get_tag_name_locs
defines heap_is_wellformed = a_heap_is_wellformed
  and parent_child_rel = CD.a_parent_child_rel
  and host_shadow_root_rel = a_host_shadow_root_rel
  and all_ptrs_in_heap = a_all_ptrs_in_heap
  and distinct_lists = a_distinct_lists
  and shadow_root_valid = a_shadow_root_valid
  and heap_is_wellformedCore_DOM = CD.a_heap_is_wellformed
  and parent_child_relCore_DOM = CD.a_parent_child_rel
  and acyclic_heapCore_DOM = CD.a_acyclic_heap
  and all_ptrs_in_heapCore_DOM = CD.a_all_ptrs_in_heap
  and distinct_listsCore_DOM = CD.a_distinct_lists
  and owner_document_validCore_DOM = CD.a_owner_document_valid
⟨proof⟩
```

interpretation i_heap_is_wellformed_{Core_DOM}: l_heap_is_wellformed_{Core_DOM} known_ptr type_wf
 get_child_nodes get_child_nodes_locs get_disconnected_nodes get_disconnected_nodes_locs
 heap_is_wellformed_{Core_DOM} parent_child_rel
 ⟨proof⟩

declare i_heap_is_wellformed_{Core_DOM}.l_heap_is_wellformed_{Core_DOM_axioms}[instances]

lemma heap_is_wellformed_{Core_DOM_is_l_heap_is_wellformed} [instances]:
 "l_heap_is_wellformed type_wf known_ptr heap_is_wellformed_{Core_DOM} parent_child_rel get_child_nodes
 get_disconnected_nodes"
 ⟨proof⟩

locale l_heap_is_wellformed_{Shadow_DOM} =
 l_heap_is_wellformed_{Shadow_DOM_defs}
 get_child_nodes get_child_nodes_locs get_disconnected_nodes get_disconnected_nodes_locs
 get_shadow_root get_shadow_root_locs get_tag_name get_tag_name_locs
 + CD: l_heap_is_wellformed_{Core_DOM}
 known_ptr type_wf get_child_nodes get_child_nodes_locs get_disconnected_nodes
 get_disconnected_nodes_locs heap_is_wellformed_{Core_DOM} parent_child_rel
 + l_heap_is_wellformed_defs
 heap_is_wellformed parent_child_rel
 + l_get_host_{Shadow_DOM}
 get_shadow_root get_shadow_root_locs get_host get_host_locs type_wf
 + l_get_disconnected_document_{Core_DOM} get_disconnected_nodes get_disconnected_nodes_locs
 get_disconnected_document get_disconnected_document_locs type_wf
 + l_get_shadow_root_{Shadow_DOM} type_wf get_shadow_root get_shadow_root_locs
 for get_child_nodes :: "(_::linorder) object_ptr \Rightarrow ((_) heap, exception, (_ node_ptr list) prog"
 and get_child_nodes_locs :: "(_ object_ptr \Rightarrow ((_) heap \Rightarrow (_ heap \Rightarrow bool) set"
 and get_disconnected_nodes :: "(_ document_ptr \Rightarrow ((_) heap, exception, (_ node_ptr list) prog"
 and get_disconnected_nodes_locs :: "(_ document_ptr \Rightarrow ((_) heap \Rightarrow (_ heap \Rightarrow bool) set"
 and get_shadow_root :: "(_ element_ptr \Rightarrow ((_) heap, exception, (_ shadow_root_ptr option) prog"
 and get_shadow_root_locs :: "(_ element_ptr \Rightarrow ((_) heap \Rightarrow (_ heap \Rightarrow bool) set"

```

and get_tag_name :: "(_ element_ptr ⇒ ((_) heap, exception, char list) prog"
and get_tag_name_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
and known_ptr :: "(_ object_ptr ⇒ bool"
and type_wf :: "(_ heap ⇒ bool"
and heap_is_wellformed :: "(_ heap ⇒ bool"
and parent_child_rel :: "(_ heap ⇒ ((_) object_ptr × (_ object_ptr) set"
and heap_is_wellformedCore_DOM :: "(_ heap ⇒ bool"
and get_host :: "(_ shadow_root_ptr ⇒ ((_) heap, exception, (_ element_ptr) prog"
and get_host_locs :: "((_) heap ⇒ (_ heap ⇒ bool) set"
and get_disconnected_document :: "(_ node_ptr ⇒ ((_) heap, exception, (_ document_ptr) prog"
and get_disconnected_document_locs :: "((_) heap ⇒ (_ heap ⇒ bool) set" +
assumes heap_is_wellformed_impl: "heap_is_wellformed = a_heap_is_wellformed"
begin
lemmas heap_is_wellformed_def =
  heap_is_wellformed_impl[unfolded a_heap_is_wellformed_def,
  folded CD.heap_is_wellformed_impl CD.parent_child_relImpl]

lemma a_distinct_lists_code [code]:
  "a_all_ptrs_in_heap h = ((∀ host ∈ fset (element_ptr_kinds h).
    h ⊢ ok (get_shadow_root host) → (case |h ⊢ get_shadow_root host|,r of
      Some shadow_root_ptr ⇒ shadow_root_ptr ∉ shadow_root_ptr_kinds h |
      None ⇒ True)))"
  ⟨proof⟩

lemma get_shadow_root_shadow_root_ptr_in_heap:
  assumes "heap_is_wellformed h"
  assumes "h ⊢ get_shadow_root host →r Some shadow_root_ptr"
  shows "shadow_root_ptr ∉ shadow_root_ptr_kinds h"
  ⟨proof⟩

lemma get_host_ptr_in_heap:
  assumes "heap_is_wellformed h"
  assumes "h ⊢ get_host shadow_root_ptr →r host"
  shows "shadow_root_ptr ∉ shadow_root_ptr_kinds h"
  ⟨proof⟩

lemma shadow_root_same_host:
  assumes "heap_is_wellformed h" and "type_wf h"
  assumes "h ⊢ get_shadow_root host →r Some shadow_root_ptr"
  assumes "h ⊢ get_shadow_root host' →r Some shadow_root_ptr"
  shows "host = host'"
  ⟨proof⟩

lemma shadow_root_host_dual:
  assumes "h ⊢ get_host shadow_root_ptr →r host"
  shows "h ⊢ get_shadow_root host →r Some shadow_root_ptr"
  ⟨proof⟩

lemma disc_doc_disc_node_dual:
  assumes "h ⊢ get_disconnected_document disc_node →r disc_doc"
  obtains disc_nodes where
    "h ⊢ get_disconnected_nodes disc_doc →r disc_nodes" and
    "disc_node ∈ set disc_nodes"
  ⟨proof⟩

lemma get_host_valid_tag_name:
  assumes "heap_is_wellformed h" and "type_wf h"
  assumes "h ⊢ get_host shadow_root_ptr →r host"
  assumes "h ⊢ get_tag_name host →r tag"
  shows "tag ∈ safe_shadow_root_element_types"
  ⟨proof⟩

```

```

lemma a_host_shadow_root_rel_finite: "finite (a_host_shadow_root_rel h)"
⟨proof⟩

lemma heap_is_wellformed_children_in_heap:
  "heap_is_wellformed h ⟹ h ⊢ get_child_nodes ptr →r children ⟹ child ∈ set children ⟹
  child ∉ node_ptr_kinds h"
⟨proof⟩

lemma heap_is_wellformed_disc_nodes_in_heap:
  "heap_is_wellformed h ⟹ h ⊢ get_disconnected_nodes document_ptr →r disc_nodes ⟹
  node ∈ set disc_nodes ⟹ node ∉ node_ptr_kinds h"
⟨proof⟩

lemma heap_is_wellformed_one_parent:
  "heap_is_wellformed h ⟹ h ⊢ get_child_nodes ptr →r children ⟹
  h ⊢ get_child_nodes ptr' →r children' ⟹ set children ∩ set children' ≠ {} ⟹ ptr = ptr'"
⟨proof⟩

lemma heap_is_wellformed_one_disc_parent:
  "heap_is_wellformed h ⟹ h ⊢ get_disconnected_nodes document_ptr →r disc_nodes ⟹
  h ⊢ get_disconnected_nodes document_ptr' →r disc_nodes' ⟹ set disc_nodes ∩ set disc_nodes' ≠ {}
  ⟹ document_ptr = document_ptr'"
⟨proof⟩

lemma heap_is_wellformed_children_disc_nodes_different:
  "heap_is_wellformed h ⟹ h ⊢ get_child_nodes ptr →r children ⟹
  h ⊢ get_disconnected_nodes document_ptr →r disc_nodes ⟹ set children ∩ set disc_nodes = {}"
⟨proof⟩

lemma heap_is_wellformed_disconnected_nodes_distinct:
  "heap_is_wellformed h ⟹ h ⊢ get_disconnected_nodes document_ptr →r disc_nodes ⟹
  distinct disc_nodes"
⟨proof⟩

lemma heap_is_wellformed_children_distinct:
  "heap_is_wellformed h ⟹ h ⊢ get_child_nodes ptr →r children ⟹ distinct children"
⟨proof⟩

lemma heap_is_wellformed_children_disc_nodes:
  "heap_is_wellformed h ⟹ node_ptr ∉ node_ptr_kinds h ⟹
  ¬(∃parent ∈ fset (object_ptr_kinds h). node_ptr ∈ set |h ⊢ get_child_nodes parent|r) ⟹
  (∃document_ptr ∈ fset (document_ptr_kinds h).
    node_ptr ∈ set |h ⊢ get_disconnected_nodes document_ptr|r)"
⟨proof⟩

lemma parent_child_rel_finite: "heap_is_wellformed h ⟹ finite (parent_child_rel h)"
⟨proof⟩

lemma parent_child_rel_acyclic: "heap_is_wellformed h ⟹ acyclic (parent_child_rel h)"
⟨proof⟩

lemma parent_child_rel_child_in_heap:
  "heap_is_wellformed h ⟹ type_wf h ⟹ known_ptr parent ⟹
  (parent, child_ptr) ∈ parent_child_rel h ⟹ child_ptr ∉ object_ptr_kinds h"
⟨proof⟩

end

interpretation i_heap_is_wellformed?: l_heap_is_wellformedShadow_DOM get_child_nodes
get_child_nodes_locs get_disconnected_nodes get_disconnected_nodes_locs get_shadow_root
get_shadow_root_locs get_tag_name get_tag_name_locs known_ptr type_wf heap_is_wellformed
parent_child_rel heap_is_wellformedCore_DOM get_host get_host_locs get_disconnected_document
get_disconnected_document_locs
⟨proof⟩

declare l_heap_is_wellformedShadow_DOM_axioms [instances]

lemma heap_is_wellformed_is_l_heap_is_wellformed [instances]:
  "l_heap_is_wellformed ShadowRootClass.type_wf ShadowRootClass.known_ptr
  Shadow_DOM.heap_is_wellformed Shadow_DOM.parent_child_rel Shadow_DOM.get_child_nodes
  get_disconnected_nodes"
⟨proof⟩

```

get_parent

```

interpretation i_get_parent_wfCore_DOM: l_get_parent_wfCore_DOM known_ptr type_wf get_child_nodes
  get_child_nodes_locs known_ptrs get_parent get_parent_locs heap_is_wellformedCore_DOM
  parent_child_rel get_disconnected_nodes
  ⟨proof⟩
declare i_get_parent_wfCore_DOM.l_get_parent_wfCore_DOM_axioms[instances]

interpretation i_get_parent_wf2Core_DOM: l_get_parent_wf2Core_DOM known_ptr type_wf get_child_nodes
  get_child_nodes_locs known_ptrs get_parent get_parent_locs heap_is_wellformedCore_DOM
  parent_child_rel get_disconnected_nodes get_disconnected_nodes_locs
  ⟨proof⟩
declare i_get_parent_wf2Core_DOM.l_get_parent_wf2Core_DOM_axioms[instances]

lemma get_parent_wfCore_DOM_is_l_get_parent_wf [instances]: "l_get_parent_wf type_wf known_ptr
  known_ptrs heap_is_wellformedCore_DOM parent_child_rel get_child_nodes get_parent"
  ⟨proof⟩

get_disconnected_nodes
set_disconnected_nodes
get_disconnected_nodes interpretation i_set_disconnected_nodes_get_disconnected_nodes_wfCore_DOM:
  l_set_disconnected_nodes_get_disconnected_nodes_wfCore_DOM known_ptr type_wf
  get_disconnected_nodes get_disconnected_nodes_locs set_disconnected_nodes
  set_disconnected_nodes_locs heap_is_wellformedCore_DOM parent_child_rel get_child_nodes
  ⟨proof⟩
declare i_set_disconnected_nodes_get_disconnected_nodes_wfCore_DOM.l_set_disconnected_nodes_get_disconnected_nodes_wfCore_DOM_axioms[instances]

lemma set_disconnected_nodes_get_disconnected_nodes_wfCore_DOM_is_l_set_disconnected_nodes_get_disconnected_nodes [instances]:
  "l_set_disconnected_nodes_get_disconnected_nodes_wf type_wf known_ptr heap_is_wellformedCore_DOM
  parent_child_rel get_child_nodes get_disconnected_nodes get_disconnected_nodes_locs
  set_disconnected_nodes set_disconnected_nodes_locs"
  ⟨proof⟩

get_root_node interpretation i_get_root_node_wfCore_DOM: l_get_root_node_wfCore_DOM known_ptr type_wf
  known_ptrs
  heap_is_wellformedCore_DOM parent_child_rel get_child_nodes get_child_nodes_locs get_disconnected_nodes
  get_disconnected_nodes_locs get_parent get_parent_locs get_ancestors get_ancestors_locs
  get_root_node get_root_node_locs
  ⟨proof⟩
declare i_get_root_node_wfCore_DOM.l_get_root_node_wfCore_DOM_axioms[instances]

lemma get_ancestors_wfCore_DOM_is_l_get_ancestors_wf [instances]:
  "l_get_ancestors_wf heap_is_wellformedCore_DOM parent_child_rel known_ptr known_ptrs type_wf
  get_ancestors get_ancestors_locs get_child_nodes get_parent"
  ⟨proof⟩

lemma get_root_node_wfCore_DOM_is_l_get_root_node_wf [instances]:
  "l_get_root_node_wf heap_is_wellformedCore_DOM get_root_node type_wf known_ptr known_ptrs
  get_ancestors get_parent"
  ⟨proof⟩

to_tree_order

interpretation i_to_tree_order_wfCore_DOM: l_to_tree_order_wfCore_DOM known_ptr type_wf get_child_nodes
  get_child_nodes_locs to_tree_order known_ptrs get_parent get_parent_locs heap_is_wellformedCore_DOM
  parent_child_rel get_disconnected_nodes get_disconnected_nodes_locs
  ⟨proof⟩
declare i_to_tree_order_wfCore_DOM.l_to_tree_order_wfCore_DOM_axioms [instances]

lemma to_tree_order_wfCore_DOM_is_l_to_tree_order_wf [instances]:
  "l_to_tree_order_wf heap_is_wellformedCore_DOM parent_child_rel type_wf known_ptr known_ptrs
  get_ancestors get_parent"
  ⟨proof⟩

```

```

to_tree_order get_parent get_child_nodes"
⟨proof⟩

get_root_node interpretation i_to_tree_order_wf_get_root_node_wfCore_DOM: l_to_tree_order_wf_get_root_node_wfCore_DOM
  known_ptr type_wf known_ptrs heap_is_wellformedCore_DOM parent_child_rel get_child_nodes
  get_child_nodes_locs get_disconnected_nodes get_disconnected_nodes_locs get_parent get_parent_locs
  get_ancestors get_ancestors_locs get_root_node get_root_node_locs to_tree_order
  ⟨proof⟩
declare i_to_tree_order_wf_get_root_node_wfCore_DOM.l_to_tree_order_wf_get_root_node_wfCore_DOM_axioms
[instances]

lemma to_tree_order_wf_get_root_node_wfCore_DOM_is_l_to_tree_order_wf_get_root_node_wf [instances]:
  "l_to_tree_order_wf_get_root_node_wf type_wf known_ptr known_ptrs to_tree_order get_root_node
   heap_is_wellformedCore_DOM"
  ⟨proof⟩

remove_child

interpretation i_remove_child_wf2Core_DOM: l_remove_child_wf2Core_DOM get_child_nodes get_child_nodes_locs
  set_child_nodes set_child_nodes_locs get_parent
  get_parent_locs get_owner_document get_disconnected_nodes get_disconnected_nodes_locs
  set_disconnected_nodes set_disconnected_nodes_locs remove_child remove_child_locs remove type_wf
  known_ptr known_ptrs heap_is_wellformedCore_DOM parent_child_rel
  ⟨proof⟩
declare i_remove_child_wf2Core_DOM.l_remove_child_wf2Core_DOM_axioms [instances]

lemma remove_child_wf2Core_DOM_is_l_remove_child_wf2 [instances]: "l_remove_child_wf2 type_wf known_ptr
  known_ptrs remove_child heap_is_wellformedCore_DOM get_child_nodes remove"
  ⟨proof⟩

```

2.3.3 A wellformed heap

get_parent

```

interpretation i_get_parent_wf?: l_get_parent_wfCore_DOM known_ptr type_wf get_child_nodes
  get_child_nodes_locs known_ptrs get_parent get_parent_locs heap_is_wellformed parent_child_rel
  get_disconnected_nodes
  ⟨proof⟩
declare l_get_parent_wfCore_DOM_axioms[instances]

lemma get_parent_wf_is_l_get_parent_wf [instances]:
  "l_get_parent_wf ShadowRootClass.type_wf ShadowRootClass.known_ptr ShadowRootClass.known_ptrs
   heap_is_wellformed parent_child_rel Shadow_DOM.get_child_nodes Shadow_DOM.get_parent"
  ⟨proof⟩

```

remove_shadow_root

```

locale l_remove_shadow_root_wfShadow_DOM =
  l_get_tag_name +
  l_get_disconnected_nodes +
  l_set_shadow_root_get_tag_name +
  l_get_child_nodes +
  l_heap_is_wellformedShadow_DOM +
  l_remove_shadow_rootShadow_DOM +
  l_delete_shadow_root_get_disconnected_nodes +
  l_delete_shadow_root_get_child_nodes +
  l_set_shadow_root_get_disconnected_nodes +
  l_set_shadow_root_get_child_nodes +
  l_delete_shadow_root_get_tag_name +
  l_set_shadow_root_get_shadow_root +
  l_delete_shadow_root_get_shadow_root +
  l_get_parentCore_DOM
begin

```

```

lemma remove_shadow_root_preserves:
  assumes "heap_is_wellformed h" and "type_wf h" and "known_ptrs h"
  assumes "h ⊢ remove_shadow_root ptr →h h'"
  shows "known_ptrs h'" and "type_wf h'" "heap_is_wellformed h'"
⟨proof⟩
end

interpretation i_remove_shadow_root_wf?: l_remove_shadow_root_wfShadow_DOM
  type_wf get_tag_name get_tag_name_locs get_disconnected_nodes get_disconnected_nodes_locs
  set_shadow_root set_shadow_root_locs known_ptr get_child_nodes get_child_nodes_locs get_shadow_root
  get_shadow_root_locs heap_is_wellformed parent_child_rel heap_is_wellformedCore_DOM get_host
  get_host_locs get_disconnected_document get_disconnected_document_locs remove_shadow_root
  remove_shadow_root_locs known_ptrs get_parent get_parent_locs
⟨proof⟩
declare l_remove_shadow_root_wfShadow_DOM_axioms [instances]

get_root_node

interpretation i_get_root_node_wf?: l_get_root_node_wfCore_DOM known_ptr type_wf known_ptrs
  heap_is_wellformed parent_child_rel get_child_nodes get_child_nodes_locs get_disconnected_nodes
  get_disconnected_nodes_locs get_parent get_parent_locs get_ancestors get_ancestors_locs
  get_root_node get_root_node_locs
⟨proof⟩
declare l_get_root_node_wfCore_DOM_axioms [instances]

lemma get_ancestors_wf_is_l_get_ancestors_wf [instances]:
  "l_get_ancestors_wf heap_is_wellformed parent_child_rel known_ptr known_ptrs type_wf get_ancestors
  get_ancestors_locs get_child_nodes get_parent"
⟨proof⟩

lemma get_root_node_wf_is_l_get_root_node_wf [instances]:
  "l_get_root_node_wf heap_is_wellformed get_root_node type_wf known_ptr known_ptrs get_ancestors
  get_parent"
⟨proof⟩

get_parent_get_host

locale l_get_parent_get_host_wfShadow_DOM =
  l_heap_is_wellformedShadow_DOM +
  l_get_parent_wf +
  l_get_shadow_root +
  l_get_host +
  l_get_child_nodes
begin

lemma host_shadow_root_rel_finite: "finite (a_host_shadow_root_rel h)"
⟨proof⟩

lemma host_shadow_root_rel_shadow_root:
  "h ⊢ get_shadow_root host →r shadow_root_option ==>
  shadow_root_option = Some shadow_root ↔ ((cast host, cast shadow_root) ∈ a_host_shadow_root_rel h)"
⟨proof⟩

lemma host_shadow_root_rel_host:
  "heap_is_wellformed h ==> h ⊢ get_host shadow_root →r host ==>
  (cast host, cast shadow_root) ∈ a_host_shadow_root_rel h"
⟨proof⟩

lemma heap_wellformed_induct_si [consumes 1, case_names step]:
  assumes "heap_is_wellformed h"
  assumes "¬ parent. (¬ children child. h ⊢ get_child_nodes parent →r children ==>
  child ∈ set children ==> P (cast child)) ==> (¬ shadow_root host. parent = cast host ==>
  h ⊢ get_shadow_root host →r Some shadow_root ==> P (cast shadow_root)) ==> P parent"
  shows "P ptr"

```

(proof)

```

lemma heap_wellformed_induct_rev_si [consumes 1, case_names step]:
assumes "heap_is_wellformed h"
assumes "\child. (\parent child_node. child = cast child_node ==>
h ⊢ get_parent child_node →r Some parent ==> P parent) ==>
(＼host shadow_root. child = cast shadow_root ==> h ⊢ get_host shadow_root →r host ==>
P (cast host)) ==> P child"
shows "P ptr"
(proof)
end

interpretation i_get_parent_get_host_wf?: l_get_parent_get_host_wfShadow_DOM
get_child_nodes get_child_nodes_locs get_disconnected_nodes get_disconnected_nodes_locs
get_shadow_root get_shadow_root_locs get_tag_name get_tag_name_locs known_ptr type_wf
heap_is_wellformed parent_child_rel heap_is_wellformedCore_DOM get_host get_host_locs
get_disconnected_document get_disconnected_document_locs known_ptrs get_parent get_parent_locs
(proof)
declare l_get_parent_get_host_wfShadow_DOM_axioms [instances]

locale l_get_parent_get_host_wf =
l_heap_is_wellformed_defs +
l_get_parent_defs +
l_get_shadow_root_defs +
l_get_host_defs +
l_get_child_nodes_defs +
assumes heap_wellformed_induct_si [consumes 1, case_names step]:
"heap_is_wellformed h
==> (\parent. (\children child. h ⊢ get_child_nodes parent →r children ==> child ∈ set children
==> P (cast child))
==> (\shadow_root host. parent = cast host ==> h ⊢ get_shadow_root host →r Some shadow_root
==> P (cast shadow_root))
==> P parent)
==> P ptr"
assumes heap_wellformed_induct_rev_si [consumes 1, case_names step]:
"heap_is_wellformed h
==> (\child. (\parent child_node. child = cast child_node ==>
h ⊢ get_parent child_node →r Some parent ==> P parent)
==> (\host shadow_root. child = cast shadow_root ==> h ⊢ get_host shadow_root →r host
==> P (cast host))
==> P child)
==> P ptr"

lemma l_get_parent_get_host_wf_is_get_parent_get_host_wf [instances]:
"l_get_parent_get_host_wf heap_is_wellformed get_parent get_shadow_root get_host get_child_nodes"
(proof)

```

get_host

```

locale l_get_host_wfShadow_DOM =
l_heap_is_wellformedShadow_DOM get_child_nodes get_child_nodes_locs get_disconnected_nodes
get_disconnected_nodes_locs get_shadow_root get_shadow_root_locs get_tag_name get_tag_name_locs
known_ptr type_wf heap_is_wellformed parent_child_rel heap_is_wellformedCore_DOM get_host
get_host_locs +
l_type_wf type_wf +
l_get_hostShadow_DOM get_shadow_root get_shadow_root_locs get_host get_host_locs type_wf +
l_get_shadow_root type_wf get_shadow_root get_shadow_root_locs
for known_ptr :: "(_ : linorder) object_ptr ⇒ bool"
and known_ptrs :: "(_) heap ⇒ bool"
and type_wf :: "(_) heap ⇒ bool"
and get_host :: "(_) shadow_root_ptr ⇒ ((_) heap, exception, (_) element_ptr) prog"
and get_host_locs :: "((_) heap ⇒ (_ heap ⇒ bool) set"

```

```

and get_shadow_root :: "(_ element_ptr ⇒ ((_) heap, exception, (_ shadow_root_ptr option) prog"
and get_shadow_root_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ bool) set"
and get_child_nodes :: "(_ :linorder) object_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
and get_child_nodes_locs :: "(_ object_ptr ⇒ ((_) heap ⇒ bool) set"
and get_disconnected_nodes :: "(_ document_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
and get_disconnected_nodes_locs :: "(_ document_ptr ⇒ ((_) heap ⇒ bool) set"
and get_tag_name :: "(_ element_ptr ⇒ ((_) heap, exception, char list) prog"
and get_tag_name_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ bool) set"
and heap_is_wellformed :: "(_ heap ⇒ bool"
and parent_child_rel :: "(_ heap ⇒ ((_) object_ptr × (_ object_ptr) set"
and heap_is_wellformedCore_DOM :: "(_ heap ⇒ bool"

begin

lemma get_host_ok [simp]:
assumes "heap_is_wellformed h"
assumes "type_wf h"
assumes "known_ptrs h"
assumes "shadow_root_ptr ∉ shadow_root_ptr_kinds h"
shows "h ⊢ ok (get_host shadow_root_ptr)"
⟨proof⟩
end

interpretation i_get_host_wf?: l_get_host_wfShadow_DOM get_disconnected_document
get_disconnected_document_locs known_ptr known_ptrs type_wf get_host get_host_locs get_shadow_root
get_shadow_root_locs get_child_nodes get_child_nodes_locs get_disconnected_nodes
get_disconnected_nodes_locs get_tag_name get_tag_name_locs heap_is_wellformed parent_child_rel
heap_is_wellformedCore_DOM
⟨proof⟩
declare l_get_host_wfShadow_DOM_axioms [instances]

locale l_get_host_wf = l_heap_is_wellformed_defs + l_known_ptrs + l_type_wf + l_get_host_defs +
assumes get_host_ok:
"heap_is_wellformed h ⟹ known_ptrs h ⟹ type_wf h ⟹
shadow_root_ptr ∉ shadow_root_ptr_kinds h ⟹ h ⊢ ok (get_host shadow_root_ptr)"

lemma get_host_wf_is_l_get_host_wf [instances]:
"l_get_host_wf heap_is_wellformed known_ptr known_ptrs type_wf get_host"
⟨proof⟩

get_root_node_si

locale l_get_root_node_si_wfShadow_DOM =
l_get_root_node_siShadow_DOM +
l_heap_is_wellformedShadow_DOM +
l_get_parent_wf +
l_get_parent_get_host_wf +
l_get_host_wf

begin
lemma get_root_node_si_ptr_in_heap:
assumes "h ⊢ ok (get_root_node_si ptr)"
shows "ptr ∉ object_ptr_kinds h"
⟨proof⟩

lemma get_ancestors_si_ok:
assumes "heap_is_wellformed h" and "known_ptrs h" and "type_wf h"
and "ptr ∉ object_ptr_kinds h"
shows "h ⊢ ok (get_ancestors_si ptr)"
⟨proof⟩

lemma get_ancestors_si_remains_not_in_ancestors:
assumes "heap_is_wellformed h"
and "heap_is_wellformed h'"

```

```

and "h ⊢ get_ancestors_si ptr →r ancestors"
and "h' ⊢ get_ancestors_si ptr →r ancestors''"
and "¬p children children'. h ⊢ get_child_nodes p →r children
    ⇒ h' ⊢ get_child_nodes p →r children' ⇒ set children' ⊆ set children"
and "¬p shadow_root_option shadow_root_option'. h ⊢ get_shadow_root p →r shadow_root_option ⇒
    h' ⊢ get_shadow_root p →r shadow_root_option' ⇒ (if shadow_root_option = None
        then shadow_root_option' = None else shadow_root_option' = shadow_root_option)"
and "node ∉ set ancestors"
and object_ptr_kinds_eq3: "object_ptr_kinds h = object_ptr_kinds h''"
and known_ptrs: "known_ptrs h"
and type_wf: "type_wf h"
and type_wf': "type_wf h''"
shows "node ∉ set ancestors"
⟨proof⟩

lemma get_ancestors_si_ptrs_in_heap:
assumes "heap_is_wellformed h" and "type_wf h" and "known_ptrs h"
assumes "h ⊢ get_ancestors_si ptr →r ancestors"
assumes "ptr' ∈ set ancestors"
shows "ptr' ∉ object_ptr_kinds h"
⟨proof⟩

lemma get_ancestors_si_reads:
assumes "heap_is_wellformed h"
shows "reads get_ancestors_si_locs (get_ancestors_si node_ptr) h h''"
⟨proof⟩

lemma get_ancestors_si_subset:
assumes "heap_is_wellformed h"
and "h ⊢ get_ancestors_si ptr →r ancestors"
and "ancestor ∈ set ancestors"
and "h ⊢ get_ancestors_si ancestor →r ancestor_ancestors"
and type_wf: "type_wf h"
and known_ptrs: "known_ptrs h"
shows "set ancestor_ancestors ⊆ set ancestors"
⟨proof⟩

lemma get_ancestors_si_also_parent:
assumes "heap_is_wellformed h"
and "h ⊢ get_ancestors_si some_ptr →r ancestors"
and "cast child ∈ set ancestors"
and "h ⊢ get_parent child →r Some parent"
and type_wf: "type_wf h"
and known_ptrs: "known_ptrs h"
shows "parent ∈ set ancestors"
⟨proof⟩

lemma get_ancestors_si_also_host:
assumes "heap_is_wellformed h"
and "h ⊢ get_ancestors_si some_ptr →r ancestors"
and "cast shadow_root ∈ set ancestors"
and "h ⊢ get_host shadow_root →r host"
and type_wf: "type_wf h"
and known_ptrs: "known_ptrs h"
shows "cast host ∈ set ancestors"
⟨proof⟩

lemma get_ancestors_si_parent_child_rel:
assumes "heap_is_wellformed h" and "known_ptrs h" and "type_wf h"
assumes "h ⊢ get_ancestors_si child →r ancestors"

```

```

assumes "((ptr, child) ∈ (parent_child_rel h)*)"
shows "ptr ∈ set ancestors"
⟨proof⟩

lemma get_ancestors_si_parent_child_host_shadow_root_rel:
  assumes "heap_is_wellformed h" and "known_ptrs h" and "type_wf h"
  assumes "h ⊢ get_ancestors_si child →r ancestors"
  assumes "((ptr, child) ∈ (parent_child_rel h ∪ a_host_shadow_root_rel h)*)"
  shows "ptr ∈ set ancestors"
⟨proof⟩

lemma get_root_node_si_ok:
  assumes "heap_is_wellformed h" and "known_ptrs h" and "type_wf h"
  and "ptr /∈ object_ptr_kinds h"
  shows "h ⊢ ok (get_root_node_si ptr)"
⟨proof⟩

lemma get_root_node_si_root_in_heap:
  assumes "heap_is_wellformed h" and "type_wf h" and "known_ptrs h"
  assumes "h ⊢ get_root_node_si ptr →r root"
  shows "root /∈ object_ptr_kinds h"
⟨proof⟩

lemma get_root_node_si_same_no_parent:
  assumes "heap_is_wellformed h" and "type_wf h" and "known_ptrs h"
  assumes "h ⊢ get_root_node_si ptr →r cast child"
  shows "h ⊢ get_parent child →r None"
⟨proof⟩
end

interpretation i_get_root_node_si_wf?: l_get_root_node_si_wfShadow_DOM type_wf known_ptr known_ptrs
  get_parent get_parent_locs get_child_nodes get_child_nodes_locs get_host get_host_locs
  get_ancestors_si get_ancestors_si_locs get_root_node_si get_root_node_si_locs
  get_disconnected_nodes get_disconnected_nodes_locs get_shadow_root get_shadow_root_locs
  get_tag_name get_tag_name_locs heap_is_wellformed parent_child_rel heap_is_wellformedCore_DOM
  get_disconnected_document get_disconnected_document_locs
⟨proof⟩
declare l_get_root_node_si_wfShadow_DOM_axioms [instances]

get_disconnected_document

locale l_get_disconnected_document_wfShadow_DOM =
  l_heap_is_wellformedShadow_DOM +
  l_get_disconnected_documentCore_DOM +
  l_get_parent_wf +
  l_get_parent
begin

lemma get_disconnected_document_ok:
  assumes "heap_is_wellformed h" and "type_wf h" and "known_ptrs h"
  assumes "h ⊢ get_parent node_ptr →r None"
  shows "h ⊢ ok (get_disconnected_document node_ptr)"
⟨proof⟩
end

interpretation i_get_disconnected_document_wf?: l_get_disconnected_document_wfShadow_DOM
  get_child_nodes get_child_nodes_locs get_disconnected_nodes get_disconnected_nodes_locs
  get_shadow_root get_shadow_root_locs get_tag_name get_tag_name_locs known_ptr type_wf
  heap_is_wellformed parent_child_rel heap_is_wellformedCore_DOM get_host get_host_locs
  get_disconnected_document get_disconnected_document_locs known_ptrs get_parent get_parent_locs
⟨proof⟩
declare l_get_disconnected_document_wfShadow_DOM_axioms [instances]

```

get_owner_document

```

locale l_get_owner_document_wfShadow_DOM =
l_get_disconnected_nodes +
l_get_child_nodes +
l_get_owner_documentShadow_DOM +
l_heap_is_wellformedShadow_DOM +
l_get_parent_wf +
l_known_ptrs +
l_get_root_node_si_wfShadow_DOM +
l_get_parentCore_DOM +
assumes known_ptr_impl: "known_ptr = ShadowRootClass.known_ptr"
begin
lemma get_owner_document_disconnected_nodes:
assumes "heap_is_wellformed h"
assumes "h ⊢ get_disconnected_nodes document_ptr →r disc_nodes"
assumes "node_ptr ∈ set disc_nodes"
assumes known_ptrs: "known_ptrs h"
assumes type_wf: "type_wf h"
shows "h ⊢ get_owner_document (cast node_ptr) →r document_ptr"
⟨proof⟩

lemma in_disconnected_nodes_no_parent:
assumes "heap_is_wellformed h"
assumes "h ⊢ get_parent node_ptr →r None"
assumes "h ⊢ get_owner_document (cast node_ptr) →r owner_document"
assumes "h ⊢ get_disconnected_nodes owner_document →r disc_nodes"
assumes "known_ptrs h"
assumes "type_wf h"
shows "node_ptr ∈ set disc_nodes"
⟨proof⟩

lemma get_owner_document_owner_document_in_heap_node:
assumes "heap_is_wellformed h" and "type_wf h" and "known_ptrs h"
assumes "h ⊢ CD.a_get_owner_documentnode_ptr node_ptr () →r owner_document"
shows "owner_document /∈ document_ptr_kinds h"
⟨proof⟩

lemma get_owner_document_owner_document_in_heap:
assumes "heap_is_wellformed h" and "type_wf h" and "known_ptrs h"
assumes "h ⊢ get_owner_document ptr →r owner_document"
shows "owner_document /∈ document_ptr_kinds h"
⟨proof⟩

lemma get_owner_document_ok:
assumes "heap_is_wellformed h" "known_ptrs h" "type_wf h"
assumes "ptr /∈ object_ptr_kinds h"
shows "h ⊢ ok (get_owner_document ptr)"
⟨proof⟩
end
interpretation i_get_owner_document_wf?: l_get_owner_document_wfShadow_DOM
type_wf get_disconnected_nodes get_disconnected_nodes_locs known_ptr
get_child_nodes get_child_nodes_locs DocumentClass.known_ptr get_parent get_parent_locs
get_root_node_si get_root_node_si_locs CD.a_get_owner_document get_host get_host_locs
get_owner_document get_shadow_root get_shadow_root_locs get_tag_name get_tag_name_locs
heap_is_wellformed parent_child_rel heap_is_wellformedCore_DOM get_disconnected_document
get_disconnected_document_locs known_ptrs get_ancestors_si get_ancestors_si_locs
⟨proof⟩
declare l_get_owner_document_wfShadow_DOM_axioms [instances]

lemma get_owner_document_wf_is_l_get_owner_document_wf [instances]: "l_get_owner_document_wf

```

```

heap_is_wellformed type_wf known_ptr known_ptrs get_disconnected_nodes get_owner_document
get_parent"
⟨proof⟩

remove_child

locale l_remove_child_wf2Shadow_DOM =
l_set_disconnected_nodes_get_disconnected_nodes +
l_get_child_nodes +
l_heap_is_wellformedShadow_DOM +
l_get_owner_document_wfShadow_DOM +
l_remove_childCore_DOM +
l_set_child_nodes_get_shadow_root +
l_set_disconnected_nodes_get_shadow_root +
l_set_child_nodes_get_tag_name +
l_set_disconnected_nodes_get_tag_name +
CD: l_remove_child_wf2Core_DOM ----- heap_is_wellformedCore_DOM
begin
lemma remove_child_preserves_type_wf:
assumes "heap_is_wellformed h" and "type_wf h" and "known_ptrs h"
assumes "h ⊢ remove_child ptr child →_h h'"
shows "type_wf h'"
⟨proof⟩

lemma remove_child_preserves_known_ptrs:
assumes "heap_is_wellformed h" and "type_wf h" and "known_ptrs h"
assumes "h ⊢ remove_child ptr child →_h h'"
shows "known_ptrs h'"
⟨proof⟩

lemma remove_child_heap_is_wellformed_preserved:
assumes "heap_is_wellformed h" and "type_wf h" and "known_ptrs h"
assumes "h ⊢ remove_child ptr child →_h h'"
shows "heap_is_wellformed h'"
⟨proof⟩

lemma remove_preserves_type_wf:
assumes "heap_is_wellformed h" and "type_wf h" and "known_ptrs h"
assumes "h ⊢ remove child →_h h'"
shows "type_wf h'"
⟨proof⟩

lemma remove_preserves_known_ptrs:
assumes "heap_is_wellformed h" and "type_wf h" and "known_ptrs h"
assumes "h ⊢ remove child →_h h'"
shows "known_ptrs h'"
⟨proof⟩

lemma remove_heap_is_wellformed_preserved:
assumes "heap_is_wellformed h" and "type_wf h" and "known_ptrs h"
assumes "h ⊢ remove child →_h h'"
shows "heap_is_wellformed h'"
⟨proof⟩

lemma remove_child_removes_child:
"heap_is_wellformed h ⇒ h ⊢ remove_child ptr' child →_h h'
⇒ h' ⊢ get_child_nodes ptr →_r children
⇒ known_ptrs h ⇒ type_wf h
⇒ child ∉ set children"
⟨proof⟩
lemma remove_child_removes_first_child: "heap_is_wellformed h ⇒ type_wf h ⇒ known_ptrs h ⇒

```

```

h ⊢ get_child_nodes ptr →r node_ptr # children ⇒ h ⊢ remove_child ptr node_ptr →h h' ⇒
h' ⊢ get_child_nodes ptr →r children"
⟨proof⟩
lemma remove_removes_child: "heap_is_wellformed h ⇒ type_wf h ⇒ known_ptrs h ⇒
h ⊢ get_child_nodes ptr →r node_ptr # children ⇒ h ⊢ remove node_ptr →h h' ⇒
h' ⊢ get_child_nodes ptr →r children"
⟨proof⟩
lemma remove_for_all_empty_children: "heap_is_wellformed h ⇒ type_wf h ⇒ known_ptrs h ⇒
h ⊢ get_child_nodes ptr →r children ⇒ h ⊢ forall_M remove children →h h' ⇒
h' ⊢ get_child_nodes ptr →r []"
⟨proof⟩
end

interpretation i_remove_child_wf2?: l_remove_child_wf2Shadow_DOM
type_wf get_disconnected_nodes get_disconnected_nodes_locs set_disconnected_nodes
set_disconnected_nodes_locs known_ptr get_child_nodes get_child_nodes_locs get_shadow_root
get_shadow_root_locs get_tag_name get_tag_name_locs heap_is_wellformed parent_child_rel
heap_is_wellformedCore_DOM get_host get_host_locs get_disconnected_document
get_disconnected_document_locs DocumentClass.known_ptr get_parent get_parent_locs get_root_node_si
get_root_node_si_locs CD.a_get_owner_document get_owner_document known_ptrs get_ancestors_si
get_ancestors_si_locs set_child_nodes set_child_nodes_locs remove_child remove_child_locs remove
⟨proof⟩
declare l_remove_child_wf2Shadow_DOM_axioms [instances]

lemma remove_child_wf2_is_l_remove_child_wf2 [instances]:
"l_remove_child_wf2 type_wf known_ptr known_ptrs remove_child heap_is_wellformed get_child_nodes remove"
⟨proof⟩

adopt_node

locale l_adopt_node_wf2Shadow_DOM =
l_get_child_nodes +
l_get_disconnected_nodes +
l_set_child_nodes_get_shadow_root +
l_set_disconnected_nodes_get_shadow_root +
l_set_child_nodes_get_tag_name +
l_set_disconnected_nodes_get_tag_name +
l_heap_is_wellformedShadow_DOM +
l_get_root_node +
l_set_disconnected_nodes_get_child_nodes +
l_get_owner_document_wf +
l_remove_child_wf2 +
l_adopt_node_wfCore_DOM +
l_adopt_nodeCore_DOM +
l_get_parent_wfCore_DOM
begin

lemma adopt_node_removes_child:
assumes wellformed: "heap_is_wellformed h"
and adopt_node: "h ⊢ adopt_node owner_document node_ptr →h h2"
and children: "h2 ⊢ get_child_nodes ptr →r children"
and known_ptrs: "known_ptrs h"
and type_wf: "type_wf h"
shows "node_ptr ∉ set children"
⟨proof⟩

lemma adopt_node_preserves_wellformedness:
assumes "heap_is_wellformed h"
and "h ⊢ adopt_node document_ptr child →h h'"
and known_ptrs: "known_ptrs h"
and type_wf: "type_wf h"
shows "heap_is_wellformed h'" and "known_ptrs h'" and "type_wf h'"
⟨proof⟩

```

```

lemma adopt_node_node_in_disconnected_nodes:
  assumes wellformed: "heap_is_wellformed h"
    and adopt_node: "h ⊢ adopt_node owner_document node_ptr →_h h'"
    and "h' ⊢ get_disconnected_nodes owner_document →_r disc_nodes"
    and known_ptrs: "known_ptrs h"
    and type_wf: "type_wf h"
  shows "node_ptr ∈ set disc_nodes"
⟨proof⟩
end

interpretation l_adopt_node_wfCore_DOM Shadow_DOM.get_owner_document Shadow_DOM.get_parent
  Shadow_DOM.get_parent_locs Shadow_DOM.remove_child Shadow_DOM.remove_child_locs
  get_disconnected_nodes get_disconnected_nodes_locs
  set_disconnected_nodes set_disconnected_nodes_locs Shadow_DOM.adopt_node Shadow_DOM.adopt_node_locs
  ShadowRootClass.known_ptr ShadowRootClass.type_wf Shadow_DOM.get_child_nodes
  Shadow_DOM.get_child_nodes_locs
  ShadowRootClass.known_ptrs Shadow_DOM.set_child_nodes Shadow_DOM.set_child_nodes_locs
  Shadow_DOM.remove Shadow_DOM.heap_is_wellformed Shadow_DOM.parent_child_rel
⟨proof⟩
declare l_adopt_node_wfCore_DOM_axioms [instances]

interpretation i_adopt_node_wf2?: l_adopt_node_wf2Shadow_DOM
  type_wf known_ptr get_child_nodes get_child_nodes_locs get_disconnected_nodes
  get_disconnected_nodes_locs set_child_nodes set_child_nodes_locs get_shadow_root get_shadow_root_locs
  set_disconnected_nodes set_disconnected_nodes_locs get_tag_name get_tag_name_locs heap_is_wellformed
  parent_child_rel heap_is_wellformedCore_DOM get_host get_host_locs get_disconnected_document
  get_disconnected_document_locs get_root_node get_root_node_locs get_parent get_parent_locs known_ptrs
  get_owner_document remove_child remove_child_locs remove adopt_node adopt_node_locs
⟨proof⟩
declare l_adopt_node_wf2Shadow_DOM_axioms [instances]

lemma adopt_node_wf_is_l_adopt_node_wf [instances]:
  "l_adopt_node_wf type_wf known_ptr heap_is_wellformed parent_child_rel get_child_nodes
  get_disconnected_nodes known_ptrs adopt_node"
⟨proof⟩

insert_before

locale l_insert_before_wf2Shadow_DOM =
  l_get_child_nodes +
  l_get_disconnected_nodes +
  l_set_child_nodes_get_shadow_root +
  l_set_disconnected_nodes_get_shadow_root +
  l_set_child_nodes_get_tag_name +
  l_set_disconnected_nodes_get_tag_name +
  l_set_disconnected_nodes_get_disconnected_nodes +
  l_set_child_nodes_get_disconnected_nodes +
  l_set_disconnected_nodes_get_disconnected_nodes_wf +
  l_set_disconnected_nodes_get_ancestors_si +
  l_insert_beforeCore_DOM _ _ _ _ _ get_ancestors_si get_ancestors_si_locs +
  l_get_root_node_si_wfShadow_DOM +
  l_get_owner_document +
  l_adopt_node +
  l_adopt_node_wf +
  l_heap_is_wellformedShadow_DOM +
  l_adopt_node_get_shadow_root

begin
lemma insert_before_child_preserves:
  assumes "heap_is_wellformed h" and "type_wf h" and "known_ptrs h"
  assumes "h ⊢ insert_before ptr node child →_h h'"

```

```

shows "type_wf h'" and "known_ptrs h'" and "heap_is_wellformed h'"
⟨proof⟩
end

interpretation i_insert_before_wf?: l_insert_before_wfCore_DOM get_parent get_parent_locs
get_child_nodes get_child_nodes_locs set_child_nodes set_child_nodes_locs get_ancestors_si
get_ancestors_si_locs adopt_node adopt_node_locs set_disconnected_nodes set_disconnected_nodes_locs
get_disconnected_nodes get_disconnected_nodes_locs get_owner_document insert_before
insert_before_locs append_child type_wf known_ptr known_ptrs heap_is_wellformed parent_child_rel
⟨proof⟩
declare l_insert_before_wfCore_DOM_axioms [instances]

lemma insert_before_wf_is_l_insert_before_wf [instances]:
  "l_insert_before_wf Shadow_DOM.heap_is_wellformed ShadowRootClass.type_wf
ShadowRootClass.known_ptr ShadowRootClass.known_ptrs
  Shadow_DOM.insert_before Shadow_DOM.get_child_nodes"
⟨proof⟩

lemma l_set_disconnected_nodes_get_disconnected_nodes_wf [instances]: "l_set_disconnected_nodes_get_disconnected_
ShadowRootClass.type_wf
ShadowRootClass.known_ptr Shadow_DOM.heap_is_wellformed Shadow_DOM.parent_child_rel Shadow_DOM.get_child_nodes
  get_disconnected_nodes get_disconnected_nodes_locs set_disconnected_nodes set_disconnected_nodes_locs"
⟨proof⟩

interpretation l_get_root_node_si_wfShadow_DOM
type_wf known_ptr known_ptrs get_parent get_parent_locs get_child_nodes get_child_nodes_locs
get_host get_host_locs get_ancestors_si get_ancestors_si_locs get_root_node_si get_root_node_si_locs
get_disconnected_nodes get_disconnected_nodes_locs get_shadow_root get_shadow_root_locs
get_tag_name get_tag_name_locs heap_is_wellformed parent_child_rel heap_is_wellformedCore_DOM
get_disconnected_document get_disconnected_document_locs
⟨proof⟩
declare l_get_root_node_si_wfShadow_DOM_axioms [instances]

interpretation i_insert_before_wf2?: l_insert_before_wf2Shadow_DOM type_wf known_ptr get_child_nodes
get_child_nodes_locs get_disconnected_nodes get_disconnected_nodes_locs set_child_nodes set_child_nodes_locs
get_shadow_root get_shadow_root_locs set_disconnected_nodes set_disconnected_nodes_locs get_tag_name get_tag_name
heap_is_wellformed parent_child_rel get_ancestors_si get_ancestors_si_locs get_parent get_parent_locs adopt_node
adopt_node_locs get_owner_document insert_before insert_before_locs append_child known_ptrs get_host get_host_locs
get_root_node_si get_root_node_si_locs heap_is_wellformedCore_DOM get_disconnected_document get_disconnected_document
⟨proof⟩
declare l_insert_before_wf2Shadow_DOM_axioms [instances]

lemma insert_before_wf2_is_l_insert_before_wf2 [instances]:
  "l_insert_before_wf2 ShadowRootClass.type_wf ShadowRootClass.known_ptr ShadowRootClass.known_ptrs
Shadow_DOM.insert_before
  Shadow_DOM.heap_is_wellformed"
⟨proof⟩

append_child

interpretation i_append_child_wf?: l_append_child_wfCore_DOM get_owner_document get_parent
get_parent_locs remove_child remove_child_locs
get_disconnected_nodes get_disconnected_nodes_locs
set_disconnected_nodes set_disconnected_nodes_locs
adopt_node adopt_node_locs known_ptr type_wf get_child_nodes
get_child_nodes_locs known_ptrs set_child_nodes
set_child_nodes_locs remove get_ancestors_si get_ancestors_si_locs
insert_before insert_before_locs append_child heap_is_wellformed
parent_child_rel
⟨proof⟩
declare l_append_child_wfCore_DOM_axioms [instances]

```

```

lemma append_child_wf_is_l_append_child_wf [instances]:
  "l_append_child_wf type_wf known_ptr known_ptrs append_child heap_is_wellformed"
  ⟨proof⟩

to_tree_order

interpretation i_to_tree_order_wf?: l_to_tree_order_wfCore_DOM known_ptr type_wf get_child_nodes
  get_child_nodes_locs to_tree_order known_ptrs get_parent get_parent_locs heap_is_wellformed
  parent_child_rel get_disconnected_nodes get_disconnected_nodes_locs
  ⟨proof⟩
declare l_to_tree_order_wfCore_DOM_axioms [instances]

lemma to_tree_order_wf_is_l_to_tree_order_wf [instances]:
  "l_to_tree_order_wf heap_is_wellformed parent_child_rel type_wf known_ptr known_ptrs
  to_tree_order get_parent get_child_nodes"
  ⟨proof⟩

get_root_node interpretation i_to_tree_order_wf_get_root_node_wf?: l_to_tree_order_wf_get_root_node_wfCore_DOM
  known_ptr type_wf known_ptrs heap_is_wellformed parent_child_rel
  get_child_nodes get_child_nodes_locs get_disconnected_nodes get_disconnected_nodes_locs
  get_parent get_parent_locs get_ancestors get_ancestors_locs get_root_node get_root_node_locs
  to_tree_order
  ⟨proof⟩
declare l_to_tree_order_wf_get_root_node_wfCore_DOM_axioms [instances]

lemma to_tree_order_wf_get_root_node_wf_is_l_to_tree_order_wf_get_root_node_wf [instances]:
  "l_to_tree_order_wf_get_root_node_wf ShadowRootClass.type_wf ShadowRootClass.known_ptr
  ShadowRootClass.known_ptrs to_tree_order Shadow_DOM.get_root_node
  Shadow_DOM.heap_is_wellformed"
  ⟨proof⟩

to_tree_order_si

locale l_to_tree_order_si_wfShadow_DOM =
  l_get_child_nodes +
  l_get_parent_get_host_wfShadow_DOM +
  l_to_tree_order_siShadow_DOM
begin
lemma to_tree_order_si_ok:
  assumes "heap_is_wellformed h" and "known_ptrs h" and "type_wf h"
  and "ptr /∈ object_ptr_kinds h"
  shows "h ⊢ ok (to_tree_order_si ptr)"
  ⟨proof⟩
end

interpretation i_to_tree_order_si_wf?: l_to_tree_order_si_wfShadow_DOM
  type_wf known_ptr get_child_nodes get_child_nodes_locs get_disconnected_nodes
  get_disconnected_nodes_locs get_shadow_root get_shadow_root_locs get_tag_name
  get_tag_name_locs heap_is_wellformed parent_child_rel heap_is_wellformedCore_DOM
  get_host get_host_locs get_disconnected_document get_disconnected_document_locs
  known_ptrs get_parent get_parent_locs to_tree_order_si
  ⟨proof⟩
declare l_to_tree_order_si_wfShadow_DOM_axioms [instances]

get_assigned_nodes

lemma forall_M_small_big: "h ⊢ forall_M f xs →h h' ⇒ P h ⇒
  (¬ h h' x. x ∈ set xs ⇒ h ⊢ f x →h h' ⇒ P h ⇒ P h') ⇒ P h'"
  ⟨proof⟩

locale l_assigned_nodes_wfShadow_DOM =
  l_assigned_nodesShadow_DOM +
  l_heap_is_wellformed +

```

```

l_remove_child_wf2 +
l_append_child_wf +
l_remove_shadow_root_wfShadow_DOM
begin

lemma assigned_nodes_distinct:
  assumes "heap_is_wellformed h"
  assumes "h ⊢ assigned_nodes slot →r nodes"
  shows "distinct nodes"
⟨proof⟩

lemma flatten_dom_preserves:
  assumes "heap_is_wellformed h" and "known_ptrs h" and "type_wf h"
  assumes "h ⊢ flatten_dom →h h'"
  shows "heap_is_wellformed h'" and "known_ptrs h'" and "type_wf h'"
⟨proof⟩
end

interpretation i_assigned_nodes_wf?: l_assigned_nodes_wfShadow_DOM
  known_ptr assigned_nodes assigned_nodes_flatten flatten_dom get_child_nodes get_child_nodes_locs
  get_tag_name get_tag_name_locs get_root_node get_root_node_locs get_host get_host_locs find_slot
  assigned_slot remove insert_before insert_before_locs append_child remove_shadow_root
  remove_shadow_root_locs type_wf get_shadow_root get_shadow_root_locs set_shadow_root
  set_shadow_root_locs get_parent get_parent_locs to_tree_order heap_is_wellformed parent_child_rel
  get_disconnected_nodes get_disconnected_nodes_locs known_ptrs remove_child remove_child_locs
  heap_is_wellformedCore_DOM get_disconnected_document get_disconnected_document_locs
⟨proof⟩
declare l_assigned_nodes_wfShadow_DOM_axioms [instances]

get_shadow_root_safe

locale l_get_shadow_root_safe_wfShadow_DOM =
  l_heap_is_wellformedShadow_DOM get_child_nodes get_child_nodes_locs get_disconnected_nodes
  get_disconnected_nodes_locs get_shadow_root get_shadow_root_locs get_tag_name get_tag_name_locs
  known_ptr type_wf heap_is_wellformed parent_child_rel heap_is_wellformedCore_DOM get_host
  get_host_locs +
  l_type_wf type_wf +
  l_get_shadow_root_safeShadow_DOM type_wf get_shadow_root_safe get_shadow_root_safe_locs
  get_shadow_root get_shadow_root_locs get_mode get_mode_locs
  for known_ptr :: "(_ : linorder) object_ptr ⇒ bool"
    and known_ptrs :: "(_ heap ⇒ bool"
    and type_wf :: "(_ heap ⇒ bool"
    and get_host :: "(_ shadow_root_ptr ⇒ ((_) heap, exception, (_ element_ptr) prog"
    and get_host_locs :: "((_) heap ⇒ (_ heap ⇒ bool) set"
    and get_shadow_root :: "
      (" element_ptr ⇒ ((_) heap, exception, (_ shadow_root_ptr option) prog"
      and get_shadow_root_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
      and get_shadow_root_safe :: "
        (" element_ptr ⇒ ((_) heap, exception, (_ shadow_root_ptr option) prog"
        and get_shadow_root_safe_locs :: "
          (" element_ptr ⇒ (_ shadow_root_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
          and get_child_nodes :: "(_ : linorder) object_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
          and get_child_nodes_locs :: "(_ object_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
          and get_disconnected_nodes :: "(_ document_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
          and get_disconnected_nodes_locs :: "(_ document_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
          and get_tag_name :: "(_ element_ptr ⇒ ((_) heap, exception, char list) prog"
          and get_tag_name_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"
          and heap_is_wellformed :: "(_ heap ⇒ bool"
          and parent_child_rel :: "(_ heap ⇒ ((_) object_ptr × (_ object_ptr) set"
          and heap_is_wellformedCore_DOM :: "(_ heap ⇒ bool"
          and get_mode :: "(_ shadow_root_ptr ⇒ ((_) heap, exception, shadow_root_mode) prog"
          and get_mode_locs :: "(_ shadow_root_ptr ⇒ ((_) heap ⇒ (_ heap ⇒ bool) set"

```

```

begin

end

create_element

locale l_create_element_wfShadow_DOM =
  l_get_disconnected_nodes type_wf get_disconnected_nodes get_disconnected_nodes_locs +
  l_set_tag_name type_wf set_tag_name set_tag_name_locs +
  l_create_element_defs create_element +
  l_heap_is_wellformedShadow_DOM get_child_nodes get_child_nodes_locs get_disconnected_nodes
  get_disconnected_nodes_locs
  get_shadow_root get_shadow_root_locs get_tag_name get_tag_name_locs known_ptr type_wf
  heap_is_wellformed parent_child_rel
  heap_is_wellformedCore_DOM get_host get_host_locs get_disconnected_document
  get_disconnected_document_locs +
  l_new_element_get_disconnected_nodes get_disconnected_nodes get_disconnected_nodes_locs +
  l_set_tag_name_get_disconnected_nodes type_wf set_tag_name set_tag_name_locs
  get_disconnected_nodes get_disconnected_nodes_locs +
  l_create_elementShadow_DOM get_disconnected_nodes get_disconnected_nodes_locs set_disconnected_nodes
  set_disconnected_nodes_locs set_tag_name set_tag_name_locs type_wf create_element known_ptr
  type_wfCore_DOM known_ptrCore_DOM +
  l_new_element_get_child_nodes type_wf known_ptr get_child_nodes get_child_nodes_locs +
  l_set_tag_name_get_child_nodes type_wf set_tag_name set_tag_name_locs known_ptr
  get_child_nodes get_child_nodes_locs +
  l_set_tag_name_get_tag_name type_wf get_tag_name get_tag_name_locs set_tag_name set_tag_name_locs +
  l_new_element_get_tag_name type_wf get_tag_name get_tag_name_locs +
  l_set_disconnected_nodes_get_child_nodes set_disconnected_nodes set_disconnected_nodes_locs
  get_child_nodes get_child_nodes_locs +
  l_set_disconnected_nodes_get_shadow_root set_disconnected_nodes set_disconnected_nodes_locs
  get_shadow_root get_shadow_root_locs +
  l_set_disconnected_nodes_get_tag_name type_wf set_disconnected_nodes set_disconnected_nodes_locs
  get_tag_name get_tag_name_locs +
  l_set_disconnected_nodes type_wf set_disconnected_nodes set_disconnected_nodes_locs +
  l_set_disconnected_nodes_get_disconnected_nodes type_wf get_disconnected_nodes
  get_disconnected_nodes_locs set_disconnected_nodes set_disconnected_nodes_locs +
  l_new_element_get_shadow_root type_wf get_shadow_root get_shadow_root_locs +
  l_set_tag_name_get_shadow_root type_wf set_tag_name set_tag_name_locs get_shadow_root
  get_shadow_root_locs +
  l_new_element type_wf +
  l_known_ptrs known_ptr known_ptrs
  for known_ptr :: "(_::linorder) object_ptr => bool"
    and known_ptrs :: "(_ heap => bool"
    and type_wf :: "(_ heap => bool"
    and get_child_nodes :: "(_ object_ptr => ((_) heap, exception, (_ node_ptr list) prog"
    and get_child_nodes_locs :: "(_ object_ptr => ((_) heap => (_ heap => bool) set"
    and get_disconnected_nodes :: "(_ document_ptr => ((_) heap, exception, (_ node_ptr list) prog"
    and get_disconnected_nodes_locs :: "(_ document_ptr => ((_) heap => (_ heap => bool) set"
    and heap_is_wellformed :: "(_ heap => bool"
    and parent_child_rel :: "(_ heap => ((_) object_ptr <*> (_ object_ptr) set"
    and set_tag_name :: "(_ element_ptr => char list => ((_) heap, exception, unit) prog"
    and set_tag_name_locs :: "(_ element_ptr => ((_) heap, exception, unit) prog set"
    and set_disconnected_nodes :::
      "(_ document_ptr => (_ node_ptr list => ((_) heap, exception, unit) prog"
    and set_disconnected_nodes_locs :: "(_ document_ptr => ((_) heap, exception, unit) prog set"
    and create_element :::
      "(_ document_ptr => char list => ((_) heap, exception, (_ element_ptr) prog"
    and get_shadow_root :: "(_ element_ptr => ((_) heap, exception, (_ shadow_root_ptr option) prog"
    and get_shadow_root_locs :: "(_ element_ptr => ((_) heap => (_ heap => bool) set"
    and get_tag_name :: "(_ element_ptr => ((_) heap, exception, char list) prog"
    and get_tag_name_locs :: "(_ element_ptr => ((_) heap => (_ heap => bool) set"
    and heap_is_wellformedCore_DOM :: "(_ heap => bool"

```

```

and get_host :: "(_ shadow_root_ptr ⇒ ((_) heap, exception, (_ element_ptr) prog"
and get_host_locs :: "((_) heap ⇒ (_ heap ⇒ bool) set"
and get_disconnected_document :: "(_ node_ptr ⇒ ((_) heap, exception, (_ document_ptr) prog"
and get_disconnected_document_locs :: "((_) heap ⇒ (_ heap ⇒ bool) set"
and known_ptrCore_DOM :: "(_::linorder) object_ptr ⇒ bool"
and type_wfCore_DOM :: "(_ heap ⇒ bool"

begin
lemma create_element_preserves_wellformedness:
assumes "heap_is_wellformed h"
  and "h ⊢ create_element document_ptr tag →h h'"
  and "type_wf h"
  and "known_ptrs h"
shows "heap_is_wellformed h'" and "type_wf h'" and "known_ptrs h'"
⟨proof⟩
end

interpretation i_create_element_wf?: l_create_element_wfShadow_DOM known_ptr known_ptrs type_wf
get_child_nodes get_child_nodes_locs get_disconnected_nodes get_disconnected_nodes_locs
heap_is_wellformed parent_child_rel set_tag_name set_tag_name_locs set_disconnected_nodes
set_disconnected_nodes_locs create_element get_shadow_root get_shadow_root_locs get_tag_name
get_tag_name_locs heap_is_wellformedCore_DOM get_host get_host_locs get_disconnected_document
get_disconnected_document_locs DocumentClass.known_ptr DocumentClass.type_wf
⟨proof⟩
declare l_create_element_wfCore_DOM_axioms [instances]

create_character_data

locale l_create_character_data_wfShadow_DOM =
l_get_disconnected_nodes type_wf get_disconnected_nodes get_disconnected_nodes_locs +
l_heap_is_wellformedShadow_DOM get_child_nodes get_child_nodes_locs get_disconnected_nodes
get_disconnected_nodes_locs
get_shadow_root get_shadow_root_locs get_tag_name get_tag_name_locs known_ptr type_wf
heap_is_wellformed parent_child_rel
heap_is_wellformedCore_DOM get_host get_host_locs get_disconnected_document
get_disconnected_document_locs +
l_create_character_dataShadow_DOM get_disconnected_nodes get_disconnected_nodes_locs
set_disconnected_nodes set_disconnected_nodes_locs set_val set_val_locs create_character_data
known_ptr type_wfCore_DOM known_ptrCore_DOM
+ l_new_character_data_get_disconnected_nodes
get_disconnected_nodes get_disconnected_nodes_locs

+ l_set_val_get_disconnected_nodes
type_wf set_val set_val_locs get_disconnected_nodes get_disconnected_nodes_locs
+ l_new_character_data_get_child_nodes
type_wf known_ptr get_child_nodes get_child_nodes_locs
+ l_set_val_get_child_nodes
type_wf set_val set_val_locs known_ptr get_child_nodes get_child_nodes_locs
+ l_set_disconnected_nodes_get_child_nodes
set_disconnected_nodes set_disconnected_nodes_locs get_child_nodes get_child_nodes_locs
+ l_set_disconnected_nodes
type_wf set_disconnected_nodes set_disconnected_nodes_locs
+ l_set_disconnected_nodes_get_disconnected_nodes
type_wf get_disconnected_nodes get_disconnected_nodes_locs set_disconnected_nodes
set_disconnected_nodes_locs
+ l_set_val_get_shadow_root type_wf set_val set_val_locs get_shadow_root get_shadow_root_locs
+ l_set_disconnected_nodes_get_shadow_root set_disconnected_nodes set_disconnected_nodes_locs
get_shadow_root get_shadow_root_locs
+ l_new_character_data_get_tag_name
get_tag_name get_tag_name_locs
+ l_set_val_get_tag_name type_wf set_val set_val_locs get_tag_name get_tag_name_locs
+ l_get_tag_name type_wf get_tag_name get_tag_name_locs
+ l_set_disconnected_nodes_get_tag_name type_wf set_disconnected_nodes set_disconnected_nodes_locs
get_tag_name get_tag_name_locs

```

```

+ l_new_character_data
type_wf
+ l_known_ptrs
known_ptr known_ptrs
for known_ptr :: "(_::linorder) object_ptr ⇒ bool"
  and known_ptrs :: "(_ heap ⇒ bool"
  and type_wf :: "(_ heap ⇒ bool"
  and get_child_nodes :: "(_ object_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
  and get_child_nodes_locs :: "(_ object_ptr ⇒ ((_) heap ⇒ bool) set"
  and get_disconnected_nodes :: "(_ document_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
  and get_disconnected_nodes_locs :: "(_ document_ptr ⇒ ((_) heap ⇒ bool) set"
  and heap_is_wellformed :: "(_ heap ⇒ bool"
  and parent_child_rel :: "(_ heap ⇒ ((_) object_ptr × (_ object_ptr) set"
  and set_tag_name :: "(_ element_ptr ⇒ char list ⇒ ((_) heap, exception, unit) prog"
  and set_tag_name_locs :: "(_ element_ptr ⇒ ((_) heap, exception, unit) prog set"
  and set_disconnected_nodes :: "(_ document_ptr ⇒ (_ node_ptr list ⇒ ((_) heap, exception, unit) prog"
  and set_disconnected_nodes_locs :: "(_ document_ptr ⇒ ((_) heap, exception, unit) prog set"
  and create_element :: "(_ document_ptr ⇒ char list ⇒ ((_) heap, exception, (_ element_ptr) prog"
  and get_shadow_root :: "(_ element_ptr ⇒ ((_) heap, exception, (_ shadow_root_ptr option) prog"
  and get_shadow_root_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ bool) set"
  and get_tag_name :: "(_ element_ptr ⇒ ((_) heap, exception, char list) prog"
  and get_tag_name_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ bool) set"
  and heap_is_wellformedCore_DOM :: "(_ heap ⇒ bool"
  and get_host :: "(_ shadow_root_ptr ⇒ ((_) heap, exception, (_ element_ptr) prog"
  and get_host_locs :: "(_ heap ⇒ bool) set"
  and get_disconnected_document :: "(_ node_ptr ⇒ ((_) heap, exception, (_ document_ptr) prog"
  and get_disconnected_document_locs :: "((_) heap ⇒ bool) set"
  and set_val :: "(_ character_data_ptr ⇒ char list ⇒ ((_) heap, exception, unit) prog"
  and set_val_locs :: "(_ character_data_ptr ⇒ ((_) heap, exception, unit) prog set"
  and create_character_data :: "(_ document_ptr ⇒ char list ⇒ ((_) heap, exception, (_ character_data_ptr) prog"
  and known_ptrCore_DOM :: "(_::linorder) object_ptr ⇒ bool"
  and type_wfCore_DOM :: "(_ heap ⇒ bool"
begin
lemma create_character_data_preserves_wellformedness:
  assumes "heap_is_wellformed h"
    and "h ⊢ create_character_data document_ptr text →h h'"
    and "type_wf h"
    and "known_ptrs h"
  shows "heap_is_wellformed h'" and "type_wf h'" and "known_ptrs h'"
{proof}
end

```

create_document

```

locale l_create_document_wfShadow_DOM =
l_heap_is_wellformedShadow_DOM get_child_nodes get_child_nodes_locs get_disconnected_nodes
get_disconnected_nodes_locs
get_shadow_root get_shadow_root_locs get_tag_name get_tag_name_locs known_ptr type_wf
heap_is_wellformed parent_child_rel
heap_is_wellformedCore_DOM get_host get_host_locs get_disconnected_document
get_disconnected_document_locs
+ l_new_document_get_disconnected_nodes
get_disconnected_nodes get_disconnected_nodes_locs
+ l_create_documentCore_DOM
create_document
+ l_new_document_get_child_nodes
type_wf known_ptr get_child_nodes get_child_nodes_locs
+ l_get_tag_name type_wf get_tag_name get_tag_name_locs
+ l_new_document_get_tag_name get_tag_name get_tag_name_locs
+ l_get_disconnected_nodesShadow_DOM type_wf type_wfCore_DOM get_disconnected_nodes
get_disconnected_nodes_locs
+ l_new_document

```

```

type_wf
+ l_known_ptrs
known_ptr known_ptrs
for known_ptr :: "(_ : linorder) object_ptr ⇒ bool"
  and type_wf :: "(_ heap ⇒ bool"
  and type_wfCore_DOM :: "(_ heap ⇒ bool"
  and get_child_nodes :: "(_ object_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
  and get_child_nodes_locs :: "(_ object_ptr ⇒ ((_) heap ⇒ bool) set"
  and get_disconnected_nodes :: "(_ document_ptr ⇒ ((_) heap, exception, (_ node_ptr list) prog"
  and get_disconnected_nodes_locs :: "(_ document_ptr ⇒ ((_) heap ⇒ bool) set"
  and get_shadow_root :: "(_ element_ptr ⇒ ((_) heap, exception, (_ shadow_root_ptr option) prog"
  and get_shadow_root_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ bool) set"
  and get_tag_name :: "(_ element_ptr ⇒ ((_) heap, exception, char list) prog"
  and get_tag_name_locs :: "(_ element_ptr ⇒ ((_) heap ⇒ bool) set"
  and heap_is_wellformedCore_DOM :: "(_ heap ⇒ bool"
  and get_host :: "(_ shadow_root_ptr ⇒ ((_) heap, exception, (_ element_ptr) prog"
  and get_host_locs :: "((_) heap ⇒ (_ heap ⇒ bool) set"
  and get_disconnected_document :: "(_ node_ptr ⇒ ((_) heap, exception, (_ document_ptr) prog"
  and get_disconnected_document_locs :: "((_) heap ⇒ (_ heap ⇒ bool) set"
  and heap_is_wellformed :: "(_ heap ⇒ bool"
  and parent_child_rel :: "(_ heap ⇒ ((_) object_ptr × (_ object_ptr) set"
  and set_val :: "(_ character_data_ptr ⇒ char list ⇒ ((_) heap, exception, unit) prog"
  and set_val_locs :: "(_ character_data_ptr ⇒ ((_) heap, exception, unit) prog set"
  and set_disconnected_nodes :: "
    "(_ document_ptr ⇒ (_ node_ptr list ⇒ ((_) heap, exception, unit) prog"
  and set_disconnected_nodes_locs :: "(_ document_ptr ⇒ ((_) heap, exception, unit) prog set"
  and create_document :: "((_) heap, exception, (_ document_ptr) prog"
  and known_ptrs :: "(_ heap ⇒ bool"
begin

lemma create_document_preserves_wellformedness:
  assumes "heap_is_wellformed h"
    and "h ⊢ create_document →h h"
    and "type_wf h"
    and "known_ptrs h"
  shows "heap_is_wellformed h"
⟨proof⟩
end

interpretation l_create_document_wfShadow_DOM known_ptr type_wf DocumentClass.type_wf get_child_nodes
get_child_nodes_locs get_disconnected_nodes get_disconnected_nodes_locs get_shadow_root
get_shadow_root_locs get_tag_name get_tag_name_locs
heap_is_wellformedCore_DOM get_host get_host_locs get_disconnected_document
get_disconnected_document_locs heap_is_wellformed parent_child_rel set_val set_val_locs
set_disconnected_nodes set_disconnected_nodes_locs create_document known_ptrs
⟨proof⟩

```

attach_shadow_root

```

locale l_attach_shadow_root_wfShadow_DOM =
l_get_disconnected_nodes
type_wf get_disconnected_nodes get_disconnected_nodes_locs
+ l_heap_is_wellformedShadow_DOM
get_child_nodes get_child_nodes_locs get_disconnected_nodes get_disconnected_nodes_locs
get_shadow_root get_shadow_root_locs get_tag_name get_tag_name_locs known_ptr type_wf
heap_is_wellformed parent_child_rel
heap_is_wellformedCore_DOM get_host get_host_locs get_disconnected_document
get_disconnected_document_locs
+ l_attach_shadow_rootShadow_DOM known_ptr set_shadow_root set_shadow_root_locs set_mode
set_mode_locs attach_shadow_root type_wf get_tag_name get_tag_name_locs get_shadow_root
get_shadow_root_locs
+ l_new_shadow_root_get_disconnected_nodes
get_disconnected_nodes get_disconnected_nodes_locs

```

```

+ l_set_mode_get_disconnected_nodes
type_wf set_mode set_mode_locs get_disconnected_nodes get_disconnected_nodes_locs
+ l_new_shadow_root_get_child_nodes
type_wf known_ptr get_child_nodes get_child_nodes_locs
+ l_new_shadow_root_get_tag_name
type_wf get_tag_name get_tag_name_locs
+ l_set_mode_get_child_nodes
type_wf set_mode set_mode_locs known_ptr get_child_nodes get_child_nodes_locs
+ l_set_shadow_root_get_child_nodes
type_wf set_shadow_root set_shadow_root_locs known_ptr get_child_nodes get_child_nodes_locs
+ l_set_shadow_root
type_wf set_shadow_root set_shadow_root_locs
+ l_set_shadow_root_get_disconnected_nodes
set_shadow_root set_shadow_root_locs get_disconnected_nodes get_disconnected_nodes_locs
+ l_set_mode_get_shadow_root type_wf set_mode set_mode_locs get_shadow_root get_shadow_root_locs
+ l_set_shadow_root_get_shadow_root type_wf set_shadow_root set_shadow_root_locs
get_shadow_root get_shadow_root_locs
+ l_new_character_data_get_tag_name
get_tag_name get_tag_name_locs
+ l_set_mode_get_tag_name type_wf set_mode set_mode_locs get_tag_name get_tag_name_locs
+ l_get_tag_name type_wf get_tag_name get_tag_name_locs
+ l_set_shadow_root_get_tag_name set_shadow_root set_shadow_root_locs get_tag_name get_tag_name_locs
+ l_new_shadow_root
type_wf
+ l_known_ptrs
known_ptr known_ptrs
for known_ptr :: "(_::linorder) object_ptr => bool"
  and known_ptrs :: "(_ heap => bool"
  and type_wf :: "(_ heap => bool"
  and get_child_nodes :: "(_ object_ptr => (_ heap, exception, (_ node_ptr list) prog"
  and get_child_nodes_locs :: "(_ object_ptr => (_ heap => (_ heap => bool) set"
  and get_disconnected_nodes :: "(_ document_ptr => (_ heap, exception, (_ node_ptr list) prog"
  and get_disconnected_nodes_locs :: "(_ document_ptr => (_ heap => (_ heap => bool) set"
  and heap_is_wellformed :: "(_ heap => bool"
  and parent_child_rel :: "(_ heap => (_ object_ptr x (_ object_ptr) set"
  and set_tag_name :: "(_ element_ptr => char list => (_ heap, exception, unit) prog"
  and set_tag_name_locs :: "(_ element_ptr => (_ heap, exception, unit) prog set"
  and set_disconnected_nodes :: "(_ document_ptr => (_ node_ptr list => (_ heap, exception, unit) prog"
  and set_disconnected_nodes_locs :: "(_ document_ptr => (_ heap, exception, unit) prog set"
  and create_element :: "(_ document_ptr => char list => (_ heap, exception, (_ element_ptr) prog"
  and get_shadow_root :: "(_ element_ptr => (_ heap, exception, (_ shadow_root_ptr option) prog"
  and get_shadow_root_locs :: "(_ element_ptr => (_ heap => (_ heap => bool) set"
  and get_tag_name :: "(_ element_ptr => (_ heap, exception, char list) prog"
  and get_tag_name_locs :: "(_ element_ptr => (_ heap => (_ heap => bool) set"
  and heap_is_wellformedCore_DOM :: "(_ heap => bool"
  and get_host :: "(_ shadow_root_ptr => (_ heap, exception, (_ element_ptr) prog"
  and get_host_locs :: "(_ heap => (_ heap => bool) set"
  and get_disconnected_document :: "(_ node_ptr => (_ heap, exception, (_ document_ptr) prog"
  and get_disconnected_document_locs :: "(_ heap => (_ heap => bool) set"
  and set_val :: "(_ character_data_ptr => char list => (_ heap, exception, unit) prog"
  and set_val_locs :: "(_ character_data_ptr => (_ heap, exception, unit) prog set"
  and create_character_data :: "(_ document_ptr => char list => (_ heap, exception, (_ character_data_ptr) prog"
  and known_ptrCore_DOM :: "(_::linorder) object_ptr => bool"
  and type_wfCore_DOM :: "(_ heap => bool"
  and set_shadow_root :: "(_ element_ptr => (_ shadow_root_ptr option => (_, unit) dom_prog"
  and set_shadow_root_locs :: "(_ element_ptr => (_, unit) dom_prog set"
  and set_mode :: "(_ shadow_root_ptr => shadow_root_mode => (_, unit) dom_prog"
  and set_mode_locs :: "(_ shadow_root_ptr => (_, unit) dom_prog set"
  and attach_shadow_root :: "(_ element_ptr => shadow_root_mode => (_, (_ shadow_root_ptr) dom_prog"
begin
lemma attach_shadow_root_child_preserves:

```

```

assumes "heap_is_wellformed h" and "type_wf h" and "known_ptrs h"
assumes "h ⊢ attach_shadow_root element_ptr new_mode →h h'"
shows "type_wf h'" and "known_ptrs h'" and "heap_is_wellformed h'"
⟨proof⟩
end

interpretation l_attach_shadow_root_wf?: l_attach_shadow_root_wfShadow_DOM known_ptr known_ptrs type_wf
  get_child_nodes get_child_nodes_locs get_disconnected_nodes get_disconnected_nodes_locs
  heap_is_wellformed parent_child_rel set_tag_name set_tag_name_locs set_disconnected_nodes
  set_disconnected_nodes_locs create_element get_shadow_root get_shadow_root_locs get_tag_name
  get_tag_name_locs heap_is_wellformedCore_DOM get_host get_host_locs get_disconnected_document
  get_disconnected_document_locs set_val set_val_locs create_character_data DocumentClass.known_ptr
  DocumentClass.type_wf set_shadow_root set_shadow_root_locs set_mode set_mode_locs attach_shadow_root
  ⟨proof⟩
declare l_attach_shadow_root_wfShadow_DOM_axioms [instances]

end

```

3 Test Suite

In this chapter, we present the formalized compliance test cases for the core DOM. As our formalization is executable, we can (symbolically) execute the test cases on top of our model. Executing these test cases successfully shows that our model is compliant to the official DOM standard. As future work, we plan to generate test cases from our formal model (e.g., using [7, 9]) to improve the quality of the official compliance test suite. For more details on the relation of test and proof in the context of web standards, we refer the reader to [4].

3.1 Shadow DOM Base Tests (Shadow_DOM_BaseTest)

```
theory Shadow_DOM_BaseTest
imports
  "../../Shadow_DOM"
begin

definition "assert_throws e p = do {
  h ← get_heap;
  (if (h ⊢ p →e e) then return () else error AssertException)
}''"
notation assert_throws (⟨assert'_throws'(_, _')⟩)

definition "test p h ↔ h ⊢ ok p"

definition field_access :: "(string ⇒ (_, _) object_ptr option) dom_prog ⇒ string ⇒
  (_, _) object_ptr option dom_prog" (infix <.> 80)
  where
    "field_access m field = m field"

definition assert_equals :: "'a ⇒ 'a ⇒ (_, unit) dom_prog"
  where
    "assert_equals l r = (if l = r then return () else error AssertException)"
definition assert_equals_with_message :: "'a ⇒ 'a ⇒ 'b ⇒ (_, unit) dom_prog"
  where
    "assert_equals_with_message l r = (if l = r then return () else error AssertException)"
notation assert_equals (⟨assert'_equals'(_, _)⟩)
notation assert_equals_with_message (⟨assert'_equals'(_, _, _)⟩)
notation assert_equals (⟨assert'_array'_equals'(_, _)⟩)
notation assert_equals_with_message (⟨assert'_array'_equals'(_, _, _)⟩)

definition assert_not_equals :: "'a ⇒ 'a ⇒ (_, unit) dom_prog"
  where
    "assert_not_equals l r = (if l ≠ r then return () else error AssertException)"
definition assert_not_equals_with_message :: "'a ⇒ 'a ⇒ 'b ⇒ (_, unit) dom_prog"
  where
    "assert_not_equals_with_message l r = (if l ≠ r then return () else error AssertException)"
notation assert_not_equals (⟨assert'_not'_equals'(_, _)⟩)
notation assert_not_equals_with_message (⟨assert'_not'_equals'(_, _, _)⟩)
notation assert_not_equals (⟨assert'_array'_not'_equals'(_, _)⟩)
notation assert_not_equals_with_message (⟨assert'_array'_not'_equals'(_, _, _)⟩)

definition removeWhiteSpaceOnlyTextNodes :: "((_) object_ptr option) ⇒ (_, unit) dom_prog"
  where
```

```
"removeWhiteSpaceOnlyTextNodes _ = return ()"
```

3.1.1 Making the functions under test compatible with untyped languages such as JavaScript

```
fun set_attribute_with_null :: "((_) object_ptr option) ⇒ attr_key ⇒ attr_value ⇒ (_, unit) dom_prog"
where
"set_attribute_with_null (Some ptr) k v = (case cast ptr of
  Some element_ptr ⇒ set_attribute element_ptr k (Some v))"
fun set_attribute_with_null2 :: "((_) object_ptr option) ⇒ attr_key ⇒ attr_value option ⇒ (_, unit) dom_prog"
where
"set_attribute_with_null2 (Some ptr) k v = (case cast ptr of
  Some element_ptr ⇒ set_attribute element_ptr k v)"
notation set_attribute_with_null (<_ . setAttribute'(_, _')>)
notation set_attribute_with_null2 (<_ . setAttribute'(_, _')>)

fun get_child_nodesCore_DOM_with_null :: "((_) object_ptr option) ⇒ (_, (_) object_ptr option list) dom_prog"
where
"get_child_nodesCore_DOM_with_null (Some ptr) = do {
  children ← get_child_nodes ptr;
  return (map (Some ∘ cast) children)
}"
notation get_child_nodesCore_DOM_with_null (<_ . childNodes>)

fun create_element_with_null :: "((_) object_ptr option) ⇒ string ⇒ (_, ((_) object_ptr option)) dom_prog"
where
"create_element_with_null (Some owner_document_obj) tag = (case cast owner_document_obj of
  Some owner_document ⇒ do {
    element_ptr ← create_element owner_document tag;
    return (Some (cast element_ptr)))"
notation create_element_with_null (<_ . createElement'(_')>)

fun create_character_data_with_null :: "((_) object_ptr option) ⇒ string ⇒ (_, ((_) object_ptr option)) dom_prog"
where
"create_character_data_with_null (Some owner_document_obj) tag = (case cast owner_document_obj of
  Some owner_document ⇒ do {
    character_data_ptr ← create_character_data owner_document tag;
    return (Some (cast character_data_ptr)))"
notation create_character_data_with_null (<_ . createTextNode'(_')>)

definition create_document_with_null :: "string ⇒ (_, ((_:linorder) object_ptr option)) dom_prog"
where
"create_document_with_null title = do {
  new_document_ptr ← create_document;
  html ← create_element new_document_ptr ''html'';
  append_child (cast new_document_ptr) (cast html);
  heap ← create_element new_document_ptr ''heap'';
  append_child (cast html) (cast heap);
  body ← create_element new_document_ptr ''body'';
  append_child (cast html) (cast body);
  return (Some (cast new_document_ptr))
}"
abbreviation "create_document_with_null2 _ _ _ ≡ create_document_with_null , , , "
notation create_document_with_null (<createDocument'(_')>)
notation create_document_with_null2 (<createDocument'(_, _, _')>)

fun get_element_by_id_with_null :: "((_:linorder) object_ptr option) ⇒ string ⇒ (_, ((_) object_ptr option)) dom_prog"
where
"get_element_by_id_with_null (Some ptr) id' = do {
  element_ptr_opt ← get_element_by_id ptr id';
  (case element_ptr_opt of
```

```

    Some element_ptr => return (Some (castelement_ptr2object_ptr element_ptr))
    | None => return None)"}
  / "get_element_by_id_with_null _ _ = error SegmentationFault"
notation get_element_by_id_with_null (<_ . getElementById'(_')>)

fun get_elements_by_class_name_with_null :: 
  "((_:linorder) object_ptr option) => string => (_, ((_) object_ptr option) list) dom_prog"
where
  "get_elements_by_class_name_with_null (Some ptr) class_name =
   get_elements_by_class_name ptr class_name >> map_M (return o Some o castelement_ptr2object_ptr)"
notation get_elements_by_class_name_with_null (<_ . getElementsByClassName'(_')>)

fun get_elements_by_tag_name_with_null :: 
  "((_:linorder) object_ptr option) => string => (_, ((_) object_ptr option) list) dom_prog"
where
  "get_elements_by_tag_name_with_null (Some ptr) tag =
   get_elements_by_tag_name ptr tag >> map_M (return o Some o castelement_ptr2object_ptr)"
notation get_elements_by_tag_name_with_null (<_ . getElementsByTagName'(_')>)

fun insert_before_with_null :: 
  "((_:linorder) object_ptr option) => ((_) object_ptr option) => ((_) object_ptr option) =>
  (_, ((_) object_ptr option)) dom_prog"
where
  "insert_before_with_null (Some ptr) (Some child_obj) ref_child_obj_opt = (case cast child_obj of
  Some child => do {
    (case ref_child_obj_opt of
      Some ref_child_obj => insert_before ptr child (cast ref_child_obj)
      | None => insert_before ptr child None);
    return (Some child_obj)}
  | None => error HierarchyRequestError)"
notation insert_before_with_null (<_ . insertBefore'(_, _, _)>)

fun append_child_with_null :: 
  "((_:linorder) object_ptr option) => ((_) object_ptr option) => (_, unit) dom_prog"
where
  "append_child_with_null (Some ptr) (Some child_obj) = (case cast child_obj of
  Some child => append_child ptr child
  | None => error SegmentationFault)"
notation append_child_with_null (<_ . appendChild'(_')>)
code_thms append_child_with_null

fun get_body :: "((_:linorder) object_ptr option) => (_, ((_) object_ptr option)) dom_prog"
where
  "get_body ptr = do {
  ptrs <- ptr . getElementsByTagName('body');
  return (hd ptrs)
  }"
notation get_body (<_ . body>)

fun get_document_element_with_null :: 
  "((_:linorder) object_ptr option) => (_, ((_) object_ptr option)) dom_prog"
where
  "get_document_element_with_null (Some ptr) = (case castobject_ptr2document_ptr ptr of
  Some document_ptr => do {
    element_ptr_opt <- get_M document_ptr document_element;
    return (case element_ptr_opt of
      Some element_ptr => Some (castelement_ptr2object_ptr element_ptr)
      | None => None)})"
notation get_document_element_with_null (<_ . documentElement>)

fun get_owner_document_with_null :: "((_:linorder) object_ptr option) => (_, ((_) object_ptr option)) dom_prog"
where
  "get_owner_document_with_null (Some ptr) = (do {
  document_ptr <- get_owner_document ptr;
  
```

3 Test Suite

```

return (Some (cast_document_ptr2object_ptr document_ptr)))}"
notation get_owner_document_with_null (<_ . ownerDocument>)

fun remove_with_null :: "(_::linorder) object_ptr option) ⇒ (_ , ((_) object_ptr option)) dom_prog"
where
  "remove_with_null (Some child) = (case cast child of
    Some child_node ⇒ do {
      remove child_node;
      return (Some child)}
    | None ⇒ error NotFoundError)"
  | "remove_with_null None = error TypeError"
notation remove_with_null (<_ . remove'(')>)

fun remove_child_with_null :: 
  "(_::linorder) object_ptr option) ⇒ ((_) object_ptr option) ⇒ (_ , ((_) object_ptr option)) dom_prog"
where
  "remove_child_with_null (Some ptr) (Some child) = (case cast child of
    Some child_node ⇒ do {
      remove_child_ptr child_node;
      return (Some child)}
    | None ⇒ error NotFoundError)"
  | "remove_child_with_null None _ = error TypeError"
  | "remove_child_with_null _ None = error TypeError"
notation remove_child_with_null (<_ . removeChild>)

fun get_tag_name_with_null :: "(_ object_ptr option) ⇒ (_ , attr_value) dom_prog"
where
  "get_tag_name_with_null (Some ptr) = (case cast ptr of
    Some element_ptr ⇒ get_M_element_ptr tag_name)"
notation get_tag_name_with_null (<_ . tagName>)

abbreviation "remove_attribute_with_null ptr k ≡ set_attribute_with_null2 ptr k None"
notation remove_attribute_with_null (<_ . removeAttribute'(')>)

fun get_attribute_with_null :: "(_ object_ptr option) ⇒ attr_key ⇒ (_ , attr_value option) dom_prog"
where
  "get_attribute_with_null (Some ptr) k = (case cast ptr of
    Some element_ptr ⇒ get_attribute_element_ptr k)"
fun get_attribute_with_null2 :: "(_ object_ptr option) ⇒ attr_key ⇒ (_ , attr_value) dom_prog"
where
  "get_attribute_with_null2 (Some ptr) k = (case cast ptr of
    Some element_ptr ⇒ do {
      a ← get_attribute_element_ptr k;
      return (the a)})"
notation get_attribute_with_null (<_ . getAttribute'(')>)
notation get_attribute_with_null2 (<_ . getAttribute'(')>)

fun get_parent_with_null :: "(_::linorder) object_ptr option) ⇒ (_ , (_ object_ptr option)) dom_prog"
where
  "get_parent_with_null (Some ptr) = (case cast ptr of
    Some node_ptr ⇒ get_parent_node_ptr)"
notation get_parent_with_null (<_ . parentNode>)

fun first_child_with_null :: "(_ object_ptr option) ⇒ (_ , ((_) object_ptr option)) dom_prog"
where
  "first_child_with_null (Some ptr) = do {
    child_opt ← first_child_ptr;
    return (case child_opt of
      Some child ⇒ Some (cast child)
      | None ⇒ None)}"
notation first_child_with_null (<_ . firstChild>)

fun adopt_node_with_null ::
```

```

"((_:linorder) object_ptr option) ⇒ ((_) object_ptr option) ⇒ (_, ((_) object_ptr option)) dom_prog"
where
  "adopt_node_with_null (Some ptr) (Some child) = (case cast ptr of
  Some document_ptr ⇒ (case cast child of
  Some child_node ⇒ do {
    adopt_node document_ptr child_node;
    return (Some child)}))"
notation adopt_node_with_null (<_ . adoptNode'(_)>)

fun get_shadow_root_with_null :: "((_) object_ptr option) ⇒ (_, (_ object_ptr option) dom_prog"
where
  "get_shadow_root_with_null (Some ptr) = (case cast ptr of
  Some element_ptr ⇒ do {
    shadow_root ← get_shadow_root element_ptr;
    (case shadow_root of Some sr ⇒ return (Some (cast sr))
    | None ⇒ return None)}"
notation get_shadow_root_with_null (<_ . shadowRoot>)

```

3.1.2 Making the functions under test compatible with untyped languages such as JavaScript

```

fun get_element_by_id_si_with_null :: 
  "(_:_linorder) object_ptr option ⇒ string ⇒ (_, (_ object_ptr option) dom_prog"
where
  "get_element_by_id_si_with_null (Some ptr) id' = do {
    element_ptr_opt ← get_element_by_id_si ptr id';
    (case element_ptr_opt of
    Some element_ptr ⇒ return (Some (castelement_ptr2object_ptr element_ptr))
    | None ⇒ return None)}"
  | "get_element_by_id_si_with_null _ _ = error SegmentationFault"

fun find_slot_closed_with_null :: 
  "(_:_linorder) object_ptr option ⇒ (_, (_ object_ptr option) dom_prog"
where
  "find_slot_closed_with_null (Some ptr) = (case castobject_ptr2node_ptr ptr of
  Some node_ptr ⇒ do {
    element_ptr_opt ← find_slot True node_ptr;
    (case element_ptr_opt of
    Some element_ptr ⇒ return (Some (castelement_ptr2object_ptr element_ptr))
    | None ⇒ return None)}"
  | None ⇒ error SegmentationFault)"
  | "find_slot_closed_with_null None = error SegmentationFault"
notation find_slot_closed_with_null (<_ . assignedSlot>)

fun assigned_nodes_with_null :: 
  "(_:_linorder) object_ptr option ⇒ (_, (_ object_ptr option list) dom_prog"
where
  "assigned_nodes_with_null (Some ptr) = (case castobject_ptr2element_ptr ptr of
  Some element_ptr ⇒ do {
    l ← assigned_nodes element_ptr;
    return (map Some (map castnode_ptr2object_ptr 1)))}
  | None ⇒ error SegmentationFault)"
  | "assigned_nodes_with_null None = error SegmentationFault"
notation assigned_nodes_with_null (<_ . assignedNodes'(')>)

fun assigned_nodes_flatten_with_null :: 
  "(_:_linorder) object_ptr option ⇒ (_, (_ object_ptr option list) dom_prog"
where
  "assigned_nodes_flatten_with_null (Some ptr) = (case castobject_ptr2element_ptr ptr of
  Some element_ptr ⇒ do {
    l ← assigned_nodes_flatten element_ptr;
    return (map Some (map castnode_ptr2object_ptr 1)))}
  | None ⇒ error SegmentationFault)"

```

3 Test Suite

```

| None ⇒ error SegmentationFault)"
| "assigned_nodes_flatten_with_null None = error SegmentationFault"
notation assigned_nodes_flatten_with_null (<_ . assignedNodes'('True'))>

fun get_assigned_elements_with_null :: 
  "(_::linorder) object_ptr option ⇒ (_, (_ object_ptr option list) dom_prog"
where
  "get_assigned_elements_with_null (Some ptr) = (case castobject_ptr2element_ptr ptr of
  Some element_ptr ⇒ do {
    l ← assigned_nodes element_ptr;
    l ← map_filter_M (return o castnode_ptr2element_ptr) l;
    return (map Some (map cast l))
  | None ⇒ error SegmentationFault)"
  | "get_assigned_elements_with_null None = error SegmentationFault"
notation get_assigned_elements_with_null (<_ . assignedElements'('))>

fun get_assigned_elements_flatten_with_null :: 
  "(_::linorder) object_ptr option ⇒ (_, (_ object_ptr option list) dom_prog"
where
  "get_assigned_elements_flatten_with_null (Some ptr) = (case castobject_ptr2element_ptr ptr of
  Some element_ptr ⇒ do {
    l ← assigned_nodes_flatten element_ptr;
    return (map Some (map castnode_ptr2object_ptr l))
  | None ⇒ error SegmentationFault)"
  | "get_assigned_elements_flatten_with_null None = error SegmentationFault"
notation get_assigned_elements_flatten_with_null (<_ . assignedElements'('True'))>

fun createTestTree :: 
  "(_::linorder) object_ptr option ⇒ (_, string ⇒ (_, (_ object_ptr option) dom_prog) dom_prog"
where
  "createTestTree (Some ref) = do {
    tups ← to_tree_order_si ref ≫= map_filter_M (λptr. do {
      (case cast ptr of
        Some element_ptr ⇒ do {
          iden_opt ← get_attribute element_ptr ''id'';
          (case iden_opt of
            Some iden ⇒ return (Some (iden, ptr))
          | None ⇒ return None)
        }
      | None ⇒ return None)}));
    return (return o map_of tups)
  }"
  | "createTestTree None = error SegmentationFault"

end

```

3.2 Testing slots (slots)

This theory contains the test cases for slots.

```

theory slots
imports
  "Shadow_DOM_BaseTest"
begin

definition slots_heap :: "heapfinal" where
  "slots_heap = create_heap [(cast (document_ptr.Ref 1), cast (create_document_obj html (Some (cast (element_ptr.Ref 1)))) []),
  (cast (element_ptr.Ref 1), cast (create_element_obj ''html'' [cast (element_ptr.Ref 2), cast (element_ptr.Ref 8)] fmempty None)),
  (cast (element_ptr.Ref 2), cast (create_element_obj ''head'' [cast (element_ptr.Ref 3), cast (element_ptr.Ref 4), cast (element_ptr.Ref 5), cast (element_ptr.Ref 6), cast (element_ptr.Ref 7)] fmempty None)),
```

```

(cast (element_ptr.Ref 3), cast (create_element_obj ''title'' [cast (character_data_ptr.Ref 1)] fmempty
None)),
  (cast (character_data_ptr.Ref 1), cast (create_character_data_obj ''Shadow%20DOM%3A%20Slots%20and%20assignments
  (cast (element_ptr.Ref 4), cast (create_element_obj ''meta'' [] (fmap_of_list [('name', 'author'),
('title', 'Hayato Ito'), ('href', 'mailto:hayato@google.com')])) None)),
    (cast (element_ptr.Ref 5), cast (create_element_obj ''script'' [] (fmap_of_list [('src', '/resources/testhan
None)),
      (cast (element_ptr.Ref 6), cast (create_element_obj ''script'' [] (fmap_of_list [('src', '/resources/testhan
None)),
        (cast (element_ptr.Ref 7), cast (create_element_obj ''script'' [] (fmap_of_list [('src', '/resources/shadow-
None)),
          (cast (element_ptr.Ref 8), cast (create_element_obj ''body'' [cast (element_ptr.Ref 9), cast (element_ptr.Ref
13), cast (element_ptr.Ref 14), cast (element_ptr.Ref 18), cast (element_ptr.Ref 19), cast (element_ptr.Ref
21), cast (element_ptr.Ref 22), cast (element_ptr.Ref 30), cast (element_ptr.Ref 31), cast (element_ptr.Ref
39), cast (element_ptr.Ref 40), cast (element_ptr.Ref 48), cast (element_ptr.Ref 49), cast (element_ptr.Ref
57), cast (element_ptr.Ref 58), cast (element_ptr.Ref 64), cast (element_ptr.Ref 65), cast (element_ptr.Ref
71), cast (element_ptr.Ref 72), cast (element_ptr.Ref 78), cast (element_ptr.Ref 79), cast (element_ptr.Ref
85), cast (element_ptr.Ref 86), cast (element_ptr.Ref 92), cast (element_ptr.Ref 93), cast (element_ptr.Ref
112)] fmempty None)),
            (cast (element_ptr.Ref 9), cast (create_element_obj ''div'' [cast (element_ptr.Ref 10)] (fmap_of_list
[('id', 'test_basic')]) None)),
              (cast (element_ptr.Ref 10), cast (create_element_obj ''div'' [cast (element_ptr.Ref 11)] (fmap_of_list
[('id', 'host')]) (Some (cast (shadow_root_ptr.Ref 1)))),
                (cast (element_ptr.Ref 11), cast (create_element_obj ''div'' [] (fmap_of_list [('id', 'c1'), ('slot',
'slot1')]) None)),
                  (cast (shadow_root_ptr.Ref 1), cast (create_shadow_root_obj Open [cast (element_ptr.Ref 12)])),
                    (cast (element_ptr.Ref 12), cast (create_element_obj ''slot'' [] (fmap_of_list [('id', 's1'), ('name',
'slot1')]) None)),
                      (cast (element_ptr.Ref 13), cast (create_element_obj ''script'' [cast (character_data_ptr.Ref 2)] fmempty
None)),
                        (cast (character_data_ptr.Ref 2), cast (create_character_data_obj ''%3C%3Cscript%3E%3E'')),
                          (cast (element_ptr.Ref 14), cast (create_element_obj ''div'' [cast (element_ptr.Ref 15)] (fmap_of_list
[('id', 'test_basic_closed')]) None)),
                            (cast (element_ptr.Ref 15), cast (create_element_obj ''div'' [cast (element_ptr.Ref 16)] (fmap_of_list
[('id', 'host')]) (Some (cast (shadow_root_ptr.Ref 2)))),
                              (cast (element_ptr.Ref 16), cast (create_element_obj ''div'' [] (fmap_of_list [('id', 'c1'), ('slot',
'slot1')]) None)),
                                (cast (shadow_root_ptr.Ref 2), cast (create_shadow_root_obj Closed [cast (element_ptr.Ref 17)])),
                                  (cast (element_ptr.Ref 17), cast (create_element_obj ''slot'' [] (fmap_of_list [('id', 's1'), ('name',
'slot1')]) None)),
                                    (cast (element_ptr.Ref 18), cast (create_element_obj ''script'' [cast (character_data_ptr.Ref 3)] fmempty
None)),
                                      (cast (character_data_ptr.Ref 3), cast (create_character_data_obj ''%3C%3Cscript%3E%3E'')),
                                        (cast (element_ptr.Ref 19), cast (create_element_obj ''div'' [cast (element_ptr.Ref 20)] (fmap_of_list
[('id', 'test_slot_not_in_shadow')]) None)),
                                          (cast (element_ptr.Ref 20), cast (create_element_obj ''slot'' [] (fmap_of_list [('id', 's1')]) None)),
                                            (cast (element_ptr.Ref 21), cast (create_element_obj ''script'' [cast (character_data_ptr.Ref 4)] fmempty
None)),
                                              (cast (character_data_ptr.Ref 4), cast (create_character_data_obj ''%3C%3Cscript%3E%3E'')),
                                                (cast (element_ptr.Ref 22), cast (create_element_obj ''div'' [cast (element_ptr.Ref 23), cast (element_ptr.Ref
25)] (fmap_of_list [('id', 'test_slot_not_in_shadow_2')]) None)),
                                                  (cast (element_ptr.Ref 23), cast (create_element_obj ''slot'' [cast (element_ptr.Ref 24)] (fmap_of_list
[('id', 's1')]) None)),
                                                    (cast (element_ptr.Ref 24), cast (create_element_obj ''div'' [] (fmap_of_list [('id', 'c1')]) None)),
                                                      (cast (element_ptr.Ref 25), cast (create_element_obj ''slot'' [cast (element_ptr.Ref 26), cast (element_ptr.Ref
27)] (fmap_of_list [('id', 's2')]) None)),
                                                        (cast (element_ptr.Ref 26), cast (create_element_obj ''div'' [] (fmap_of_list [('id', 'c2')]) None)),
                                                          (cast (element_ptr.Ref 27), cast (create_element_obj ''slot'' [cast (element_ptr.Ref 28), cast (element_ptr.Ref
29)] (fmap_of_list [('id', 's3')]) None)),
                                                            (cast (element_ptr.Ref 28), cast (create_element_obj ''div'' [] (fmap_of_list [('id', 'c3_1')]) None)),
                                                              (cast (element_ptr.Ref 29), cast (create_element_obj ''div'' [] (fmap_of_list [('id', 'c3_2')]) None)),

```

```

(cast (element_ptr.Ref 30), cast (create_element_obj ''script'' [cast (character_data_ptr.Ref 5)] fmempty
None)),
  (cast (character_data_ptr.Ref 5), cast (create_character_data_obj ''%3C%3Cscript%3E%3E'')),
    (cast (element_ptr.Ref 31), cast (create_element_obj ''div'' [cast (element_ptr.Ref 32)] (fmap_of_list
[(''id'', ''test_slot_name_matching'')] None)),
      (cast (element_ptr.Ref 32), cast (create_element_obj ''div'' [cast (element_ptr.Ref 33), cast (element_ptr.Ref
34), cast (element_ptr.Ref 35)] (fmap_of_list [(''id'', ''host'')] (Some (cast (shadow_root_ptr.Ref 3))))),
        (cast (element_ptr.Ref 33), cast (create_element_obj ''div'' [] (fmap_of_list [(''id'', ''c1''), (''slot'',
''slot1'')] None)),
          (cast (element_ptr.Ref 34), cast (create_element_obj ''div'' [] (fmap_of_list [(''id'', ''c2''), (''slot'',
''slot2'')] None)),
            (cast (element_ptr.Ref 35), cast (create_element_obj ''div'' [] (fmap_of_list [(''id'', ''c3''), (''slot'',
''yyy'')] None)),
              (cast (shadow_root_ptr.Ref 3), cast (create_shadow_root_obj Open [cast (element_ptr.Ref 36), cast (element_ptr.
37), cast (element_ptr.Ref 38)])),
                (cast (element_ptr.Ref 36), cast (create_element_obj ''slot'' [] (fmap_of_list [(''id'', ''s1''), (''name'',
''slot1'')] None)),
                  (cast (element_ptr.Ref 37), cast (create_element_obj ''slot'' [] (fmap_of_list [(''id'', ''s2''), (''name'',
''slot2'')] None)),
                    (cast (element_ptr.Ref 38), cast (create_element_obj ''slot'' [] (fmap_of_list [(''id'', ''s3''), (''name'',
''xxx'')] None)),
                      (cast (element_ptr.Ref 39), cast (create_element_obj ''script'' [cast (character_data_ptr.Ref 6)] fmempty
None)),
                        (cast (character_data_ptr.Ref 6), cast (create_character_data_obj ''%3C%3Cscript%3E%3E'')),
                          (cast (element_ptr.Ref 40), cast (create_element_obj ''div'' [cast (element_ptr.Ref 41)] (fmap_of_list
[(''id'', ''test_no_direct_host_child'')] None)),
                            (cast (element_ptr.Ref 41), cast (create_element_obj ''div'' [cast (element_ptr.Ref 42), cast (element_ptr.Ref
43), cast (element_ptr.Ref 44)] (fmap_of_list [(''id'', ''host'')] (Some (cast (shadow_root_ptr.Ref 4))))),
                              (cast (element_ptr.Ref 42), cast (create_element_obj ''div'' [] (fmap_of_list [(''id'', ''c1''), (''slot'',
''slot1'')] None)),
                                (cast (element_ptr.Ref 43), cast (create_element_obj ''div'' [] (fmap_of_list [(''id'', ''c2''), (''slot'',
''slot1'')] None)),
                                  (cast (element_ptr.Ref 44), cast (create_element_obj ''div'' [cast (element_ptr.Ref 45)] fmempty None),
                                    (cast (element_ptr.Ref 45), cast (create_element_obj ''div'' [] (fmap_of_list [(''id'', ''c3''), (''slot'',
''slot1'')] None)),
                                      (cast (shadow_root_ptr.Ref 4), cast (create_shadow_root_obj Open [cast (element_ptr.Ref 46), cast (element_ptr.
47)])),
                                        (cast (element_ptr.Ref 46), cast (create_element_obj ''slot'' [] (fmap_of_list [(''id'', ''s1''), (''name'',
''slot1'')] None)),
                                          (cast (element_ptr.Ref 47), cast (create_element_obj ''slot'' [] (fmap_of_list [(''id'', ''s2''), (''name'',
''slot1'')] None)),
                                            (cast (element_ptr.Ref 48), cast (create_element_obj ''script'' [cast (character_data_ptr.Ref 7)] fmempty
None)),
                                              (cast (character_data_ptr.Ref 7), cast (create_character_data_obj ''%3C%3Cscript%3E%3E'')),
                                                (cast (element_ptr.Ref 49), cast (create_element_obj ''div'' [cast (element_ptr.Ref 50)] (fmap_of_list
[(''id'', ''test_default_slot'')] None)),
                                                  (cast (element_ptr.Ref 50), cast (create_element_obj ''div'' [cast (element_ptr.Ref 51), cast (element_ptr.Ref
52), cast (element_ptr.Ref 53)] (fmap_of_list [(''id'', ''host'')] (Some (cast (shadow_root_ptr.Ref 5))))),
                                                    (cast (element_ptr.Ref 51), cast (create_element_obj ''div'' [] (fmap_of_list [(''id'', ''c1'')] None)),
                                                      (cast (element_ptr.Ref 52), cast (create_element_obj ''div'' [] (fmap_of_list [(''id'', ''c2''), (''slot'',
''slot1'')] None)),
                                                        (cast (element_ptr.Ref 53), cast (create_element_obj ''div'' [] (fmap_of_list [(''id'', ''c3''), (''slot'',
''foo'')] None)),
                                                          (cast (shadow_root_ptr.Ref 5), cast (create_shadow_root_obj Open [cast (element_ptr.Ref 54), cast (element_ptr.
55), cast (element_ptr.Ref 56)])),
                (cast (element_ptr.Ref 54), cast (create_element_obj ''slot'' [] (fmap_of_list [(''id'', ''s1''), (''name'',
''slot1'')] None)),
                  (cast (element_ptr.Ref 55), cast (create_element_obj ''slot'' [] (fmap_of_list [(''id'', ''s2'')] None)),
                    (cast (element_ptr.Ref 56), cast (create_element_obj ''slot'' [] (fmap_of_list [(''id'', ''s3'')] None)),
                      (cast (element_ptr.Ref 57), cast (create_element_obj ''script'' [cast (character_data_ptr.Ref 8)] fmempty
None)),
                        (cast (character_data_ptr.Ref 8), cast (create_character_data_obj ''%3C%3Cscript%3E%3E'')),
                          (cast (element_ptr.Ref 58), cast (create_element_obj ''div'' [cast (element_ptr.Ref 59)] (fmap_of_list

```

```

[("id", "test_slot_in_slot")]) None)),
  (cast (element_ptr.Ref 59), cast (create_element_obj "div" [cast (element_ptr.Ref 60), cast (element_ptr.Ref 61)] (fmap_of_list [(("id", "host")]) (Some (cast (shadow_root_ptr.Ref 6))))),
   (cast (element_ptr.Ref 60), cast (create_element_obj "div" [] (fmap_of_list [(("id", "c1"), ("slot", "slot2")]) None)),
    (cast (element_ptr.Ref 61), cast (create_element_obj "div" [] (fmap_of_list [(("id", "c2"), ("slot", "slot1")]) None)),
     (cast (shadow_root_ptr.Ref 6), cast (create_shadow_root_obj Open [cast (element_ptr.Ref 62)])),
      (cast (element_ptr.Ref 62), cast (create_element_obj "slot" [cast (element_ptr.Ref 63)] (fmap_of_list [(("id", "s1"), ("name", "slot1")]) None)),
       (cast (element_ptr.Ref 63), cast (create_element_obj "slot" [] (fmap_of_list [(("id", "s2"), ("name", "slot2")]) None)),
        (cast (element_ptr.Ref 64), cast (create_element_obj "script" [cast (character_data_ptr.Ref 9)] fmempty None)),
         (cast (character_data_ptr.Ref 9), cast (create_character_data_obj "%3C%3Cscript%3E%3E")),
          (cast (element_ptr.Ref 65), cast (create_element_obj "div" [cast (element_ptr.Ref 66)] (fmap_of_list [(("id", "test_slot_is_assigned_to_slot")]) None)),
           (cast (element_ptr.Ref 66), cast (create_element_obj "div" [cast (element_ptr.Ref 67)] (fmap_of_list [(("id", "host1")]) (Some (cast (shadow_root_ptr.Ref 7))))),
            (cast (element_ptr.Ref 67), cast (create_element_obj "div" [] (fmap_of_list [(("id", "c1"), ("slot", "slot1")]) None)),
             (cast (shadow_root_ptr.Ref 7), cast (create_shadow_root_obj Open [cast (element_ptr.Ref 68)])),
              (cast (element_ptr.Ref 68), cast (create_element_obj "div" [cast (element_ptr.Ref 69)] (fmap_of_list [(("id", "host2")]) (Some (cast (shadow_root_ptr.Ref 8))))),
               (cast (element_ptr.Ref 69), cast (create_element_obj "slot" [] (fmap_of_list [(("id", "s1"), ("name", "slot1"), ("slot", "slot2")]) None)),
                (cast (shadow_root_ptr.Ref 8), cast (create_shadow_root_obj Open [cast (element_ptr.Ref 70)])),
                 (cast (element_ptr.Ref 70), cast (create_element_obj "slot" [] (fmap_of_list [(("id", "s2"), ("name", "slot2")]) None)),
                  (cast (element_ptr.Ref 71), cast (create_element_obj "script" [cast (character_data_ptr.Ref 10)] fmempty None)),
                   (cast (character_data_ptr.Ref 10), cast (create_character_data_obj "%3C%3Cscript%3E%3E")),
                    (cast (element_ptr.Ref 72), cast (create_element_obj "div" [cast (element_ptr.Ref 73)] (fmap_of_list [(("id", "test_open_closed")]) None)),
                     (cast (element_ptr.Ref 73), cast (create_element_obj "div" [cast (element_ptr.Ref 74)] (fmap_of_list [(("id", "host1")]) (Some (cast (shadow_root_ptr.Ref 9))))),
                      (cast (element_ptr.Ref 74), cast (create_element_obj "div" [] (fmap_of_list [(("id", "c1"), ("slot", "slot1")]) None)),
                       (cast (shadow_root_ptr.Ref 9), cast (create_shadow_root_obj Open [cast (element_ptr.Ref 75)])),
                        (cast (element_ptr.Ref 75), cast (create_element_obj "div" [cast (element_ptr.Ref 76)] (fmap_of_list [(("id", "host2")]) (Some (cast (shadow_root_ptr.Ref 10))))),
                         (cast (element_ptr.Ref 76), cast (create_element_obj "slot" [] (fmap_of_list [(("id", "s1"), ("name", "slot1"), ("slot", "slot2")]) None)),
                          (cast (shadow_root_ptr.Ref 10), cast (create_shadow_root_obj Closed [cast (element_ptr.Ref 77)])),
                           (cast (element_ptr.Ref 77), cast (create_element_obj "slot" [] (fmap_of_list [(("id", "s2"), ("name", "slot2")]) None)),
                            (cast (element_ptr.Ref 78), cast (create_element_obj "script" [cast (character_data_ptr.Ref 11)] fmempty None)),
                             (cast (character_data_ptr.Ref 11), cast (create_character_data_obj "%3C%3Cscript%3E%3E")),
                              (cast (element_ptr.Ref 79), cast (create_element_obj "div" [cast (element_ptr.Ref 80)] (fmap_of_list [(("id", "test_closed_closed")]) None)),
                               (cast (element_ptr.Ref 80), cast (create_element_obj "div" [cast (element_ptr.Ref 81)] (fmap_of_list [(("id", "host1")]) (Some (cast (shadow_root_ptr.Ref 11))))),
                                (cast (element_ptr.Ref 81), cast (create_element_obj "div" [] (fmap_of_list [(("id", "c1"), ("slot", "slot1")]) None)),
                                 (cast (shadow_root_ptr.Ref 11), cast (create_shadow_root_obj Closed [cast (element_ptr.Ref 82)])),
                                  (cast (element_ptr.Ref 82), cast (create_element_obj "div" [cast (element_ptr.Ref 83)] (fmap_of_list [(("id", "host2")]) (Some (cast (shadow_root_ptr.Ref 12))))),
                                   (cast (element_ptr.Ref 83), cast (create_element_obj "slot" [] (fmap_of_list [(("id", "s1"), ("name", "slot1"), ("slot", "slot2")]) None)),
                                    (cast (shadow_root_ptr.Ref 12), cast (create_shadow_root_obj Closed [cast (element_ptr.Ref 84)])),
                                     (cast (element_ptr.Ref 84), cast (create_element_obj "slot" [] (fmap_of_list [(("id", "s2"), ("name", "slot2")]) None))))))

```

```

(cast (element_ptr.Ref 85), cast (create_element_obj ''script'' [cast (character_data_ptr.Ref 12)] fmempty
None)),
  (cast (character_data_ptr.Ref 12), cast (create_character_data_obj ''%3C%3Cscript%3E%3E'')),
    (cast (element_ptr.Ref 86), cast (create_element_obj ''div'' [cast (element_ptr.Ref 87)] (fmap_of_list
[(''id'', ''test_closed_open'')] None)),
      (cast (element_ptr.Ref 87), cast (create_element_obj ''div'' [cast (element_ptr.Ref 88)] (fmap_of_list
[(''id'', ''host1'')] (Some (cast (shadow_root_ptr.Ref 13))))),
        (cast (element_ptr.Ref 88), cast (create_element_obj ''div'' [] (fmap_of_list [((''id'', ''c1''), (''slot'',
''slot1'')] None)),
          (cast (shadow_root_ptr.Ref 13), cast (create_shadow_root_obj Closed [cast (element_ptr.Ref 89)])),
            (cast (element_ptr.Ref 89), cast (create_element_obj ''div'' [cast (element_ptr.Ref 90)] (fmap_of_list
[(''id'', ''host2'')] (Some (cast (shadow_root_ptr.Ref 14))))),
              (cast (element_ptr.Ref 90), cast (create_element_obj ''slot'' [] (fmap_of_list [((''id'', ''s1''), (''name'',
''slot1''), (''slot'', ''slot2'')] None)),
                (cast (shadow_root_ptr.Ref 14), cast (create_shadow_root_obj Open [cast (element_ptr.Ref 91)])),
                  (cast (element_ptr.Ref 91), cast (create_element_obj ''slot'' [] (fmap_of_list [((''id'', ''s2''), (''name'',
''slot2'')] None)),
                    (cast (element_ptr.Ref 92), cast (create_element_obj ''script'' [cast (character_data_ptr.Ref 13)] fmempty
None)),
                      (cast (character_data_ptr.Ref 13), cast (create_character_data_obj ''%3C%3Cscript%3E%3E'')),
                        (cast (element_ptr.Ref 93), cast (create_element_obj ''div'' [cast (element_ptr.Ref 94)] (fmap_of_list
[(''id'', ''test_complex'')] None)),
                          (cast (element_ptr.Ref 94), cast (create_element_obj ''div'' [cast (element_ptr.Ref 95), cast (element_ptr.Ref
96), cast (element_ptr.Ref 97), cast (element_ptr.Ref 98)] (fmap_of_list [((''id'', ''host1'')] (Some (cast
(shadow_root_ptr.Ref 15))))),
                            (cast (element_ptr.Ref 95), cast (create_element_obj ''div'' [] (fmap_of_list [((''id'', ''c1''), (''slot'',
''slot1'')] None)),
                              (cast (element_ptr.Ref 96), cast (create_element_obj ''div'' [] (fmap_of_list [((''id'', ''c2''), (''slot'',
''slot2'')] None)),
                                (cast (element_ptr.Ref 97), cast (create_element_obj ''div'' [] (fmap_of_list [((''id'', ''c3'')] None)),
                                  (cast (element_ptr.Ref 98), cast (create_element_obj ''div'' [] (fmap_of_list [((''id'', ''c4''), (''slot'',
''slot-none'')] None)),
                                    (cast (shadow_root_ptr.Ref 15), cast (create_shadow_root_obj Open [cast (element_ptr.Ref 99)])),
                                      (cast (element_ptr.Ref 99), cast (create_element_obj ''div'' [cast (element_ptr.Ref 100), cast (element_ptr.Ref
101), cast (element_ptr.Ref 102), cast (element_ptr.Ref 103), cast (element_ptr.Ref 104), cast (element_ptr.Ref
105), cast (element_ptr.Ref 106), cast (element_ptr.Ref 107)] (fmap_of_list [((''id'', ''host2'')] (Some
(cast (shadow_root_ptr.Ref 16))))),
                                        (cast (element_ptr.Ref 100), cast (create_element_obj ''slot'' [] (fmap_of_list [((''id'', ''s1''), (''name'',
''slot1''), (''slot'', ''slot5'')] None)),
                                          (cast (element_ptr.Ref 101), cast (create_element_obj ''slot'' [] (fmap_of_list [((''id'', ''s2''), (''name'',
''slot2''), (''slot'', ''slot6'')] None)),
                                            (cast (element_ptr.Ref 102), cast (create_element_obj ''slot'' [] (fmap_of_list [((''id'', ''s3'')] None)),
                                              (cast (element_ptr.Ref 103), cast (create_element_obj ''slot'' [] (fmap_of_list [((''id'', ''s4''), (''name'',
''slot4''), (''slot'', ''slot-none'')] None)),
                                                (cast (element_ptr.Ref 104), cast (create_element_obj ''div'' [] (fmap_of_list [((''id'', ''c5''), (''slot'',
''slot5'')] None)),
                                                  (cast (element_ptr.Ref 105), cast (create_element_obj ''div'' [] (fmap_of_list [((''id'', ''c6''), (''slot'',
''slot6'')] None)),
                                                    (cast (element_ptr.Ref 106), cast (create_element_obj ''div'' [] (fmap_of_list [((''id'', ''c7'')] None)),
                                                      (cast (element_ptr.Ref 107), cast (create_element_obj ''div'' [] (fmap_of_list [((''id'', ''c8''), (''slot'',
''slot-none'')] None)),
                                                        (cast (shadow_root_ptr.Ref 16), cast (create_shadow_root_obj Open [cast (element_ptr.Ref 108), cast
(element_ptr.Ref 109), cast (element_ptr.Ref 110), cast (element_ptr.Ref 111)])),
                                                          (cast (element_ptr.Ref 108), cast (create_element_obj ''slot'' [] (fmap_of_list [((''id'', ''s5''), (''name'',
''slot5'')] None)),
                                                            (cast (element_ptr.Ref 109), cast (create_element_obj ''slot'' [] (fmap_of_list [((''id'', ''s6''), (''name'',
''slot6'')] None)),
                                                              (cast (element_ptr.Ref 110), cast (create_element_obj ''slot'' [] (fmap_of_list [((''id'', ''s7'')] None)),
                                                                (cast (element_ptr.Ref 111), cast (create_element_obj ''slot'' [] (fmap_of_list [((''id'', ''s8''), (''name'',
''slot8'')] None)),
                                                                  (cast (element_ptr.Ref 112), cast (create_element_obj ''script'' [cast (character_data_ptr.Ref 14)])

```

```

fmempty None)),
  (cast (character_data_ptr.Ref 14), cast (create_character_data_obj ''%3C%3Cscript%3E%3E''))]"
```

definition slots_document :: "(unit, unit, unit, unit, unit) object_ptr option" where "slots_document = Some (cast (document_ptr.Ref 1))"

'Slots: Basic.'

```

lemma "test (do {
  tmp0 ← slots_document . getElementById(''test_basic'');
  n ← createTestTree(tmp0);
  tmp1 ← n . ''test_basic'';
  removeWhiteSpaceOnlyTextNodes(tmp1);
  tmp2 ← n . ''c1'';
  tmp3 ← tmp2 . assignedSlot;
  tmp4 ← n . ''s1'';
  assert_equals(tmp3, tmp4);
  tmp5 ← n . ''s1'';
  tmp6 ← tmp5 . assignedNodes();
  tmp7 ← n . ''c1'';
  assert_array_equals(tmp6, [tmp7])
}) slots_heap"
  ⟨proof⟩
```

'Slots: Basic, elements only.'

```

lemma "test (do {
  tmp0 ← slots_document . getElementById(''test_basic'');
  n ← createTestTree(tmp0);
  tmp1 ← n . ''s1'';
  tmp2 ← tmp1 . assignedElements();
  tmp3 ← n . ''c1'';
  assert_array_equals(tmp2, [tmp3])
}) slots_heap"
  ⟨proof⟩
```

'Slots: Slots in closed.'

```

lemma "test (do {
  tmp0 ← slots_document . getElementById(''test_basic_closed'');
  n ← createTestTree(tmp0);
  tmp1 ← n . ''test_basic_closed'';
  removeWhiteSpaceOnlyTextNodes(tmp1);
  tmp2 ← n . ''c1'';
  tmp3 ← tmp2 . assignedSlot;
  assert_equals(tmp3, None);
  tmp4 ← n . ''s1'';
  tmp5 ← tmp4 . assignedNodes();
  tmp6 ← n . ''c1'';
  assert_array_equals(tmp5, [tmp6])
}) slots_heap"
  ⟨proof⟩
```

'Slots: Slots in closed, elements only.'

```

lemma "test (do {
  tmp0 ← slots_document . getElementById(''test_basic_closed'');
  n ← createTestTree(tmp0);
  tmp1 ← n . ''s1'';
  tmp2 ← tmp1 . assignedElements();
  tmp3 ← n . ''c1'';
  assert_array_equals(tmp2, [tmp3])
}) slots_heap"
  ⟨proof⟩
```

'Slots: Slots not in a shadow tree.'

```

lemma "test (do {
```

3 Test Suite

```

tmp0 ← slots_document . getElementById(''test_slot_not_in_shadow'');
n ← createTestTree(tmp0);
tmp1 ← n . ''test_slot_not_in_shadow'';
removeWhiteSpaceOnlyTextNodes(tmp1);
tmp2 ← n . ''s1'';
tmp3 ← tmp2 . assignedNodes();
assert_array_equals(tmp3, [])
}) slots_heap"
⟨proof⟩

```

'Slots: Slots not in a shadow tree, elements only.'

```

lemma "test (do {
    tmp0 ← slots_document . getElementById(''test_slot_not_in_shadow'');
    n ← createTestTree(tmp0);
    tmp1 ← n . ''s1'';
    tmp2 ← tmp1 . assignedElements();
    assert_array_equals(tmp2, [])
}) slots_heap"
⟨proof⟩

```

'Slots: Distributed nodes for Slots not in a shadow tree.'

```

lemma "test (do {
    tmp0 ← slots_document . getElementById(''test_slot_not_in_shadow_2'');
    n ← createTestTree(tmp0);
    tmp1 ← n . ''test_slot_not_in_shadow_2'';
    removeWhiteSpaceOnlyTextNodes(tmp1);
    tmp2 ← n . ''c1'';
    tmp3 ← tmp2 . assignedSlot;
    assert_equals(tmp3, None);
    tmp4 ← n . ''c2'';
    tmp5 ← tmp4 . assignedSlot;
    assert_equals(tmp5, None);
    tmp6 ← n . ''c3_1'';
    tmp7 ← tmp6 . assignedSlot;
    assert_equals(tmp7, None);
    tmp8 ← n . ''c3_2'';
    tmp9 ← tmp8 . assignedSlot;
    assert_equals(tmp9, None);
    tmp10 ← n . ''s1'';
    tmp11 ← tmp10 . assignedNodes();
    assert_array_equals(tmp11, []);
    tmp12 ← n . ''s2'';
    tmp13 ← tmp12 . assignedNodes();
    assert_array_equals(tmp13, []);
    tmp14 ← n . ''s3'';
    tmp15 ← tmp14 . assignedNodes();
    assert_array_equals(tmp15, []);
    tmp16 ← n . ''s1'';
    tmp17 ← tmp16 . assignedNodes(True);
    assert_array_equals(tmp17, []);
    tmp18 ← n . ''s2'';
    tmp19 ← tmp18 . assignedNodes(True);
    assert_array_equals(tmp19, []);
    tmp20 ← n . ''s3'';
    tmp21 ← tmp20 . assignedNodes(True);
    assert_array_equals(tmp21, [])
}) slots_heap"
⟨proof⟩

```

'Slots: Name matching'

```

lemma "test (do {
    tmp0 ← slots_document . getElementById(''test_slot_name_matching'');
    n ← createTestTree(tmp0);

```

```

tmp1 ← n . ''test_slot_name_matching'';
removeWhiteSpaceOnlyTextNodes(tmp1);
tmp2 ← n . ''c1'';
tmp3 ← tmp2 . assignedSlot;
tmp4 ← n . ''s1'';
assert_equals(tmp3, tmp4);
tmp5 ← n . ''c2'';
tmp6 ← tmp5 . assignedSlot;
tmp7 ← n . ''s2'';
assert_equals(tmp6, tmp7);
tmp8 ← n . ''c3'';
tmp9 ← tmp8 . assignedSlot;
assert_equals(tmp9, None)
}) slots_heap"
⟨proof⟩

'Slots: No direct host child.'

lemma "test (do {
tmp0 ← slots_document . getElementById(''test_no_direct_host_child'');
n ← createTestTree(tmp0);
tmp1 ← n . ''test_no_direct_host_child'';
removeWhiteSpaceOnlyTextNodes(tmp1);
tmp2 ← n . ''c1'';
tmp3 ← tmp2 . assignedSlot;
tmp4 ← n . ''s1'';
assert_equals(tmp3, tmp4);
tmp5 ← n . ''c2'';
tmp6 ← tmp5 . assignedSlot;
tmp7 ← n . ''s1'';
assert_equals(tmp6, tmp7);
tmp8 ← n . ''c3'';
tmp9 ← tmp8 . assignedSlot;
assert_equals(tmp9, None);
tmp10 ← n . ''s1'';
tmp11 ← tmp10 . assignedNodes();
tmp12 ← n . ''c1'';
tmp13 ← n . ''c2'';
assert_array_equals(tmp11, [tmp12, tmp13])
}) slots_heap"
⟨proof⟩

'Slots: Default Slot.'

lemma "test (do {
tmp0 ← slots_document . getElementById(''test_default_slot'');
n ← createTestTree(tmp0);
tmp1 ← n . ''test_default_slot'';
removeWhiteSpaceOnlyTextNodes(tmp1);
tmp2 ← n . ''c1'';
tmp3 ← tmp2 . assignedSlot;
tmp4 ← n . ''s2'';
assert_equals(tmp3, tmp4);
tmp5 ← n . ''c2'';
tmp6 ← tmp5 . assignedSlot;
tmp7 ← n . ''s2'';
assert_equals(tmp6, tmp7);
tmp8 ← n . ''c3'';
tmp9 ← tmp8 . assignedSlot;
assert_equals(tmp9, None)
}) slots_heap"
⟨proof⟩

'Slots: Slot in Slot does not matter in assignment.'

lemma "test (do {

```

3 Test Suite

```

tmp0 ← slots_document . getElementById(''test_slot_in_slot'');
n ← createTestTree(tmp0);
tmp1 ← n . ''test_slot_in_slot'';
removeWhiteSpaceOnlyTextNodes(tmp1);
tmp2 ← n . ''c1'';
tmp3 ← tmp2 . assignedSlot;
tmp4 ← n . ''s2'';
assert_equals(tmp3, tmp4);
tmp5 ← n . ''c2'';
tmp6 ← tmp5 . assignedSlot;
tmp7 ← n . ''s1'';
assert_equals(tmp6, tmp7)
}) slots_heap"
⟨proof⟩

'Slots: Slot is assigned to another slot'

lemma "test (do {
tmp0 ← slots_document . getElementById(''test_slot_is_assigned_to_slot'');
n ← createTestTree(tmp0);
tmp1 ← n . ''test_slot_is_assigned_to_slot'';
removeWhiteSpaceOnlyTextNodes(tmp1);
tmp2 ← n . ''c1'';
tmp3 ← tmp2 . assignedSlot;
tmp4 ← n . ''s1'';
assert_equals(tmp3, tmp4);
tmp5 ← n . ''s1'';
tmp6 ← tmp5 . assignedSlot;
tmp7 ← n . ''s2'';
assert_equals(tmp6, tmp7);
tmp8 ← n . ''s1'';
tmp9 ← tmp8 . assignedNodes();
tmp10 ← n . ''c1'';
assert_array_equals(tmp9, [tmp10]);
tmp11 ← n . ''s2'';
tmp12 ← tmp11 . assignedNodes();
tmp13 ← n . ''s1'';
assert_array_equals(tmp12, [tmp13]);
tmp14 ← n . ''s1'';
tmp15 ← tmp14 . assignedNodes(True);
tmp16 ← n . ''c1'';
assert_array_equals(tmp15, [tmp16]);
tmp17 ← n . ''s2'';
tmp18 ← tmp17 . assignedNodes(True);
tmp19 ← n . ''c1'';
assert_array_equals(tmp18, [tmp19])
}) slots_heap"
⟨proof⟩

'Slots: Open > Closed.'

lemma "test (do {
tmp0 ← slots_document . getElementById(''test_open_closed'');
n ← createTestTree(tmp0);
tmp1 ← n . ''test_open_closed'';
removeWhiteSpaceOnlyTextNodes(tmp1);
tmp2 ← n . ''c1'';
tmp3 ← tmp2 . assignedSlot;
tmp4 ← n . ''s1'';
assert_equals(tmp3, tmp4);
tmp5 ← n . ''s1'';
tmp6 ← tmp5 . assignedSlot;
assert_equals(tmp6, None, ''A slot in a closed shadow tree should not be accessed via assignedSlot'');
tmp7 ← n . ''s1'';
tmp8 ← tmp7 . assignedNodes();

```

```

tmp9 ← n . ''c1'';
assert_array_equals(tmp8, [tmp9]);
tmp10 ← n . ''s2'';
tmp11 ← tmp10 . assignedNodes();
tmp12 ← n . ''s1'';
assert_array_equals(tmp11, [tmp12]);
tmp13 ← n . ''s1'';
tmp14 ← tmp13 . assignedNodes(True);
tmp15 ← n . ''c1'';
assert_array_equals(tmp14, [tmp15]);
tmp16 ← n . ''s2'';
tmp17 ← tmp16 . assignedNodes(True);
tmp18 ← n . ''c1'';
assert_array_equals(tmp17, [tmp18])
}) slots_heap"
⟨proof⟩

'Slots: Closed > Closed.'

lemma "test (do {
  tmp0 ← slots_document . getElementById(''test_closed_closed'');
  n ← createTestTree(tmp0);
  tmp1 ← n . ''test_closed_closed'';
  removeWhiteSpaceOnlyTextNodes(tmp1);
  tmp2 ← n . ''c1'';
  tmp3 ← tmp2 . assignedSlot;
  assert_equals(tmp3, None, ''A slot in a closed shadow tree should not be accessed via assignedSlot'');
  tmp4 ← n . ''s1'';
  tmp5 ← tmp4 . assignedSlot;
  assert_equals(tmp5, None, ''A slot in a closed shadow tree should not be accessed via assignedSlot'');
  tmp6 ← n . ''s1'';
  tmp7 ← tmp6 . assignedNodes();
  tmp8 ← n . ''c1'';
  assert_array_equals(tmp7, [tmp8]);
  tmp9 ← n . ''s2'';
  tmp10 ← tmp9 . assignedNodes();
  tmp11 ← n . ''s1'';
  assert_array_equals(tmp10, [tmp11]);
  tmp12 ← n . ''s1'';
  tmp13 ← tmp12 . assignedNodes(True);
  tmp14 ← n . ''c1'';
  assert_array_equals(tmp13, [tmp14]);
  tmp15 ← n . ''s2'';
  tmp16 ← tmp15 . assignedNodes(True);
  tmp17 ← n . ''c1'';
  assert_array_equals(tmp16, [tmp17])
}) slots_heap"
⟨proof⟩

'Slots: Closed > Open.'

lemma "test (do {
  tmp0 ← slots_document . getElementById(''test_closed_open'');
  n ← createTestTree(tmp0);
  tmp1 ← n . ''test_closed_open'';
  removeWhiteSpaceOnlyTextNodes(tmp1);
  tmp2 ← n . ''c1'';
  tmp3 ← tmp2 . assignedSlot;
  assert_equals(tmp3, None, ''A slot in a closed shadow tree should not be accessed via assignedSlot'');
  tmp4 ← n . ''s1'';
  tmp5 ← tmp4 . assignedSlot;
  tmp6 ← n . ''s2'';
  assert_equals(tmp5, tmp6);
  tmp7 ← n . ''s1'';
  tmp8 ← tmp7 . assignedNodes();

```

3 Test Suite

```

tmp9 ← n . ''c1'';
assert_array_equals(tmp8, [tmp9]);
tmp10 ← n . ''s2'';
tmp11 ← tmp10 . assignedNodes();
tmp12 ← n . ''s1'';
assert_array_equals(tmp11, [tmp12]);
tmp13 ← n . ''s1'';
tmp14 ← tmp13 . assignedNodes(True);
tmp15 ← n . ''c1'';
assert_array_equals(tmp14, [tmp15]);
tmp16 ← n . ''s2'';
tmp17 ← tmp16 . assignedNodes(True);
tmp18 ← n . ''c1'';
assert_array_equals(tmp17, [tmp18])
}) slots_heap"
⟨proof⟩

```

'Slots: Complex case: Basi line.'

```

lemma "test (do {
  tmp0 ← slots_document . getElementById(''test_complex'');
  n ← createTestTree(tmp0);
  tmp1 ← n . ''test_complex'';
  removeWhiteSpaceOnlyTextNodes(tmp1);
  tmp2 ← n . ''c1'';
  tmp3 ← tmp2 . assignedSlot;
  tmp4 ← n . ''s1'';
  assert_equals(tmp3, tmp4);
  tmp5 ← n . ''c2'';
  tmp6 ← tmp5 . assignedSlot;
  tmp7 ← n . ''s2'';
  assert_equals(tmp6, tmp7);
  tmp8 ← n . ''c3'';
  tmp9 ← tmp8 . assignedSlot;
  tmp10 ← n . ''s3'';
  assert_equals(tmp9, tmp10);
  tmp11 ← n . ''c4'';
  tmp12 ← tmp11 . assignedSlot;
  assert_equals(tmp12, None);
  tmp13 ← n . ''s1'';
  tmp14 ← tmp13 . assignedSlot;
  tmp15 ← n . ''s5'';
  assert_equals(tmp14, tmp15);
  tmp16 ← n . ''s2'';
  tmp17 ← tmp16 . assignedSlot;
  tmp18 ← n . ''s6'';
  assert_equals(tmp17, tmp18);
  tmp19 ← n . ''s3'';
  tmp20 ← tmp19 . assignedSlot;
  tmp21 ← n . ''s7'';
  assert_equals(tmp20, tmp21);
  tmp22 ← n . ''s4'';
  tmp23 ← tmp22 . assignedSlot;
  assert_equals(tmp23, None);
  tmp24 ← n . ''c5'';
  tmp25 ← tmp24 . assignedSlot;
  tmp26 ← n . ''s5'';
  assert_equals(tmp25, tmp26);
  tmp27 ← n . ''c6'';
  tmp28 ← tmp27 . assignedSlot;
  tmp29 ← n . ''s6'';
  assert_equals(tmp28, tmp29);
  tmp30 ← n . ''c7'';
  tmp31 ← tmp30 . assignedSlot;
})

```

```

tmp32 ← n . ''s7'';
assert_equals(tmp31, tmp32);
tmp33 ← n . ''c8'';
tmp34 ← tmp33 . assignedSlot;
assert_equals(tmp34, None);
tmp35 ← n . ''s1'';
tmp36 ← tmp35 . assignedNodes();
tmp37 ← n . ''c1'';
assert_array_equals(tmp36, [tmp37]);
tmp38 ← n . ''s2'';
tmp39 ← tmp38 . assignedNodes();
tmp40 ← n . ''c2'';
assert_array_equals(tmp39, [tmp40]);
tmp41 ← n . ''s3'';
tmp42 ← tmp41 . assignedNodes();
tmp43 ← n . ''c3'';
assert_array_equals(tmp42, [tmp43]);
tmp44 ← n . ''s4'';
tmp45 ← tmp44 . assignedNodes();
assert_array_equals(tmp45, []);
tmp46 ← n . ''s5'';
tmp47 ← tmp46 . assignedNodes();
tmp48 ← n . ''s1'';
tmp49 ← n . ''c5'';
assert_array_equals(tmp47, [tmp48, tmp49]);
tmp50 ← n . ''s6'';
tmp51 ← tmp50 . assignedNodes();
tmp52 ← n . ''s2'';
tmp53 ← n . ''c6'';
assert_array_equals(tmp51, [tmp52, tmp53]);
tmp54 ← n . ''s7'';
tmp55 ← tmp54 . assignedNodes();
tmp56 ← n . ''s3'';
tmp57 ← n . ''c7'';
assert_array_equals(tmp55, [tmp56, tmp57]);
tmp58 ← n . ''s8'';
tmp59 ← tmp58 . assignedNodes();
assert_array_equals(tmp59, []);
tmp60 ← n . ''s1'';
tmp61 ← tmp60 . assignedNodes(True);
tmp62 ← n . ''c1'';
assert_array_equals(tmp61, [tmp62]);
tmp63 ← n . ''s2'';
tmp64 ← tmp63 . assignedNodes(True);
tmp65 ← n . ''c2'';
assert_array_equals(tmp64, [tmp65]);
tmp66 ← n . ''s3'';
tmp67 ← tmp66 . assignedNodes(True);
tmp68 ← n . ''c3'';
assert_array_equals(tmp67, [tmp68]);
tmp69 ← n . ''s4'';
tmp70 ← tmp69 . assignedNodes(True);
assert_array_equals(tmp70, []);
tmp71 ← n . ''s5'';
tmp72 ← tmp71 . assignedNodes(True);
tmp73 ← n . ''c1'';
tmp74 ← n . ''c5'';
assert_array_equals(tmp72, [tmp73, tmp74]);
tmp75 ← n . ''s6'';
tmp76 ← tmp75 . assignedNodes(True);
tmp77 ← n . ''c2'';
tmp78 ← n . ''c6'';
assert_array_equals(tmp76, [tmp77, tmp78]);

```

3 Test Suite

```
tmp79 ← n . ''s7'';
tmp80 ← tmp79 . assignedNodes(True);
tmp81 ← n . ''c3'';
tmp82 ← n . ''c7'';
assert_array_equals(tmp80, [tmp81, tmp82]);
tmp83 ← n . ''s8'';
tmp84 ← tmp83 . assignedNodes(True);
assert_array_equals(tmp84, [])
}) slots_heap"
⟨proof⟩

'Slots: Mutation: appendChild.'

lemma "test (do {
  tmp0 ← slots_document . getElementById(''test_complex'');
  n ← createTestTree(tmp0);
  tmp1 ← n . ''test_complex'';
  removeWhiteSpaceOnlyTextNodes(tmp1);
  d1 ← slots_document . createElement(''div'');
  d1 . setAttribute(''slot'', ''slot1'');
  tmp2 ← n . ''host1'';
  tmp2 . appendChild(d1);
  tmp3 ← n . ''s1'';
  tmp4 ← tmp3 . assignedNodes();
  tmp5 ← n . ''c1'';
  assert_array_equals(tmp4, [tmp5, d1]);
  tmp6 ← d1 . assignedSlot;
  tmp7 ← n . ''s1'';
  assert_equals(tmp6, tmp7);
  tmp8 ← n . ''s5'';
  tmp9 ← tmp8 . assignedNodes(True);
  tmp10 ← n . ''c1'';
  tmp11 ← n . ''c5'';
  assert_array_equals(tmp9, [tmp10, d1, tmp11])
}) slots_heap"
⟨proof⟩

'Slots: Mutation: Change slot= attribute 1.'

lemma "test (do {
  tmp0 ← slots_document . getElementById(''test_complex'');
  n ← createTestTree(tmp0);
  tmp1 ← n . ''test_complex'';
  removeWhiteSpaceOnlyTextNodes(tmp1);
  tmp2 ← n . ''c1'';
  tmp2 . setAttribute(''slot'', ''slot-none'');
  tmp3 ← n . ''s1'';
  tmp4 ← tmp3 . assignedNodes();
  assert_array_equals(tmp4, []);
  tmp5 ← n . ''c1'';
  tmp6 ← tmp5 . assignedSlot;
  assert_equals(tmp6, None);
  tmp7 ← n . ''s5'';
  tmp8 ← tmp7 . assignedNodes(True);
  tmp9 ← n . ''c5'';
  assert_array_equals(tmp8, [tmp9])
}) slots_heap"
⟨proof⟩

'Slots: Mutation: Change slot= attribute 2.'

lemma "test (do {
  tmp0 ← slots_document . getElementById(''test_complex'');
  n ← createTestTree(tmp0);
  tmp1 ← n . ''test_complex'';
  removeWhiteSpaceOnlyTextNodes(tmp1);
```

```

tmp2 ← n . ''c1'';
tmp2 . setAttribute(''slot'', ''slot2'');
tmp3 ← n . ''s1'';
tmp4 ← tmp3 . assignedNodes();
assert_array_equals(tmp4, []);
tmp5 ← n . ''s2'';
tmp6 ← tmp5 . assignedNodes();
tmp7 ← n . ''c1'';
tmp8 ← n . ''c2'';
assert_array_equals(tmp6, [tmp7, tmp8]);
tmp9 ← n . ''c1'';
tmp10 ← tmp9 . assignedSlot;
tmp11 ← n . ''s2'';
assert_equals(tmp10, tmp11);
tmp12 ← n . ''s5'';
tmp13 ← tmp12 . assignedNodes(True);
tmp14 ← n . ''c5'';
assert_array_equals(tmp13, [tmp14]);
tmp15 ← n . ''s6'';
tmp16 ← tmp15 . assignedNodes(True);
tmp17 ← n . ''c1'';
tmp18 ← n . ''c2'';
tmp19 ← n . ''c6'';
assert_array_equals(tmp16, [tmp17, tmp18, tmp19])
}) slots_heap"
⟨proof⟩

```

'Slots: Mutation: Change slot= attribute 3.'

```

lemma "test (do {
tmp0 ← slots_document . getElementById(''test_complex'');
n ← createTestTree(tmp0);
tmp1 ← n . ''test_complex'';
removeWhiteSpaceOnlyTextNodes(tmp1);
tmp2 ← n . ''c4'';
tmp2 . setAttribute(''slot'', ''slot1'');
tmp3 ← n . ''s1'';
tmp4 ← tmp3 . assignedNodes();
tmp5 ← n . ''c1'';
tmp6 ← n . ''c4'';
assert_array_equals(tmp4, [tmp5, tmp6]);
tmp7 ← n . ''c4'';
tmp8 ← tmp7 . assignedSlot;
tmp9 ← n . ''s1'';
assert_equals(tmp8, tmp9);
tmp10 ← n . ''s5'';
tmp11 ← tmp10 . assignedNodes(True);
tmp12 ← n . ''c1'';
tmp13 ← n . ''c4'';
tmp14 ← n . ''c5'';
assert_array_equals(tmp11, [tmp12, tmp13, tmp14])
}) slots_heap"
⟨proof⟩

```

'Slots: Mutation: Remove a child.'

```

lemma "test (do {
tmp0 ← slots_document . getElementById(''test_complex'');
n ← createTestTree(tmp0);
tmp1 ← n . ''test_complex'';
removeWhiteSpaceOnlyTextNodes(tmp1);
tmp2 ← n . ''c1'';
tmp2 . remove();
tmp3 ← n . ''s1'';
tmp4 ← tmp3 . assignedNodes();

```

3 Test Suite

```

assert_array_equals(tmp4, []);
tmp5 ← n . 'c1';
tmp6 ← tmp5 . assignedSlot;
assert_equals(tmp6, None);
tmp7 ← n . 's5';
tmp8 ← tmp7 . assignedNodes(True);
tmp9 ← n . 'c5';
assert_array_equals(tmp8, [tmp9])
}) slots_heap"
⟨proof⟩

'Slots: Mutation: Add a slot: after.'

lemma "test (do {
    tmp0 ← slots_document . getElementById('test_complex');
    n ← createTestTree(tmp0);
    tmp1 ← n . 'test_complex';
    removeWhiteSpaceOnlyTextNodes(tmp1);
    slot ← slots_document . createElement('slot');
    slot . setAttribute('name', 'slot1');
    tmp2 ← n . 'host2';
    tmp2 . appendChild(slot);
    tmp3 ← slot . assignedNodes();
    assert_array_equals(tmp3, [])
}) slots_heap"
⟨proof⟩

'Slots: Mutation: Add a slot: before.'

lemma "test (do {
    tmp0 ← slots_document . getElementById('test_complex');
    n ← createTestTree(tmp0);
    tmp1 ← n . 'test_complex';
    removeWhiteSpaceOnlyTextNodes(tmp1);
    slot ← slots_document . createElement('slot');
    slot . setAttribute('name', 'slot1');
    tmp3 ← n . 's1';
    tmp2 ← n . 'host2';
    tmp2 . insertBefore(slot, tmp3);
    tmp4 ← slot . assignedNodes();
    tmp5 ← n . 'c1';
    assert_array_equals(tmp4, [tmp5]);
    tmp6 ← n . 'c1';
    tmp7 ← tmp6 . assignedSlot;
    assert_equals(tmp7, slot);
    tmp8 ← n . 's7';
    tmp9 ← tmp8 . assignedNodes();
    tmp10 ← n . 's3';
    tmp11 ← n . 'c7';
    assert_array_equals(tmp9, [slot, tmp10, tmp11]);
    tmp12 ← n . 's7';
    tmp13 ← tmp12 . assignedNodes(True);
    tmp14 ← n . 'c1';
    tmp15 ← n . 'c3';
    tmp16 ← n . 'c7';
    assert_array_equals(tmp13, [tmp14, tmp15, tmp16])
}) slots_heap"
⟨proof⟩

'Slots: Mutation: Remove a slot.'

lemma "test (do {
    tmp0 ← slots_document . getElementById('test_complex');
    n ← createTestTree(tmp0);
    tmp1 ← n . 'test_complex';
    removeWhiteSpaceOnlyTextNodes(tmp1);

```

```

tmp2 ← n . ''s1'';
tmp2 . remove();
tmp3 ← n . ''s1'';
tmp4 ← tmp3 . assignedNodes();
assert_array_equals(tmp4, []);
tmp5 ← n . ''c1'';
tmp6 ← tmp5 . assignedSlot;
assert_equals(tmp6, None);
tmp7 ← n . ''s5'';
tmp8 ← tmp7 . assignedNodes();
tmp9 ← n . ''c5'';
assert_array_equals(tmp8, [tmp9]);
tmp10 ← n . ''s5'';
tmp11 ← tmp10 . assignedNodes(True);
tmp12 ← n . ''c5'';
assert_array_equals(tmp11, [tmp12])
}) slots_heap"
⟨proof⟩

```

'Slots: Mutation: Change slot name= attribute.'

```

lemma "test (do {
  tmp0 ← slots_document . getElementById(''test_complex'');
  n ← createTestTree(tmp0);
  tmp1 ← n . ''test_complex'';
  removeWhiteSpaceOnlyTextNodes(tmp1);
  tmp2 ← n . ''s1'';
  tmp2 . setAttribute(''name'', ''slot2'');
  tmp3 ← n . ''s1'';
  tmp4 ← tmp3 . assignedNodes();
  tmp5 ← n . ''c2'';
  assert_array_equals(tmp4, [tmp5]);
  tmp6 ← n . ''c1'';
  tmp7 ← tmp6 . assignedSlot;
  assert_equals(tmp7, None);
  tmp8 ← n . ''c2'';
  tmp9 ← tmp8 . assignedSlot;
  tmp10 ← n . ''s1'';
  assert_equals(tmp9, tmp10);
  tmp11 ← n . ''s5'';
  tmp12 ← tmp11 . assignedNodes();
  tmp13 ← n . ''s1'';
  tmp14 ← n . ''c5'';
  assert_array_equals(tmp12, [tmp13, tmp14]);
  tmp15 ← n . ''s5'';
  tmp16 ← tmp15 . assignedNodes(True);
  tmp17 ← n . ''c2'';
  tmp18 ← n . ''c5'';
  assert_array_equals(tmp16, [tmp17, tmp18])
}) slots_heap"
⟨proof⟩

```

'Slots: Mutation: Change slot slot= attribute.'

```

lemma "test (do {
  tmp0 ← slots_document . getElementById(''test_complex'');
  n ← createTestTree(tmp0);
  tmp1 ← n . ''test_complex'';
  removeWhiteSpaceOnlyTextNodes(tmp1);
  tmp2 ← n . ''s1'';
  tmp2 . setAttribute(''slot'', ''slot6'');
  tmp3 ← n . ''s1'';
  tmp4 ← tmp3 . assignedNodes();
  tmp5 ← n . ''c1'';
  assert_array_equals(tmp4, [tmp5]);
}) slots_heap"
⟨proof⟩

```

```

tmp6 ← n . 's5';
tmp7 ← tmp6 . assignedNodes();
tmp8 ← n . 'c5';
assert_array_equals(tmp7, [tmp8]);
tmp9 ← n . 's6';
tmp10 ← tmp9 . assignedNodes();
tmp11 ← n . 's1';
tmp12 ← n . 's2';
tmp13 ← n . 'c6';
assert_array_equals(tmp10, [tmp11, tmp12, tmp13]);
tmp14 ← n . 's6';
tmp15 ← tmp14 . assignedNodes(True);
tmp16 ← n . 'c1';
tmp17 ← n . 'c2';
tmp18 ← n . 'c6';
assert_array_equals(tmp15, [tmp16, tmp17, tmp18])
} slots_heap"
⟨proof⟩

```

end

3.3 Testing slots_fallback (slots_fallback)

This theory contains the test cases for slots_fallback.

```

(cast (character_data_ptr.Ref 2), cast (create_character_data_obj ''%3C%3Cscript%3E%3E'')),
  (cast (element_ptr.Ref 14), cast (create_element_obj 'div' [cast (element_ptr.Ref 15)] (fmap_of_list
[('id', 'test2')])) None),
    (cast (element_ptr.Ref 15), cast (create_element_obj 'div' [] (fmap_of_list [(('id', 'host')])])
(Some (cast (shadow_root_ptr.Ref 2)))),
      (cast (shadow_root_ptr.Ref 2), cast (create_shadow_root_obj Open [cast (element_ptr.Ref 16)])),
        (cast (element_ptr.Ref 16), cast (create_element_obj 'slot' [cast (element_ptr.Ref 17)] (fmap_of_list
[('id', 's1'), ('name', 'slot1')]) None)),
          (cast (element_ptr.Ref 17), cast (create_element_obj 'slot' [cast (element_ptr.Ref 18)] (fmap_of_list
[('id', 's2'), ('name', 'slot2')]) None)),
            (cast (element_ptr.Ref 18), cast (create_element_obj 'div' [] (fmap_of_list [(('id', 'f1')]) None)),
              (cast (element_ptr.Ref 19), cast (create_element_obj 'script' [cast (character_data_ptr.Ref 3)] fmempty
None)),
                (cast (character_data_ptr.Ref 3), cast (create_character_data_obj ''%3C%3Cscript%3E%3E'')),
                  (cast (element_ptr.Ref 20), cast (create_element_obj 'div' [cast (element_ptr.Ref 21)] (fmap_of_list
[('id', 'test3')]) None),
                    (cast (element_ptr.Ref 21), cast (create_element_obj 'div' [cast (element_ptr.Ref 22)] (fmap_of_list
[('id', 'host')]) (Some (cast (shadow_root_ptr.Ref 3)))),
                      (cast (element_ptr.Ref 22), cast (create_element_obj 'div' [] (fmap_of_list [(('id', 'c1'),
('slot', 'slot1')]) None)),
                        (cast (shadow_root_ptr.Ref 3), cast (create_shadow_root_obj Open [cast (element_ptr.Ref 23)])),
                          (cast (element_ptr.Ref 23), cast (create_element_obj 'slot' [cast (element_ptr.Ref 24)] (fmap_of_list
[('id', 's1'), ('name', 'slot1')]) None)),
                            (cast (element_ptr.Ref 24), cast (create_element_obj 'slot' [cast (element_ptr.Ref 25)] (fmap_of_list
[('id', 's2'), ('name', 'slot2')]) None)),
                              (cast (element_ptr.Ref 25), cast (create_element_obj 'div' [] (fmap_of_list [(('id', 'f1')]) None)),
                                (cast (element_ptr.Ref 26), cast (create_element_obj 'script' [cast (character_data_ptr.Ref 4)] fmempty
None)),
                                  (cast (character_data_ptr.Ref 4), cast (create_character_data_obj ''%3C%3Cscript%3E%3E'')),
                                    (cast (element_ptr.Ref 27), cast (create_element_obj 'div' [cast (element_ptr.Ref 28)] (fmap_of_list
[('id', 'test4')]) None),
                                      (cast (element_ptr.Ref 28), cast (create_element_obj 'div' [cast (element_ptr.Ref 29)] (fmap_of_list
[('id', 'host')]) (Some (cast (shadow_root_ptr.Ref 4)))),
                                        (cast (element_ptr.Ref 29), cast (create_element_obj 'div' [] (fmap_of_list [(('id', 'c1'),
('slot', 'slot2')]) None)),
                                          (cast (shadow_root_ptr.Ref 4), cast (create_shadow_root_obj Open [cast (element_ptr.Ref 30)])),
                                            (cast (element_ptr.Ref 30), cast (create_element_obj 'slot' [cast (element_ptr.Ref 31)] (fmap_of_list
[('id', 's1'), ('name', 'slot1')]) None)),
                                              (cast (element_ptr.Ref 31), cast (create_element_obj 'slot' [cast (element_ptr.Ref 32)] (fmap_of_list
[('id', 's2'), ('name', 'slot2')]) None)),
                                                (cast (element_ptr.Ref 32), cast (create_element_obj 'div' [] (fmap_of_list [(('id', 'f1')]) None)),
                                                  (cast (element_ptr.Ref 33), cast (create_element_obj 'script' [cast (character_data_ptr.Ref 5)] fmempty
None)),
                                                    (cast (character_data_ptr.Ref 5), cast (create_character_data_obj ''%3C%3Cscript%3E%3E'')),
                                                      (cast (element_ptr.Ref 34), cast (create_element_obj 'div' [cast (element_ptr.Ref 35)] (fmap_of_list
[('id', 'test5')]) None),
                                                        (cast (element_ptr.Ref 35), cast (create_element_obj 'div' [cast (element_ptr.Ref 36)] (fmap_of_list
[('id', 'host1')]) (Some (cast (shadow_root_ptr.Ref 5)))),
                                                          (cast (element_ptr.Ref 36), cast (create_element_obj 'div' [] (fmap_of_list [(('id', 'c1'),
('slot', 'slot1')]) None)),
                                                            (cast (shadow_root_ptr.Ref 5), cast (create_shadow_root_obj Open [cast (element_ptr.Ref 37)])),
                                                              (cast (element_ptr.Ref 37), cast (create_element_obj 'div' [cast (element_ptr.Ref 38)] (fmap_of_list
[('id', 'host2')]) (Some (cast (shadow_root_ptr.Ref 6)))),
                                                                (cast (element_ptr.Ref 38), cast (create_element_obj 'slot' [cast (element_ptr.Ref 39), cast (element_ptr.Ref
41)] (fmap_of_list [(('id', 's2'), ('name', 'slot2'), ('slot', 'slot3')]) None)),
                                                                  (cast (element_ptr.Ref 39), cast (create_element_obj 'slot' [cast (element_ptr.Ref 40)] (fmap_of_list
[('id', 's1'), ('name', 'slot1')]) None)),
                                                                    (cast (element_ptr.Ref 40), cast (create_element_obj 'div' [] (fmap_of_list [(('id', 'f1')]) None)),
                                                                      (cast (element_ptr.Ref 41), cast (create_element_obj 'div' [] (fmap_of_list [(('id', 'f2')]) None)),
                                                                        (cast (shadow_root_ptr.Ref 6), cast (create_shadow_root_obj Open [cast (element_ptr.Ref 42)])),
                                                                          (cast (element_ptr.Ref 42), cast (create_element_obj 'slot' [cast (element_ptr.Ref 43), cast (element_ptr.Ref
45)] (fmap_of_list [(('id', 's4'), ('name', 'slot4')]) None)),
                                                                            (cast (element_ptr.Ref 43), cast (create_element_obj 'slot' [cast (element_ptr.Ref 44)] (fmap_of_list

```

3 Test Suite

```

[(''id'', ''s3''), (''name'', ''slot3'')] None)),
  (cast (element_ptr.Ref 44), cast (create_element_obj ''div'' [] (fmap_of_list [(''id'', ''f3'')] None))),
  (cast (element_ptr.Ref 45), cast (create_element_obj ''div'' [] (fmap_of_list [(''id'', ''f4'')] None))),
  (cast (element_ptr.Ref 46), cast (create_element_obj ''script'' [cast (character_data_ptr.Ref 6)] fmempty
None)),
  (cast (character_data_ptr.Ref 6), cast (create_character_data_obj ''%3C%3Cscript%3E%3E''))]

definition slots_fallback_document :: "(unit, unit, unit, unit, unit, unit) object_ptr option" where "slots_fallba
= Some (cast (document_ptr.Ref 1))"

'Slots fallback: Basic.'

lemma "test (do {
  tmp0 ← slots_fallback_document . getElementById(''test1'');
  n ← createTestTree(tmp0);
  tmp1 ← n . ''test1'';
  removeWhiteSpaceOnlyTextNodes(tmp1);
  tmp2 ← n . ''f1'';
  tmp3 ← tmp2 . assignedSlot;
  assert_equals(tmp3, None);
  tmp4 ← n . ''s1'';
  tmp5 ← tmp4 . assignedNodes();
  assert_array_equals(tmp5, []);
  tmp6 ← n . ''s1'';
  tmp7 ← tmp6 . assignedNodes(True);
  tmp8 ← n . ''f1'';
  assert_array_equals(tmp7, [tmp8])
}) slots_fallback_heap"
  ⟨proof⟩

'Slots fallback: Basic, elements only.'

lemma "test (do {
  tmp0 ← slots_fallback_document . getElementById(''test1'');
  n ← createTestTree(tmp0);
  tmp1 ← n . ''s1'';
  tmp2 ← tmp1 . assignedElements();
  assert_array_equals(tmp2, []);
  tmp3 ← n . ''s1'';
  tmp4 ← tmp3 . assignedElements(True);
  tmp5 ← n . ''f1'';
  assert_array_equals(tmp4, [tmp5])
}) slots_fallback_heap"
  ⟨proof⟩

'Slots fallback: Slots in Slots.'

lemma "test (do {
  tmp0 ← slots_fallback_document . getElementById(''test2'');
  n ← createTestTree(tmp0);
  tmp1 ← n . ''test2'';
  removeWhiteSpaceOnlyTextNodes(tmp1);
  tmp2 ← n . ''f1'';
  tmp3 ← tmp2 . assignedSlot;
  assert_equals(tmp3, None);
  tmp4 ← n . ''s1'';
  tmp5 ← tmp4 . assignedNodes();
  assert_array_equals(tmp5, []);
  tmp6 ← n . ''s2'';
  tmp7 ← tmp6 . assignedNodes();
  assert_array_equals(tmp7, []);
  tmp8 ← n . ''s1'';
  tmp9 ← tmp8 . assignedNodes(True);
  tmp10 ← n . ''f1'';
  assert_array_equals(tmp9, [tmp10]);
  tmp11 ← n . ''s2'';
}) slots_fallback_heap"
  ⟨proof⟩

```

```

tmp12 ← tmp11 . assignedNodes(True);
tmp13 ← n . ''f1'';
assert_array_equals(tmp12, [tmp13])
}) slots_fallback_heap"
⟨proof⟩

```

'Slots fallback: Slots in Slots, elements only.'

```

lemma "test (do {
  tmp0 ← slots_fallback_document . getElementById(''test2'');
  n ← createTestTree(tmp0);
  tmp1 ← n . ''s1'';
  tmp2 ← tmp1 . assignedElements();
  assert_array_equals(tmp2, []);
  tmp3 ← n . ''s2'';
  tmp4 ← tmp3 . assignedElements();
  assert_array_equals(tmp4, []);
  tmp5 ← n . ''s1'';
  tmp6 ← tmp5 . assignedElements(True);
  tmp7 ← n . ''f1'';
  assert_array_equals(tmp6, [tmp7]);
  tmp8 ← n . ''s2'';
  tmp9 ← tmp8 . assignedElements(True);
  tmp10 ← n . ''f1'';
  assert_array_equals(tmp9, [tmp10])
}) slots_fallback_heap"
⟨proof⟩

```

'Slots fallback: Fallback contents should not be used if a node is assigned.'

```

lemma "test (do {
  tmp0 ← slots_fallback_document . getElementById(''test3'');
  n ← createTestTree(tmp0);
  tmp1 ← n . ''test3'';
  removeWhiteSpaceOnlyTextNodes(tmp1);
  tmp2 ← n . ''c1'';
  tmp3 ← tmp2 . assignedSlot;
  tmp4 ← n . ''s1'';
  assert_equals(tmp3, tmp4);
  tmp5 ← n . ''f1'';
  tmp6 ← tmp5 . assignedSlot;
  assert_equals(tmp6, None);
  tmp7 ← n . ''s1'';
  tmp8 ← tmp7 . assignedNodes();
  tmp9 ← n . ''c1'';
  assert_array_equals(tmp8, [tmp9]);
  tmp10 ← n . ''s2'';
  tmp11 ← tmp10 . assignedNodes();
  assert_array_equals(tmp11, []);
  tmp12 ← n . ''s1'';
  tmp13 ← tmp12 . assignedNodes(True);
  tmp14 ← n . ''c1'';
  assert_array_equals(tmp13, [tmp14]);
  tmp15 ← n . ''s2'';
  tmp16 ← tmp15 . assignedNodes(True);
  tmp17 ← n . ''f1'';
  assert_array_equals(tmp16, [tmp17])
}) slots_fallback_heap"
⟨proof⟩

```

'Slots fallback: Slots in Slots: Assigned nodes should be used as fallback contents of another slot'

```

lemma "test (do {
  tmp0 ← slots_fallback_document . getElementById(''test4'');
  n ← createTestTree(tmp0);
  tmp1 ← n . ''test4'';

```

3 Test Suite

```

removeWhiteSpaceOnlyTextNodes(tmp1);
tmp2 ← n . ''c1'';
tmp3 ← tmp2 . assignedSlot;
tmp4 ← n . ''s2'';
assert_equals(tmp3, tmp4);
tmp5 ← n . ''f1'';
tmp6 ← tmp5 . assignedSlot;
assert_equals(tmp6, None);
tmp7 ← n . ''s1'';
tmp8 ← tmp7 . assignedNodes();
assert_array_equals(tmp8, []);
tmp9 ← n . ''s2'';
tmp10 ← tmp9 . assignedNodes();
tmp11 ← n . ''c1'';
assert_array_equals(tmp10, [tmp11]);
tmp12 ← n . ''s1'';
tmp13 ← tmp12 . assignedNodes(True);
tmp14 ← n . ''c1'';
assert_array_equals(tmp13, [tmp14]);
tmp15 ← n . ''s2'';
tmp16 ← tmp15 . assignedNodes(True);
tmp17 ← n . ''c1'';
assert_array_equals(tmp16, [tmp17])
}) slots_fallback_heap"
⟨proof⟩

```

'Slots fallback: Complex case.'

```

lemma "test (do {
    tmp0 ← slots_fallback_document . getElementById(''test5'');
    n ← createTestTree(tmp0);
    tmp1 ← n . ''test5'';
    removeWhiteSpaceOnlyTextNodes(tmp1);
    tmp2 ← n . ''s1'';
    tmp3 ← tmp2 . assignedNodes();
    tmp4 ← n . ''c1'';
    assert_array_equals(tmp3, [tmp4]);
    tmp5 ← n . ''s2'';
    tmp6 ← tmp5 . assignedNodes();
    assert_array_equals(tmp6, []);
    tmp7 ← n . ''s3'';
    tmp8 ← tmp7 . assignedNodes();
    tmp9 ← n . ''s2'';
    assert_array_equals(tmp8, [tmp9]);
    tmp10 ← n . ''s4'';
    tmp11 ← tmp10 . assignedNodes();
    assert_array_equals(tmp11, []);
    tmp12 ← n . ''s1'';
    tmp13 ← tmp12 . assignedNodes(True);
    tmp14 ← n . ''c1'';
    assert_array_equals(tmp13, [tmp14]);
    tmp15 ← n . ''s2'';
    tmp16 ← tmp15 . assignedNodes(True);
    tmp17 ← n . ''c1'';
    tmp18 ← n . ''f2'';
    assert_array_equals(tmp16, [tmp17, tmp18]);
    tmp19 ← n . ''s3'';
    tmp20 ← tmp19 . assignedNodes(True);
    tmp21 ← n . ''c1'';
    tmp22 ← n . ''f2'';
    assert_array_equals(tmp20, [tmp21, tmp22]);
    tmp23 ← n . ''s4'';
    tmp24 ← tmp23 . assignedNodes(True);
    tmp25 ← n . ''c1'';
})

```

```

tmp26 ← n . ''f2'';
tmp27 ← n . ''f4'';
assert_array_equals(tmp24, [tmp25, tmp26, tmp27])
}) slots_fallback_heap"
⟨proof⟩

```

'Slots fallback: Complex case, elements only.'

```

lemma "test (do {
  tmp0 ← slots_fallback_document . getElementById(''test5'');
  n ← createTestTree(tmp0);
  tmp1 ← n . ''s1'';
  tmp2 ← tmp1 . assignedElements();
  tmp3 ← n . ''c1'';
  assert_array_equals(tmp2, [tmp3]);
  tmp4 ← n . ''s2'';
  tmp5 ← tmp4 . assignedElements();
  assert_array_equals(tmp5, []);
  tmp6 ← n . ''s3'';
  tmp7 ← tmp6 . assignedElements();
  tmp8 ← n . ''s2'';
  assert_array_equals(tmp7, [tmp8]);
  tmp9 ← n . ''s4'';
  tmp10 ← tmp9 . assignedElements();
  assert_array_equals(tmp10, []);
  tmp11 ← n . ''s1'';
  tmp12 ← tmp11 . assignedElements(True);
  tmp13 ← n . ''c1'';
  assert_array_equals(tmp12, [tmp13]);
  tmp14 ← n . ''s2'';
  tmp15 ← tmp14 . assignedElements(True);
  tmp16 ← n . ''c1'';
  tmp17 ← n . ''f2'';
  assert_array_equals(tmp15, [tmp16, tmp17]);
  tmp18 ← n . ''s3'';
  tmp19 ← tmp18 . assignedElements(True);
  tmp20 ← n . ''c1'';
  tmp21 ← n . ''f2'';
  assert_array_equals(tmp19, [tmp20, tmp21]);
  tmp22 ← n . ''s4'';
  tmp23 ← tmp22 . assignedElements(True);
  tmp24 ← n . ''c1'';
  tmp25 ← n . ''f2'';
  tmp26 ← n . ''f4'';
  assert_array_equals(tmp23, [tmp24, tmp25, tmp26])
}) slots_fallback_heap"
⟨proof⟩

```

'Slots fallback: Mutation. Append fallback contents.'

```

lemma "test (do {
  tmp0 ← slots_fallback_document . getElementById(''test5'');
  n ← createTestTree(tmp0);
  tmp1 ← n . ''test5'';
  removeWhiteSpaceOnlyTextNodes(tmp1);
  d1 ← slots_fallback_document . createElement(''div'');
  tmp2 ← n . ''s2'';
  tmp2 . appendChild(d1);
  tmp3 ← n . ''s1'';
  tmp4 ← tmp3 . assignedNodes(True);
  tmp5 ← n . ''c1'';
  assert_array_equals(tmp4, [tmp5]);
  tmp6 ← n . ''s2'';
  tmp7 ← tmp6 . assignedNodes(True);
  tmp8 ← n . ''c1'';

```

3 Test Suite

```
tmp9 ← n . ''f2'';
assert_array_equals(tmp7, [tmp8, tmp9, d1]);
tmp10 ← n . ''s3'';
tmp11 ← tmp10 . assignedNodes(True);
tmp12 ← n . ''c1'';
tmp13 ← n . ''f2'';
assert_array_equals(tmp11, [tmp12, tmp13, d1]);
tmp14 ← n . ''s4'';
tmp15 ← tmp14 . assignedNodes(True);
tmp16 ← n . ''c1'';
tmp17 ← n . ''f2'';
tmp18 ← n . ''f4'';
assert_array_equals(tmp15, [tmp16, tmp17, d1, tmp18])
}) slots_fallback_heap"
⟨proof⟩
```

'Slots fallback: Mutation. Remove fallback contents.'

```
lemma "test (do {
tmp0 ← slots_fallback_document . getElementById(''test5'');
n ← createTestTree(tmp0);
tmp1 ← n . ''test5'';
removeWhiteSpaceOnlyTextNodes(tmp1);
tmp2 ← n . ''f2'';
tmp2 . remove();
tmp3 ← n . ''s1'';
tmp4 ← tmp3 . assignedNodes(True);
tmp5 ← n . ''c1'';
assert_array_equals(tmp4, [tmp5]);
tmp6 ← n . ''s2'';
tmp7 ← tmp6 . assignedNodes(True);
tmp8 ← n . ''c1'';
assert_array_equals(tmp7, [tmp8]);
tmp9 ← n . ''s3'';
tmp10 ← tmp9 . assignedNodes(True);
tmp11 ← n . ''c1'';
assert_array_equals(tmp10, [tmp11]);
tmp12 ← n . ''s4'';
tmp13 ← tmp12 . assignedNodes(True);
tmp14 ← n . ''c1'';
tmp15 ← n . ''f4'';
assert_array_equals(tmp13, [tmp14, tmp15])
}) slots_fallback_heap"
⟨proof⟩
```

'Slots fallback: Mutation. Assign a node to a slot so that fallback contents are no longer used.'

```
lemma "test (do {
tmp0 ← slots_fallback_document . getElementById(''test5'');
n ← createTestTree(tmp0);
tmp1 ← n . ''test5'';
removeWhiteSpaceOnlyTextNodes(tmp1);
d2 ← slots_fallback_document . createElement(''div'');
d2 . setAttribute(''slot'', ''slot2'');
tmp2 ← n . ''host1'';
tmp2 . appendChild(d2);
tmp3 ← n . ''s2'';
tmp4 ← tmp3 . assignedNodes();
assert_array_equals(tmp4, [d2]);
tmp5 ← n . ''s2'';
tmp6 ← tmp5 . assignedNodes(True);
assert_array_equals(tmp6, [d2]);
tmp7 ← n . ''s3'';
tmp8 ← tmp7 . assignedNodes(True);
assert_array_equals(tmp8, [d2]);
}) slots_fallback_heap"
⟨proof⟩
```

```

tmp9 ← n . ''s4'';
tmp10 ← tmp9 . assignedNodes(True);
tmp11 ← n . ''f4'';
assert_array_equals(tmp10, [d2, tmp11])
}) slots_fallback_heap"
⟨proof⟩

```

'Slots fallback: Mutation. Remove an assigned node from a slot so that fallback contents will be used.'

```

lemma "test (do {
    tmp0 ← slots_fallback_document . getElementById(''test5'');
    n ← createTestTree(tmp0);
    tmp1 ← n . ''test5'';
    removeWhiteSpaceOnlyTextNodes(tmp1);
    tmp2 ← n . ''c1'';
    tmp2 . remove();
    tmp3 ← n . ''s1'';
    tmp4 ← tmp3 . assignedNodes();
    assert_array_equals(tmp4, []);
    tmp5 ← n . ''s1'';
    tmp6 ← tmp5 . assignedNodes(True);
    tmp7 ← n . ''f1'';
    assert_array_equals(tmp6, [tmp7]);
    tmp8 ← n . ''s2'';
    tmp9 ← tmp8 . assignedNodes(True);
    tmp10 ← n . ''f1'';
    tmp11 ← n . ''f2'';
    assert_array_equals(tmp9, [tmp10, tmp11]);
    tmp12 ← n . ''s3'';
    tmp13 ← tmp12 . assignedNodes(True);
    tmp14 ← n . ''f1'';
    tmp15 ← n . ''f2'';
    assert_array_equals(tmp13, [tmp14, tmp15]);
    tmp16 ← n . ''s4'';
    tmp17 ← tmp16 . assignedNodes(True);
    tmp18 ← n . ''f1'';
    tmp19 ← n . ''f2'';
    tmp20 ← n . ''f4'';
    assert_array_equals(tmp17, [tmp18, tmp19, tmp20])
}) slots_fallback_heap"
⟨proof⟩

```

'Slots fallback: Mutation. Remove a slot which is a fallback content of another slot.'

```

lemma "test (do {
    tmp0 ← slots_fallback_document . getElementById(''test5'');
    n ← createTestTree(tmp0);
    tmp1 ← n . ''test5'';
    removeWhiteSpaceOnlyTextNodes(tmp1);
    tmp2 ← n . ''s1'';
    tmp2 . remove();
    tmp3 ← n . ''s1'';
    tmp4 ← tmp3 . assignedNodes();
    assert_array_equals(tmp4, []);
    tmp5 ← n . ''s1'';
    tmp6 ← tmp5 . assignedNodes(True);
    assert_array_equals(tmp6, [], ''fall back contents should be empty because s1 is not in a shadow tree.'');
    tmp7 ← n . ''s2'';
    tmp8 ← tmp7 . assignedNodes(True);
    tmp9 ← n . ''f2'';
    assert_array_equals(tmp8, [tmp9]);
    tmp10 ← n . ''s3'';
    tmp11 ← tmp10 . assignedNodes(True);
    tmp12 ← n . ''f2'';
    assert_array_equals(tmp11, [tmp12]);
}) slots_fallback_heap"
⟨proof⟩

```

```

tmp13 ← n . ''s4'';
tmp14 ← tmp13 . assignedNodes(True);
tmp15 ← n . ''f2'';
tmp16 ← n . ''f4'';
assert_array_equals(tmp14, [tmp15, tmp16])
}) slots_fallback_heap"
  ⟨proof⟩

```

end

3.4 Testing Document_adoptNode (Shadow_DOM_Document_adoptNode)

This theory contains the test cases for Document_adoptNode.

```

theory Shadow_DOM_Document_adoptNode
imports
  "Shadow_DOM_BaseTest"
begin

definition Document_adoptNode_heap :: heap_final where
  "Document_adoptNode_heap = create_heap [(cast (document_ptr.Ref 1), cast (create_document_obj html (Some
  (cast (element_ptr.Ref 1)))) []),
  (cast (element_ptr.Ref 1), cast (create_element_obj ''html'' [cast (element_ptr.Ref 2), cast (element_ptr.Ref
  8)] fmempty None)),
  (cast (element_ptr.Ref 2), cast (create_element_obj ''head'' [cast (element_ptr.Ref 3), cast (element_ptr.Ref
  4), cast (element_ptr.Ref 5), cast (element_ptr.Ref 6), cast (element_ptr.Ref 7)] fmempty None)),
  (cast (element_ptr.Ref 3), cast (create_element_obj ''meta'' [] (fmap_of_list [(''charset'', ''utf-8'')])))
  None)),
  (cast (element_ptr.Ref 4), cast (create_element_obj ''title'' [cast (character_data_ptr.Ref 1)] fmempty
  None)),
  (cast (character_data_ptr.Ref 1), cast (create_character_data_obj ''Document.adoptNode'')),
  (cast (element_ptr.Ref 5), cast (create_element_obj ''link'' [] (fmap_of_list [(''rel'', ''help''),
  (''href'', ''https://dom.spec.whatwg.org/#dom-document-adoptnode'')] None)),
  (cast (element_ptr.Ref 6), cast (create_element_obj ''script'' [] (fmap_of_list [(''src'', ''/resources/testhan
  None)),
  (cast (element_ptr.Ref 7), cast (create_element_obj ''script'' [] (fmap_of_list [(''src'', ''/resources/testhan
  None)),
  (cast (element_ptr.Ref 8), cast (create_element_obj ''body'' [cast (element_ptr.Ref 9), cast (element_ptr.Ref
  10), cast (element_ptr.Ref 11)] fmempty None)),
  (cast (element_ptr.Ref 9), cast (create_element_obj ''div'' [] (fmap_of_list [(''id'', ''log'')] None)),
  (cast (element_ptr.Ref 10), cast (create_element_obj ''x<'' [cast (character_data_ptr.Ref 2)] fmempty
  None)),
  (cast (character_data_ptr.Ref 2), cast (create_character_data_obj ''x'')),
  (cast (element_ptr.Ref 11), cast (create_element_obj ''script'' [cast (character_data_ptr.Ref 3)] fmempty
  None)),
  (cast (character_data_ptr.Ref 3), cast (create_character_data_obj ''%3C%3Cscript%3E%3E''))])]

definition Document_adoptNode_document :: "(unit, unit, unit, unit, unit, unit) object_ptr option" where
"Document_adoptNode_document = Some (cast (document_ptr.Ref 1))"

  "Adopting an Element called 'x<' should work."
lemma "test (do {
  tmp0 ← Document_adoptNode_document . getElementsByTagName(''x<'');
  y ← return (tmp0 ! 0);
  child ← y . firstChild;
  tmp1 ← y . parentNode;
  tmp2 ← Document_adoptNode_document . body;
  assert_equals(tmp1, tmp2);
  tmp3 ← y . ownerDocument;
  assert_equals(tmp3, Document_adoptNode_document);
```

3.5 Testing Document_getElementById (Shadow_DOM_Document_getElementById)

```

tmp4 ← Document_adoptNode_document . adoptNode(y);
assert_equals(tmp4, y);
tmp5 ← y . parentNode;
assert_equals(tmp5, None);
tmp6 ← y . firstChild;
assert_equals(tmp6, child);
tmp7 ← y . ownerDocument;
assert_equals(tmp7, Document_adoptNode_document);
tmp8 ← child . ownerDocument;
assert_equals(tmp8, Document_adoptNode_document);
doc ← createDocument(None, None, None);
tmp9 ← doc . adoptNode(y);
assert_equals(tmp9, y);
tmp10 ← y . parentNode;
assert_equals(tmp10, None);
tmp11 ← y . firstChild;
assert_equals(tmp11, child);
tmp12 ← y . ownerDocument;
assert_equals(tmp12, doc);
tmp13 ← child . ownerDocument;
assert_equals(tmp13, doc)
}) Document_adoptNode_heap"
⟨proof⟩

```

"Adopting an Element called ':good:times:' should work."

```

lemma "test (do {
  x ← Document_adoptNode_document . createElement('':good:times:'');
  tmp0 ← Document_adoptNode_document . adoptNode(x);
  assert_equals(tmp0, x);
  doc ← createDocument(None, None, None);
  tmp1 ← doc . adoptNode(x);
  assert_equals(tmp1, x);
  tmp2 ← x . parentNode;
  assert_equals(tmp2, None);
  tmp3 ← x . ownerDocument;
  assert_equals(tmp3, doc)
}) Document_adoptNode_heap"
⟨proof⟩

```

end

3.5 Testing Document_getElementById (Shadow_DOM_Document_getElementById)

This theory contains the test cases for Document_getElementById.

```

theory Shadow_DOM_Document_getElementById
imports
  "Shadow_DOM_BaseTest"
begin

definition Document_getElementById_heap :: heap_final where
  "Document_getElementById_heap = create_heap [(cast (document_ptr.Ref 1), cast (create_document_obj html
(Some (cast (element_ptr.Ref 1)))) []),
  (cast (element_ptr.Ref 1), cast (create_element_obj ''html'' [cast (element_ptr.Ref 2), cast (element_ptr.Ref
9)] fmempty None)),
  (cast (element_ptr.Ref 2), cast (create_element_obj ''head'' [cast (element_ptr.Ref 3), cast (element_ptr.Ref
4), cast (element_ptr.Ref 5), cast (element_ptr.Ref 6), cast (element_ptr.Ref 7), cast (element_ptr.Ref
8)] fmempty None)),
  (cast (element_ptr.Ref 3), cast (create_element_obj ''meta'' [] (fmap_of_list [(''charset'', ''utf-8'')]) None))",

```

3 Test Suite

```

(cast (element_ptr.Ref 4), cast (create_element_obj ''title'' [cast (character_data_ptr.Ref 1)] fmempty None)),
  (cast (character_data_ptr.Ref 1), cast (create_character_data_obj ''Document.getElementById'')),
    (cast (element_ptr.Ref 5), cast (create_element_obj ''link'' [] (fmap_of_list [(''rel'', ''author''), (''title'', ''Tetsuharu OHZEKI''), (''href'', ''mailto:saneyuki.snyk@gmail.com'')]) None)),
      (cast (element_ptr.Ref 6), cast (create_element_obj ''link'' [] (fmap_of_list [(''rel'', ''help''), (''href'', ''https://dom.spec.whatwg.org/#dom-document-getelementbyid'')]) None)),
        (cast (element_ptr.Ref 7), cast (create_element_obj ''script'' [] (fmap_of_list [(''src'', ''/resources/testthanNone))],
          (cast (element_ptr.Ref 8), cast (create_element_obj ''script'' [] (fmap_of_list [(''src'', ''/resources/testthanNone)),

(cast (element_ptr.Ref 9), cast (create_element_obj ''body'' [cast (element_ptr.Ref 10), cast (element_ptr.Ref 11), cast (element_ptr.Ref 12), cast (element_ptr.Ref 13), cast (element_ptr.Ref 16), cast (element_ptr.Ref 19)] fmempty None)),
  (cast (element_ptr.Ref 10), cast (create_element_obj ''div'' [] (fmap_of_list [(''id'', ''log'')]) None)),
    (cast (element_ptr.Ref 11), cast (create_element_obj ''div'' [] (fmap_of_list [(''id'', '''')]) None)),
      (cast (element_ptr.Ref 12), cast (create_element_obj ''div'' [] (fmap_of_list [(''id'', ''test1'')]) None)),
        (cast (element_ptr.Ref 13), cast (create_element_obj ''div'' [cast (element_ptr.Ref 14), cast (element_ptr.Ref 15)] (fmap_of_list [(''id'', ''test5''), (''data-name'', ''1st'')]) None)),
          (cast (element_ptr.Ref 14), cast (create_element_obj ''p'' [cast (character_data_ptr.Ref 2)] (fmap_of_list [(''id'', ''test5''), (''data-name'', ''2nd'')]) None)),
            (cast (character_data_ptr.Ref 2), cast (create_character_data_obj ''P'')),
              (cast (element_ptr.Ref 15), cast (create_element_obj ''input'' [] (fmap_of_list [(''id'', ''test5''), (''type'', ''submit''), (''value'', ''Submit''), (''data-name'', ''3rd'')]) None)),
                (cast (element_ptr.Ref 16), cast (create_element_obj ''div'' [cast (element_ptr.Ref 17)] (fmap_of_list [(''id'', ''outer'')]) None)),
                  (cast (element_ptr.Ref 17), cast (create_element_obj ''div'' [cast (element_ptr.Ref 18)] (fmap_of_list [(''id'', ''middle'')]) None)),
                    (cast (element_ptr.Ref 18), cast (create_element_obj ''div'' [] (fmap_of_list [(''id'', ''inner'')]) None)),
                      (cast (element_ptr.Ref 19), cast (create_element_obj ''script'' [cast (character_data_ptr.Ref 3)] fmempty None)),
                        (cast (character_data_ptr.Ref 3), cast (create_character_data_obj ''%3C%3Cscript%3E%3E''))]

definition Document_getElementById_document :: "(unit, unit, unit, unit, unit, unit) object_ptr option" where
"Document_getElementById_document = Some (cast (document_ptr.Ref 1))"

"Document.getElementById with a script-inserted element"

lemma "test (do {
  gBody ← Document_getElementById_document . body;
  TEST_ID ← return ''test2'';
  test ← Document_getElementById_document . createElement(''div'');
  test . setAttribute(''id'', TEST_ID);
  gBody . appendChild(test);
  result ← Document_getElementById_document . getElementById(TEST_ID);
  assert_not_equals(result, None, ''should not be null.'');
  tmp0 ← result . tagName;
  assert_equals(tmp0, ''div'', ''should have appended element's tag name'');
  gBody . removeChild(test);
  removed ← Document_getElementById_document . getElementById(TEST_ID);
  assert_equals(removed, None, ''should not get removed element.'')
}) Document_getElementById_heap"
  ⟨proof⟩

"update 'id' attribute via setAttribute/removeAttribute"

lemma "test (do {
  gBody ← Document_getElementById_document . body;
  TEST_ID ← return ''test3'';
  test ← Document_getElementById_document . createElement(''div'');
  test . setAttribute(''id'', TEST_ID);
  gBody . appendChild(test);
  UPDATED_ID ← return ''test3-updated'';
})

```

3.5 Testing Document_getElementById (Shadow_DOM_Document_getElementById)

```

test . setAttribute('id', UPDATED_ID);
e ← Document_getElementById_document . getElementById(UPDATED_ID);
assert_equals(e, test, 'should get the element with id.');
old ← Document_getElementById_document . getElementById(TEST_ID);
assert_equals(old, None, 'shouldn't get the element by the old id.');
test . removeAttribute('id');
e2 ← Document_getElementById_document . getElementById(UPDATED_ID);
assert_equals(e2, None, 'should return null when the passed id is none in document.')
}) Document_getElementById_heap"
⟨proof⟩

```

"Ensure that the id attribute only affects elements present in a document"

```

lemma "test (do {
TEST_ID ← return 'test4-should-not-exist';
e ← Document_getElementById_document . createElement('div');
e . setAttribute('id', TEST_ID);
tmp0 ← Document_getElementById_document . getElementById(TEST_ID);
assert_equals(tmp0, None, 'should be null');
tmp1 ← Document_getElementById_document . body;
tmp1 . appendChild(e);
tmp2 ← Document_getElementById_document . getElementById(TEST_ID);
assert_equals(tmp2, e, 'should be the appended element')
}) Document_getElementById_heap"
⟨proof⟩

```

"in tree order, within the context object's tree"

```

lemma "test (do {
gBody ← Document_getElementById_document . body;
TEST_ID ← return 'test5';
target ← Document_getElementById_document . getElementById(TEST_ID);
assert_not_equals(target, None, 'should not be null');
tmp0 ← target . getAttribute('data-name');
assert_equals(tmp0, '1st', 'should return the 1st');
element4 ← Document_getElementById_document . createElement('div');
element4 . setAttribute('id', TEST_ID);
element4 . setAttribute('data-name', '4th');
gBody . appendChild(element4);
target2 ← Document_getElementById_document . getElementById(TEST_ID);
assert_not_equals(target2, None, 'should not be null');
tmp1 ← target2 . getAttribute('data-name');
assert_equals(tmp1, '1st', 'should be the 1st');
tmp2 ← target2 . parentNode;
tmp2 . removeChild(target2);
target3 ← Document_getElementById_document . getElementById(TEST_ID);
assert_not_equals(target3, None, 'should not be null');
tmp3 ← target3 . getAttribute('data-name');
assert_equals(tmp3, '4th', 'should be the 4th')
}) Document_getElementById_heap"
⟨proof⟩

```

"Modern browsers optimize this method with using internal id cache. This test checks that their optimization should effect only append to 'Document', not append to 'Node'."

```

lemma "test (do {
TEST_ID ← return 'test6';
s ← Document_getElementById_document . createElement('div');
s . setAttribute('id', TEST_ID);
tmp0 ← Document_getElementById_document . createElement('div');
tmp0 . appendChild(s);
tmp1 ← Document_getElementById_document . getElementById(TEST_ID);
assert_equals(tmp1, None, 'should be null')
}) Document_getElementById_heap"
⟨proof⟩

```

3 Test Suite

"changing attribute's value via 'Attr' gotten from 'Element.getAttribute'."

```
lemma "test (do {
    gBody ← Document_getElementById_document . body;
    TEST_ID ← return ''test7'';
    element ← Document_getElementById_document . createElement(''div'');
    element . setAttribute(''id'', TEST_ID);
    gBody . appendChild(element);
    target ← Document_getElementById_document . getElementById(TEST_ID);
    assert_equals(target, element, ''should return the element before changing the value'');
    element . setAttribute(''id'', (TEST_ID @ ''-updated''));
    target2 ← Document_getElementById_document . getElementById(TEST_ID);
    assert_equals(target2, None, ''should return null after updated id via Attr.value'');
    target3 ← Document_getElementById_document . getElementById((TEST_ID @ ''-updated''));
    assert_equals(target3, element, ''should be equal to the updated element.'')
}) Document_getElementById_heap"
    ⟨proof⟩
}
```

"update 'id' attribute via element.id"

```
lemma "test (do {
    gBody ← Document_getElementById_document . body;
    TEST_ID ← return ''test12'';
    test ← Document_getElementById_document . createElement(''div'');
    test . setAttribute(''id'', TEST_ID);
    gBody . appendChild(test);
    UPDATED_ID ← return (TEST_ID @ ''-updated'');
    test . setAttribute(''id'', UPDATED_ID);
    e ← Document_getElementById_document . getElementById(UPDATED_ID);
    assert_equals(e, test, ''should get the element with id.'');
    old ← Document_getElementById_document . getElementById(TEST_ID);
    assert_equals(old, None, ''shouldn't get the element by the old id.'');
    test . setAttribute(''id'', '');
    e2 ← Document_getElementById_document . getElementById(UPDATED_ID);
    assert_equals(e2, None, ''should return null when the passed id is none in document.''
}) Document_getElementById_heap"
    ⟨proof⟩
}
```

"where insertion order and tree order don't match"

```
lemma "test (do {
    gBody ← Document_getElementById_document . body;
    TEST_ID ← return ''test13'';
    container ← Document_getElementById_document . createElement(''div'');
    container . setAttribute(''id'', (TEST_ID @ ''-fixture''));
    gBody . appendChild(container);
    element1 ← Document_getElementById_document . createElement(''div'');
    element1 . setAttribute(''id'', TEST_ID);
    element2 ← Document_getElementById_document . createElement(''div'');
    element2 . setAttribute(''id'', TEST_ID);
    element3 ← Document_getElementById_document . createElement(''div'');
    element3 . setAttribute(''id'', TEST_ID);
    element4 ← Document_getElementById_document . createElement(''div'');
    element4 . setAttribute(''id'', TEST_ID);
    container . appendChild(element2);
    container . appendChild(element4);
    container . insertBefore(element3, element4);
    container . insertBefore(element1, element2);
    test ← Document_getElementById_document . getElementById(TEST_ID);
    assert_equals(test, element1, ''should return 1st element'');
    container . removeChild(element1);
    test ← Document_getElementById_document . getElementById(TEST_ID);
    assert_equals(test, element2, ''should return 2nd element'');
    container . removeChild(element2);
    test ← Document_getElementById_document . getElementById(TEST_ID);
    assert_equals(test, None, ''should return null when the passed id is none in document.''
}) Document_getElementById_heap"
    ⟨proof⟩
}
```

```

assert_equals(test, element3, "'should return 3rd element'");
container . removeChild(element3);
test ← Document_getElementById_document . getElementById(TEST_ID);
assert_equals(test, element4, "'should return 4th element'");
container . removeChild(element4)
}) Document_getElementById_heap"
⟨proof⟩

"Inserting an id by inserting its parent node"

lemma "test (do {
gBody ← Document_getElementById_document . body;
TEST_ID ← return 'test14';
a ← Document_getElementById_document . createElement(''a'');
b ← Document_getElementById_document . createElement(''b'');
a . appendChild(b);
b . setAttribute(''id'', TEST_ID);
tmp0 ← Document_getElementById_document . getElementById(TEST_ID);
assert_equals(tmp0, None);
gBody . appendChild(a);
tmp1 ← Document_getElementById_document . getElementById(TEST_ID);
assert_equals(tmp1, b)
}) Document_getElementById_heap"
⟨proof⟩

"Document.getElementById must not return nodes not present in document"

lemma "test (do {
TEST_ID ← return 'test15';
outer ← Document_getElementById_document . getElementById(''outer'');
middle ← Document_getElementById_document . getElementById(''middle'');
inner ← Document_getElementById_document . getElementById(''inner'');
tmp0 ← Document_getElementById_document . getElementById(''middle'');
outer . removeChild(tmp0);
new_el ← Document_getElementById_document . createElement(''h1'');
new_el . setAttribute(''id'', ''heading'');
inner . appendChild(new_el);
tmp1 ← Document_getElementById_document . getElementById(''heading'');
assert_equals(tmp1, None)
}) Document_getElementById_heap"
⟨proof⟩

end

```

3.6 Testing Node_insertBefore (Shadow_DOM_Node_insertBefore)

This theory contains the test cases for Node_insertBefore.

```

theory Shadow_DOM_Node_insertBefore
imports
  "Shadow_DOM_BaseTest"
begin

definition Node_insertBefore_heap :: heapfinal where
  "Node_insertBefore_heap = create_heap [(cast (document_ptr.Ref 1), cast (create_document_obj html (Some
  (cast (element_ptr.Ref 1)))) []),
  (cast (element_ptr.Ref 1), cast (create_element_obj ''html'' [cast (element_ptr.Ref 2), cast (element_ptr.Ref
  6)] fmempty None)),
  (cast (element_ptr.Ref 2), cast (create_element_obj ''head'' [cast (element_ptr.Ref 3), cast (element_ptr.Ref
  4), cast (element_ptr.Ref 5)] fmempty None)),
  (cast (element_ptr.Ref 3), cast (create_element_obj ''title'' [cast (character_data_ptr.Ref 1)] fmempty
  None)),
  (cast (character_data_ptr.Ref 1), cast (create_character_data_obj ''Node.insertBefore''))),
  ...
]
```

3 Test Suite

```

(cast (element_ptr.Ref 4), cast (create_element_obj ''script'' []) (fmap_of_list [(''src'', ''/resources/testthan
None)),
(cast (element_ptr.Ref 5), cast (create_element_obj ''script'' []) (fmap_of_list [(''src'', ''/resources/testthan
None)),
(cast (element_ptr.Ref 6), cast (create_element_obj ''body'' [cast (element_ptr.Ref 7), cast (element_ptr.Ref
8)] fmempty None)),
(cast (element_ptr.Ref 7), cast (create_element_obj ''div'' []) (fmap_of_list [(''id'', ''log'')] None)),
(cast (element_ptr.Ref 8), cast (create_element_obj ''script'' [cast (character_data_ptr.Ref 2)] fmempty
None)),
(cast (character_data_ptr.Ref 2), cast (create_character_data_obj ''%3C%3Cscript%3E%3E''))]

definition Node_insertBefore_document :: "(unit, unit, unit, unit, unit) object_ptr option" where
"Node_insertBefore_document = Some (cast (document_ptr.Ref 1))"

"Calling insertBefore an a leaf node Text must throw HIERARCHY_REQUEST_ERR."

lemma "test (do {
node ← Node_insertBefore_document . createTextNode(''Foo'');
tmp0 ← Node_insertBefore_document . createTextNode(''fail'');
assert_throws(HierarchyRequestError, node . insertBefore(tmp0, None))
}) Node_insertBefore_heap"
⟨proof⟩

"Calling insertBefore with an inclusive ancestor of the context object must throw HIERARCHY_REQUEST_ERR."

lemma "test (do {
tmp1 ← Node_insertBefore_document . body;
tmp2 ← Node_insertBefore_document . getElementById(''log'');
tmp0 ← Node_insertBefore_document . body;
assert_throws(HierarchyRequestError, tmp0 . insertBefore(tmp1, tmp2));
tmp4 ← Node_insertBefore_document . documentElement;
tmp5 ← Node_insertBefore_document . getElementById(''log'');
tmp3 ← Node_insertBefore_document . body;
assert_throws(HierarchyRequestError, tmp3 . insertBefore(tmp4, tmp5))
}) Node_insertBefore_heap"
⟨proof⟩

"Calling insertBefore with a reference child whose parent is not the context node must throw a NotFoundError."

lemma "test (do {
a ← Node_insertBefore_document . createElement(''div'');
b ← Node_insertBefore_document . createElement(''div'');
c ← Node_insertBefore_document . createElement(''div'');
assert_throws(NotFoundError, a . insertBefore(b, c))
}) Node_insertBefore_heap"
⟨proof⟩

"If the context node is a document, inserting a document or text node should throw a HierarchyRequestError."

lemma "test (do {
doc ← createDocument(''title'');
doc2 ← createDocument(''title2'');
tmp0 ← doc . documentElement;
assert_throws(HierarchyRequestError, doc . insertBefore(doc2, tmp0));
tmp1 ← doc . createTextNode(''text'');
tmp2 ← doc . documentElement;
assert_throws(HierarchyRequestError, doc . insertBefore(tmp1, tmp2))
}) Node_insertBefore_heap"
⟨proof⟩

"Inserting a node before itself should not move the node"

lemma "test (do {
a ← Node_insertBefore_document . createElement(''div'');
b ← Node_insertBefore_document . createElement(''div'');
c ← Node_insertBefore_document . createElement(''div'');
a . appendChild(b);
}) Node_insertBefore_heap"
⟨proof⟩

```

```

a . appendChild(c);
tmp0 ← a . childNodes;
assert_array_equals(tmp0, [b, c]);
tmp1 ← a . insertBefore(b, b);
assert_equals(tmp1, b);
tmp2 ← a . childNodes;
assert_array_equals(tmp2, [b, c]);
tmp3 ← a . insertBefore(c, c);
assert_equals(tmp3, c);
tmp4 ← a . childNodes;
assert_array_equals(tmp4, [b, c])
}) Node_insertBefore_heap"
  ⟨proof⟩

```

end

3.7 Testing Node_removeChild (Shadow_DOM_Node_removeChild)

This theory contains the test cases for Node_removeChild.

```

theory Shadow_DOM_Node_removeChild
imports
  "Shadow_DOM_BaseTest"
begin

definition Node_removeChild_heap :: heapfinal where
  "Node_removeChild_heap = create_heap [(cast (document_ptr.Ref 1), cast (create_document_obj html (Some
  (cast (element_ptr.Ref 1)))) []),
  (cast (element_ptr.Ref 1), cast (create_element_obj ''html'' [cast (element_ptr.Ref 2), cast (element_ptr.Ref
  7)] fmempty None)),
  (cast (element_ptr.Ref 2), cast (create_element_obj ''head'' [cast (element_ptr.Ref 3), cast (element_ptr.Ref
  4), cast (element_ptr.Ref 5), cast (element_ptr.Ref 6)] fmempty None)),
  (cast (element_ptr.Ref 3), cast (create_element_obj ''title'' [cast (character_data_ptr.Ref 1)] fmempty
  None)),
  (cast (character_data_ptr.Ref 1), cast (create_character_data_obj ''Node.removeChild'')),
  (cast (element_ptr.Ref 4), cast (create_element_obj ''script'' [] (fmap_of_list [(''src'', ''/resources/testhan
  None)]),
  (cast (element_ptr.Ref 5), cast (create_element_obj ''script'' [] (fmap_of_list [(''src'', ''/resources/testhan
  None)]),
  (cast (element_ptr.Ref 6), cast (create_element_obj ''script'' [] (fmap_of_list [(''src'', ''creators.js'')])))
  None)),
  (cast (element_ptr.Ref 7), cast (create_element_obj ''body'' [cast (element_ptr.Ref 8), cast (element_ptr.Ref
  9), cast (element_ptr.Ref 10)] fmempty None)),
  (cast (element_ptr.Ref 8), cast (create_element_obj ''div'' [] (fmap_of_list [(''id'', ''log'')] None)),
  (cast (element_ptr.Ref 9), cast (create_element_obj ''iframe'' [] (fmap_of_list [(''src'', ''about:blank'')])))
  None)),
  (cast (element_ptr.Ref 10), cast (create_element_obj ''script'' [cast (character_data_ptr.Ref 2)] fmempty
  None)),
  (cast (character_data_ptr.Ref 2), cast (create_character_data_obj ''%3C%3Cscript%3E%3E''))]

definition Node_removeChild_document :: "(unit, unit, unit, unit, unit) object_ptr option" where "Node_remove
= Some (cast (document_ptr.Ref 1))"

  "Passing a detached Element to removeChild should not affect it."
lemma "test (do {
  doc ← return Node_removeChild_document;
  s ← doc . createElement(''div'');
  tmp0 ← s . ownerDocument;
  assert_equals(tmp0, doc);
  tmp1 ← Node_removeChild_document . body;
  assert_throws(NotFoundError, tmp1 . removeChild(s));
  tmp2 ← s . ownerDocument;

```

3 Test Suite

```
    assert_equals(tmp2, doc)
}) Node_removeChild_heap"
⟨proof⟩
```

"Passing a non-detached Element to removeChild should not affect it."

```
lemma "test (do {
    doc ← return Node_removeChild_document;
    s ← doc . createElement(''div'');
    tmp0 ← doc . documentElement;
    tmp0 . appendChild(s);
    tmp1 ← s . ownerDocument;
    assert_equals(tmp1, doc);
    tmp2 ← Node_removeChild_document . body;
    assert_throws(NotFoundError, tmp2 . removeChild(s));
    tmp3 ← s . ownerDocument;
    assert_equals(tmp3, doc)
}) Node_removeChild_heap"
⟨proof⟩
```

"Calling removeChild on an Element with no children should throw NOT_FOUND_ERR."

```
lemma "test (do {
    doc ← return Node_removeChild_document;
    s ← doc . createElement(''div'');
    tmp0 ← doc . body;
    tmp0 . appendChild(s);
    tmp1 ← s . ownerDocument;
    assert_equals(tmp1, doc);
    assert_throws(NotFoundError, s . removeChild(doc))
}) Node_removeChild_heap"
⟨proof⟩
```

"Passing a detached Element to removeChild should not affect it."

```
lemma "test (do {
    doc ← createDocument('');
    s ← doc . createElement(''div'');
    tmp0 ← s . ownerDocument;
    assert_equals(tmp0, doc);
    tmp1 ← Node_removeChild_document . body;
    assert_throws(NotFoundError, tmp1 . removeChild(s));
    tmp2 ← s . ownerDocument;
    assert_equals(tmp2, doc)
}) Node_removeChild_heap"
⟨proof⟩
```

"Passing a non-detached Element to removeChild should not affect it."

```
lemma "test (do {
    doc ← createDocument('');
    s ← doc . createElement(''div'');
    tmp0 ← doc . documentElement;
    tmp0 . appendChild(s);
    tmp1 ← s . ownerDocument;
    assert_equals(tmp1, doc);
    tmp2 ← Node_removeChild_document . body;
    assert_throws(NotFoundError, tmp2 . removeChild(s));
    tmp3 ← s . ownerDocument;
    assert_equals(tmp3, doc)
}) Node_removeChild_heap"
⟨proof⟩
```

"Calling removeChild on an Element with no children should throw NOT_FOUND_ERR."

```
lemma "test (do {
    doc ← createDocument('');
    s ← doc . createElement(''div'');
    tmp0 ← doc . documentElement;
    tmp0 . appendChild(s);
    tmp1 ← s . ownerDocument;
    assert_equals(tmp1, doc);
    tmp2 ← Node_removeChild_document . body;
    assert_throws(NotFoundError, tmp2 . removeChild(s));
    tmp3 ← s . ownerDocument;
    assert_equals(tmp3, doc)
}) Node_removeChild_heap"
⟨proof⟩
```

```

s ← doc . createElement(''div'');
tmp0 ← doc . body;
tmp0 . appendChild(s);
tmp1 ← s . ownerDocument;
assert_equals(tmp1, doc);
assert_throws(NotFoundError, s . removeChild(doc))
}) Node_removeChild_heap"
⟨proof⟩

"Passing a value that is not a Node reference to removeChild should throw TypeError."
lemma "test (do {
  tmp0 ← Node_removeChild_document . body;
  assert_throws(TypeError, tmp0 . removeChild(None))
}) Node_removeChild_heap"
⟨proof⟩

end

```

3.8 Shadow DOM Tests (Shadow_DOM_Tests)

```

theory Shadow_DOM_Tests
imports
"tests/slots"
"tests/slots_fallback"
"tests/Shadow_DOM_Document_adoptNode"
"tests/Shadow_DOM_Document_getElementById"
"tests/Shadow_DOM_Node_insertBefore"
"tests/Shadow_DOM_Node_removeChild"
begin
end

```


Bibliography

- [1] A. Bohannon and B. C. Pierce. Featherweight Firefox: Formalizing the core of a web browser. In *Usenix Conference on Web Application Development (WebApps)*, June 2010. URL <http://www.cis.upenn.edu/~bohannon/browser-model/>.
- [2] A. D. Brucker. *An Interactive Proof Environment for Object-oriented Specifications*. PhD thesis, ETH Zurich, mar 2007. URL <https://www.brucker.ch/bibliography/abstract/brucker-interactive-2007>. ETH Dissertation No. 17097.
- [3] A. D. Brucker and M. Herzberg. The core DOM. *Archive of Formal Proofs*, dec 2018. ISSN 2150-914x. URL <https://www.brucker.ch/bibliography/abstract/brucker.ea-afp-core-dom-2018-a>. http://www.isa-afp.org/entries/Core_DOM.html, Formal proof development.
- [4] A. D. Brucker and M. Herzberg. Formalizing (web) standards: An application of test and proof. In C. Dubois and B. Wolff, editors, *TAP 2018: Tests And Proofs*, number 10889 in Lecture Notes in Computer Science, pages 159–166. Springer-Verlag, Heidelberg, 2018. ISBN 978-3-642-38915-3. doi: 10.1007/978-3-319-92994-1_9. URL <http://www.brucker.ch/bibliography/abstract/brucker.ea-standard-compliance-testing-2018>.
- [5] A. D. Brucker and M. Herzberg. A formalization of web components. *Archive of Formal Proofs*, Sept. 2020. ISSN 2150-914x. http://www.isa-afp.org/entries/DOM_Components.html, Formal proof development.
- [6] A. D. Brucker and M. Herzberg. A formally verified model of web components. In S.-S. Jongmans and F. Arbab, editors, *Formal Aspects of Component Software (FACS)*, number 12018 in Lecture Notes in Computer Science. Springer-Verlag, Heidelberg, 2020. ISBN 3-540-25109-X. doi: 10.1007/978-3-030-40914-2_3. URL <https://www.brucker.ch/bibliography/abstract/brucker.ea-web-components-2019>.
- [7] A. D. Brucker and B. Wolff. Interactive testing using HOL-TestGen. In W. Grieskamp and C. Weise, editors, *Formal Approaches to Testing of Software*, number 3997 in Lecture Notes in Computer Science. Springer-Verlag, Heidelberg, 2005. ISBN 3-540-25109-X. doi: 10.1007/11759744_7. URL <http://www.brucker.ch/bibliography/abstract/brucker.ea-interactive-2005>.
- [8] A. D. Brucker and B. Wolff. An extensible encoding of object-oriented data models in hol. *Journal of Automated Reasoning*, 41:219–249, 2008. ISSN 0168-7433. doi: 10.1007/s10817-008-9108-3. URL <https://www.brucker.ch/bibliography/abstract/brucker.ea-extensible-2008-b>.
- [9] A. D. Brucker and B. Wolff. On theorem prover-based testing. *Formal Aspects of Computing*, 25(5):683–721, 2013. ISSN 0934-5043. doi: 10.1007/s00165-012-0222-y. URL <http://www.brucker.ch/bibliography/abstract/brucker.ea-theorem-prover-2012>.
- [10] P. Gardner, G. Smith, M. J. Wheelhouse, and U. Zarfaty. DOM: towards a formal specification. In *PLAN-X 2008, Programming Language Technologies for XML, An ACM SIGPLAN Workshop colocated with POPL 2008, San Francisco, California, USA, January 9, 2008*, 2008. URL <http://gemo.futurs.inria.fr/events/PLANX2008/papers/p18.pdf>.
- [11] M. Herzberg. *Formal Foundations for Provably Safe Web Components*. PhD thesis, The University of Sheffield, 2020.
- [12] D. Jang, Z. Tatlock, and S. Lerner. Establishing browser security guarantees through formal shim verification. In T. Kohno, editor, *Proceedings of the 21th USENIX Security Symposium, Bellevue, WA, USA, August 8-10, 2012*, pages 113–128. USENIX Association, 2012. URL <https://www.usenix.org/conference/usenixsecurity12/technical-sessions/presentation/jang>.
- [13] G. Klein. Operating system verification — an overview. *Sādhāraṇā*, 34(1):27–69, Feb. 2009.
- [14] A. Raad, J. F. Santos, and P. Gardner. DOM: specification and client reasoning. In A. Igarashi, editor, *Programming Languages and Systems - 14th Asian Symposium, APLAS 2016, Hanoi, Vietnam, November 21-23, 2016, Proceedings*, volume 10017 of *Lecture Notes in Computer Science*, pages 401–422, 2016. ISBN 978-3-319-47957-6. doi: 10.1007/978-3-319-47958-3_21.
- [15] W3C. W3C DOM4, Nov. 2015. URL <https://www.w3.org/TR/dom/>.
- [16] WHATWG. DOM – living standard, Mar. 2017. URL <https://dom.spec.whatwg.org/commit-snapshots/6253e53af2fbfaa6d25ad09fd54280d8083b2a97/>. Last Updated 24 March 2017.